

ASME B18.3-2003
(Revision of ASME B18.3-1998)

Socket Cap, Shoulder, and Set Screws, Hex and Spline Keys (Inch Series)

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

ASME B18.3-2003
(Revision of ASME B18.3-1998)

Socket Cap, Shoulder, and Set Screws, Hex and Spline Keys (Inch Series)

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

Three Park Avenue • New York, NY 10016

Date of Issuance: April 29, 2005

The 2003 edition of this Standard is being issued with an automatic addenda subscription service. The use of addenda allows revisions made in response to public review comments or committee actions to be published as necessary. This Standard will be revised when the Society approves the issuance of a new edition.

ASME issues written replies to inquiries concerning interpretations of technical aspects of this Standard. Interpretations are published on the ASME Web site under the Committee Pages at <http://www.asme.org/codes/> as they are issued.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The Standards Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment that provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not “approve,” “rate,” or “endorse” any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor assume any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.

The American Society of Mechanical Engineers
Three Park Avenue, New York, NY 10016-5990

Copyright © 2005 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All rights reserved
Printed in U.S.A.

CONTENTS

Foreword	iv
Committee Roster	vi
Correspondence With the B18 Committee	vii
1 Introductory Notes	1
2 General Data	2
Figure	
1 Optional Types of Cup Points	40
Tables	
1A Dimensions of Hexagon and Spline Socket Head Cap Screws	3
1B-1 Dimensions of Under Head Fillets for Socket Head Cap Screws Threaded to the Head	6
1B-2 Dimensions of Under Head Fillets for Socket Head Cap Screws With an Unthreaded Length of Body Diameter	7
1C Body and Grip Lengths for Socket Head Cap Screws	8
1D Lengths Beyond Sizes in Table 1C	11
1E Shank Straightness for Socket Head Cap Screws	12
1F Dimensions of Drilled Hexagon Socket Head Cap Screws	14
1G Dimensions of Low Head Hexagon Socket Cap Screws	16
2A Dimensions of Hexagon and Spline Socket Flat Countersunk Head Cap Screws	18
2B Body and Grip Lengths for Socket Flat Countersunk Head Cap Screws	21
2C Lengths Beyond Sizes in Table 2B	24
3 Dimensions of Hexagon and Spline Socket Button Head Cap Screws	25
4 Dimensions of Hexagon Socket Head Shoulder Screws	28
5A Dimensions of Hexagon and Spline Socket Set Screws	32
5B Hexagon Key Engagements for Short Length Set Screws	37
5C Dimensions of Optional Cup Points	39
6 Dimensions of Hexagon Sockets	41
7 Dimensions of Spline Sockets	42
8 Dimensions of Hexagon Keys and Bits	43
9 Dimensions of Spline Keys and Bits	45
Mandatory Appendices	
I Gages and Gaging for Hexagon and Spline Sockets	47
II Protrusion Gaging of Flat Countersunk Heads	50
III Straightness Gage and Gaging	51
Nonmandatory Appendices	
A Drill and Counterbore Sizes for Socket Head Cap Screws	52
B Applicability of Keys and Bits to Various Socket Screw Types and Sizes	54
C Formulas for Dimensions	56
D Hexagon and Spline Socket Head Cap Screws (1936 Series)	58

FOREWORD

American National Standards Committee B18 for the standardization of bolts, screws, nuts, rivets, and similar fasteners was organized in March 1922 as Sectional Committee B18 under the aegis of the American Engineering Standards Committee (later the American Standards Association, then the United States of America Standards Institute and, as of October 6, 1969, the American National Standards Institute) with the Society of Automotive Engineers and the American Society of Mechanical Engineers as joint sponsors.

Subcommittee No. 9¹ on Socket Head Cap and Set Screws was organized in April 1929 and completed its first report in November 1931. Seven successive drafts were issued during which the content of the proposal was considerably extended and refined, and in March 1933 copies were distributed to industry for criticism and comment. The suggestions received were carefully reviewed, and in April 1935 the proposal was presented to the members of Sectional Committee B18 for letter ballot vote. Following the acceptance by the two sponsor organizations, it was designated an American Standard (ASA B18.3) in February 1936 by the American Standards Association.

For the purpose of keeping the work of the Subcommittee in line with the developments in industry, the Committee prepared a supplement to the standard in the form of a table covering the dimensions of hexagonal and fluted socket head shoulder screws (stripper bolts) optional, which received approval of the American Standards Association in April 1944 and was designated ASA B18.3a.

In March 1945, the Subcommittee submitted certain fundamental changes and additions to the Standard, and the Sectional Committee recommended issuance of a completely revised standard. Following approval of the Sectional Committee, the revised document was approved by the sponsor organizations and the American Standards Association and designated an American Standard in April 1947.

In accordance with ASA procedure, a review of the standard was undertaken in 1950 and certain additional changes were recommended by the Subcommittee. Cap screw sizes No. 0 and 1 and set screw sizes No. 0, 1, 2, 3, and 4 were added to satisfy increasing demand from various industries. Material, hardness, and thread fit were included to provide a more complete standard. A draft dated November 1951 was distributed to industry

for criticism and comment. A further revision, dated November 1953, was presented to Sectional Committee B18 for letter ballot vote. Following approval of the Sectional Committee and sponsors, the proposal was submitted to the American Standards Association. It was approved and designated an American Standard on August 26, 1954.

Shortly after the 1954 standard was issued, work was initiated on the development of standards covering flat countersunk head cap screws, button head cap screws, and cap screws up to 4 in. in diameter. As these proposals evolved with comments received from various industries, it became evident that a major revision was required, particularly in regard to insufficient bearing surface under the head on some sizes as well as increased socket sizes to permit higher set-up torque. The resulting proposed revision was presented to Sectional Committee B18 for letter ballot vote. Following approval of the Sectional Committee and sponsors, the proposal was submitted to the American Standards Association. It was approved and designated an American Standard on December 21, 1961.

Continued surveillance of the 1961 standard by the Subcommittee indicated by 1966 that a complete revision of the document was necessary to provide recognition of technical improvements in materials and manufacturing methods. Work over the next 2 years culminated in a March 1968 draft proposal incorporating revisions in the following areas:

- (a) more clearly defined materials for all products
- (b) application of Unified radius root threads to all cap screws
- (c) refinements to underhead fillets
- (d) extension of size coverage for flat countersunk head cap screws to include $\frac{7}{8}$ in. through $1\frac{1}{2}$ in. diameters, and tabulation of body and grip lengths for sizes 0 in. through 1 in.
- (e) increased key engagements in socket set screws and implementation of minimum hexagon key engagement in short length set screws
- (f) addition of width across corner dimensions for hexagon keys and bits
- (g) the inclusion of appendices covering drill and counterbore sizes for socket head cap screws (1960 Series), and gages and gaging for spline sockets.

Following acceptance of this draft by the Subcommittee, it was approved by letter ballot of USA Standards

¹ As of April 1, 1966, Subcommittee 9 was redesignated as Subcommittee 3.

Committee B18 and the sponsor organizations, and submitted to the United States of America Standards Institute. It was approved and designated a USA Standard on September 19, 1969.

A periodic review of the standard, undertaken by Subcommittee 3 in 1973, resulted in agreement that the document be revised to reflect clarification of the underhead fillet on socket head cap screws, add coverage on drilled socket head cap screws, lengthen the thread undercut on socket head shoulder screws, and extend the coverage on the latter to include the 1½ in., 1¾ in., and 2 in. sizes. A proposal incorporating these changes together with numerous editorial corrections was prepared and, subsequent to Subcommittee acceptance, approved by letter ballot to American National Standards Committee B18. Following approval by the sponsor organizations, the proposal was submitted to the American National Standards Institute and designated an American National Standard on November 1, 1976.

A periodic review of the standard, undertaken by the Subcommittee in 1980, resulted in agreement that the document be revised

- (a) to clarify the notes on screw point chamfers
- (b) in socket tolerances for large sockets and in counterbore sizes to reflect standard tooling
- (c) to reference the ASTM document A 574 for the appropriate mechanical and chemical requirements

A proposal containing these changes, as well as many editorial corrections, was prepared for and balloted by letter ballot to the ASME Committee B18. Following approval by the sponsor organization, the proposal was submitted to the American National Standards Institute and designated an American National Standard on January 4, 1982.

A periodic review of the standard, undertaken by the Committee in 1985, resulted in agreement that the document be revised to clarify the dimensions with respect to plated products, and to incorporate by reference the new ASTM documents for the appropriate mechanical, chemical, and testing requirements for the

button head, flat countersunk head, and set screw products. A proposal containing these changes, as well as editorial corrections, was prepared and balloted by letter ballot to ASME Committee B18. Following approval by ASME, the proposal was submitted to the American National Standards Institute and designated an American National Standard on August 7, 1986.

A periodic review of this Standard was undertaken by the Committee in 1990. Based on this review, it was determined that the document needed significant revisions to clarify and update the Standard. These revisions would need to address the technical changes in manufacturing methods and changes in the standards community. To accomplish this objective, established quality standards were recognized and integrated into the Standard. In addition, designated characteristics for each product and product identification were established and gaging techniques for countersunk screws were added. These changes were balloted and approved by the ASME B18 Committee. The proposal was submitted to the American National Standards Institute and designated an American National Standard on January 14, 1998.

A periodic review of this Standard was again undertaken by the Committee in 2000. It was determined that there were many technical printing errors that had to be revised. Inspection definitions were added to clarify bearing surface, runout, and straightness for various products. The radius under the head for socket head screws was clarified by the addition of drawings showing the radius on thread to the head socket screws, and also showing the radius on socket screws with an unthreaded shoulder. The protrusion gage dimensions were changed on flat head socket cap screws. The thread requirements for short length socket set screws were also changed. A standard was also developed for low head socket cap screws. These changes were balloted and approved by the ASME B18 Committee. The proposal was submitted to the American National Standards Institute and designated as an American National Standard on July 8, 2003.

ASME B18 STANDARDS COMMITTEE

Standardization of Bolts, Nuts, Rivets, Screws, Washers, and Similar Fasteners

(The following is the roster of the Committee at the time of approval of this Standard.)

OFFICERS

D. A. Clever, *Chair*
R. D. Strong, *Vice Chair*
S. W. Vass, *Vice Chair*
A. Guzman, *Secretary*

COMMITTEE PERSONNEL

J. Altman , Rotor Clip Co.	M. Levison , <i>Alternate</i> , ITW Shakeproof Assembly Co.
J. H. Slass , <i>Alternate</i> , Rotor Clip Co.	J. G. Langenstein , Consultant
J. B. Belford , Lawson Products, Inc.	D. Liesche , Defense Supply Center
R. M. Byrne , Trade Association Management, Inc.	L. L. Lord , Caterpillar, Inc.
D. A. Clever , Deere & Co.	W. J. Lutkus , Heil Coil Emhart
A. P. Cockman , Ford Motor Co.	A. D. McCrindle , Canadian Fasteners Institute
T. Collier , Cam-Tech Industries, Inc.	K. E. McCullough , Consultant
R. L. Crane , The American Society of Mechanical Engineers	R. B. Meade , Textron Fastening Systems
A. C. Dicola , Wrought Washer Manufacturing, Inc.	M. D. Prasad , General Motors Corp.
B. A. Dusina , Federal Screw Works	S. Savoji , ITW Medalist
D. S. George , Ford Motor Co.	W. Schevey , BGM Fastener Co., Inc.
D. L. Droblich , <i>Alternate</i> , Ford Motor Co.	R. D. Strong , General Motors Corp.
J. Greenslade , Greenslade and Co.	R. Torres , NFDA
J. Grey , Fastener Consulting Services, Inc.	S. W. Vass , Lake Erie Screw Corp.
B. Hasiuk , Defense Supply Center	C. B. Wackrow , MNP Corp.
A. Herskovitz , Consultant	R. G. Weber , Fairfield University
J. Hubbard , Rockford Fastener, Inc.	W. K. Wilcox , Consultant
J. F. Koehl , Spirol International Corp.	C. J. Wilson , Industrial Fasteners Institute
W. H. Kopke , ITW Shakeproof Assembly Co.	R. B. Wright , Wright Tool Co.
	J. G. Zeratsky , National Rivet and Manufacturing Co.

SUBCOMMITTEE 3 — SOCKET HEAD, CAP, AND SET SCREWS (B18)

R. Kerr , <i>Chair</i> , Kerr Lakeside Inc.	M. Keller , Para CAD
R. L. Crane , <i>Secretary</i> , The American Society of Mechanical Engineers	H. Lo , Defense Supply Center
J. Buda , SPS Tech	L. Lord , Caterpillar, Inc.
T. Collier , Cam-Tech Industries, Inc.	R. B. Meade , Textron Fastening Systems
J. Foote , Trade Association Management, Inc.	L. Schroeder , Kansas Department of Transportation
J. Greenslade , Greenslade & Co.	G. Simpson , Semblex Corp.
J. Grey , Fastener Consulting Services, Inc.	R. Strong , GM Vehicle Engineering Center
A. Herskovitz , Consultant	J. Tyler , Holo-Krome
M. W. Holubecki , Electric Boat Corp.	C. B. Wackrow , MNP Corp.
J. Hubbard , Rockford Fastener, Inc.	P. Werner , Safety Socket Screw Corp.
	W. Wilcox , Consultant
	C. J. Wilson , Industrial Fasteners Institute

CORRESPONDENCE WITH THE B18 COMMITTEE

General. ASME Standards are developed and maintained with the intent to represent the consensus of concerned interests. As such, users of this Standard may interact with the Committee by requesting interpretations, proposing revisions, and attending Committee meetings. Correspondence should be addressed to:

Secretary, B18 Standards Committee
The American Society of Mechanical Engineers
Three Park Avenue
New York, NY 10016-5990

Proposing Revisions. Revisions are made periodically to the Standard to incorporate changes that appear necessary or desirable, as demonstrated by the experience gained from the application of the Standard. Approved revisions will be published periodically.

The Committee welcomes proposals for revisions to this Standard. Such proposals should be as specific as possible, citing the paragraph number(s), the proposed wording, and a detailed description of the reasons for the proposal, including any pertinent documentation.

Interpretations. Upon request, the B18 Committee will render an interpretation of any requirement of the Standard. Interpretations can only be rendered in response to a written request sent to the Secretary of the B18 Standards Committee.

The request for interpretation should be clear and unambiguous. It is further recommended that the inquirer submit his/her request in the following format:

Subject: Cite the applicable paragraph number(s) and the topic of the inquiry.
Edition: Cite the applicable edition of the Standard for which the interpretation is being requested.
Question: Phrase the question as a request for an interpretation of a specific requirement suitable for general understanding and use, not as a request for an approval of a proprietary design or situation. The inquirer may also include any plans or drawings, which are necessary to explain the question; however, they should not contain proprietary names or information.

Requests that are not in this format may be rewritten in the appropriate format by the Committee prior to being answered, which may inadvertently change the intent of the original request.

ASME procedures provide for reconsideration of any interpretation when or if additional information that might affect an interpretation is available. Further, persons aggrieved by an interpretation may appeal to the cognizant ASME Committee or Subcommittee. ASME does not "approve," "certify," "rate," or "endorse" any item, construction, proprietary device, or activity.

Attending Committee Meetings. The B18 Standards Committee regularly holds meetings, which are open to the public. Persons wishing to attend any meeting should contact the Secretary of the B18 Standards Committee.

SOCKET CAP, SHOULDER, AND SET SCREWS, HEX AND SPLINE KEYS (INCH SERIES)

1 INTRODUCTORY NOTES

1.1 Scope

1.1.1 This Standard covers complete general and dimensional data for various types of hexagon and spline (fluted) socket cap screws, shoulder screws, set screws, and hexagon and spline keys recognized as an American National Standard. Also, included are appendices that provide specifications for hexagon and spline socket gages and gaging, tables showing applicability of keys and bits to various socket screws types and sizes, drill and counterbore sizes for socket head cap screws, and formulas on which dimensional data are based. However, where questions arise concerning acceptance of product, the dimensions in the tables shall govern over recalculation by formula.

1.1.2 The inclusion of dimensional data in this Standard is not intended to imply that all of the products described are stock production sizes. Consumers should consult with manufacturers concerning lists of stock production sizes.

1.2 Socket Cap Screws

The head types covered by this Standard are specified in paras. 1.2.1 through 1.2.5.

1.2.1 Socket Head Cap Screws. The socket head shall have a flat chamfered top surface with smooth or knurled cylindrical sides and a flat bearing surface. Specifications are given in Tables 1A through 1F. Both hexagon and spline socket types are included.

Dimensions for drilled holes and counterbores are included in Table A-1 of Nonmandatory Appendix A.

1.2.2 Drilled Hexagon Socket Head Cap Screws. Specifications for hexagon socket head cap screws having two, four, and six holes drilled in the head for lock wire application are given in Table 1F.

1.2.3 Socket Flat Countersunk Head Cap Screws. The flat countersunk head shall have a flat top surface and a conical bearing surface with included angle of approximately 82 deg. Specifications are given in Tables 2A, 2B, and 2C. Both hexagon and spline socket types are included.

1.2.4 Socket Button Head Cap Screws. The button head shall have a low rounded top surface with a large flat bearing surface. Specifications are given in Table 3. Both hexagon and spline socket types are included.

1.2.5 Socket Low Head Cap Screws. These are similar to socket head cap screws, except they have reduced head height and a smaller socket size. They are designed to be used in applications where height clearance is a problem. Specifications are given in Table 1G. Spline socket types are excluded.

1.3 Socket Head Shoulder Screws

The socket head shoulder screw is a hexagon socket head screw having a cylindrical shoulder under the head. Specifications are given in Table 4.

1.4 Socket Set Screws

The socket set screw is a screw threaded the entire length except for its length of point. The point is designed to bear on a mating part. The common point styles are cup, flat, oval, cone, and half dog. Specifications for set screws are shown in Tables 5A through 5C for both hexagon and spline socket types.

1.5 Keys and Bits for Driving Socket Screws

The tools for driving socket screws are hexagon or spline keys and bits, the specifications for which appear in Tables 8 and 9, respectively.

1.6 Dimensions

All dimensions in this Standard are given in inches unless stated otherwise.

All dimensions apply prior to coating unless stated otherwise.

1.7 Finish

Because of the high hardness of these products, it is recommended that they not be electroplated.

1.8 Identification Marking

Products described in paras. 1.2.1 through 1.2.4 and 1.3 with diameters larger than #10 must be marked with the identification of the source manufacturer or private label distributor accepting the responsibility for conformance to this Standard. Marking size, type, and location of marks are at manufacturer's option. Products shall not be marked on bearing surface.

1.9 Options

Options, where specified, shall be at the discretion of the manufacturer unless agreed upon otherwise by the manufacturer and purchaser.