



**ASA/ANSI S2.8-2007
(Revision of ANSI S2.8-1972)**

Reaffirmed by ANSI June 19, 2020

AMERICAN NATIONAL STANDARD

Technical Information Used for Resilient Mounting Applications

Secretariat:

Acoustical Society of America

Approved on March 22, 2007:

American National Standards Institute, Inc.

Abstract

This standard establishes requirements to promote appropriate exchange of information regarding the application and selection of isolation for the reduction of vibrations generated by equipment and machines. It is beyond the scope of this standard to present characteristics of resilient mountings. Rather, it is intended to outline, in standardized form, what data should be presented to enable the experienced designer to apply resilient mountings correctly. Also, the standard defines terminology in a further effort to ease the problem of communication between user and manufacturer.

ANSI/ASA S2.8-2007
(Revision of ANSI S2.8-1972)

Reaffirmed by ANSI
June 19, 2020

Reaffirmed by ANSI
March 16, 2017

Reaffirmed by ANSI
on April 18, 2012

AMERICAN NATIONAL STANDARD

Technical Information Used for Resilient Mounting Applications

ANSI S2.8-2007
(Revision of ANSI S2.8-1972)

Accredited Standards Committee S2, Mechanical Vibration and Shock

Standards Secretariat
Acoustical Society of America
35 Pinelawn Road, Suite 114 E
Melville, NY 11747-3177

The American National Standards Institute, Inc. (ANSI) is the national coordinator of voluntary standards development and the clearinghouse in the U.S.A. for information on national and international standards.

The Acoustical Society of America (ASA) is an organization of scientists and engineers formed in 1929 to increase and diffuse the knowledge of acoustics and to promote its practical applications.



ANSI S2.8-2007
(Revision of ANSI S2.8-1972)

AMERICAN NATIONAL STANDARD

Technical Information Used for Resilient Mounting Applications

Secretariat

Acoustical Society of America

Approved March 22, 2007

American National Standards Institute, Inc.

Abstract

This standard establishes requirements to promote appropriate exchange of information regarding the application and selection of isolation for the reduction of vibrations generated by equipment and machines. It is beyond the scope of this standard to present characteristics of resilient mountings. Rather, it is intended to outline, in standardized form, what data should be presented to enable the experienced designer to apply resilient mountings correctly. Also, the standard defines terminology in a further effort to ease the problem of communication between user and manufacturer.

AMERICAN NATIONAL STANDARDS ON ACOUSTICS

The Acoustical Society of America (ASA) provides the Secretariat for Accredited Standards Committees S1 on Acoustics, S2 on Mechanical Vibration and Shock, S3 on Bioacoustics, and S12 on Noise. These committees have wide representation from the technical community (manufacturers, consumers, trade associations, organizations with a general interest, and government representatives). The standards are published by the Acoustical Society of America as American National Standards after approval by their respective Standards Committees and the American National Standards Institute.


These standards are developed and published as a public service to provide standards useful to the public, industry, and consumers, and to Federal, State, and local governments.

Each of the accredited Standards Committees [operating in accordance with procedures approved by American National Standards Institute (ANSI)] is responsible for developing, voting upon, and maintaining or revising its own Standards. The ASA Standards Secretariat administers Committee organization and activity and provides liaison between the Accredited Standards Committees and ANSI. After the Standards have been produced and adopted by the Accredited Standards Committees, and approved as American National Standards by ANSI, the ASA Standards Secretariat arranges for their publication and distribution.

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered and that a concerted effort be made towards their resolution.

The use of an American National Standard is completely voluntary. Their existence does not in any respect preclude anyone, whether he or she has approved the Standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the Standards.

NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this Standard.



Acoustical Society of America
ASA Secretariat
35 Pinelawn Road, Suite 114E
Melville, New York 11747-3177
Telephone: 1 (631) 390-0215
Fax: 1 (631) 390-0217
E-mail: asastds@aip.org

© 2007 by Acoustical Society of America. This standard may not be reproduced in whole or in part in any form for sale, promotion, or any commercial purpose, or any purpose not falling within the provisions of the U.S. Copyright Act of 1976, without prior written permission of the publisher. For permission, address a request to the Standards Secretariat of the Acoustical Society of America.

Contents

1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Applications of isolation.....	6
5	Technical information needed for the selection and application of resilient mounting system	7
5.1	Classical model of resilient mounting.....	7
5.2	Transmissibility.....	7
5.3	Isolation efficiency.....	9
5.4	Effect of damping	10
5.5	Damping and energy dissipation.....	10
5.6	Effects of inertial bases	11
5.7	Effect of machine speed	11
5.8	Coupling of vertical motion and rocking.....	11
6	Requirements of the standard.....	12
6.1	Information supplied by the user of resilient mountings.....	12
6.2	Information supplied by the manufacturer of mountings.....	17

Tables

Table 1	— Information Supplied by the User	16
Table 2	— Information Supplied by the Mounting Manufacturer	20

Figures

Figure 1	— Base mounting system	2
Figure 2	— Center-of-gravity mounting system.....	2
Figure 3	— One-dimensional translational mass-spring-dashpot system: (a) excited by the support motion; (b) excited by force acting on the mass.....	7
Figure 4	— Transmissibility of mass-spring-dashpot system, [1].....	9
Figure 5	— Mass m with moment of inertia J supported on two isolators.....	12

Foreword

[This Foreword is for information only, and is not a part of the American National Standard ANSI S2.8-2007 American National Standard Technical Information Used for Resilient Mounting Applications].

This standard comprises a part of a group of definitions, standards, and specifications for use in mechanical vibration and shock. It was developed and approved by Accredited Standards Committee S2, Mechanical Vibration and Shock, under its approved operating procedures. Those procedures have been accredited by the American National Standards Institute (ANSI). The Scope of Accredited Standards Committee S2 is as follows:

Standards, specification, methods of measurement and test, and terminology in the field of mechanical vibration and shock, and condition monitoring and diagnostics of machines, including the effects of exposure to mechanical vibration and shock on humans, including those aspects which pertain to biological safety, tolerance and comfort.

This standard is a revision of ANSI S2.8-1972, which has been technically revised. This new edition has been restructured and some of the formulae, terms and definitions, and illustrations (Figures) have been revised and corrected. Additional exhibits, illustrations, and tables have been added to this revision of this document.

At the time this Standard was submitted to Accredited Standards Committee S2, Mechanical Vibration and Shock for approval, the membership was as follows:

R.L. Eshleman, *Chair*

A.T. Herfat, *Vice-Chair*

S.B. Blaeser, *Secretary*

Acoustical Society of America	S.I. Hayek
.....	B.E. Douglas (Alt.)
American Industrial Hygiene Association	J.J. Earshen
.....	D. Driscoll (Alt.)
Association of American Railroads	J. Moller
.....	N. Cooperrider (Alt.)
Calnetix	L. Hawkins
.....	P. McMullen (Alt.)
Caterpillar, Inc.	D. Roley
Charles M. Salter Associates	A. Nash
Commercial Vehicle Group	L. Mullinix
Emerson Electric – Copeland Corporation	A.T. Herfat
.....	M. Mezache (Alt.)
Endevco Corp.	B. Yang

GE Energy	R. Bankert
Infrared Training Center	G. Orlove
.....	R. Madding (Alt.)
John Deere	L. DeVries
Lord Corporation	L. Miller
.....	A. Crocket (Alt.)
Mechanical Solutions, Inc.	W.D. Marscher
.....	M. Gaydon (Alt.)
MIMOSA	K. Bever
.....	A. Johnston (Alt.)
National Institute for Occupational Safety & Health	R.G. Dong
.....	N.K. Kittusamy (Alt.)
National Institute of Standards & Technology	D.J. Evans
.....	S. Fick (Alt.)
PCB Group	R.D. Sill
.....	D. Lally (Alt.)
Power Tool Institute, Inc.	W.D. Spencer
.....	M. Hickok (Alt.)
Precision Labs	M. Kelly
Quest Technologies, Inc.	M. Wurm
.....	P. Battenberg (Alt.)
Sandia National Laboratories	D. Briand
.....	R.M. Cranwell (Alt.)
Shock and Vibration Information and Analysis Center	C.R. Welch
.....	H.C. Pusey (Alt.)
Scantek	R.J. Peppin
.....	M. Buzduga (Alt.)
Schenck Trebel Corp.	B. Dittmar
Society for Machinery Failure Prevention Technology	A.J. Hess
.....	H.A. Gaberson (Alt.)
Sundyne Corporation	F. Robinson
.....	T. Maceyka (Alt.)
U.S. Air Force	S.D. Smith
U.S. Department of Transportation	J. Pollard
.....	T. Raslear (Alt.)
U.S. Naval Sea Systems Command	R. Taddeo
.....	M.T. McGown (Alt.)
U.S. Naval Surface Warfare Center	P. Shang
.....	S. Antonides (Alt.)

UE Systems, Inc. M. Goodman

Vibration Institute R. Eshleman
..... D.J. Vendittis (Alt.)

Waukesha Magnetic Bearings K. Bornstein
..... R. Shultz (Alt.)

Individual Experts of Accredited Standards Committee S2, Mechanical Vibration and Shock, were:

A.J. Brammer
L.A. Herstein

D.F. Muster
D.D. Reynolds
D.E. Wasserman

Working Group S2/WG 4, Characterization of the Dynamic Mechanical Properties of Visco-elastic Polymers, which assisted Accredited Standards Committee S2, Mechanical Vibration and Shock, in the development of this standard, had the following membership.

W.M. Madigosky, Chair
J. Niemiec, Vice-Chair

D.A. Brown
R.J. Deigan
J.J. Dlubac
J. Fedderly

A.T. Herfat
D. Hunston
J. Jarzynski
R. Landel
G. Lee

J. Lee
M. Mezache
K. Ng
A.O. Sykes

Suggestions for improvements of this standard will be welcomed. They should be sent to Accredited Standards Committee S2, Mechanical Vibration and Shock, in care of the Standards Secretariat of the Acoustical Society of America, 35 Pinelawn Road, Suite 114E, Melville, New York 11747-3177. Telephone: 631-390-0215; FAX: 631-390-0217; E-mail: asastds@aip.org

Introduction

Users of resilient mountings are sometimes handicapped in applying mounting systems properly because sufficient technical information is not furnished by the manufacturer. Consequently, the users often conduct their own experimental evaluation of mountings and perhaps unknowingly duplicate work already performed by the manufacturer. Also, in some industries and military applications, the user may not be at liberty to disclose applicable information which might otherwise facilitate suggestions and recommendations by the mounting manufacturer. Hence, many times the user must acquire considerable proficiency in the art of applying resilient mountings and, in these instances, they need appropriate technical information from the manufacturer.

On the other hand, some manufacturers of resilient mountings have experience covering a wide variety of mounting applications. Manufacturers, in most instances, are willing to use their background information for solving the user's mounting problems. However, it frequently is difficult for the manufacturer to provide this service, because the user has not furnished sufficient information to the manufacturer regarding the application.

This American National Standard is intended to serve as a guide for the exchange of technical information regarding the application of isolation for vibrations generated by equipment and machines, and for use between the customer and supplier of resilient mounting systems for their proper applications.

For the purposes of this ANSI Standard, a resilient mounting system is defined as a flexible element or system used between an equipment item and its supporting structure to attenuate the transmission of shock or vibration from the equipment and machine to the structure.

American National Standard

Technical Information Used for Resilient Mounting Applications

1 Scope

This American National Standard establishes the requirements to promote an appropriate exchange of information regarding the application and selection of isolation for the reduction of vibrations generated by equipment and machines. Therefore, use of this standard can improve communication among engineers, manufacturers and end-users concerned with vibration isolation.

It is beyond the scope of this standard to present characteristics of resilient mountings. Rather, it is intended to outline, in standardized form, what data and preliminary technical information should be presented to enable the experienced designer to apply resilient mountings correctly.

2 Normative references

The following referenced documents are indispensable for the application of this standard. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ANSI S1.1-1994 *American National Standard Acoustical Terminology*

ANSI S2.1-2000/ISO 2041:1990 *American National Standard Vibration and shock - Vocabulary*

3 Terms and definitions

For the purposes of this standard, the terms and definitions given in ANSI S1.1-1994, ANSI S2.1-2000/ISO 2041:1990, and the following apply.

3.1

axial stiffness

load-deflection ratio of a mounting along the line of application of the load

NOTE Stiffness is the ratio of change of force to the corresponding change in translational (or rotational) deformation of an elastic element. The stiffness can be dynamic or static, and the mounting shall have an axis of symmetry.

3.2

base mounting system

system which has the resilient mountings attached underneath the mounted item (see Figure 1)