



**ASA/ANSI S2.34-1964
(ASA 34-1984)**

Reaffirmed by ANSI June 19, 2020

AMERICAN NATIONAL STANDARD

Guide to the Experimental Determination of Rotational Mobility Properties and the Complete Mobility Matrix

Secretariat:

Acoustical Society of America

Approved on 6 July 1984:

American National Standards Institute, Inc.

Abstract

This Guide is the fourth part of a set of five documents covering the experimental determination of the mechanical mobility of structures by a variety of methods appropriate for different test situations. The present Part IV of the set offers guidance in situations where it is necessary to measure not only translational motion responses to a translational exciting force but also the rotational and combination terms of the 6x6 mobility matrix required to fully describe each point of a structure. This part of the set is published as an ANSI Guide rather than as a Standard because the state of the art of rotational motion and force measurement is still in flux. Several methods are described, all requiring attached excitors.

**ANSI S2.34-1984
(ASA 34-1984)**

Reaffirmed by ANSI
July 10, 2001

Reaffirmed by ANSI
May 24, 2005

Reaffirmed by ANSI
April 22, 2010

Reaffirmed by ANSI
April 1, 2015

Reaffirmed by ANSI
June 19, 2020

Standards Secretariat
Acoustical Society of America
335 East 45th Street
New York, New York 10017

AMERICAN NATIONAL STANDARD

Guide to the Experimental Determination of Rotational Mobility Properties and the Complete Mobility Matrix

This Guide is the fourth part of a set of five documents covering the experimental determination of the mechanical mobility of structures by a variety of methods appropriate for different test situations. The present Part IV of the set offers guidance in situations where it is necessary to measure not only translational motion responses to a translational exciting force but also the rotational and combination terms of the 6×6 mobility matrix required to fully describe each point of a structure. This part of the set is published as an ANSI Guide rather than as a Standard because the state of the art of rotational motion and force measurement is still in flux. Several methods are described, all requiring attached exciters.

Published by the American Institute of Physics for the Acoustical Society of America

AMERICAN NATIONAL STANDARDS ON ACOUSTICS


The Acoustical Society of America is the Secretariat for Accredited Standards Committees S1 on Acoustics, S2 on Mechanical Shock and Vibration, S3 on Bioacoustics, and S12 on Noise. Standards developed by these committees, which have wide representation for the technical community (manufacturers, consumers, and general-interest representatives), are published by the Acoustical Society of America as American National Standards after approval by their respective standards committees.

These standards are developed as a public service to provide standards useful to the public, industry, and consumers, and to Federal, State, and local governments.

This guide was approved by the American National Standards Institute as ANSI S2.34-1984 on 6 July 1984.

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. An American National Standard is intended as a guide to aid the manufacturer, the consumer, and the general public. The existence of an American National Standard does not in any respect preclude anyone, whether he has approved the standard or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standard. American National Standards are subject to periodic review and users are cautioned to obtain the latest editions.

Caution Notice: An American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken to reaffirm, revise, or withdraw this standard no later than five years from the date of publication.



Copyright © 1984 by the Acoustical Society of America. No portion of this publication may be quoted or reproduced in any form without permission of the Acoustical Society of America.

FOREWORD

[This Foreword is not a part of American National Standard Guide S2.34-1984 (ASA Catalog No. 34-1984).]

This standard Guide has been developed under the jurisdiction of Accredited Standards Committee S2 using the American National Standards Institute (ANSI) Committee Procedure. The Acoustical Society of America holds the Secretariat for Committee S2. This guide has been approved for publication by S2 and by the Acoustical Society of America Committee on Standards (ASACOS).

The scope of Standards Committee S2 on Mechanical Shock and Vibration under whose jurisdiction this standard was prepared is as follows:

Standards, specifications, methods of measurement and test, and terminology in the fields of mechanical shock and vibration, but excluding those aspects which pertain to safety, tolerance, and comfort.

At the time it approved this standard Guide, the S2 Committee had the following members (organization/representatives):

P. Maedel, *Chairman*

S. Feldman, *Vice-Chairman*

A. Brenig, *Secretary*

Acoustical Society of America • P. H. Maedel, Jr., S. Feldman, (*Alt*)

American Iron & Steel Institute • E. H. Toothman, P. A. Hernandez (*Alt*)

American Mining Congress • G. R. Coonan, H. B. Johnson (*Alt*)

Anti-Friction Bearing Manufacturers Association • J. C. Morrison

Institute of Environmental Sciences • H. Pusey

National Bureau of Standards • M. R. Serbyn, D. R. Flynn (*Alt*)

National Electrical Manufacturers Association • D. V. Wright, J. R. Keinz (*Alt*)

Naval Biodynamics Laboratory • J. Guignard, C. L. Ewing (*Alt*)

Naval Ship Research & Development Center • A. Zaloumis

Schenck Trebel Corporation • D. G. Stadelbauer

U. S. Dept. of the Air Force • N. Bingman, R. F. Wilkus (*1st Alt*), J. P. Henderson (*2nd Alt*)

U. S. Dept. of Defense • H. Pusey, R. J. Volin (*Alt*)

U. S. Dept. of the Navy—Naval Sea Systems Command • A. R. Paladino, D. D. Bernhard (*Alt*)

Individual experts of the S2 Committee were

P. K. Baade
R. G. Bartheld
J. C. Barton
L. Batchelder
G. Booth

R. A. DiTaranto
K. M. Eldred
R. Eshleman
S. Feldman
D. Johnson

D. Muster
H. L. Rich
A. O. Sykes
H. E. von Gierke

Working Group S2-74 on Measurement of Mechanical Mobility, which assisted the committee in preparing this standard Guide, had the following membership:

P. K. Baade, *Chairman*

R. R. Bouche
J. P. Catlin
B. E. Douglas
E. L. Hixson
A. C. Keller

S. R. Mannava
L. D. Mitchell
E. L. Peterson
D. D. Reynolds
S. S. Sattinger

D. O. Smallwood
J. E. Smith
E. V. Thomas

Suggestions for improvement of this standard Guide will be welcomed. They should be sent to the Standards Secretariat, Acoustical Society of America, 335 East 45th Street, New York, NY 10017.

CONTENTS

0 INTRODUCTION	1
0.1 Introduction to the Set of ANSI Mobility Measurement Documents.....	1
0.2 Introduction to Part IV of the Set (American National Standard Guide S2.34-1984)	2
1 PURPOSE AND SCOPE	2
1.1 Purpose	2
1.2 Scope	2
1.3 Related Standards	2
2 DEFINITIONS	3
2.1 Rotational Mobility	3
2.1.1 Rotational Velocity/Moment Mobility	3
2.1.2 Rotational Velocity/Force Mobility	3
2.1.3 Translational Velocity/Moment Mobility	3
2.2 The Mobility Matrix	3
3 DETERMINATION OF ROTATIONAL MOBILITY USING A SINGLE EXCITER AT MULTIPLE POSITIONS	4
3.1 Background	4
3.2 Direct Method	4
3.2.1 Rotational Mobilities as Spatial Derivatives of Translational Mobilities	4
3.2.2 Finite Difference Evaluation of Derivatives	5
3.2.3 Implementation and Limitations	5
3.3 Methods Using Special Fixtures.....	6
4 MEASUREMENT OF THE COMPLETE MOBILITY MATRIX BY THE SCALAR FIXTURE METHOD..	7
4.1 Background	7
4.2 Measurement Method.....	7
4.3 Experimental Apparatus	9
4.4 Calibration	10
4.5 Data Accuracy.....	11
4.6 Coordinate Axes Translation	11
5 REFERENCES	12
APPENDIX A: EXCITATION SOURCE SCALAR MATRIX FIXTURE DESIGNS	12
FIGURES	
FIG. 1 General coordinate system for structural mobility measurements	3
FIG. 2 Rotational mobilities as spatial derivatives of translational mobilities.....	4
FIG. 3 Exciting block MK 1(not to scale).....	6
FIG. 4 Exciting block MK 2(not to scale).....	7
FIG. 5 Schematic of excitation source	8
FIG. 6 Cube with cubic void	9
FIG. 7 Fixture attachment points arrangement	10
FIG. 8 Wire drive rod.....	10
FIG. 9 (a) Calibration mass; (b) calibration schematic.....	10
FIG. 10 Valid measurement region for scalar matrix fixture method.....	11
FIG. A1 Hollow right circular cylinder	12
FIG. A2 Right circular cylinder with cylindrical void	12
FIG. A3 Solid right circular cylinders with center space.....	13
FIG. A4 Cylindrical cup	13

FIG. A5 Cylindrical cup (diameter in UL units)	14
FIG. A6 Cylindrical cup (g/h ratio)	14
FIG. A7 Cylindrical cup (h/D ratio)	15
FIG. A8 Cylindrical cup (volume in UL units)	15

TABLES

TABLE I	Finite difference approximations to the first partial derivatives of a translational mobility	5
TABLE II	Finite difference approximations to the second partial derivative of a translational mobility .	5

American National Standard

Guide to the Experimental Determination of Rotational Mobility Properties and the Complete Mobility Matrix

0 INTRODUCTION

0.1 Introduction to the Set of ANSI Mobility Measurement Documents

Dynamic characteristics of structures can be determined as a function of frequency from measurements of mobility or of the related frequency response functions called accelerance and dynamic compliance. Each of these frequency response functions is a ratio of the motion response of a structure to the excitation force or moment at a single point. The magnitude and the phase of these ratios are functions of frequency.

Accelerance and dynamic compliance differ from mobility only in that the motion response is expressed in terms of acceleration or displacement, respectively, instead of in terms of velocity. To simplify the standards, only the term "mobility" will be used. It is understood that all test procedures and requirements described are applicable also to the determination of accelerance and dynamic compliance.

Mobility measurements are typically used for:

- (1) Predicting the dynamic response of structures to known or assumed input excitation;
- (2) Determining the modal properties of a structure (natural frequencies, mode shapes, and damping ratios);
- (3) Predicting the dynamic interaction of interconnected structures;
- (4) Determining dynamic properties (i.e., the complex modulus of elasticity) of materials in pure or composite forms;
- (5) Checking the validity and improving the accuracy of mathematical models of structures.

For some applications, a *complete* description of the dynamic characteristics may be required considering translational forces and motions along three mutually perpendicular axes, as well as moments and rotational motions about these three axes. This results in a 6×6 mobility matrix for each location of interest. For N locations on a structure, the system thus has an overall mobility matrix of size $6N \times 6N$.

For most practical applications, it is not necessary to know the *entire* $6N \times 6N$ matrix. Often, it is sufficient to measure the driving-point mobility and a few

transfer mobilities by exciting with a force at a single point in a single direction and measuring the translational response motions at key points on the structure. In other applications, only rotational response to moment excitation around a single axis may be of interest.

In order to simplify the use of standards for the varied mobility measurement tasks encountered in practice, a set of ANSI documents on mobility measurement will be published in five separate parts:

Part I (ANSI S2.31-1979) covers basic definitions and transducers. The information in Part I is common to most mobility measurement tasks.

Part II (ANSI S2.32-1982) covers mobility measurements using single-point translational excitation with an attached exciter.

Part III will cover mobility measurements using single-point rotational excitation with an attached exciter. This information is primarily intended for rotor system torsional resonance predictions.

Part IV (the present Guide) covers measurements of the entire mobility matrix using attached exciters. This includes the translational, rotational, and combination terms required for the 6×6 matrix for each location on the structure.

Part V will cover mobility measurements using impact excitation with an exciter which is not attached to the structure.

NOTE: At the time when Part IV was published, Parts III and V were in preparation. Part IV is published as an ANSI Guide, whereas Parts I and II are ANSI standards.

Mechanical mobility is defined as the frequency response function formed by the ratio of the phasor of the translational or rotational response velocity to the phasor of the applied force or moment excitation. If the response is measured with an accelerometer, conversion to velocity is required to obtain the mobility. Alternatively, the ratio of acceleration to force or moment, called accelerance, may be used to characterize a structure. In still other cases, dynamic compliance, the ratio of displacement to force or moment, may be used.