



ASA/ANSI S12.67-2008

Reaffirmed by ANSI June 19, 2020

AMERICAN NATIONAL STANDARD

Pre-Installation Airborne Sound Measurements and Acceptance Criteria of Shipboard Equipment

Secretariat:

Acoustical Society of America

Approved on November 20, 2008:

American National Standards Institute, Inc.

Abstract

This standard describes instrumentation and procedures for the pre-installation measurement and analysis of airborne noise generated by shipboard equipment. Maximum noise level criteria are presented for several types of equipment. This standard may be used in the achievement of shipboard noise goals through the timely and affordable airborne noise testing of shipboard equipment before it is delivered and installed.

This standard is based on MIL-STD-740-1 "Airborne Sound Measurements and Acceptance Criteria of Shipboard Equipment" and MIL-STD-1474D (Requirement 5, Shipboard Equipment Noise).

ANSI/ASA S12.67-2008

Reaffirmed by ANSI
November 26, 2013

Reaffirmed by ANSI
June 19, 2020

AMERICAN NATIONAL STANDARD

Pre-Installation Airborne Sound Measurements and Acceptance Criteria of Shipboard Equipment

ANSI/ASA S12.67-2008

Accredited Standards Committee S12, Noise

Standards Secretariat
Acoustical Society of America
35 Pinelawn Road, Suite 114 E
Melville, NY 11747-3177

The American National Standards Institute, Inc. (ANSI) is the national coordinator of voluntary standards development and the clearinghouse in the U.S.A. for information on national and international standards.

The Acoustical Society of America (ASA) is an organization of scientists and engineers formed in 1929 to increase and diffuse the knowledge of acoustics and to promote its practical applications.



AMERICAN NATIONAL STANDARD

Pre-Installation Airborne Sound Measurements and Acceptance Criteria of Shipboard Equipment

Secretariat:

Acoustical Society of America

Approved November 20, 2008 by:

American National Standards Institute, Inc.

Abstract

This standard describes instrumentation and procedures for the pre-installation measurement and analysis of airborne noise generated by shipboard equipment. Maximum noise level criteria are presented for several types of equipment. This standard may be used in the achievement of shipboard noise goals through the timely and affordable airborne noise testing of shipboard equipment before it is delivered and installed.

This standard is based on MIL-STD-740-1 "Airborne Sound Measurements and Acceptance Criteria of Shipboard Equipment" and MIL-STD-1474D (Requirement 5, Shipboard Equipment Noise).

AMERICAN NATIONAL STANDARDS ON ACOUSTICS

The Acoustical Society of America (ASA) provides the Secretariat for Accredited Standards Committees S1 on Acoustics, S2 on Mechanical Vibration and Shock, S3 on Bioacoustics, S3/SC 1 on Animal Bioacoustics, and S12 on Noise. These committees have wide representation from the technical community (manufacturers, consumers, trade associations, organizations with a general interest, and government representatives). The standards are published by the Acoustical Society of America as American National Standards after approval by their respective Standards Committees and the American National Standards Institute (ANSI).


These standards are developed and published as a public service to provide standards useful to the public, industry, and consumers, and to Federal, State, and local governments.

Each of the Accredited Standards Committees (operating in accordance with procedures approved by ANSI) is responsible for developing, voting upon, and maintaining or revising its own Standards. The ASA Standards Secretariat administers Committee organization and activity and provides liaison between the Accredited Standards Committees and ANSI. After the Standards have been produced and adopted by the Accredited Standards Committees, and approved as American National Standards by ANSI, the ASA Standards Secretariat arranges for their publication and distribution.

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered and that a concerted effort be made towards their resolution.

The use of an American National Standard is completely voluntary. Their existence does not in any respect preclude anyone, whether he or she has approved the Standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the Standards.

NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this Standard.



Acoustical Society of America
ASA Secretariat
35 Pinelawn Road, Suite 114E
Melville, New York 11747-3177
Telephone: 1 (631) 390-0215
Fax: 1 (631) 390-0217
E-mail: asastds@aip.org

© 2008 by Acoustical Society of America. This standard may not be reproduced in whole or in part in any form for sale, promotion, or any commercial purpose, or any purpose not falling within the provisions of the U.S. Copyright Act of 1976, without prior written permission of the publisher. For permission, address a request to the Standards Secretariat of the Acoustical Society of America.

Contents

1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Measurement procedure	2
4.1	Measurements	2
4.2	Measurement point locations	4
4.3	Mounting of equipment	7
4.4	External influences	8
4.5	Equipment operating conditions and background noise	8
4.6	Calibration of instrumentation	11
5	Application guidance	11
6	Reporting	12
6.1	Types of reports	12
6.2	General report	12
6.3	Detailed report	13
6.4	Drawings and sketches	14
6.5	Test data	15
Annex A	(normative) Airborne sound acceptance criteria	16
A.1	Introduction	16
A.2	Recommended acceptance criteria and associated threshold levels	16

Figures

Figure 1	— Sound measurement locations for small equipment, in addition to location of operator's head	5
Figure 2	— Sound measurement locations for valves	5
Figure 3	— Sound measurement locations for medium size equipment, in addition to location of operator's head	6
Figure 4	— Sound measurement locations for large equipment	7
Figure 5	— Standard test fixture	9

Tables

Table A.1	— Threshold A-weighted and C-weighted sound levels in dB re 20 μ Pa	17
Table A.2	— Acceptable octave-band sound pressure levels in dB re 20 μ Pa	19

Foreword

[This Foreword is for information only and is not a part of the American National Standard ANSI/ASA S12.67-2008 American National Standard Pre-Installation Airborne Sound Measurements and Acceptance Criteria of Shipboard Equipment.]

This standard comprises a part of a group of definitions, standards, and specifications for use in noise. It was developed and approved by Accredited Standards Committee S12, Noise, under its approved operating procedures. Those procedures have been accredited by the American National Standards Institute (ANSI). The Scope of Accredited Standards Committee S12 is as follows:

Standards, specifications, and terminology in the field of acoustical noise pertaining to methods of measurement, evaluation, and control; including biological safety, tolerance, and comfort, and physical acoustics as related to environmental and occupational noise.

This standard is not comparable to any existing ISO Standard.

At the time this standard was submitted to Accredited Standards Committee S12, Noise, for approval, the membership was as follows:

R.D. Hellweg, *Chair*

W.J. Murphy, *Vice Chair*

S.B. Blaeser, *Secretary*

Acoustical Society of America	B.M. Brooks
.....	D. Lubman (Alt.)
Aearo Company	E.H. Berger
Air-Conditioning and Refrigeration Institute	S. Lind
.....	D. Brown (Alt.)
Alcoa Inc.	W.D. Gallagher
American Academy of Otolaryngology	R.A. Dobie
.....	L.A. Michael (Alt.)
American Industrial Hygiene Association	D. Driscoll
.....	S.N. Hacker (Alt.)
American Society of Heating, Refrigeration and Air-Conditioning Engineers	R.J. Peppin
American Speech-Hearing-Language Association	L.A. Wilber
.....	V. Gladstone (Alt.)
Bruel & Kjaer Instruments, Inc.	M. Alexander
.....	J. Chou (Alt.)
Caterpillar, Inc.	K.G. Meitl
Compressed Air and Gas Institute	R.C. Johnson
.....	D.R. Bookshar (Alt.)

Council for Accreditation in Occupational Hearing Conservation	J.A. Mann E.H. Berger (Alt.)
Emerson Electric – Copeland Corporation	A.T. Herfat
General Motors	D. Moore
Howard Leight Industries	B. Witt V. Larson (Alt.)
Information Technology Industry Council	R.D. Hellweg J. Rosenberg (Alt.)
Institute of Noise Control Engineering	B. Tinianov M. Lucas (Alt.)
International Safety Equipment Association	J. Birkner J.C. Bradley (Alt.)
James, Anderson & Associates	R.R. Anderson R.R. James (Alt.)
John Deere	K. Cone
Modular Building Institute	D. Shuford J. Brosius (Alt.)
National Council of Acoustical Consultants	J. Erdreich G.E. Winzer (Alt.)
National Hearing Conservation Association	K. Michael
National Institute for Occupational Safety and Health	W.J. Murphy M. Stephenson (Alt.)
Noise Control Engineering, Inc.	M. Bahtiarian R. Fischer (Alt.)
Noise Pollution Clearinghouse	L. Blomberg
North American Insulation Manufacturers Association	R.D. Godfrey
PCB Group	K. Cox L. Harbaugh (Alt.)
Plantronics, Inc.	A.K. Woo
Power Tool Institute, Inc.	W.D. Spencer M. Hickok (Alt.)
Quest Technologies, Inc.	M. Wurm P. Battenberg (Alt.)
Rubber Manufacturers Association	S. Butcher A. Hartke (Alt.)
SAE	C. Michaels
Schomer and Associates	P.D. Schomer
U.S. Air Force	R. McKinley

U.S. Army Aeromedical Research LabW. Ahroon
U.S. Army Center for Health Promotion and Preventive Medicine W.A. Russell
 D. Fenneman (Alt.)
U.S. Army Construction Engineering Research Laboratories M. White
 L. Pater (Alt.)
U.S. Army Research Laboratory, Human Research and Engineering DirectorateK. Cave
 M.S. Binseel (Alt.)
U.S. Department of Transportation..... A. Konheim
U.S. Naval Surface Warfare Center CarderockM. Craun

Individual Experts of Accredited Standards Committee S12, Noise, were:

P.K. Baade	L.S. Finegold	P.D. Schomer
L.L. Beranek	W.J. Galloway	J.P. Seiler
E.H. Berger	R.D. Hellweg	L.C. Sutherland
S.H.P. Bly	R.K. Hillquist	W.R. Thornton
B.M. Brooks	W.W. Lang	L.A. Wilber
A.J. Campanella	D. Lubman	G.E. Winzer
K.M. Eldred	R.J. Peppin	G.S.K. Wong
	J. Pope	

Working Group S12/WG 40 – “Measurement of the noise aboard ships” which assisted Accredited Standards Committee S12, Noise, in the development of this standard, had the following membership:

S. Antonides, Chair
 S.A. Fisher, Vice-Chair

M. Bodde	A.F. Kilcullen	M. Strasberg
D.J. Evans	J. Niemiec	R.F. Taddeo
R. Fischer	R.J. Peppin	K. Tooke
P. Kasper	P.D. Schomer	D.J. Vendittis
	R. Shaw	

Suggestions for improvements to this standard will be welcomed. They should be sent to Accredited Standards Committee S12, Noise, in care of the Standards Secretariat of the Acoustical Society of America, 35 Pinelawn Road, Suite 114E, Melville, New York 11747-3177. Telephone: 631-390-0215; FAX: 631-390-0217; E-mail: asastds@aip.org.

Introduction

The installation of machinery and operating equipment onboard ship often leads to a degradation in the acoustic environment in occupied spaces. Measurements taken according to standardized procedures and compared with acceptance criteria will provide requisite information to the shipbuilder for the proper selection and installation of equipment and for adequate acoustic design of shipboard spaces and areas.

This standard may be used in ship acquisition programs for the following purposes:

- To separate individual equipment noise from other compartment sources
- To avoid expensive and time-consuming rework of noisy equipment
- To provide early confirmation of the ship's acoustical design
- To assist in compartment noise predictions

The measurement procedures delineated herein primarily measure steady-state sound pressure levels due to equipment and near the equipment. Impact noise measurements are also included. These levels serve well in predicting sound pressure levels from the subject equipment to which crew members are exposed in ship spaces or compartments which have typical acoustic characteristics. To that end, when using this standard it is the intent that the sound pressure levels measured at each location near the equipment be compared to specified acceptance criteria and that an excess at any frequency or any location be considered a failure; averaging methods are not utilized. Sound power procedures and criteria, although useful under certain circumstances, are not covered in this standard.

American National Standard

Pre-Installation Airborne Sound Measurements and Acceptance Criteria of Shipboard Equipment

1 Scope

This standard specifies procedures and instrumentation for the sound pressure measurement of airborne sound generated by shipboard equipment. Exceptions or additions to the requirements of this standard may be granted or added by the purchaser of equipment being tested in accordance with this standard. Overall noise in ship compartments is a combination of noise generated from all equipment installed in or near that compartment as well as other possible sources. Noise in ship compartments is not addressed in this standard.

Airborne acceptance criteria for several grades of equipment are presented in Annex A.

2 Normative references

The following referenced documents are indispensable for the application of this standard. For dated references, only the edition cited applies.

ANSI S1.1-1994 (R 2004) *American National Standard Acoustical Terminology*

ANSI S1.4-1983 (R 2006) *American National Standard Specification for Sound Level Meters*

ANSI S1.11-2004 *American National Standard Specification for Octave-Band and Fractional-Octave-Band Analog and Digital Filters*

ANSI S1.40-2006 *American National Standard Specifications and Verification Procedures for Sound Calibrators*

3 Terms and definitions

For the purposes of this standard, the terms and definitions given in ANSI S1.1-1994 (R 2004) and the following apply:

3.1 equipment. Refers to any machine system, subsystem, or part thereof, which is being measured to determine compliance with the airborne acceptance criteria.

3.2 Mounts and equipment mounting

3.2.1 resilient mount. Device with elastic properties used to reduce transmission of structure-borne noise. Typically a shaped block of rubber or similar elastic material and used at discrete locations at the component's attachment points for the purpose of supporting the component and providing acoustic isolation between the component and the support foundation or structure, and which approximates a free-free condition.