

**INSTITUTE OF
ENVIRONMENTAL
SCIENCES AND
TECHNOLOGY**

**Design, Test and Evaluation Division
Recommended Practice 009.1**

IEST-RP-DTE009.1

Vibration Shaker System Selection

INSTITUTE OF ENVIRONMENTAL SCIENCES AND TECHNOLOGY

1827 Walden Office Square, Suite 400 |
Schaumburg, IL 60173 USA
Phone: (847) 981-0100 • Fax: (847) 981-4130
E-mail: iest@iest.org • Web: www.iest.org



COPYING IS ILLEGAL

This Recommended Practice is published by the **INSTITUTE OF ENVIRONMENTAL SCIENCES AND TECHNOLOGY** to advance design, test, and evaluation technology and the technical and engineering sciences. Its use is entirely voluntary, and determination of its applicability and suitability for any particular use is solely the responsibility of the user.

This Recommended Practice was prepared by and is under the jurisdiction of Working Group 009 of the Institute's Design, Test, and Evaluation Division.

Copyright© 1997 by the Institute of Environmental Sciences and Technology

Third printing, July 2017

ISBN 978-1-877862-58-8

INSTITUTE OF ENVIRONMENTAL SCIENCES AND TECHNOLOGY

1827 Walden Office Square, Suite 400 | Schaumburg, IL 60173 USA

Phone: (847) 981-0100 • Fax (847) 981-4130

E-mail: iest@iest.org • Web: www.iest.org

COPYING IS ILLEGAL

VIBRATION SHAKER SYSTEM SELECTION

IEST-RP-DTE009.1

CONTENTS

1	SCOPE AND LIMITATIONS	6
2	REFERENCES AND APPLICABLE DOCUMENTS	6
3	TERMS AND DEFINITIONS	6
4	BACKGROUND AND PURPOSE	7
5	SHAKER SELECTION FOR VIBRATION AND SHOCK	7
6	NONRECOMMENDED PRACTICES	14
	Table 1—Frequency range and waveforms	8
	Table 2—Displacement and velocity	10
	Table 3—Worksheet for determining target tests	15
	PROPOSAL FOR IMPROVEMENT	17

VIBRATION SHAKER SYSTEM SELECTION IEST-RP-DTE009.1

1 SCOPE AND LIMITATIONS

1.1 Scope

The purpose of this Recommended Practice (RP) is to define an orderly approach that addresses the major issues involved in selecting a shaker for dynamic testing. In some cases, this selection process is associated with deciding which shaker system to procure. In other cases, the user will already have shaker systems available (in-house or at commercial test laboratories) and must decide which one is best suited for the task at hand. The process is the same in either case.

Shakers are generally used for sine vibration, random vibration, and many types of shock tests.

It is the intent of this document to cover the following applications for shakers: simulation of operating conditions, design qualification tests, transportation simulation, and vibration for environmental stress screening (ESS).

All major types of shaker systems will be included in the discussions, namely: electrodynamic (E-D), servo-hydraulic (hydraulic), mechanical, and pneumatic impactor. In the context of this Recommended Practice, a shaker system includes the power supply (electronic, hydraulic, or pneumatic) as well as the cooling system required for the shaker system. Closed-loop control systems (required to run tests on E-D and hydraulic shakers) are addressed in a different RP.

1.2 Limitations

This document addresses technical matters and does not present any issues relating to specific commercial applications. This document also does not address any specific financial considerations, which certainly must be considered when selecting a vibration shaker system.

2 REFERENCES AND APPLICABLE DOCUMENTS

None.

3 TERMS AND DEFINITIONS

armature

That part of an electrodynamic shaker that moves with the payload.

The armature consists of a mounting table, a driver coil, and the structure that connects the mounting table to the driver coil.

axial resonance

The first mode of vibration of an armature that has the mounting table moving out-of-phase with the driver coil.

diaphragm mode

The first mode of vibration of an armature that has significant variations in vibration amplitude across the surface of the mounting table.

driver coil

The part of an armature that converts electrical energy to mechanical motion.

E-D

An abbreviation for electrodynamic (which see).

electrodynamic

A type of shaker that uses electrical energy to create dynamic motion. In physics, the technology used is called the voice coil principal.

exciter

Another word for shaker.

hydraulic

A shortened form of the phrase servo-hydraulic.