

ASME B30.29-2012

# Self-Erecting Tower Cranes

**Safety Standard for Cableways, Cranes,  
Derricks, Hoists, Hooks, Jacks, and  
Slings**

**AN AMERICAN NATIONAL STANDARD**



**The American Society of  
Mechanical Engineers**

Copyright © 2013 by the American Society of Mechanical Engineers.  
No reproduction may be made of this material without written consent of ASME.



INTENTIONALLY LEFT BLANK



**ASME B30.29-2012**

# **Self-Erecting Tower Cranes**

---

**Safety Standard for Cableways, Cranes,  
Derricks, Hoists, Hooks, Jacks, and  
Slings**

**AN AMERICAN NATIONAL STANDARD**



**The American Society of  
Mechanical Engineers**

**Three Park Avenue • New York, NY • 10016 USA**

Copyright © 2013 by the American Society of Mechanical Engineers.  
No reproduction may be made of this material without written consent of ASME.



Date of Issuance: February 5, 2013

The next edition of this Standard is scheduled for publication in 2018. This Standard will become effective 1 year after the Date of Issuance.

ASME issues written replies to inquiries concerning interpretations of technical aspects of this Standard. Interpretations are published on the ASME Web site under the Committee Pages at <http://cstools.asme.org/> as they are issued. Interpretations will also be included with each edition.

Errata to codes and standards may be posted on the ASME Web site under the Committee Pages to provide corrections to incorrectly published items, or to correct typographical or grammatical errors in codes and standards. Such errata shall be used on the date posted.

The Committee Pages can be found at <http://cstools.asme.org/>. There is an option available to automatically receive an e-mail notification when errata are posted to a particular code or standard. This option can be found on the appropriate Committee Page after selecting “Errata” in the “Publication Information” section.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The Standards Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment that provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not “approve,” “rate,” or “endorse” any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor assumes any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

No part of this document may be reproduced in any form,  
in an electronic retrieval system or otherwise,  
without the prior written permission of the publisher.

The American Society of Mechanical Engineers  
Three Park Avenue, New York, NY 10016-5990

Copyright © 2013 by  
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS  
All rights reserved  
Printed in U.S.A.



# CONTENTS

Foreword .....	v
Committee Roster .....	vii
B30 Standard Introduction .....	ix
<b>Chapter 29-0</b> <b>Scope, Definitions, and References</b> .....	1
Section 29-0.1    Scope of B30.29 .....	1
Section 29-0.2    Definitions .....	1
Section 29-0.3    References .....	5
<b>Chapter 29-1</b> <b>General Construction and Installation</b> .....	7
Section 29-1.1    Site Preparation and Erection .....	7
Section 29-1.2    Rated Loads .....	9
Section 29-1.3    Stability .....	9
Section 29-1.4    Documentation .....	10
Section 29-1.5    Hoisting and Erecting Mechanism .....	11
Section 29-1.6    Slewing (Swing) Mechanism .....	12
Section 29-1.7    Travel Equipment .....	12
Section 29-1.8    Mast Erection Equipment .....	12
Section 29-1.9    Jib Erection Equipment .....	12
Section 29-1.10    Trolleys .....	12
Section 29-1.11    Brakes .....	13
Section 29-1.12    Operational Aids .....	13
Section 29-1.13    Pendants and Stay Ropes .....	13
Section 29-1.14    Reeving Accessories .....	13
Section 29-1.15    Counterweight and Ballast .....	13
Section 29-1.16    Crane Function Controls .....	13
Section 29-1.17    Electrical Equipment: General Requirements .....	14
Section 29-1.18    Operator’s Cab .....	14
Section 29-1.19    General Requirements .....	15
<b>Chapter 29-2</b> <b>Inspection, Testing, and Maintenance</b> .....	17
Section 29-2.1    Inspection .....	17
Section 29-2.2    Testing .....	18
Section 29-2.3    Maintenance and Repairs .....	18
Section 29-2.4    Rope Inspection, Replacement, and Maintenance .....	19
<b>Chapter 29-3</b> <b>Operation</b> .....	21
Section 29-3.1    Qualifications for and Conduct of Operators and Operating Practices .....	21
Section 29-3.2    Signals .....	26
Section 29-3.3    Miscellaneous .....	28
<b>Figures</b>	
29-0.2.1-1    Types of Self-Erect Tower Cranes by Base Type .....	2
29-0.2.1-2    Types of Self-Erect Tower Cranes by Mast Type .....	3
29-1.14-1    Wedge Sockets .....	14
29-2.4.2-1    Core Failure in Rotation-Resistant Ropes .....	20
29-3.2.4-1    Standard Hand Signals for Controlling Self-Erect Tower Cranes .....	27
29-3.3.3-1    Danger Zone for Cranes and Lifted Loads Operating Near Electrical Transmission Lines .....	29



**Table**

29-3.3.3-1

Required Clearance for Normal Voltage in Operation Near High-Voltage  
Power Lines and Operation in Transit With No Load and Boom or  
Mast Lowered ..... 30



# FOREWORD

This American National Standard, Safety Standard for Cableways, Cranes, Derricks, Hoists, Hooks, Jacks, and Slings, has been developed under the procedures accredited by the American National Standards Institute (ANSI). This Standard had its beginning in December 1916, when an eight-page Code of Safety Standards for Cranes, prepared by an American Society of Mechanical Engineers (ASME) Committee on the Protection of Industrial Workers, was presented at the annual meeting of ASME.

Meetings and discussions regarding safety on cranes, derricks, and hoists were held from 1920 to 1925, involving the ASME Safety Code Correlating Committee, the Association of Iron and Steel Electrical Engineers, the American Museum of Safety, the American Engineering Standards Committee [AESC, later changed to American Standards Association (ASA), and subsequently to the United States of America Standards Institute (USASI)], Department of Labor — State of New Jersey, Department of Labor and Industry — State of Pennsylvania, and the Locomotive Crane Manufacturers Association. On June 11, 1925, the AESC approved the ASME Safety Code Correlating Committee's recommendation and authorized the project with the U.S. Department of the Navy, Bureau of Yards and Docks, and ASME as sponsors.

In March 1926, invitations were issued to 50 organizations to appoint representatives to a Sectional Committee. The call for organization of this Sectional Committee was sent out October 2, 1926, and the committee organized November 4, 1926, with 57 members representing 29 national organizations.

Commencing June 1, 1927, and using the eight-page code published by ASME in 1916 as a basis, the Sectional Committee developed the Safety Code for Cranes, Derricks, and Hoists. The early drafts of this safety code included requirements for jacks, but due to inputs and comments on those drafts, the Sectional Committee decided in 1938 to make the requirements for jacks a separate code. In January 1943, ASA B30.2-1943 was published, addressing a multitude of equipment types, and in August 1943, ASA B30.1-1943 was published, addressing only jacks. Both documents were reaffirmed in 1952 and widely accepted as safety standards.

Due to changes in design, advancement in techniques, and general interest of labor and industry in safety, the Sectional Committee, under the joint sponsorship of ASME and the Bureau of Yards and Docks (now the Naval Facilities Engineering Command), U.S. Department of the Navy, was reorganized on January 31, 1962, with 39 members representing 27 national organizations.

The new Committee changed the format of ASA B30.2-1943 so that the multitude of equipment types it addressed could be published in separate volumes that could completely cover the construction, installation, inspection, testing, maintenance, and operation of each type of equipment included in the scope of ASA B30.2. This format change resulted in the initial publication of B30.3, B30.5, B30.6, B30.11, and B30.16 being designated as revisions of B30.2, with the remainder of the B30 volumes being published as new volumes. The USASI changed its name to the American National Standards Institute in 1969, which resulted in B30 volumes from 1943 to 1968 being designated as either ASA B30, USAS B30, or ANSI B30, depending on their date of publication.

In 1982, the Committee was reorganized as an Accredited Organization Committee, operating under procedures developed by ASME and accredited by ANSI.

This Standard presents a coordinated set of rules that may serve as a guide to government and other regulatory bodies and municipal authorities responsible for the guarding and inspection of the equipment falling within its scope. The suggestions leading to accident prevention are given both as mandatory and advisory provisions; compliance with both types may be required by employers of their employees.

In case of practical difficulties, new developments, or unnecessary hardship, the administrative or regulatory authority may grant variances from the literal requirements or permit the use of other devices or methods, but only when it is clearly evident that an equivalent degree of protection is thereby secured. To secure uniform application and interpretation of this Standard, administrative or regulatory authorities are urged to consult the B30 Committee, in accordance



with the format described in Section IX of the B30 Standard Introduction, before rendering decisions on disputed points.

Safety codes and standards are intended to enhance public safety. Revisions result from committee consideration of factors such as technological advances, new data, and changing environmental and industry needs. Revisions do not imply that previous editions were inadequate.

The ASME B30 Safety Standard for Cableways, Cranes, Derricks, Hoists, Hooks, Jacks, and Slings has not included cranes referred to as self-erect tower cranes in the past. Self-erect tower cranes have distinct operating, erecting, and transporting characteristics that do not allow them to be included in ASME B30.3 or ASME B30.5. The use of these machines has increased rapidly in the United States of America in recent years. In 2007, the ASME B30 committee voted to form a subcommittee to write a volume for the B30 Safety Standard covering self-erecting tower cranes.

This first edition of the B30.29 Volume was approved by the B30 Standards Committee and by ASME. It was approved by ANSI and designated as an American National Standard on November 27, 2012.



# ASME B30 COMMITTEE

## Safety Standard for Cableways, Cranes, Derricks, Hoists, Hooks, Jacks, and Slings

(The following is the roster of the Committee at the time of approval of this Standard.)

### STANDARDS COMMITTEE OFFICERS

**L. D. Means**, *Chair*  
**R. M. Parnell**, *Vice Chair*  
**K. M. Hyam**, *Secretary*

### STANDARDS COMMITTEE PERSONNEL

**N. E. Andrew**, ThyssenKrupp Steel USA, LLC  
**C. M. Robison**, *Alternate*, UT-Battelle/Oak Ridge National Laboratory  
**T. L. Blanton**, NACB, Inc.  
**P. A. Boeckman**, The Crosby Group  
**C. Lucas**, *Alternate*, The Crosby Group  
**R. J. Bolen**, Consultant  
**C. Cotton**, *Alternate*, Navy Crane Center  
**M. E. Brunet**, The Manitowoc Co., Inc.  
**T. A. Christensen**, Liberty Mutual Insurance Co.  
**M. W. Mills**, *Alternate*, Liberty Mutual Group  
**B. D. Closson**, Craft Forensic Services  
**B. A. Pickett**, *Alternate*, Forensic Engineering & Applied Science Institute  
**R. M. Cutshall**, Savannah River Nuclear Solutions, LLC  
**J. A. Danielson**, The Boeing Co.  
**P. Boyd**, *Alternate*, The Boeing Co.  
**L. D. DeMark, Sr.**, Equipment Training Solutions  
**D. F. Jordan**, *Alternate*, BP America  
**D. Eckstine**, Eckstine & Associates, Inc.  
**H. G. Leidich**, *Alternate*, Leidich Consulting Service, Inc.  
**R. J. Edwards**, NBIS  
**A. J. Egging**, National Oilwell Varco  
**C. W. Ireland**, *Alternate*, National Oilwell Varco  
**E. D. Fidler**, The Manitowoc Co., Inc.  
**G. D. Miller**, *Alternate*, Manitowoc Cranes  
**J. L. Gordon**, Acco Chain & Lifting Products  
**N. C. Hargreaves**, Consultant  
**C. E. Imerman**, *Alternate*, Link-Belt Construction Equipment Co.  
**J. J. Headley**, Crane Institute of America, Inc.  
**W. C. Dickinson**, *Alternate*, Crane Industry Services, LLC  
**G. B. Hetherston**, E. I. Dupont  
**J. Greenwood**, *Alternate*, Navy Crane Center  
**K. M. Hyam**, The American Society of Mechanical Engineers  
**D. C. Jackson**, Tulsa Winch Group  
**M. M. Jaxtheimer**, Navy Crane Center  
**S. Gridley**, *Alternate*, Navy Crane Center  
**P. R. Juhren**, Morrow Equipment Co., LLC  
**M. J. Quinn**, *Alternate*, Morrow Equipment Co., LLC  
**R. M. Kohner**, Landmark Engineering Service  
**D. Duerr**, *Alternate*, 2DM Associates, Inc.  
**C. E. Lucas**, The Crosby Group  
**A. J. Lusi, Jr.**, LuMark Consulting  
**D. W. Frantz**, *Alternate*, Ohio Operating Engineers, Local 18  
**E. K. Marburg**, Columbus McKinnon Corp.  
**D. K. Huber**, *Alternate*, Columbus McKinnon Corp.  
**L. D. Means**, Means Engineering & Consulting  
**D. A. Henninger**, *Alternate*, Bridon American  
**D. L. Morgan**, Mission Support Alliance  
**C. E. Brewer**, *Alternate*, Mission Support Alliance  
**G. L. Owens**, Consultant  
**R. M. Parnell**, Industrial Training International, Inc.  
**J. T. Perkins**, Consultant  
**J. E. Richardson**, U.S. Department of the Navy  
**K. Kennedy**, *Alternate*, Navy Crane Center  
**D. W. Ritchie**, Dave Ritchie Consultant, LLC  
**J. W. Rowland III**, Consultant  
**D. A. Moore**, *Alternate*, Unified Engineering  
**J. C. Ryan**, Boh Bros. Construction Co.  
**A. R. Ruud**, *Alternate*, Atkinson Construction  
**D. W. Smith**, CB&I  
**S. K. Rammelsberg**, *Alternate*, CB&I  
**W. J. Smith, Jr.**, NBIS  
**J. Schoppert**, *Alternate*, NBIS Claims & Risk Management  
**R. S. Stemp**, Lampson International, LLC  
**R. G. Strain**, Advanced Crane Technologies, LLC  
**J. Sturm**, Sturm Corp.  
**P. D. Sweeney**, General Dynamics Electric Boat  
**B. M. Casey**, *Alternate*, General Dynamics Electric Boat  
**J. D. Wiethorn**, Haag Engineering  
**R. C. Wild**, U.S. Army Corps of Engineers  
**E. B. Stewart**, *Alternate*, U.S. Army Corps of Engineers  
**D. N. Wolff**, National Crane/Manitowoc Cranes  
**J. A. Pilgrim**, *Alternate*, Manitowoc Cranes

### HONORARY MEMBERS

**J. W. Downs, Jr.**, Downs Crane & Hoist Co.  
**J. L. Franks**, Consultant  
**J. M. Klibert**, Lift-All, Inc.  
**R. W. Parry**, Consultant  
**P. S. Zorich**, RZP International Ltd.



### B30 INTEREST REVIEW GROUP

**P. W. Boyd**, The Boeing Co.  
**M. J. Eggenberger**, Bay Ltd.  
**A. Gomes Rocha**, Belgo Bekaert Arames  
**J. Hui**, School of Civil Engineering, Nanjing

**A. C. Mattoli**, Prowinch, LLC  
**M. W. Osborne**, E-Crane International USA  
**W. G. Rumburg**, Crane Consultants, Inc.

### B30 REGULATORY AUTHORITY COUNCIL

**C. Shelhamer**, *Chair*, New York City Department of Buildings  
**W. J. Dougherty, Jr.**, *Vice Chair*, City of Philadelphia  
**K. M. Hyam**, The American Society of Mechanical Engineers  
**L. G. Champion**, DOL/OSHA  
**C. Harris**, City of Chicago — Department of Buildings  
**C. Lemon**, Washington State Department of Labor and Industries

**L. C. Markee**, *Alternate*, Washington State Department of Labor and Industries  
**D. G. Merriman**, New York State Department of Labor  
**C. R. Smith**, Pennsylvania Department of State, Bureau of Professional and Occupational Affairs

### B30.29 SUBCOMMITTEE PERSONNEL

**D. W. Ritchie**, *Chair*, Dave Ritchie Consultant, LLC  
**L. D. Demark, Sr.**, Equipment Training Solutions  
**E. D. Fidler**, The Manitowoc Co., Inc.  
**M. D. Heacock**, Manitowoc Cranes  
**T. S. Heitchue**, Terex  
**P. R. Juhren**, Morrow Equipment Co., LLC

**A. J. Lusi, Jr.**, LuMark Consulting  
**K. J. Shinn**, K.J. Shinn, Inc.  
**W. J. Smith, Jr.**, NBIS  
**C. R. Thoreson**, All Tower Crane, LLC  
**J. D. Wiethorn**, Haag Engineering Co.



# SAFETY STANDARD FOR CABLEWAYS, CRANES, DERRICKS, HOISTS, HOOKS, JACKS, AND SLINGS

## B30 STANDARD INTRODUCTION

### SECTION I: SCOPE

The ASME B30 Standard contains provisions that apply to the construction, installation, operation, inspection, testing, maintenance, and use of cranes and other lifting and material-movement related equipment. For the convenience of the reader, the Standard has been divided into separate volumes. Each volume has been written under the direction of the ASME B30 Standard Committee and has successfully completed a consensus approval process under the general auspices of the American National Standards Institute (ANSI).

As of the date of issuance of this Volume, the B30 Standard comprises the following volumes:

- B30.1 Jacks, Industrial Rollers, Air Casters, and Hydraulic Gantries
- B30.2 Overhead and Gantry Cranes (Top Running Bridge, Single or Multiple Girder, Top Running Trolley Hoist)
- B30.3 Tower Cranes
- B30.4 Portal and Pedestal Cranes
- B30.5 Mobile and Locomotive Cranes
- B30.6 Derricks
- B30.7 Winches
- B30.8 Floating Cranes and Floating Derricks
- B30.9 Slings
- B30.10 Hooks
- B30.11 Monorails and Underhung Cranes
- B30.12 Handling Loads Suspended From Rotorcraft
- B30.13 Storage/Retrieval (S/R) Machines and Associated Equipment
- B30.14 Side Boom Tractors
- B30.15 Mobile Hydraulic Cranes  
(withdrawn 1982 — requirements found in latest revision of B30.5)
- B30.16 Overhead Hoists (Underhung)
- B30.17 Overhead and Gantry Cranes (Top Running Bridge, Single Girder, Underhung Hoist)
- B30.18 Stacker Cranes (Top or Under Running Bridge, Multiple Girder With Top or Under Running Trolley Hoist)
- B30.19 Cableways
- B30.20 Below-the-Hook Lifting Devices
- B30.21 Manually Lever-Operated Hoists
- B30.22 Articulating Boom Cranes
- B30.23 Personnel Lifting Systems
- B30.24 Container Cranes
- B30.25 Scrap and Material Handlers
- B30.26 Rigging Hardware
- B30.27 Material Placement Systems
- B30.28 Balance Lifting Units
- B30.29 Self-Erecting Tower Cranes
- B30.30 Ropes<sup>1</sup>

### SECTION II: SCOPE EXCLUSIONS

Any exclusion of, or limitations applicable to the equipment, requirements, recommendations or operations contained in this Standard are established in the affected volume's scope.

### SECTION III: PURPOSE

The B30 Standard is intended to

- (a) prevent or minimize injury to workers, and otherwise provide for the protection of life, limb, and property by prescribing safety requirements
- (b) provide direction to manufacturers, owners, employers, users, and others concerned with, or responsible for, its application
- (c) guide governments and other regulatory bodies in the development, promulgation, and enforcement of appropriate safety directives

### SECTION IV: USE BY REGULATORY AGENCIES

These Volumes may be adopted in whole or in part for governmental or regulatory use. If adopted for governmental use, the references to other national codes and standards in the specific volumes may be changed to refer to the corresponding regulations of the governmental authorities.

### SECTION V: EFFECTIVE DATE

(a) *Effective Date.* The effective date of this Volume of the B30 Standard shall be 1 yr after its date of issuance.

<sup>1</sup> This volume is currently in the development process.



Construction, installation, inspection, testing, maintenance, and operation of equipment manufactured and facilities constructed after the effective date of this Volume shall conform to the mandatory requirements of this Volume.

(b) *Existing Installations.* Equipment manufactured and facilities constructed prior to the effective date of this Volume of the B30 Standard shall be subject to the inspection, testing, maintenance, and operation requirements of this Standard after the effective date.

It is not the intent of this Volume of the B30 Standard to require retrofitting of existing equipment. However, when an item is being modified, its performance requirements shall be reviewed relative to the requirements within the current volume. The need to meet the current requirements shall be evaluated by a qualified person selected by the owner (user). Recommended changes shall be made by the owner (user) within 1 yr.

## SECTION VI: REQUIREMENTS AND RECOMMENDATIONS

Requirements of this Standard are characterized by use of the word *shall*. Recommendations of this Standard are characterized by the word *should*.

## SECTION VII: USE OF MEASUREMENT UNITS

This Standard contains SI (metric) units as well as U.S. Customary units. The values stated in U.S. Customary units are to be regarded as the standard. The SI units are a direct (soft) conversion from the U.S. Customary units.

## SECTION VIII: REQUESTS FOR REVISION

The B30 Standard Committee will consider requests for revision of any of the volumes within the B30 Standard. Such requests should be directed to

Secretary, B30 Standard Committee  
ASME Codes and Standards  
Three Park Avenue  
New York, NY 10016-5990

Requests should be in the following format:

- Volume: Cite the designation and title of the volume.
- Edition: Cite the applicable edition of the volume.
- Subject: Cite the applicable paragraph number(s) and the relevant heading(s).
- Request: Indicate the suggested revision.
- Rationale: State the rationale for the suggested revision.

Upon receipt by the Secretary, the request will be forwarded to the relevant B30 Subcommittee for consideration and action. Correspondence will be provided to the requester defining the actions undertaken by the B30 Standard Committee.

## SECTION IX: REQUESTS FOR INTERPRETATION

The B30 Standard Committee will render an interpretation of the provisions of the B30 Standard. Such requests should be directed to

Secretary, B30 Standard Committee  
ASME Codes and Standards  
Three Park Avenue  
New York, NY 10016-5990

Requests should be in the following format:

- Volume: Cite the designation and title of the volume.
- Edition: Cite the applicable edition of the volume.
- Subject: Cite the applicable paragraph number(s) and the relevant heading(s).
- Question: Phrase the question as a request for an interpretation of a specific provision suitable for general understanding and use, not as a request for approval of a proprietary design or situation. Plans or drawings that explain the question may be submitted to clarify the question. However, they should not contain any proprietary names or information.

Upon receipt by the Secretary, the request will be forwarded to the relevant B30 Subcommittee for a draft response, which will then be subject to approval by the B30 Standard Committee prior to its formal issuance.

Interpretations to the B30 Standard will be published in the subsequent edition of the respective volume, and will be available online at <http://cstools.asme.org>.

## SECTION X: ADDITIONAL GUIDANCE

The equipment covered by the B30 Standard is subject to hazards that cannot be abated by mechanical means, but only by the exercise of intelligence, care, and common sense. It is therefore essential to have personnel involved in the use and operation of equipment who are competent, careful, physically and mentally qualified, and trained in the proper operation of the equipment and the handling of loads. Serious hazards include, but are not limited to, improper or inadequate maintenance, overloading, dropping or slipping of the load, obstructing the free passage of the load, and using equipment for a purpose for which it was not intended or designed.



The B30 Standard Committee fully realizes the importance of proper design factors, minimum or maximum dimensions, and other limiting criteria of wire rope or chain and their fastenings, sheaves, sprockets, drums, and similar equipment covered by the standard, all of which are closely connected with safety. Sizes, strengths, and similar criteria are dependent on many different factors, often varying with the installation and uses. These factors depend on

- (a) the condition of the equipment or material
- (b) the loads

(c) the acceleration or speed of the ropes, chains, sheaves, sprockets, or drums

(d) the type of attachments

(e) the number, size, and arrangement of sheaves or other parts

(f) environmental conditions causing corrosion or wear

(g) many variables that must be considered in each individual case

The requirements and recommendations provided in the volumes must be interpreted accordingly, and judgment used in determining their application.



INTENTIONALLY LEFT BLANK



# SELF-ERECTING TOWER CRANES

## Chapter 29-0 Scope, Definitions, and References

### SECTION 29-0.1: SCOPE OF B30.29

Volume B30.29 includes provisions that apply to the construction, operation, inspection, testing, and maintenance of powered self-erect tower cranes that adjust operating radius by means of a trolley traversing a jib. These may be horizontal, elevated, articulating, or telescoping, and used for vertical lifting and lowering of freely suspended, unguided loads that consist of equipment and materials.

Self-erect tower cranes have vertical or nearly vertical masts that are bottom slewing and mounted on fixed, traveling, or mobile bases. The cranes are capable of moving or being moved from jobsite to jobsite fully assembled or nearly fully assembled.

This Volume does not apply to cranes used for nonvertical lifting service or lifting a guided load, or to truck-mounted material delivery cranes with a tubular boom and trolley traversing the boom. Tower cranes (refer to ASME B30.3) and mobile crane tower attachments (refer to ASME B30.5) are not within the scope of this Volume.

### SECTION 29-0.2: DEFINITIONS

#### 29-0.2.1 Types of Self-Erect Tower Cranes

See Figs. 29-0.2.1-1 and 29-0.2.1-2.

#### 29-0.2.2 General

*accessory*: a secondary part or assembly of parts that contributes to the overall function and usefulness of a machine.

*administrative or regulatory authority*: governmental agency, or the employer in the absence of governmental jurisdiction.

*appointed*: assigned specific responsibilities by the employer or the employer's representative.

*authorized*: approved as satisfactory by a duly constituted administrative or regulatory authority.

*axis of rotation*: the vertical line about which a crane swings.

*axle*: the shaft or spindle with which or about which a wheel rotates. On wheel-mounted cranes, it refers to

a type of axle assembly including housings, gearing, differential, bearings, and mounting appurtenances.

*balanced*: the condition of the superstructure of a self-erect crane necessary for telescoping the mast; the load is positioned at that radius that causes the vertical moment of the superstructure about the balance point to go to zero.

*ballast*: weights added to the fixed frame to create additional stability or to counter the effects of the lifted load.

*bogie*: the assembly that includes a pivot, frame, axle(s), and wheel(s) on which a crane rides on rails, and includes an assembly of two or more axles arranged to permit both vertical wheel displacement and an equalization of loading on the wheels.

*brake*: a device other than a motor used for retarding or stopping motion by friction or power means.

*braking means*: a method or device for retarding or stopping motion.

*buffer*: an energy-absorbing device for reducing impact when a moving crane or trolley reaches the end of its permitted travel.

*cab*: a housing provided for the operator and containing the crane controls.

*control station*: the location of the crane function controls, either cab-mounted or by remote control.

*counterweight*: weights added to the rotating frame to create additional stability or to counter the effects of the lifted load.

*crane*: in this Volume, the use of the word "crane" refers to self-erect cranes, which are lifting machines, mounted on a base, with a superstructure consisting of a mast, rotating frame, and a jib.

*crossover points*: points of rope contact where one layer of rope on a rope drum crosses over the previous layer.

*designated person*: a person selected or assigned by the employer or the employer's representative as being competent to perform specific duties.

