

PD 8010-5:2013



BSI Standards Publication

PUBLISHED DOCUMENT

Pipeline systems –

Part 5: Subsea pipelines – Guide to operational practice

This publication is not to be regarded as a British Standard.

bsi.

...making excellence a habit.™

Publishing and copyright information

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2013

Published by BSI Standards Limited 2013

ISBN 978 0 580 77047 0

ICS 23.040.10; 75.200

The following BSI references relate to the work on this document:

Committee reference PSE/17/2

Draft for comment 13/30274989 DC

Publication history

First published September 2013

Amendments issued since publication

Date	Text affected
-------------	----------------------

Contents

Foreword *iii*

- 1 Scope** 1
- 2 Normative references** 1
- 3 Terms, definitions, symbols and abbreviations** 1
- 4 Determining the requirement for a subsea isolation valve (SSIV)** 4
 - 4.1 Reasons for installing an SSIV 4
 - 4.2 Decision-making process 7
 - 4.3 Testing 13
- 5 Selection and use of high pressure in-line isolation plugs** 15
 - 5.1 General 15
 - 5.2 Supply of information 16
 - 5.3 Preparations to be made by the executive operator and site operator 16
- 6 Pipeline integrity data exchange** 20
- 7 Caisson and J-tube integrity management** 21
 - 7.1 Integrity issues 21
 - 7.2 Description of system 23
 - 7.3 Design intent 24
 - 7.4 Corrosion control and monitoring 27
- 8 Emergency shutdown valve (ESDV) testing** 30
 - 8.1 General 30
 - 8.2 Objectives 31
 - 8.3 Test procedure 32
 - 8.4 Test report 35
- 9 Operational testing of pig launchers and receivers** 35
 - 9.1 General 35
 - 9.2 Leak test 36
 - 9.3 Strength test 36
 - 9.4 Test variables 37
 - 9.5 Safety and environmental mitigations 38
 - 9.6 Risk assessment checklist 39
 - 9.7 Other integrity activities 40
 - 9.8 Pressurization after a long period at ambient pressure 41

Annexes

- Annex A (informative) Alternative approach to QRA 42
- Annex B (informative) Pro-forma for selection of high pressure in-line isolation plugs 43
- Annex C (informative) Sample failure mode listing 46
- Annex D (informative) Pro-forma sheets for pipeline integrity data exchange: main data sheet 52
- Annex E (informative) Pro-forma sheets for pipeline integrity data exchange: annual data exchange sheet 55
- Annex F (informative) Pro-forma sheets for pipeline integrity data exchange: example of completed main data sheet 62
- Annex G (informative) Caisson and J-tube risk assessment 64
- Annex H (informative) Pro-forma for ESDV test report 68

Bibliography 69

List of figures

- Figure 1 – Influences on the location of an SSIV 7
Figure 2 – Information flow – The decision whether an SSIV is required 11
Figure 3 – Information flow – The decision whether to retain an SSIV 13
Figure 4 – Example – Determination of test interval 15
Figure 5 – Risers and J-tubes within a caisson 27
Figure 6 – ESDV leak-off test arrangement 33
Figure 7 – Extended ESDV leak-off test arrangement 34
Figure 8 – Pig trap pressure testing – Restricted area 38
Figure A.1 – Possible decision tree 42
Figure B.1 – Pro-forma for the selection of isolation plugs 43
Figure D.1 – Pro-forma sheets for pipeline integrity data exchange: main data sheet 53
Figure E.1 – Pro-forma sheets for pipeline integrity data exchange: annual data exchange sheet 56
Figure F.1 – Pro-forma sheets for pipeline integrity data exchange: example of completed main data sheet 62
Figure H.1 – Pro-forma for ESDV test report 68

List of tables

- Table 1 – Description of system – Key considerations 23
Table 2 – Overall design intent – Key considerations 24
Table 3 – Top arrangement design intent – Key considerations 25
Table 4 – Splash zone design intent – Key considerations 26
Table 5 – Bottom arrangement design intent – Key considerations 26
Table C.1 – Failure modes for pipeline plugging operations 47
Table G.1 – Caisson and J-tube risk assessment 65

Summary of pages

This document comprises a front cover, an inside front cover, pages i to iv, pages 1 to 70, an inside back cover and a back cover.

Foreword

Publishing information

This part of PD 8010 is published by BSI Standards Limited, under licence from The British Standards Institution, and came into effect on 30 September 2013. It was prepared by Subcommittee PSE/17/2, *Pipeline transportation systems*, under the authority of Technical Committee PSE/17, *Materials and equipment for petroleum*. A list of organizations represented on these committees can be obtained on request to their secretary.

Relationship with other publications

PD 8010-5 is a new part of the PD 8010 series. The series comprises:

- Part 1: *Steel pipelines on land*;
- Part 2: *Subsea pipelines*;
- Part 3: *Steel pipelines on land – Guide to the application of pipeline risk assessment to proposed developments in the vicinity of major accident hazard pipelines containing flammables – Supplement to PD 8010-1:2004*;
- Part 4: *Steel pipelines on land and subsea pipelines – Code of practice for integrity management*;
- Part 5: *Subsea pipelines – Guide to operational practice*.

This part of PD 8010 is intended to be read in conjunction with PD 8010-2 and PD 8010-4:2012.

Information about this document

This part of PD 8010 was initially drafted using Pipeline Users Group documents as a basis, with their kind permission.

As an industry develops, the practices and procedures it adopts improve so that the way business is conducted within that industry improves with that development. In the oil and gas offshore industry, some subsea assets have been in operation in the North Sea for several decades, during which time lessons have been learned and operational practice improved. This part of PD 8010 presents a number of operational practices that have been established as a result of these developments.

It is anticipated that operational pipeline engineers will use this part of PD 8010 on a regular basis; pipeline design engineers will take cognisance of it in the design of pipeline systems; and third-party providers of equipment and services will be able to align the products and services they provide with the guidance and recommendations given.

Use of this document

As a guide, this part of PD 8010 takes the form of guidance and recommendations. It should not be quoted as if it were a specification or a code of practice and claims of compliance cannot be made to it.

It has been assumed in the preparation of this part of PD 8010 that the execution of its guidance will be entrusted to appropriately qualified and experienced people, for whose use it has been produced.

BSI permits the reproduction of Figure B.1, Figure D.1, Figure G.1, Figure H.1 and Table E.1. This reproduction is permitted only where it is necessary for the user to use the sample pro-formas given in the figures and table during each application of the standard.

Presentational conventions

The guidance in this part of PD 8010 is presented in roman (i.e. upright) type. Any recommendations are expressed in sentences in which the principal auxiliary verb is “should”.

Commentary, explanation and general informative material is presented in smaller italic type, and does not constitute a normative element.

Contractual and legal considerations

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a Published Document cannot confer immunity from legal obligations.

1 Scope

This part of PD 8010 gives guidance on the following aspects of offshore subsea system operational practice:

- determining the requirement for a subsea isolation valve (SSIV);
- selection and use of high pressure in-line isolation plugs;
- pipeline integrity data exchange;
- caisson and J-tube integrity management;
- emergency shutdown valve (ESDV) testing;
- operational testing of pig launchers and receivers.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

PD 8010-2, *Code of practice for pipelines – Part 2: Subsea pipelines*

PD 8010-4:2012, *Pipeline systems – Part 4: Steel pipelines on land and subsea pipelines – Code of practice for integrity management*

3 Terms, definitions, symbols and abbreviations

3.1 Terms and definitions

For the purposes of this part of PD 8010, the terms and definitions given in PD 8010-2, PD 8010-4:2012 and the following apply.

3.1.1 annulus

void between a caisson/J-tube inner wall and the outer wall of components (e.g. one or more flexible or rigid risers, J-tubes, umbilicals) installed within the caisson/J-tube

3.1.2 bellmouth

short conical extension piece at the end of a J-tube, the purpose of which is to aid insertion of risers and umbilicals into the J-tube and minimize the risk of damage during installation, and to provide a similar mechanical protection during operation by maintaining a filleted contact and supporting surface at the entry point

3.1.3 caisson

prefabricated tubular assembly, containing one or more smaller diameter tubular components (usually rigid risers and J-tubes) which pass through the top and bottom sealing bulkheads

NOTE A caisson can be in multiple components, e.g. upper and lower caisson sections.

3.1.4 closed-in tubing head pressure

pressure at the bottom of a well, caused by formation fluids at the bottom of the well, when the surface valves on the top of the well are completely closed

NOTE This is also referred to as shut-in bottomhole pressure.

3.1.5 failure

event, state or condition of not meeting a desirable or intended objective