

Orifice Metering of Natural Gas and Other Related Hydrocarbon Fluids— Concentric, Square-edged Orifice Meters

Part 3: Natural Gas Applications



American Gas Association

AGA Report No. 3
Part 3



AMERICAN PETROLEUM INSTITUTE

Manual of Petroleum
Measurement Standards
Chapter 14.3.3

American Gas Association
400 North Capitol Street, NW
Washington, DC 20001

American Petroleum Institute
1220 L Street, NW
Washington, DC 20005

FOURTH EDITION, NOVEMBER 2013

An American National Standard
ANSI/API MPMS Ch. 14.3.3/AGA Report No. 3, Part 3

Special Notes

This AGA/API publication necessarily addresses problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither AGA and API nor any of AGA's or API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither AGA and API nor any of AGA's or API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

Users of this publication should not rely exclusively on the information contained in this document. Sound business, scientific, engineering, and safety judgment should be used in employing the information contained herein.

This AGA/API publication may be used by anyone desiring to do so. Every effort has been made by AGA/API to assure the accuracy and reliability of the data contained in it; however, AGA/API makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

This AGA/API publication is published to facilitate the broad availability of proven, sound engineering and operating practices. It is not intended to obviate the need for applying sound engineering judgment regarding when and where this publication should be utilized. The formulation and publication of this AGA/API publication is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

All rights reserved. No part of this work may be reproduced, translated, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from either the American Gas Association, 400 N. Capitol St., NW, Washington, DC 20001 or API Publishing Services, 1220 L Street, NW, Washington, DC 20005.

Foreword

Nothing contained in this AGA/API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is designated as API *Manual of Petroleum Measurement Standard (MPMS)* Chapter 14.3.3 and AGA Report No. 3, Part 3. Questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, NW, Washington, DC 20005. Questions concerning the interpretation of the content of this publication should be directed to the Director of Standards, American Petroleum Institute, 1220 L Street, NW, Washington, DC 20005 and to the Vice President, Operations and Engineering, American Gas Association, 400 N. Capitol Street, NW, Washington, DC 20001, and shall be handled in accordance with API's *Procedures for Standards Development*. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the Director of Standards, American Petroleum Institute (as above) or the Vice President, Operations and Engineering, American Gas Association (as above).

Shall: As used in a standard, "shall" denotes a minimum requirement in order to conform to the specification.

Should: As used in a standard, "should" denotes a recommendation or that which is advised but not required in order to conform to the specification.

This AGA/API publication is reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually by API, 1220 L Street, NW, Washington, DC 20005.

A catalog of AGA Operations and Engineering publications, which is published and updated as needed and can be obtained by contacting AGA Operations and Engineering Department, phone (202) 824-7000 or web site http://www.aga.org/Pages/contact_us.aspx.

Suggested revisions are invited and should be submitted to the Standards Department, API, 1220 L Street, NW, Washington, DC 20005, standards@api.org or Operations and Engineering Department, American Gas Association, 400 North Capitol Street, NW, Washington, DC 20001, http://www.aga.org/Pages/contact_us.aspx.

Contents

	Page
1 Scope	1
1.1 General	1
1.2 Definition of Natural Gas	1
1.3 Basis for Equations	1
1.4 Expansion Factor Application	1
2 Normative References	1
3 Symbols, Units, and Terminology	2
3.1 General	2
3.2 Symbols and Units	2
3.3 Terminology	4
4 Flow Measurement Equations	5
4.1 General	5
4.2 Equations for Mass Flow of Natural Gas	5
4.3 Equations for Volume Flow of Natural Gas	6
4.4 Volume Conversion from Reference Base to Base Conditions	8
5 Flow Equation Components Requiring Additional Computation	9
5.1 General	9
5.2 Diameter Ratio (β)	9
5.3 Coefficient of Discharge for Flange-tapped Orifice Meter [$C_d (FT)$]	9
5.4 Velocity of Approach Factor (E_v)	11
5.5 Reynolds Number (ReD)	12
5.6 Expansion Factor (Y)	13
6 Gas Properties	16
6.1 General	16
6.2 Physical Properties	16
6.3 Compressibility	16
6.4 Relative Density	18
6.5 Density of Fluid at Flowing Conditions	20
Annex A (informative) Adjustments for Instrument Calibration	24
Annex B (informative) Factors Approach	30
Annex C (informative) Flow Calculation Examples	33
Annex D (informative) Pipe Tap Orifice Metering	41
Annex E (informative) SI Conversions	42
Annex F (informative) Development of Constants for Flow Equations	44
Annex G (informative) Buckingham and Bean Empirical Expansion Factor (Y) for Flange-tapped Orifice Meters	50
Bibliography	54

Contents

Page

Tables

1	Linear Coefficient of Thermal Expansion	10
A.1	Water Density Based on Patterson and Morris Equation	28
E.1	Volume Reference Conditions for Custody Transfer Operations: Natural Gas Volume	42
E.2	Energy Reference Conditions	42
E.3	Heating Value Reference Conditions	43
G.1	Comparison Between Equation (35) and Equation (G.3).	53

Introduction

API *MPMS* Chapter 14.3.3/AGA Report No. 3, Part 3 is organized as follows: Symbols and units are first defined, the basic flow equation is presented, then key equation components are defined, and finally the gas properties applicable to orifice metering of natural gas are developed. Factors to compensate for meter calibration and location are included in Annex A. The factor approach to orifice measurement is included in Annex B. Annex F covers derivation of constants. The user is cautioned that the symbols may be different from those used in previous orifice metering standards.

Orifice Metering of Natural Gas and Other Related Hydrocarbon Fluids— Concentric, Square-edged Orifice Meters Part 3: Natural Gas Applications

1 Scope

1.1 General

This part of API *MPMS* Ch. 14.3/AGA Report No. 3 has been developed as an application guide for the calculation of natural gas flow through a flange-tapped, concentric orifice meter, using the U.S. customary (USC) inch-pound system of units.

For applications involving international system (SI) of units, a conversion factor can be applied to the results (Q_m , Q_v , or Q_b) determined from the equations in 4.3. Intermediate conversion of units will not necessarily produce consistent results. As an alternative, the more universal approach specified in API *MPMS* Ch. 14.3.1/AGA Report No. 3, Part 1 can be used. The meter has to be constructed and installed in accordance with API *MPMS* Ch. 14.3.2/AGA Report No. 3, Part 2.

1.2 Definition of Natural Gas

As used in this document, the term natural gas applies to fluids that for all practical purposes are considered to include both pipeline and production quality gas with single-phase flow and mole percentage ranges of components as given in Table 1 of API *MPMS* Ch. 14.2/AGA Report No. 8. For other hydrocarbon mixtures, the more universal approach specified in API *MPMS* Ch. 14.3.1/AGA Report No. 3, Part 1 may be more applicable. Diluents or mixtures other than those stipulated in API *MPMS* Ch. 14.2/AGA Report No. 8 may increase the flow measurement uncertainty.

1.3 Basis for Equations

The computation methods used in this document are consistent with those developed in API *MPMS* Ch. 14.3.1/AGA Report No. 3, Part 1 and include the Reader-Harris/Gallagher (RG) equation for flange-tapped orifice meter discharge coefficient. The equation has been modified to reflect the more common units of the USC inch-pound system.

1.4 Expansion Factor Application

For all existing installations, the decision as to which expansion factor equation to use is at the discretion of the parties involved. However, the parties should be cognizant of the following:

- 1) If the calculated difference between previous revision (1990) Buckingham and Bean expansion factor equation (refer to Annex G) and the new revised expansion factor equation (refer to 5.6) is less than or equal to 0.25 %, then the expansion factor values produced by either expansion factor equation will be within the uncertainty of the new expansion factor database and the existence of any flow bias is uncertain.
- 2) However, if the calculated difference between expansion factor equations exceeds 0.25 %, then a variable flow bias, which is a function of diameter ratio (β), isentropic exponent (κ), and $\Delta P/P_{f1}$ ratio (x_1), will be experienced unless the new expansion factor equation is utilized.

2 Normative References

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

API *MPMS* Ch. 14.2/AGA Report No. 8, *Compressibility Factors of Natural Gas and Other Related Hydrocarbon Gases*