



BSI Standards Publication

Sharp edge testing apparatus and test procedure for lighting equipment — Tests for sharpness of edge

National foreword

This Published Document is the UK implementation of IEC/TR 62854:2014.

The UK participation in its preparation was entrusted by Technical Committee CPL/34, Lamps and Related Equipment, to Subcommittee CPL/34/4, Luminaires.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2014.
Published by BSI Standards Limited 2014

ISBN 978 0 580 81766 3
ICS 29.140.40

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 28 February 2014.

Amendments/corrigenda issued since publication

Date	Text affected
-------------	----------------------



TECHNICAL REPORT

RAPPORT TECHNIQUE

Sharp edge testing apparatus and test procedure for lighting equipment – Tests for sharpness of edge

Appareil et mode opératoire pour la vérification des bords vifs des appareils d'éclairage – Essais de tranchant des bords

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE
CODE PRIX



ICS 29.140.40

ISBN 978-2-8322-1418-3

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD.....	3
1 Scope.....	5
2 Test equipment.....	5
3 Calibration.....	5
4 The preparation of the test head.....	6
5 The test procedure	6
6 Criteria	6
Figure 1 – Sharp edge tester	8
Figure 2 – Sharp edge tester with tape cap (alternate construction).....	9
Figure 3 – Typical calibration procedure	9
Figure 4 – Test Head Preparation	10
Figure 5 – Test Procedure	10
Figure 6 – Edges Tested.....	10
Table 1 – Average values of tape dimensions and properties.....	7

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SHARP EDGE TESTING APPARATUS AND TEST PROCEDURE FOR LIGHTING EQUIPMENT – TESTS FOR SHARPNESS OF EDGE

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC/TR 62854, which is a technical report, has been prepared by subcommittee 34D: Luminaires, of IEC technical committee 34: Lamps and related equipment.

The text of this technical report is based on the following documents:

Enquiry draft	Report on voting
34D/1088/DTR	34D/1101A/RVC

Full information on the voting for the approval of this technical report can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

SHARP EDGE TESTING APPARATUS AND TEST PROCEDURE FOR LIGHTING EQUIPMENT – TESTS FOR SHARPNESS OF EDGE

1 Scope

This technical report details a test procedure and test equipment that may be used to assist the assessment of the risk of hazardous sharp edges that may be exposed to the user or installer of lighting equipment.

2 Test equipment

Sharp-edge tester – The instrument consists essentially of a handle with a pivoted arm attached. A constant-tension spring secured to the handle is used to apply a steady force to the arm. The arm head is a piece of cylindrical steel, with an outside diameter of 12,7 mm and a length of 19 mm, located at the end of the adjustable arm. The arm head is to be wrapped with three layers of tape, the two outer layers act as sensing tapes; the inner layer acts as an indicating tape. Alternatively, the tapes are to be applied to a maximum 15,9 mm diameter removable sleeve (cap) that is placed onto the 12,7 mm steel head. See Figure 1 or 2.

Indicating tape (inner layer) – 19,1 mm wide, adhesive backed, single-adhesive coated, vinyl foam tape, black in colour, having the tape properties given in Table 1.

Sensing tape no. 2 (middle layer) – 19,1 mm wide, double-adhesive coated, vinyl foam tape, white in colour, having the tape properties given in Table 1.

Sensing tape no. 1 (outer layer) – 19,1 mm wide, single-adhesive coated skived tetrafluorethylene tape – natural colour, having the tape properties given in Table 1. The skived tetrafluorethylene backing (film) is shaved in a thin layer from a cylindrical block of material.

Calibration equipment – A weight (mass) that can exert $6,672 \pm 0,133$ N and a length of string.

3 Calibration

The sharp edge tester shall be calibrated so that $6,7 \pm 0,133$ N force is present at the centre of the head when the arm is between stops. The length of the arm is to be adjustable for calibration purposes. For special evaluations, the force may be adjusted to a different value.

See Figure 3 for a typical calibration procedure were, the length of the arm is to be adjustable for calibration purposes:

The adjustment set screws that hold the pivoted arm in place in the main drum are to be loosened.

With the handle securely held in a horizontal position, the calibration weight is to be attached to the centre of the head.

The length of the arm within the main drum is to be adjusted so that the weighted arm remains in a horizontal position with the calibration weight attached.