



IPC-4101D

2014 - April

**Specification for Base Materials
for Rigid and Multilayer
Printed Boards**

Supersedes IPC-4101C

April 2009

A standard developed by IPC

Association Connecting Electronics Industries



The Principles of Standardization

In May 1995 the IPC's Technical Activities Executive Committee (TAEC) adopted Principles of Standardization as a guiding principle of IPC's standardization efforts.

Standards Should:

- Show relationship to Design for Manufacturability (DFM) and Design for the Environment (DFE)
- Minimize time to market
- Contain simple (simplified) language
- Just include spec information
- Focus on end product performance
- Include a feedback system on use and problems for future improvement

Standards Should Not:

- Inhibit innovation
- Increase time-to-market
- Keep people out
- Increase cycle time
- Tell you how to make something
- Contain anything that cannot be defended with data

Notice

IPC Standards and Publications are designed to serve the public interest through eliminating misunderstandings between manufacturers and purchasers, facilitating interchangeability and improvement of products, and assisting the purchaser in selecting and obtaining with minimum delay the proper product for his particular need. Existence of such Standards and Publications shall not in any respect preclude any member or nonmember of IPC from manufacturing or selling products not conforming to such Standards and Publication, nor shall the existence of such Standards and Publications preclude their voluntary use by those other than IPC members, whether the standard is to be used either domestically or internationally.

Recommended Standards and Publications are adopted by IPC without regard to whether their adoption may involve patents on articles, materials, or processes. By such action, IPC does not assume any liability to any patent owner, nor do they assume any obligation whatever to parties adopting the Recommended Standard or Publication. Users are also wholly responsible for protecting themselves against all claims of liabilities for patent infringement.

IPC Position Statement on Specification Revision Change

It is the position of IPC's Technical Activities Executive Committee that the use and implementation of IPC publications is voluntary and is part of a relationship entered into by customer and supplier. When an IPC publication is updated and a new revision is published, it is the opinion of the TAEC that the use of the new revision as part of an existing relationship is not automatic unless required by the contract. The TAEC recommends the use of the latest revision. Adopted October 6, 1998

Why is there a charge for this document?

Your purchase of this document contributes to the ongoing development of new and updated industry standards and publications. Standards allow manufacturers, customers, and suppliers to understand one another better. Standards allow manufacturers greater efficiencies when they can set up their processes to meet industry standards, allowing them to offer their customers lower costs.

IPC spends hundreds of thousands of dollars annually to support IPC's volunteers in the standards and publications development process. There are many rounds of drafts sent out for review and the committees spend hundreds of hours in review and development. IPC's staff attends and participates in committee activities, typesets and circulates document drafts, and follows all necessary procedures to qualify for ANSI approval.

IPC's membership dues have been kept low to allow as many companies as possible to participate. Therefore, the standards and publications revenue is necessary to complement dues revenue. The price schedule offers a 50% discount to IPC members. If your company buys IPC standards and publications, why not take advantage of this and the many other benefits of IPC membership as well? For more information on membership in IPC, please visit www.ipc.org or call 847/597-2872.

Thank you for your continued support.



IPC-4101D

Specification for Base Materials for Rigid and Multilayer Printed Boards

Developed by the Laminate/Prepreg Materials Subcommittee (3-11) of
the Printed Board Base Materials Committee (3-10) of IPC

Supersedes:

IPC-4101C - August 2009
IPC-4101B with
Amendments 1 & 2 - April 2007
IPC-4101B with
Amendment 1 - February 2007
IPC-4101B - June 2006
IPC-4101A with
Amendment 1 - June 2002
IPC-4101A - December 2001
IPC-4101 - December 1997
IPC-L-108
IPC-L-109
IPC-L-112
IPC-L-115
IPC-AM-361

Users of this standard are encouraged to participate in the
development of future revisions.

Contact:

IPC
3000 Lakeside Drive, Suite 309S
Bannockburn, Illinois
60015-1249
Tel 847 615.7100
Fax 847 615.7105

This Page Intentionally Left Blank

Acknowledgment

Any document involving a complex technology draws material from a vast number of sources. While the principal members of the Laminate/Prepreg Materials Subcommittee (3-11) of the Printed Board Base Materials Committee (3-10) are shown below, it is not possible to include all of those who assisted in the evolution of this standard. To each of them, the members of the IPC extend their gratitude.

Printed Board Base Materials Committee	Laminate/Prepreg Materials Subcommittee	Technical Liaison of the IPC Board of Directors
Chair Douglas J. Sober Shengyi Sci. Tech. Co., Ltd.	Chair Antonio R. Senese Panasonic Electric Works	Bob Neves Microtek Laboratories
Vice Chair Dewey Whittaker Honeywell Inc.	Vice Chair Douglas J. Sober Shengyi Sci. Tech. Co., Ltd.	
Laminate/Prepreg Materials Subcommittee		
Tomoyuki Abe, Panasonic Electric Works	Jack Bramel, Jack Bramel & Associates	William Dieffenbacher, BAE Systems Platform Solutions
Bernard Alzua, Bernard Alzua & Associates	Michael Brandon, Isola Group SARL	Denise Dodge, Maxim Integrated Products
John Andresakis, Oak-Mitsui, Inc.	Thomas Bresnan, R & D Circuits	Raimund Doppelreiter, P-D Interglas Technologies AG
Masamitsu Aoki, JETPA	Dock Brown, Medtronic	Paul DuFresne, Insulectro
Lance Auer, Raytheon Missile Systems	Mike Bryant, BGF Industries Inc.	Patricia Dupuis, Raytheon Company
Robert.Bagsby, Rockwell Collins	Victor Brzozowski, Northrop Grumman Corporation	Theodore Edwards
Lameck Banda, Dow Chemical USA	Matthew Byrne, BAE Systems Platform Solutions	Douglas Eng, PPG Industries Inc.
Richard Barnett, Hewlett-Packard Company	Tracy Cai, Shengyi Technology Co. Ltd.	Steven Ethridge, Dell Inc.
Leonard Barrett, W. L. Gore & Associates Inc.	John Callahan, High Performance Copper Foil Inc	Thomas Farrell, Thomas G. Farrell Associates
John Bauer, Rockwell Collins	Clifton Cavin, General Dynamics Advanced Information Systems	Terry Fischer, Hitachi Chemical Co. America, Ltd.
Michael Beauchesne, Amphenol Printed Circuits, Inc.	Wenwei Chen, Northrop Grumman Aerospace Systems	Jeff Fisher, Lockheed Martin Mission Systems & Training
Don Belanger, Pacific Testing Laboratories, Inc.	Jennifer Chung, Momentive Speciality Chemicals Inc.	John Fisher, Interconnect Technology Analysis, Inc.
Keith Bendyk, JPS Composite Materials Corp.	Joshua Civiello, Defense Supply Center Columbus	Larry Frost, Sanmina Corporation
Elizabeth Benedetto, Hewlett-Packard Company	Christopher Clark, L-3 Fuzing and Ordnance Systems	Satoshi Fujiki, Panasonic Electric Works
Erik Bergum, Park Electrochemical Corp.	Ron Clothier, Sanmina Corporation	Hiroyuki Fujisawa, Panasonic Electric Works
Silvio Bertling, Circuit Foil Luxembourg SARL	Christine Coapman, C2 Consulting	Kent Fujiwara, Sumitomo Plastics America Inc.
Bill Birch, PWB Interconnect Solutions Inc.	Michael Collier, Teledyne Printed Circuit Technologies	Lionel Fullwood, WKK Distribution Ltd.
Robert Black, Northrop Grumman Corporation	Paul Cooke, Viasystems Group, Inc.	Mahendra Gandhi, Northrop Grumman Aerospace Systems
	Dennis Debord, Avaya Inc	

Michael Gay, Isola Group SARL
Patricia Goldman, P. J. Goldman Consulting
Pierre-Emmanuel Goutorbe, Airbus Defence & Space
Ty Gragg, Unicircuit Inc.
Rachel Grinvalds, Rockwell Collins
William Hall, Oak-Mitsui, Inc.
Robert Hearn, Dow Chemical USA
Stan Heltzel, European Space Agency
Adam Hen, Celestica
Philip Henault, Raytheon Company
Scott Hinaga, Cisco Systems Inc.
Joseph Ho, Multek Display Ltd.
Happy Holden
Shinji Hosoki, Panasonic Electric Works
Shelly Hsu, Compeq Manufacturing Co. Ltd.
Anderson Huang, Nan Ya Plastics Corporation
Michael Jawitz, Boeing Research & Development
Yvonne Julian-Hargrove, Dow Chemical USA
Joan Karner, Holaday Circuits Inc.
Hideo Kato, Nitto Boseki Co., Ltd.
Roy Keen, Rockwell Collins
Edward Kelley, Isola Group SARL
Frank Kimmey, Powerwave Technologies
John Kozuch, CEM - Contract Engineering & Mfg.
Ernest Kreiner, L-3 Fuzing and Ordnance Systems
Karin LaBerge, KAL Consulting
Fen-Yi Lee, Nan Ya Plastics Corporation
Minsu Lee, Doosan Electro-Materials America, LLC
Joseph Leibowitz, Shirline Composites Inc.
Doug Leys, Nelco Products, Inc.
Peter Liang, Nan Ya Plastics Corporation
Louis Lin, Nan Ya Plastics Corporation
Gary Long, Intel Corporation
David Lowery, Summit Products & Services
Penghui Luo, Shengyi Technology (Suzhou) Co. Ltd.
Clifford Maddox, Boeing Company
Brian Madsen, Continental Automotive Systems
Kenneth Manning, Raytheon Company
Thomas McCarthy, Taconic Advanced Dielectric Division
Chetan Mehta, Eagle Circuits
Bill Mercer, Dow Chemical USA
Renee Michalkiewicz, Trace Laboratories - Baltimore
Roger Miedico, Raytheon Company
Ralf Miessner, Robert Bosch GmbH
Sean Mirshafiei, Enthone Inc
Keita Miyasato, Taiyo Industrial Co., Ltd.
Mike Monnin, Panasonic Electric Works
Noe Navarro, UL LLC
David Nelsen, Raytheon Company
Robert Neves, Microtek (Changzhou) Laboratories
Steven Nolan, Lockheed Martin Mission Systems & Training
Thomas Nowak, Nowak & Associates
Debora Obitz, Microtek - East
Gerard O'Brien, Solderability Testing & Solutions, Inc.
Christopher Olson, Rockwell Collins
William Ortloff, Raytheon Company
Deepak Pai, General Dynamics Info. Sys., Inc
Richard Pangier, Isola Group SARL
J. Lee Parker, JLP
Thierry Philibert, AGY
John Radman, Trace Laboratories - Denver
Terry Regan, Viasystems Group, Inc.
Paul Reid
Joseph Riendeau, Boeing Research & Development
Jerome Sallo, Ruwel GmbH
Edward Sandor, Taconic Advanced Dielectric Division
Karl Sauter, Oracle America, Inc.
Rolland Savage, High Performance Copper Foil Inc
Fabio Scari, Isola Fabrics S.r.l.
Marco Scari, Isola Fabrics S.r.l.
Carl Schlemmer, Amitron Corporation
Friedrich Schlitter, Ruwel GmbH
Joseph Schmidt, Raytheon Missile Systems
Julie Scopel, UL LLC
Steven Sekanina, Isola Group SARL
Robert Sheldon, Pioneer Circuits Inc.
Russell Shepherd, Microtek Laboratories Anaheim
Lowell Sherman, Defense Supply Center Columbus
Hans Shin, Pacific Testing Laboratories, Inc.
HyunJoon Shin, UL Korea Ltd
Michael Shin, Pacific Testing Laboratories, Inc.
David Shirrell, Momentive Speciality Chemicals Inc.
Clark Smedstad, BGF Industries Inc
Michael Smith, Arlon Materials for Electronics
Vern Solberg, Solberg Technical Consulting
David Sommervold, The Bergquist Company, Prescott
Bruce Sorensen
George Sotolongo, Boeing Company
James Stack, i3 Electronics
William Starmann, Raytheon Company
George Stoddart, CSA International
Julie Strickland, Raytheon Company
Kurt Summa, FTG Circuits, Inc.
Kunio Takahara, JPCA-Japan Electronics Packaging and Circuits Association
nYoshiyuki Takeda, Hitachi Chemical Co., Ltd.
Valentin Tereshkin, SPbC ELMA

Dung (Young) Tiet, Lockheed Martin
Space Systems Company

Roger Tietze, Huntsman Advanced
Technology Center

Larry Timberlake, Great Lakes
Solutions, A Chemtura Business

Stephen Tisdale, Intel Corporation

Bradley Toone, L-3 Communications

Crystal Vanderpan, UL LLC

Clark Webster, ALL Flex LLC

Michael Weinhold, EIPC-European
Inst of Printed Circuits

Dan Welch, Arlon Materials for
Electronics

James White, Hallmark Circuits Inc.

Kimberly White, Albemarle
Corporation

Vicka White, Honeywell Inc. Air
Transport Systems

Dewey Whittaker, Honeywell Inc. Air
Transport Systems

Reiner Wieland, Ingenieurbuero
Reiner Wieland

Lee Wilmot, TTM Technologies, Inc.

Audrey Woo, UL LLC

Takashi Yamadera, Japan

Thermosetting Polymer Industries
Association

John Zimmer, The Bergquist
Company

This Page Intentionally Left Blank

Table of Contents

1	SCOPE	1	3.4	Qualification Testing	7
1.1	Classification	1	3.4.1	Qualification Testing of Laminate	11
1.1.1	Specification Sheet Description	1	3.4.2	Qualification Testing of Prepreg	11
1.1.2	Nominal Laminate Thickness	1	3.5	Verification of Manufacturer's Quality System	11
1.1.3	Metal Cladding Type and Nominal Weight/ Thickness	1	3.6	Conflict	11
1.1.3.1	Metal Cladding Type	2	3.7	Materials	11
1.1.3.2	Nominal Weight/Thickness	2	3.7.1	Metal Cladding	11
1.1.4	Thickness Tolerance (Laminate)	2	3.7.2	Reinforcement Fabric	11
1.1.5	Surface Quality Class	2	3.7.3	Resin Systems	11
1.1.6	Reinforcement Style	2	3.8	General Requirements	11
1.1.7	Prepreg Parameters	2	3.8.1	Fabricated Sheets and Panels	11
1.1.8	Color	4	3.8.1.1	Fabricated Laminate Sheet Material	11
1.1.8.1	Contrast Agents	4	3.8.1.2	Fabricated Laminate Panel Material	11
1.2	Dimensions and Tolerances	4	3.8.1.3	Fabricated Prepreg Panels	11
1.2.1	Metric and Imperial Measurements	4	3.8.1.4	Fabricated Prepreg Rolls	12
2	APPLICABLE DOCUMENTS	4	3.8.2	Inspection Lot	12
2.1	IPC	4	3.8.2.1	Inspection Lot for Laminate	12
2.2	National Conference of Standards Laboratories (NCSL)	6	3.8.2.2	Inspection Lot for Prepreg	12
2.3	International Standards	6	3.8.2.3	Preparation of Samples	12
2.4	Underwriters Laboratories (UL)	6	3.8.2.4	Etching Process and Etchant Removal for Copper Foil Specimens	12
2.5	European Union	6	3.8.2.5	Standard Laboratory Conditions	12
2.6	ASTM International	6	3.8.3	Visual Properties	12
3	REQUIREMENTS	6	3.8.3.1	Laminate Visual Properties	12
3.1	Terms and Definitions	6	3.8.3.1.1	Foil Indentations	12
3.1.1	Qualification Assessment	6	3.8.3.1.2	Wrinkles	12
3.1.2	Quality Conformance Testing	6	3.8.3.1.3	Scratches	13
3.1.3	Supplier's Quality System	6	3.8.3.1.4	Plastic Surface Finish of Metal-Clad Single-Sided Base Material	13
3.1.4	Process Control Testing	6	3.8.3.1.5	Surface Finish of Foil after Curing – Except Double Treat	13
3.1.5	Self Declaration	6	3.8.3.1.6	Surface and Subsurface Imperfections	13
3.1.6	Quality Assessment Data	7	3.8.3.2	Prepreg Visual Properties	13
3.1.7	Sample Qualification	7	3.8.3.2.1	Inclusions	13
3.1.8	Production Data	7	3.8.3.2.2	Impregnation Imperfections	13
3.1.9	Customer Test Data	7	3.8.4	Dimensional	14
3.1.10	Internal Assessment	7	3.8.4.1	Length and Width	14
3.1.11	Individual Customer Audit	7	3.8.4.1.1	Length and Width of Laminate	14
3.1.12	Independent Third Party Assessment	7	3.8.4.1.2	Length and Width of Prepreg	14
3.1.13	Epoxy, Multifunctional	7	3.8.4.1.3	Prepreg Roll Width	14
3.1.14	Epoxy, Difunctional	7	3.8.4.1.4	Prepreg Roll Length	14
3.1.15	AABUS	7	3.8.4.2	Thickness	14
3.2	Specification Sheets	7	3.8.4.2.1	Class A, B and C Laminate Materials	14
3.3	Manufacturer Quality Profile	7			

3.8.4.2.2	Class D Laminate Materials	14	3.10.1	Chemical Requirements of Laminate Materials	18
3.8.4.2.3	Class K, L and M Laminate Materials	15	3.10.1.1	Flammability	18
3.8.4.2.4	Thickness Tolerance of Laminate Materials	15	3.10.1.2	Thermal Stress	18
3.8.4.3	Bow and Twist of Laminate Materials	15	3.10.1.3	Solderability	18
3.8.4.3.1	Sheets and Panels with Both Dimensions ≥300 mm [11.81 in]	15	3.10.1.4	Chemical Resistance (Optional Test)	19
3.8.4.3.2	Panels with One or Both Dimensions <300 mm [11.81 in]	15	3.10.1.5	Metal Surfaces Cleanability	19
3.9	Physical Requirements	15	3.10.1.6	Glass Transition Temperature (T_g) (Optional Test)	19
3.9.1	Physical Requirements of Laminate Materials	15	3.10.1.7	Delta T_g (Optional Test)	19
3.9.1.1	Peel Strength	15	3.10.1.8	Decomposition Temperature (Optional Test)	19
3.9.1.1.1	Peel Strength after Thermal Stress	16	3.10.1.9	Time to Delaminate (TMA) (Optional Test)	19
3.9.1.1.2	Peel Strength at Elevated Temperature	16	3.10.2	Chemical Requirements of Prepreg Materials	20
3.9.1.1.3	Peel Strength after Process Chemicals (Optional Test)	16	3.10.2.1	Flammability	20
3.9.1.2	Dimensional Stability	16	3.10.2.2	Chemical Resistance (Optional Test)	20
3.9.1.3	Flexural Strength	16	3.10.2.3	Presence of Dicyandiamide (Dicy) (Optional Test)	20
3.9.1.4	Flexural Strength at Elevated Temperature	17	3.11	Electrical Requirements	20
3.9.1.5	Thermal Conductivity [=] w/(m ² K)	17	3.11.1	Electrical Requirements of Laminate Materials	20
3.9.1.6	Coefficient of Thermal Expansion (CTE) (Optional Test)	17	3.11.1.1	Permittivity	20
3.9.1.7	Z-Axis CTE / Total Expansion (Optional Test)	17	3.11.1.2	Loss Tangent	20
3.9.1.8	Fracture Toughness (Optional Test)	17	3.11.1.3	Volume Resistivity	20
3.9.2	Physical Requirements of Prepreg Materials	17	3.11.1.4	Surface Resistivity	20
3.9.2.1	Resin Content	17	3.11.1.5	Arc Resistance	20
3.9.2.1.1	Resin Content Percent (RC) (by Treated Weight)	17	3.11.1.6	Dielectric Breakdown	20
3.9.2.1.2	Resin Content Percent (RC) (by Burn-Off)	17	3.11.1.7	Electric Strength	20
3.9.2.1.3	Treated Weight Total (TW)	17	3.11.2	Electrical Requirements of Prepreg Materials	20
3.9.2.1.4	Variation Within a Panel	17	3.11.2.1	Permittivity	20
3.9.2.2	Flow Parameter	17	3.11.2.2	Loss Tangent	20
3.9.2.2.1	Resin Flow Percent (MF)	18	3.11.2.3	Electric Strength	20
3.9.2.2.2	Scaled Flow Thickness (SC)	18	3.12	Environmental Requirements	20
3.9.2.2.3	No Flow (NF)	18	3.12.1	Environmental Requirements of Laminate Materials	20
3.9.2.2.4	Rheological Flow (RE)	18	3.12.1.1	Moisture Absorption	20
3.9.2.2.5	Delta H (DH)	18	3.12.1.2	Fungus Resistance	21
3.9.2.2.6	Percent Cure (PC)	18	3.12.1.3	Pressure Vessel (Optional Test)	21
3.9.2.2.7	Gel Time (GT) (Optional Test)	18	3.12.1.4	Total Halogen Content (Optional Test)	21
3.9.2.2.8	Volatile Content (VC) (Optional Test)	18	3.12.1.5	Conductive Anodic Filament (CAF) Growth (Optional Test)	21
3.9.2.2.9	Thermal Conductivity (Prepreg Reference)	18	3.12.2	Environmental Requirements of Prepreg Materials	21
3.10	Chemical Requirements	18	3.12.2.1	Fungus Resistance	21
			3.12.2.2	Conductive Anodic Filament (CAF) Growth (Optional Test)	21

3.13 Substitutability 21

3.13.1 Substitutability of Specification Sheet Materials 21

3.13.2 Substitutability of Classes of Pits and Dents 21

3.13.3 Substitutability of Classes of Thickness Tolerance 21

3.13.4 Remarking of Substituted Laminates 21

3.14 Marking 21

3.14.1 Marking Laminate Materials 21

3.14.2 Marking Prepreg Materials 22

3.14.3 Marking of Shipping Containers 22

3.15 Workmanship 22

3.16 Material Safety 22

3.17 Prepreg Shelf Life 22

4 QUALITY ASSURANCE PROVISIONS 22

4.1 Quality System 22

4.2 Responsibility for Inspection 22

4.2.1 Test Equipment and Inspection Facilities 22

4.3 Qualification Testing 22

4.3.1 Samples 22

4.3.2 Frequency 23

4.3.3 Laminator Qualification Profile 23

4.3.4 Changes in Composition 23

4.3.5 Qualification Data Retention 23

4.4 Quality Conformance Inspection 23

4.4.1 Frequency 23

4.4.2 Acceptance Criteria 23

4.4.3 Rejected Lots 23

4.4.4 Conformance Data Retention 23

4.4.5 Certificate of Conformance 24

4.5 Statistical Process Control (SPC) 24

5 PREPARATION FOR DELIVERY 24

5.1 Packaging Materials 24

5.2 Authorized Distributors 24

6 NOTES 25

6.1 Ordering Information 25

6.1.1 Ordering Data for Laminate Materials 25

6.1.2 Ordering Data for Prepreg Materials 25

6.2 New Materials 25

7 KEYWORDS 26

7.1 Keyword Search Terms (Electronic/Soft Copy Searches) 26

7.2 Segmented Keyword Search Terms and All Specification Sheets that Use the Specific Keywords for Searching

7.3 Keyword Search Terms for All Specification Sheets 26

Figures

Figure 3-1 Thickness Measurements for Laminates 15

Tables

Table 1-1 Metal Cladding Types..... 2

Table 1-2 Copper Foil Weight and Thickness..... 3

Table 3-1 Reference Information and Test Frequency of Laminate..... 8

Table 3-2 Reference Information and Test Frequency of Prepreg..... 10

Table 3-3 Point Value for Longest Dimensions of Indentation..... 12

Table 3-4 Surface Quality Classification 13

Table 3-5 Permissible Variation in Length and Width of Laminates..... 14

Table 3-6 Permissible Variation in Length and Width of Prepregs..... 14

Table 3-7 Thickness and Tolerances for Laminates 16

Table 3-8 Permissible Bow and Twist for Laminates, %.... 16

Table 3-9 Flammability Requirements..... 19

Table 4-1 Quality Conformance Plan for Monthly, Quarterly and Annual Tests – Laminate..... 23

Table 4-2 Quality Conformance Plan for Monthly, Quarterly and Annual Tests – Prepreg..... 23

This Page Intentionally Left Blank

Specification for Base Materials for Rigid and Multilayer Printed Boards

1 SCOPE

This specification covers the requirements for base materials, herein referred to as laminate or prepreg, to be used primarily for rigid or multilayer printed boards for electrical and electronic circuits.

1.1 Classification The system shown below identifies clad and unclad laminate or prepreg base materials. The specification sheets serve as a cross-reference connecting the outlined callout system in this document to previously used systems.

Example for laminate base materials where this specification is referenced:

L	Material Designator (see 1.1.1)
25	Specification Sheet Number (see 1.1.1)
1500	Nominal Laminate Thickness (see 1.1.2)
C1/C1	Metal Cladding Type and Nominal Weight/Thickness (see 1.1.3)
A	Thickness Tolerance Class (see 1.1.4)
A	Surface Quality Class (see 1.1.5)

Example for prepreg base materials where this specification is referenced:

P	Material Designator (see 1.1.1)
25	Specification Sheet Number (see 1.1.1)
E7628	Reinforcement Style (see 1.1.6)
TW	Resin Content Method (see 1.1.7)
RE	Flow Parameter Method (see 1.1.7)
VC	Optional Prepreg Method (see 1.1.7)

1.1.1 Specification Sheet Description At the end of this document is a series of specification sheets. Each specification sheet outlines requirements for both laminate and prepreg for each product grade. The specification sheets are organized by a specific reinforcement type, resin system, and/or construction and are provided with a specification sheet number for ordering purposes. For convenience, the laminate and prepreg requirements for materials of the like composition are on the same specification sheet. Material Designator “L” indicates laminate material and Material Designator “P” indicates prepreg material as shown in designation examples in 1.1. When certifying to multiple specification sheets, the strongest performance requirements **shall** apply.

The headings for each specification sheet include reference definitions for the material, which cover the reinforcements, resin systems, flame retardants, and fillers used, as well as its other known identifications and glass transition temperature, T_g . The specific line items within the specification sheets are the requirements that material **shall** meet in order to be certified to this specification.

1.1.2 Nominal Laminate Thickness The nominal thickness is identified by four digits. For all substrates covered by this document, thicknesses may be specified or measured either over the cladding or over the dielectric (see 1.1.4 and 3.8.4.2). For metric specification, the first digit represents whole millimeters, the second represents tenths of millimeters, etc. For orders requiring Imperial units, the four digits indicate the thickness in ten-thousandths of an inch. In the example shown in 1.1, 1500 designates a laminate with thickness of 1.5 mm [0.0591 in], which would be specified as 0591 when using Imperial units.

1.1.3 Metal Cladding Type and Nominal Weight/Thickness The type and nominal weight or thickness of the metallic cladding for laminate base material is identified by five designators. The first and fourth designators indicate the type of cladding; the third designator is a slash mark that differentiates sides of the base material; the second and fifth designators indicate the nominal weight or thickness of the metallic cladding.