

PD IEC/TS 62132-9:2014



BSI Standards Publication

# Integrated circuits — Measurement of electromagnetic immunity

Part 9: Measurement of radiated  
immunity — Surface scan method

**bsi.**

...making excellence a habit.™

### **National foreword**

This Published Document is the UK implementation of IEC/TS 62132-9:2014.

The UK participation in its preparation was entrusted to Technical Committee EPL/47, Semiconductors.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2014.

Published by BSI Standards Limited 2014

ISBN 978 0 580 79947 1

ICS 31.200

**Compliance with a British Standard cannot confer immunity from legal obligations.**

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 30 September 2014.

### **Amendments/corrigenda issued since publication**

<b>Date</b>	<b>Text affected</b>
-------------	----------------------

---



# TECHNICAL SPECIFICATION

# SPECIFICATION TECHNIQUE



---

**Integrated circuits – Measurement of electromagnetic immunity –  
Part 9: Measurement of radiated immunity – Surface scan method**

**Circuits intégrés – Mesure de l'immunité électromagnétique –  
Partie 9: Mesure de l'immunité rayonnée – Méthode de balayage en surface**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

COMMISSION  
ELECTROTECHNIQUE  
INTERNATIONALE

PRICE CODE  
CODE PRIX

U

---

ICS 31.200

ISBN 978-2-8322-1808-2

**Warning! Make sure that you obtained this publication from an authorized distributor.  
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

## CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references.....	7
3 Terms, definitions and abbreviations .....	7
3.1 Terms and definitions .....	7
3.2 Abbreviations .....	8
4 General .....	8
5 Test Conditions .....	9
5.1 General.....	9
5.2 Supply voltage .....	9
5.3 Frequency range .....	9
6 Test equipment.....	9
6.1 General.....	9
6.2 Shielding.....	9
6.3 RF disturbance generator .....	9
6.4 Cables .....	9
6.5 Near-field probe .....	10
6.5.1 General .....	10
6.5.2 Magnetic (H) field probe .....	10
6.5.3 Electric (E) field probe.....	10
6.6 Probe-positioning and data acquisition system .....	10
6.7 DUT monitor .....	11
7 Test setup .....	11
7.1 General.....	11
7.2 Test configuration .....	11
7.3 Test circuit board .....	12
7.4 Probe-positioning system software setup .....	12
7.5 DUT Software .....	12
8 Test procedure .....	12
8.1 General.....	12
8.2 Operational check .....	13
8.3 Immunity test .....	13
8.3.1 General .....	13
8.3.2 Amplitude modulation.....	13
8.3.3 Test frequency steps and ranges.....	13
8.3.4 Test levels and dwell time .....	13
8.3.5 DUT monitoring.....	14
8.3.6 Detailed procedure.....	14
9 Test report.....	15
9.1 General.....	15
9.2 Test conditions.....	15
9.3 Probe design and calibration .....	15
9.4 Test data .....	15
9.5 Post-processing .....	16
9.6 Data exchange.....	16

Annex A (informative) Calibration of near-field probes .....	17
A.1 General.....	17
A.2 Test equipment .....	20
A.3 Calibration setup .....	20
A.4 Calibration procedure .....	20
Annex B (informative) Electric and magnetic field probes .....	22
B.1 General.....	22
B.2 Probe electrical description .....	22
B.3 Probe physical description.....	22
B.3.1 Probe construction .....	22
B.3.2 Electric field probe .....	23
B.3.3 Magnetic field probe.....	23
Annex C (informative) Coordinate systems .....	24
C.1 General.....	24
C.2 Cartesian coordinate system .....	24
C.3 Cylindrical coordinate system .....	25
C.4 Spherical coordinate system.....	26
C.5 Coordinate system conversion.....	26
Bibliography .....	27
Figure 1 – Example of a probe-positioning system .....	11
Figure 2 – Test setup.....	12
Figure 3 – Example of data overlaid on an image of the DUT .....	16
Figure A.1 – Typical probe factor in dB ( $\Omega \cdot m^2$ ) against frequency .....	19
Figure A.2 – Typical probe factor in dB ( $S/m^2$ ) against frequency.....	19
Figure A.3 – Probe calibration setup.....	20
Figure B.1 – Basic structure of electric and magnetic field probe schematics.....	22
Figure B.2 – Example of electric field probe construction ( $E_z$ ).....	23
Figure B.3 – Example of magnetic field probe construction ( $H_x$ or $H_y$ ).....	23
Figure C.1 – Right-hand Cartesian coordinate system (preferred) .....	24
Figure C.2 – Left-hand Cartesian coordinate system.....	25
Figure C.3 – Cylindrical coordinate system .....	25
Figure C.4 – Spherical coordinate system.....	26
Table 1 – Frequency step size versus frequency range.....	13
Table A.1 – Probe factor linear units .....	18
Table A.2 – Probe factor logarithmic units .....	18
Table C.1 – Coordinate system conversion.....	26

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

---

### **INTEGRATED CIRCUITS – MEASUREMENT OF ELECTROMAGNETIC IMMUNITY –**

#### **Part 9: Measurement of radiated immunity – Surface scan method**

#### FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. In exceptional circumstances, a technical committee may propose the publication of a technical specification when

- the required support cannot be obtained for the publication of an International Standard, despite repeated efforts, or
- the subject is still under technical development or where, for any other reason, there is the future but no immediate possibility of an agreement on an International Standard.

Technical specifications are subject to review within three years of publication to decide whether they can be transformed into International Standards.

IEC TS 62132-9, which is a technical specification, has been prepared by subcommittee 47A: Integrated circuits, of IEC technical committee 47: Semiconductor devices.

The text of this technical specification is based on the following documents:

Enquiry draft	Report on voting
47A/924/DTS	47A/936/RVC

Full information on the voting for the approval of this technical specification can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62132 series, published under the general title *Integrated circuits – Measurement of electromagnetic immunity*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- transformed into an International standard,
- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

**IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**

## INTRODUCTION

Techniques for generating near-fields over integrated circuits and their surrounding environment can identify the areas susceptible to radiation, which could cause errors in the device. The ability to associate magnetic or electric field strengths with a particular location on a device can provide valuable information for improvement of an IC both in terms of functionality and EMC performance.

Near-field scan techniques have considerably evolved over recent years. The improved efficiency, bandwidth and spatial resolution of the probes offer analysis of integrated circuits operating into the gigahertz range. Post-processing can considerably enhance the resolution of a near-field scan test bench and the measured data can be shown in various ways per user's choice.

## INTEGRATED CIRCUITS – MEASUREMENT OF ELECTROMAGNETIC IMMUNITY –

### Part 9: Measurement of radiated immunity – Surface scan method

#### 1 Scope

This part of IEC 62132 provides a test procedure, which defines a method for evaluating the effect of near electric, magnetic or electromagnetic field components on an integrated circuit (IC). This diagnostic procedure is intended for IC architectural analysis such as floor planning and power distribution optimization. This test procedure is applicable to testing an IC mounted on any circuit board that is accessible to the scanning probe. In some cases it is useful to scan not only the IC but also its environment. For comparison of surface scan immunity between different ICs, the standardized test board defined in IEC 62132-1 should be used.

This measurement method provides a mapping of the sensitivity (immunity) to electric- or magnetic-near-field disturbance over the IC. The resolution of the test is determined by the capability of the test probe and the precision of the Probe-positioning system. This method is intended for use up to 6 GHz. Extending the upper limit of frequency is possible with existing probe technology but is beyond the scope of this specification. The tests described in this document are carried out in the frequency domain using continuous wave (CW), amplitude modulated (AM) or pulse modulated (PM) signals.

#### 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050 (all parts), *International Electrotechnical Vocabulary* (available at <<http://www.electropedia.org>>)

IEC 62132-1, *Integrated circuits – Measurement of electromagnetic immunity, 150 kHz to 1 GHz – Part 1: General conditions and definitions*

IEC TS 61967-3, *Integrated circuits – Measurement of electromagnetic emissions, 150 kHz to 1 GHz – Part 3: Measurement of radiated emissions – Surface scan method*

#### 3 Terms, definitions and abbreviations

##### 3.1 Terms and definitions

For the purpose of this document, the definitions and definitions given in IEC 62132-1, IEC 60050-131 and IEC 60050-161, as well as the following apply.

###### 3.1.1

###### **altitude**

distance between the tip of the near-field probe and the reference plane of the scan (e.g. the PCB, the upper surface of the package)