

**ASME BTH-1–2014**  
(Revision of ASME BTH-1–2011)

# **Design of Below-the-Hook Lifting Devices**

---

**AN AMERICAN NATIONAL STANDARD**



**The American Society of  
Mechanical Engineers**

INTENTIONALLY LEFT BLANK

**Errata**  
**to**  
**ASME BTH-1–2014**  
**Design of Below-the-Hook**  
**Lifting Devices**

On page 13, in the nomenclature for eq. (3-17), the second definition for  $C_{LTB}$  has been corrected by errata to replace the square root sign in the numerator with parentheses. The correct equation is shown below.

$$C_{LTB} = \frac{2.00(EI_x/GJ)}{(L_b/b_f)^2} + 0.275 \leq 1.00$$

THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS  
Two Park Avenue, New York, NY 10016-5990

January 2015



J0175E

**ASME BTH-1–2014**  
(Revision of ASME BTH-1–2011)

# Design of Below-the-Hook Lifting Devices

---

**AN AMERICAN NATIONAL STANDARD**



**The American Society of  
Mechanical Engineers**

Two Park Avenue • New York, NY • 10016 USA

Date of Issuance: October 29, 2014

The next edition of this Standard is scheduled for publication in 2017. This Standard will become effective 1 year after the Date of Issuance.

ASME issues written replies to inquiries concerning interpretations of technical aspects of this Standard. Interpretations may be accessed as they are issued at <http://go.asme.org/interpretations>. They are published on the ASME Web site under the Committee Pages at <http://cstools.asme.org/>.

Errata to codes and standards may be posted on the ASME Web site under the Committee Pages to provide corrections to incorrectly published items, or to correct typographical or grammatical errors in codes and standards. Such errata shall be used on the date posted.

The Committee Pages can be found at <http://cstools.asme.org/>. There is an option available to automatically receive an e-mail notification when errata are posted to a particular code or standard. This option can be found on the appropriate Committee Page after selecting “Errata” in the “Publication Information” section.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The Standards Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment that provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not “approve,” “rate,” or “endorse” any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor assumes any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

No part of this document may be reproduced in any form,  
in an electronic retrieval system or otherwise,  
without the prior written permission of the publisher.

The American Society of Mechanical Engineers  
Two Park Avenue, New York, NY 10016-5990

Copyright © 2014 by  
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS  
All rights reserved  
Printed in U.S.A.

# CONTENTS

Foreword .....	v
Committee Roster .....	vi
Correspondence With the BTH Committee .....	vii
Summary of Changes .....	viii
<b>Chapter 1 Scope, Definitions, and References</b> .....	<b>1</b>
1-1 Purpose .....	1
1-2 Scope .....	1
1-3 New and Existing Devices .....	1
1-4 General Requirements .....	1
1-5 Definitions .....	2
1-6 Symbols .....	4
1-7 References .....	7
<b>Chapter 2 Lifter Classifications</b> .....	<b>9</b>
2-1 General .....	9
2-2 Design Category .....	9
2-3 Service Class .....	9
<b>Chapter 3 Structural Design</b> .....	<b>10</b>
3-1 General .....	10
3-2 Member Design .....	10
3-3 Connection Design .....	15
3-4 Fatigue Design .....	18
3-5 Other Design Considerations .....	32
<b>Chapter 4 Mechanical Design</b> .....	<b>33</b>
4-1 General .....	33
4-2 Sheaves .....	33
4-3 Wire Rope .....	34
4-4 Drive Systems .....	34
4-5 Gearing .....	34
4-6 Bearings .....	36
4-7 Shafting .....	37
4-8 Fasteners .....	38
4-9 Grip Support Force .....	39
4-10 Vacuum Lifting Device Design .....	39
4-11 Fluid Power Systems .....	40
4-12 Lifting Magnets .....	40
<b>Chapter 5 Electrical Components</b> .....	<b>41</b>
5-1 General .....	41
5-2 Electric Motors and Brakes .....	41
5-3 Operator Interface .....	41
5-4 Controllers and Auxiliary Equipment .....	42
5-5 Grounding .....	43
5-6 Power Disconnects .....	43
5-7 Batteries .....	43

<b>Figures</b>		
4-2.6-1	Sheave Dimensions .....	33
4-2.7-1	Sheave Gap .....	33
4-9.2-1	Illustration of Holding and Support Forces .....	39
<b>Tables</b>		
2-3-1	Service Class .....	9
3-2.2-1	Limiting Width–Thickness Ratios for Compression Elements .....	11
3-3.4.2-1	Minimum Effective Throat Thickness of Partial-Penetration Groove Welds .....	17
3-3.4.3-1	Minimum Sizes of Fillet Welds .....	18
3-4.3-1	Allowable Stress Ranges, ksi (MPa) .....	19
3-4.4-1	Fatigue Design Parameters .....	20
4-5.3-1	Strength Factors for Calculating Load Capacity (American Standard Tooth Forms) .....	35
4-6.2-1	$L_{10}$ Life .....	36
4-7.5-1	Key Size Versus Shaft Diameter (ASME B17.1) .....	38
4-7.5-2	Key Size Versus Shaft Diameter (DIN 6885-1) .....	38
4-7.6.1-1	Fatigue Stress Amplification Factors .....	38
<b>Nonmandatory Appendices</b>		
A	Commentary for Chapter 1: Scope, Definitions, and References .....	45
B	Commentary for Chapter 2: Lifter Classifications .....	49
C	Commentary for Chapter 3: Structural Design .....	51
D	Commentary for Chapter 4: Mechanical Design .....	60
E	Commentary for Chapter 5: Electrical Components .....	63

# FOREWORD

There have been many formal requests for interpretation of the limited structural design criteria stated within ASME B30.20, *Below-the-Hook Lifting Devices*, a safety standard. As a consequence, industry has for quite some time expressed a need for a comprehensive design standard for below-the-hook lifting devices that would complement the safety requirements of ASME B30.20. All editions of ASME B30.20 have included structural design criteria oriented toward the industrial manufacturing community requiring a minimum design factor of three, based on the yield strength of the material; recent editions have also included design criteria for the fatigue failure mode. However, members of the construction community expressed the need for design criteria more suitable to their operating conditions, including a lower design factor, and the necessity to address other failure modes such as fracture, shear and buckling, and design topics such as impact and fasteners.

A Design Task Group was created in 1997 to begin work on a design standard as a companion document to ASME B30.20. The ASME BTH Standards Committee on the Design of Below-the-Hook Lifting Devices was formed out of the Design Task Group and held its organizational meeting on December 5, 1999.

ASME BTH-1–2005, *Design of Below-the-Hook Lifting Devices*, contained five chapters: Scope and Definitions, Lifter Classifications, Structural Design, Mechanical Design, and Electrical Components. This Standard, intended for general industry and construction, sets forth two design categories for lifters based on the magnitude and variation of loading, and operating and environmental conditions. The two design categories provide different design factors for determining allowable static stress limits. Five Service Classes based on load cycles are provided. The Service Class establishes allowable stress range values for lifter structural members and design parameters for mechanical components. ASME BTH-1–2005 was approved by the American National Standards Institute on October 18, 2005.

ASME BTH-1–2008 incorporated editorial revisions and two new mechanical design sections for grip ratio and vacuum-lifting device design. ASME BTH-1–2008 was approved by the American National Standards Institute on September 17, 2008.

ASME BTH-1–2011 incorporated revisions throughout the Standard and the addition of a new mechanical design section for fluid power systems. ASME BTH-1–2011 was approved by the American National Standards Institute on September 23, 2011.

This revision of ASME BTH-1 includes a section on lifting magnets that has been incorporated into Chapter 4. Other technical revisions include new requirements for fluid pressure control and electrical system guarding. Along with these technical changes, the nonmandatory Commentary for each chapter was moved to its own respective Nonmandatory Appendix. ASME BTH-1–2014 was approved by the American National Standards Institute on June 24, 2014.

# ASME BTH STANDARDS COMMITTEE

## Design of Below-the-Hook Lifting Devices

(The following is the roster of the Committee at the time of approval of this Standard.)

### STANDARDS COMMITTEE OFFICERS

**D. R. Verenski**, *Chair*  
**D. Duerr**, *Vice Chair*  
**M. R. Gerson**, *Secretary*

### STANDARDS COMMITTEE PERSONNEL

**S. Barton**, Doc Magnet  
**G. A. Bond**, Wood's Powr-Grip Co., Inc.  
**P. W. Boyd**, The Boeing Co.  
**D. Duerr**, 2DM Associates, Inc.  
**J. D. Edmundson**, Konecranes/P&H  
**A. Faris**, Ibberson Engineering Co.  
**M. R. Gerson**, The American Society of Mechanical Engineers  
**K. M. Jankowski**, Walker Magnetics  
**T. C. Mackey**, Washington River Protection Solutions  
**D. L. McCabe**, Babcock and Wilcox Co.  
**D. T. Rebbin**, Bradley Lifting Corp.  
**J. E. Rea**, *Alternate*, Bradley Lifting Corp.  
**J. W. Rowland III**, Consultant  
**R. S. Stemp**, Lampson International, LLC  
**P. D. Sweeney**, General Dynamics, Electric Boat  
**P. E. Van Every**, Tecnomagnete, Inc.  
**D. R. Verenski**, Hunter Lift Ltd.  
**T. J. Brookbank**, *Alternate*, Hunter Lift Ltd.

### HONORARY MEMBERS

**R. A. Dahlin**, Walker Magnetics  
**J. W. Downs, Jr.**, Downs Crane and Hoist Co.

## CORRESPONDENCE WITH THE BTH COMMITTEE

**General.** ASME Standards are developed and maintained with the intent to represent the consensus of concerned interests. As such, users of this Standard may interact with the Committee by requesting interpretations, proposing revisions, and attending Committee meetings. Correspondence should be addressed to:

Secretary, BTH Standards Committee  
The American Society of Mechanical Engineers  
Two Park Avenue  
New York, NY 10016-5990  
<http://go.asme.org/Inquiry>

**Proposing Revisions.** Revisions are made periodically to the Standard to incorporate changes that appear necessary or desirable, as demonstrated by the experience gained from the application of the Standard. Approved revisions will be published periodically.

The Committee welcomes proposals for revisions to this Standard. Such proposals should be as specific as possible, citing the paragraph number(s), the proposed wording, and a detailed description of the reasons for the proposal, including any pertinent documentation.

**Interpretations.** Upon request, the BTH Standards Committee will render an interpretation of any requirement of the Standard. Interpretations can only be rendered in response to a written request sent to the Secretary of the BTH Standards Committee at [go.asme.org/Inquiry](http://go.asme.org/Inquiry).

The request for an interpretation should be clear and unambiguous. It is further recommended that the inquirer submit his/her request in the following format:

Subject: Cite the applicable paragraph number(s) and the topic of the inquiry.  
Edition: Cite the applicable edition of the Standard for which the interpretation is being requested.  
Question: Phrase the question as a request for an interpretation of a specific requirement suitable for general understanding and use, not as a request for an approval of a proprietary design or situation. The inquirer may also include any plans or drawings that are necessary to explain the question; however, they should not contain proprietary names or information.

Requests that are not in this format may be rewritten in the appropriate format by the Committee prior to being answered, which may inadvertently change the intent of the original request.

ASME procedures provide for reconsideration of any interpretation when or if additional information that might affect an interpretation is available. Further, persons aggrieved by an interpretation may appeal to the cognizant ASME Committee or Subcommittee. ASME does not "approve," "certify," "rate," or "endorse" any item, construction, proprietary device, or activity.

**Attending Committee Meetings.** The BTH Standards Committee regularly holds meetings and/or telephone conferences that are open to the public. Persons wishing to attend any meeting and/or telephone conference should contact the Secretary of the BTH Standards Committee. Future Committee meeting dates and locations can be found on the Committee Page at <http://cstools.asme.org/>.

# ASME BTH-1–2014

## SUMMARY OF CHANGES

Following approval by the ASME BTH Standards Committee and ASME, and after public review, ASME BTH-1–2014 was approved by the American National Standards Institute on June 24, 2014.

ASME BTH-1–2014 includes editorial changes, revisions, and corrections identified by a margin note, (14).

<i>Page</i>	<i>Location</i>	<i>Change</i>
1	1-2	Second sentence of last paragraph revised
2, 3	1-4.6	Revised
	1-5.1	Definitions of <i>cycle</i> , <i>load</i> ; <i>design factor</i> ; <i>fatigue</i> ; <i>lifting attachment</i> ; <i>limit state</i> ; <i>qualified person</i> ; <i>stress, maximum</i> ; and <i>stress, minimum</i> revised
	1-5.2	Definitions of <i>brittle fracture</i> revised and <i>unbraced length</i> deleted
	1-5.3	Definitions of <i>grip ratio</i> and <i>gripping force</i> deleted
4–7	1-6.1	Nomenclature for $F_{ur}$ , $L_b$ , $M_1$ , $M_2$ , $N$ , $N_d$ , and $N_{eq}$ revised, and $I_x$ added
	1-6.2	Nomenclature for $F_H$ revised, $GR_{min}$ and $\mu_{SF}$ deleted, and $F_s$ added
	1-7	ANSI/NFPA 70 updated
10	3-1.3	3-1.3.1 and 3-1.3.2 designations added
	3-1.4	Revised
12, 13	3-2.3.1	Title revised
	3-2.3.2	Revised
	3-2.3.3	Revised
	3-2.3.4	Revised
16	3-3.3.4	Revised
17	3-3.4.1	Revised
18	3-4.2	Revised
19–32	Table 3-4.3-1	Last row added
	3-4.6	$F_{TH}$ and $N$ revised
	Table 3-4.4-1	Revised in its entirety
39	4-9	Revised in its entirety
	Figure 4-9.2-1	Added
40	4-11.5	Added

<i>Page</i>	<i>Location</i>	<i>Change</i>
	4-11.6	Previous para. 4-11.5 redesignated as 4-11.6
	4-12	Added
42, 43	5-3.8	Revised
	5-4	Title revised
	5-4.6	Revised
	5-4.10	Added
	5-6.2	Revised
	5-6.3	Revised
45–48	Nonmandatory Appendix A	Added
49, 50	Nonmandatory Appendix B	Added
51–59	Nonmandatory Appendix C	Added
60–62	Nonmandatory Appendix D	Added
63, 64	Nonmandatory Appendix E	Added

INTENTIONALLY LEFT BLANK

# DESIGN OF BELOW-THE-HOOK LIFTING DEVICES

## Chapter 1 Scope, Definitions, and References

### 1-1 PURPOSE

This Standard sets forth design criteria for ASME B30.20, Below-the-Hook Lifting Devices. This Standard serves as a guide to designers, manufacturers, purchasers, and users of below-the-hook lifting devices.

### (14) 1-2 SCOPE

This Standard provides minimum structural and mechanical design and electrical component selection criteria for ASME B30.20, Below-the-Hook Lifting Devices.

The provisions in this Standard apply to the design or modification of below-the-hook lifting devices. Compliance with requirements and criteria that may be unique to specialized industries and environments is outside the scope of this Standard.

Lifting devices designed to this Standard shall comply with ASME B30.20, Below-the-Hook Lifting Devices. ASME B30.20 includes provisions that apply to the marking, construction, installation, inspection, testing, maintenance, and operation of below-the-hook lifting devices.

The provisions defined in this Standard address the most common and broadly applicable aspects of the design of below-the-hook lifting devices. A qualified person shall determine the appropriate methods to be used to address design issues that are not explicitly covered in the standard so as to provide design factors and/or performance consistent with the intent of this Standard.

### 1-3 NEW AND EXISTING DEVICES

The effective date of this Standard shall be one year after its date of issuance. Lifting devices manufactured after the effective date shall conform to the requirements of this Standard.

When a lifter is being modified, its design shall be reviewed relative to this Standard, and the need to meet this Standard shall be evaluated by the manufacturer or a qualified person.

### 1-4 GENERAL REQUIREMENTS

#### 1-4.1 Design Responsibility

Lifting devices shall be designed by, or under the direct supervision of, a qualified person.

#### 1-4.2 Units of Measure

A dual unit format is used. Values are given in U.S. Customary units as the primary units followed by the International System of Units (SI) in parentheses as the secondary units. The values stated in U.S. Customary units are to be regarded as the standard. The SI units in the text have been directly (softly) converted from U.S. Customary units.

#### 1-4.3 Design Criteria

All below-the-hook lifting devices shall be designed for specified rated loads, load geometry, Design Category (see section 2-2), and Service Class (see section 2-3). Resolution of loads into forces and stress values affecting structural members, mechanical components, and connections shall be performed by an accepted analysis method.

#### 1-4.4 Analysis Methods

The allowable stresses and stress ranges defined in this Standard are based on the assumption of analysis by classical strength of material methods (models), although other analysis methods may be used. The analysis techniques and models used by the qualified person shall accurately represent the loads, material properties, and device geometry; stress values resulting from the analysis shall be of suitable form to permit correlation with the allowable stresses defined in this Standard.

#### 1-4.5 Material

The design provisions of this Standard are based on the use of carbon, high strength low-alloy, or heat treated constructional alloy steel for structural members and many mechanical components. Other materials may be used, provided the margins of safety and fatigue life are equal to or greater than those required by this Standard.