

BS 1139-6:2014



BSI Standards Publication

## **Metal scaffolding –**

Part 6: Prefabricated tower scaffolds outside the scope of BS EN 1004, but utilizing components from such systems – Specification

**bsi.**

...making excellence a habit.™

**Publishing and copyright information**

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2014

Published by BSI Standards Limited 2014

ISBN 978 0 580 83646 6

ICS 91.220

The following BSI references relate to the work on this document:

Committee reference B/514/24

Draft for comment 14/30286613 DC

**Publication history**

First published December 2005

Second (present) edition, December 2014

**Amendments issued since publication**

<b>Date</b>	<b>Text affected</b>
-------------	----------------------

---

## Contents

Foreword *ii*

1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	General Requirements	13
5	Materials	13
6	Dimensions	13
7	Structural design	20
8	Verification	23
9	Markings	24
10	Information to be supplied with a prefabricated tower scaffold	25

Bibliography 27

### List of figures

Figure 1	– Example of a cantilever tower scaffold	2
Figure 2	– Example of a large deck tower scaffold	3
Figure 3	– Example of a linked tower scaffold	4
Figure 4	– Example of a linked tower scaffold with bridge decks	5
Figure 5	– Example of a stepped tower scaffold	6
Figure 6	– Example of a high clearance frame	7
Figure 7	– Example of a walk through end frame at ground level	8
Figure 8	– Example of a step through end frame	8
Figure 9	– Example of a portal end frame	9
Figure 10	– Examples of bridge beams	10
Figure 11	– Example of a prefabricated tower scaffold cantilever platform	11
Figure 12	– Example showing a prefabricated tower scaffold of 2 bay lengths in Elevation A and 3 bays width in Elevation B	12
Figure 13	– Minimum clear height and width of a high clearance frame on the highway for the passage of the general public	14
Figure 14	– Minimum clear height and width of a walk through end frame for walk through frames not intended for use on the highway for the passage of the general public	15
Figure 15	– Minimum clear height and width for walk through end frames on the highway for the passage of the general public	16
Figure 16	– Minimum clear width for step through end frames	17
Figure 17	– Minimum clear width and height for portal end frames	18
Figure 18	– Maximum vertical distance between platforms used for assembly and dismantling	19

### List of tables

Table 1	– Dimensions for portal end frames	17
Table 2	– Load classes	21

### Summary of pages

This document comprises a front cover, an inside front cover, pages i to ii, pages 1 to 28, an inside back cover and a back cover.

## Foreword

### Publishing information

This part of BS 1139 is published by BSI Standards Limited, under licence from The British Standards Institution, and came into effect on 31 December 2014. It was prepared by Subcommittee B/514/24, *Access towers*, under the authority of Technical Committee B/514, *Access and support equipment*. A list of organizations represented on these committee can be obtained on request to their secretary.

### Supersession

This part of BS 1139 supersedes BS 1139-6:2005, which is withdrawn.

### Relationship to other standards

This part of BS 1139 should be read in conjunction with, and is complementary to, BS EN 1004, *Mobile access and working towers made of prefabricated elements — Materials, dimensions, design loads, safety and performance requirements*.

### Information about this document

This is a full revision of the standard and introduces the following principal changes:

- clarification of the scope;
- updated terms and definitions;
- dimensions for certain components;
- new requirements for structural design and positional stability;
- new requirements for design verification;
- new requirements for marking and for the information to be supplied.

### Presentational conventions

The provisions of this standard are presented in roman (i.e. upright) type. Its requirements are expressed in sentences in which the principal auxiliary verb is "shall".

*Commentary, explanation and general informative material is presented in smaller italic type, and does not constitute a normative element.*

Requirements in this standard are drafted in accordance with *The BSI guide to standardization – Section 2: Rules for the structure, drafting and presentation of British Standards*, subclause 11.3.1, which states, "Requirements should be expressed using wording such as: 'When tested as described in Annex A, the product shall ...'". This means that only those products that are capable of passing the specified test will be deemed to conform to this standard.

### Contractual and legal considerations

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Attention is drawn to the Work at Height Regulations 2005 [1].

**Compliance with a British Standard cannot confer immunity from legal obligations.**

## 1 Scope

This part of BS 1139 specifies requirements for the structural design of prefabricated tower scaffolds utilizing components from mobile access and working towers specified in BS EN 1004 but in configurations that are outside of the scope of that standard.

These configurations include:

- a) prefabricated tower scaffolds outside the height limits of BS EN 1004;
- b) towers with more than one working platform;
- c) large deck tower scaffolds;
- d) linked tower scaffolds;
- e) cantilever tower scaffolds;
- f) stepped tower scaffolds;
- g) tower scaffolds used as a means of access;
- h) towers built on base plates instead of castors.

This British Standard applies to prefabricated tower scaffolds subject to wind loads up to and including  $0.1 \text{ kN/m}^2$ .

*NOTE* Where a prefabricated tower scaffold might be subject to wind in excess of  $0.1 \text{ kN/m}^2$ , and it cannot be dismantled or moved to avoid these winds, suitable wind design criteria can be found in BS EN 1991-1-4.

This British Standard does not cover prefabricated tower scaffolds using guys as a method of stabilization.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

BS EN 74 (all parts), *Couplers, spigot pins and baseplates for use in falsework and scaffolds*

BS EN 1004, *Mobile access and working towers made of prefabricated elements – Materials, dimensions, design loads, safety and performance requirements*

BS EN 1298, *Mobile access and working towers – Rules and guidelines for the preparation of an instruction manual*

BS EN 1999-1-1, *Eurocode 9: Design of aluminium structures – Part 1-1: General structural rules*

BS EN 12811-2, *Temporary works equipment – Part 2: Information on materials*