

ASME B5.60-2014
(Revision of ASME B5.60-2002)

Workholding Chucks: Jaw-Type Chucks

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

ASME B5.60-2014
(Revision of ASME B5.60-2002)

Workholding Chucks: Jaw-Type Chucks

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

Two Park Avenue • New York, NY • 10016 USA

Date of Issuance: February 6, 2015

This Standard will be revised when the Society approves the issuance of a new edition.

ASME issues written replies to inquiries concerning interpretations of technical aspects of this Standard. Interpretations are published on the Committee Web page and under go.asme.org/InterpsDatabase. Periodically certain actions of the ASME B5 Committee may be published as Cases. Cases are published on the ASME Web site under the B5 Committee Page at go.asme.org/B5committee as they are issued.

Errata to codes and standards may be posted on the ASME Web site under the Committee Pages to provide corrections to incorrectly published items, or to correct typographical or grammatical errors in codes and standards. Such errata shall be used on the date posted.

The B5 Committee Page can be found at go.asme.org/B5committee. There is an option available to automatically receive an e-mail notification when errata are posted to a particular code or standard. This option can be found on the appropriate Committee Page after selecting “Errata” in the “Publication Information” section.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The Standards Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment that provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not “approve,” “rate,” or “endorse” any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor assumes any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.

The American Society of Mechanical Engineers
Two Park Avenue, New York, NY 10016-5990

Copyright © 2015 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All rights reserved
Printed in U.S.A.

CONTENTS

| | |
|---|-----------|
| Foreword | v |
| Committee Roster | vi |
| Correspondence With the B5 Committee | vii |
| 1 General Description and Definitions of Terms | 1 |
| 2 Chuck-to-Spindle Interface | 4 |
| 3 Jaw Mountings | 37 |
| 4 Performance Testing | 69 |
| 5 Safety Code of Practice | 74 |
| Figures | |
| 1-1 Example of a Power Chuck Assembly | 2 |
| 1-2 Exploded View of a Typical Manual Chuck | 3 |
| 1-3 Exploded View of a Power Chuck | 3 |
| 2-1 Type A Spindle Location of Holes and Drive Button for Sizes A-5 Through A-11 | 6 |
| 2-2 Type A Spindle Location of Holes and Drive Button for Sizes A-15 Through A-28 | 7 |
| 2-3 Type A Spindle Dimensions for Sizes A-3 Through A-28, and Location of Holes and Drive Button for Sizes A2-3 and A2-4 | 8 |
| 2-4 Type C Spindle | 10 |
| 2-5 Type C Spindle Location of Holes | 11 |
| 2-6 Type D Spindle | 13 |
| 2-7 Type A Spindle | 14 |
| 2-8 Type D Spindle Location of Holes for Size D-3 | 15 |
| 2-9 Type D Spindle Location of Holes for Size D-4 | 16 |
| 2-10 Type D Spindle Location of Holes for Sizes D-5 Through D-20 | 17 |
| 2-11 Type D Spindle Cam for Size D-3 | 18 |
| 2-12 Type D Spindle Cam for Size D-4 | 19 |
| 2-13 Type D Spindle Cams for Sizes D-5 Through D-20 | 20 |
| 2-14 Type D Spindle Detent and Cam Screws | 21 |
| 2-15 Type D Spindle Detent and Cam Springs | 21 |
| 2-16 Type D Spindle Detent Plunger | 21 |
| 2-17 Type A Chucks and Faceplates | 25 |
| 2-18 Type A Chuck and Faceplate Dimensions | 26 |
| 2-19 Type C Chucks and Faceplates | 28 |
| 2-20 Type C Chuck and Faceplate Dimensions | 29 |
| 2-21 Type D Chucks and Faceplates | 31 |
| 2-22 Types D-3 and D-4 Backs of Chucks and Faceplates | 32 |
| 2-23 Types D-5 Through D-20 Backs of Chucks and Faceplates | 33 |
| 2-24 Type D Cam Lock Studs and Stud Locking Screw | 34 |
| 3-1 Fastener Guidelines | 38 |
| 3-2 Jaw Interface Flatness Guidelines | 39 |
| 4-1 Spindle Verification Test for Chuck Mounted Directly on the Test Spindle | 69 |
| 4-2 Spindle Verification Test for Chuck Mounted on an Adapter | 70 |
| 4-3 Geometric Tests | 70 |
| 4-4 Manual-Scroll Chucks: Checking Centering Accuracy and Repeatability of Outside-Diameter Grip | 71 |
| 4-5 Manual-Scroll Chucks: Checking Centering Accuracy and Repeatability of Jaw Steps | 72 |

| | | |
|-----|---|----|
| 4-6 | Power Chucks: Checking Centering Accuracy and Repeatability for External Chucking | 72 |
| 4-7 | Power Chucks: Checking Centering Accuracy and Repeatability for Internal Chucking | 73 |

Forms

| | | |
|-----|---|----|
| 5-1 | Sample Maintenance Schedule Sheet | 77 |
| 5-2 | Sample Grip Force Log Sheet | 78 |

Tables

| | | |
|------|---|----|
| 2-1 | Type A Spindle Dimensions | 9 |
| 2-2 | Type C Spindle Dimensions | 12 |
| 2-3 | Type D Spindle Dimensions | 22 |
| 2-4 | Type D Spindle Cam Dimensions | 23 |
| 2-5 | Type D Spindle Detent and Cam Screws Dimensions | 24 |
| 2-6 | Type D Spindle Detent and Cam Spring Dimensions | 24 |
| 2-7 | Type D Spindle Detent Plunger Dimensions | 24 |
| 2-8 | Type A Chuck and Faceplate Dimensions | 27 |
| 2-9 | Type C Chuck and Faceplate Dimensions | 30 |
| 2-10 | Type D Chuck and Faceplate Dimensions | 35 |
| 2-11 | Type D Chuck and Faceplate Stud Dimensions | 36 |
| 2-12 | Type D Chuck and Faceplate Stud Locking Screw Dimensions | 36 |
| 3-1 | Top-Jaw Features | 40 |
| 3-2 | Tongue and Groove, Medium Duty Chucks, Wrench Operated | 42 |
| 3-3 | Tongue and Groove, Medium Duty Chucks, Three-Step Reversible Top Jaw, Wrench Operated | 44 |
| 3-4 | Tongue and Groove, Heavy Duty Chucks, Wrench Operated | 45 |
| 3-5 | Tongue and Groove, Heavy Duty Chucks, Three-Step Reversible Top Jaw, Wrench Operated | 47 |
| 3-6 | Tongue and Groove, Heavy Duty Chucks, Drawbar Operated | 48 |
| 3-7 | Metric Tongue and Groove Chucks, Master Jaw | 50 |
| 3-8 | Square Serrated, Heavy Duty Chucks, Wrench or Drawbar Operated | 51 |
| 3-9 | Square Serrated, Heavy Duty Chucks, Top-Jaw Master Key | 52 |
| 3-10 | Square Serrated, Heavy Duty Chucks, Master Jaw Nut | 53 |
| 3-11 | Square Serrated, Heavy Duty Chucks, Three-Step Reversible Top Jaw | 54 |
| 3-12 | Acme Serrated, Heavy Duty Chucks, Power Wrench or Drawbar Operated | 55 |
| 3-13 | Acme Serrated, Master Key | 56 |
| 3-14 | Acme Serrated, Jaw Nut | 57 |
| 3-15 | Acme Serrated, Three-Step Reversible Top Jaw | 58 |
| 3-16 | 90 deg Serrated Jaw Interface (Inch), Serration Data | 59 |
| 3-17 | 90 deg Serrated Jaw Interface (Inch), Accumulated Pitch Variation | 60 |
| 3-18 | 60 deg Serrated Jaw Interface (Metric), Serration Data | 61 |
| 3-19 | 60 deg Serrated Jaw Interface (Metric), Accumulated Pitch Variation | 62 |
| 3-20 | 60 deg Metric and 90 deg Inch Serrated Jaws and Jaw-Nut Interface | 63 |
| 3-21 | 1.5 mm × 60 deg Serrated Top Jaw (Metric) | 64 |
| 3-22 | Pin Locator Chucks, Master Jaw | 65 |
| 3-23 | Ball Style Chucks, Master Jaw | 66 |
| 3-24 | Ball Style Chucks, Top Jaw | 67 |
| 3-25 | Ball Style Chucks, Jaw Nut | 68 |

Mandatory Appendix

| | | |
|---|---|----|
| I | Calculation of Force, Torque, and Speed | 79 |
|---|---|----|

Nonmandatory Appendix

| | | |
|---|-------------------|----|
| A | Legacy Data | 83 |
|---|-------------------|----|

FOREWORD

During the review, revision, and update of the existing inch-based American National Standard B5.8 on Chucks and Chuck Jaws, Technical Committee 11 of the ASME B5 Committee on Machine Tools recognized the need for an industry standard on metric-dimensioned chucks.

This Standard was developed after reviewing currently available national and international standards, which were used as its foundation.

ASME B5.60-2002 was approved by the American National Standards Institute on June 26, 2002. Addenda were approved on February 24, 2005 and February 2, 2009.

ASME B5.60-2014 was approved by the American National Standards Institute on September 15, 2014.

ASME B5 COMMITTEE

Machine Tools — Components, Elements, Performance, and Equipment

(The following is the roster of the Committee at the time of approval of this Standard.)

STANDARDS COMMITTEE OFFICERS

S. G. Wallace, *Chair*
D. R. Alonzo, *Secretary*

STANDARDS COMMITTEE PERSONNEL

| | |
|--|---|
| D. R. Alonzo , The American Society of Mechanical Engineers | J. D. Drescher , UTC — Pratt & Whitney |
| J. A. Babinski , <i>Contributing Member</i> , Thomson Aerospace & Defense | D. A. Felinski , B11 Standards, LLC |
| A. M. Bratkovich , Consultant | D. Mancini , Edmunds Gages |
| J. B. Bryan , <i>Honorary Member</i> , Consultant | J. A. Soons , National Institute of Standards and Technology |
| H. M. Byrnes , Colfax Fluid Handling | R. C. Spooner , Powerhold, Inc. |
| H. Cooper , <i>Honorary Member</i> , Consultant | D. Springhorn , Stateline Services Division, LLC |
| | S. G. Wallace , The Boeing Co. |

TECHNICAL COMMITTEE 11 — CHUCKS AND CHUCK JAWS

| | |
|--|---|
| R. C. Spooner , <i>Chair</i> , Powerhold, Inc. | G. J. Norton , Buck Forkardt, Inc. |
| S. M. Looney , <i>Vice Chair</i> , Workholding Consultant | S. N. Roth , SMW Autoblok Corp. |
| A. M. Bratkovich , Consultant | A. J. Storms , ITW/Workholding |
| S. Hastert , LaFox Tool, Inc. | J. T. Weber , Positrol, Inc. |
| C. Mayfield , Abbott Workholding Products | T. M. Winard , NorthTech Workholding |

CORRESPONDENCE WITH THE B5 COMMITTEE

General. ASME Standards are developed and maintained with the intent to represent the consensus of concerned interests. As such, users of this Standard may interact with the Committee by requesting interpretations, proposing revisions or a Case, and attending Committee meetings. Correspondence should be addressed to:

Secretary, B5 Standards Committee
The American Society of Mechanical Engineers
Two Park Avenue
New York, NY 10016-5990
<http://go.asme.org/Inquiry>

Proposing Revisions. Revisions are made periodically to the Standard to incorporate changes that appear necessary or desirable, as demonstrated by the experience gained from the application of the Standard. Approved revisions will be published periodically.

The Committee welcomes proposals for revisions to this Standard. Such proposals should be as specific as possible, citing the paragraph number(s), the proposed wording, and a detailed description of the reasons for the proposal, including any pertinent documentation.

Proposing a Case. Cases may be issued for the purpose of providing alternative rules when justified, to permit early implementation of an approved revision when the need is urgent, or to provide rules not covered by existing provisions. Cases are effective immediately upon ASME approval and shall be posted on the ASME Committee Web page.

Requests for Cases shall provide a Statement of Need and Background Information. The request should identify the Standard and the paragraph, figure, or table number(s), and be written as a Question and Reply in the same format as existing Cases. Requests for Cases should also indicate the applicable edition(s) of the Standard to which the proposed Case applies.

Interpretations. Upon request, the B5 Committee will render an interpretation of any requirement of the Standard. Interpretations can only be rendered in response to a written request sent to the Secretary of the B5 Standards Committee at go.asme.org/Inquiry.

The request for interpretation should be clear and unambiguous. It is further recommended that the inquirer submit his/her request in the following format:

Subject: Cite the applicable paragraph number(s) and the topic of the inquiry.
Edition: Cite the applicable edition of the Standard for which the interpretation is being requested.
Question: Phrase the question as a request for an interpretation of a specific requirement suitable for general understanding and use, not as a request for an approval of a proprietary design or situation. The inquirer may also include any plans or drawings that are necessary to explain the question; however, they should not contain proprietary names or information.

Requests that are not in this format may be rewritten in the appropriate format by the Committee prior to being answered, which may inadvertently change the intent of the original request.

ASME procedures provide for reconsideration of any interpretation when or if additional information that might affect an interpretation is available. Further, persons aggrieved by an interpretation may appeal to the cognizant ASME Committee or Subcommittee. ASME does not "approve," "certify," "rate," or "endorse" any item, construction, proprietary device, or activity.

Attending Committee Meetings. The B5 Standards Committee regularly holds meetings and/or telephone conferences that are open to the public. Persons wishing to attend any meeting and/or telephone conference should contact the Secretary of the B5 Standards Committee. Future Committee meeting dates and locations can be found on the Committee Page at go.asme.org/B5committee.

WORKHOLDING CHUCKS: JAW-TYPE CHUCKS

Chapter 1 General Description and Definitions of Terms

1-1 INTRODUCTION

This Standard establishes technical requirements for workholding chucks used primarily in turning operations. It covers jaw-type chucks, whether manual or power-operated.

1-2 SCOPE

This Chapter covers the general description and definitions of terms related to jaw-type workholding chucks.

1-3 TYPES OF JAW CHUCKS BY DESIGN

compensating chuck: a chuck in which the jaw(s) moves to or away from the workpiece without altering the position of the workpiece.

independent chuck: a chuck in which each individual workholding jaw is moved to or from the workpiece without disturbing the position of any other jaw.

self-centering chuck: a chuck in which all jaws move to or away from the workpiece and maintain one common center.

An example of a power chuck assembly is presented in Fig. 1-1.

1-4 METHODS OF ACTUATION

manual: a chuck that is actuated by hand with the aid of human energy (e.g., by means of a chuck wrench). Refer to Fig. 1-2.

power: a chuck that is actuated by means of, e.g., pneumatic, hydraulic, or electrical energy. Refer to Fig. 1-3.

1-5 DEFINITIONS

actuator: a component within a chuck's body, used to operate the chuck's mechanism, e.g., a wedge, lever, or scroll.

base jaw: see *master jaw*.

centrifugal force: force generated by rotation that tends to move all parts radially away from the axis of rotation of the chuck.

chuck adapter: interface between the machine and the chuck. It can be a separate component or integral to the chuck body.

chuck body: that part of the chuck that contains the actuator and master jaws.

clamping cylinder: device that actuates the chuck through a drawbar or drawtube with the aid of pneumatic or hydraulic energy.

clamping force: algebraic sum of the individual radial forces applied by the top jaws on the workpiece.

clamping torque: product of the clamping force, clamping radius, and the coefficient of friction between the top jaw(s) and the workpiece.

countercentrifugal chuck: a chuck in which there is a system that permits compensation for the loss of clamping force due to centrifugal force.

drawbar: a bar or tube that connects the clamping cylinder to the chuck's actuator to transmit the input force to the chuck.

dynamic clamping force: actual clamping force when the chuck is rotating.

hysteresis: change in static clamping force after the chuck has been rotated at working rotational speed with a constant input force.

indicating band: a diameter on the chuck body designated for measuring runout of a chuck.

input force: force acting on the chuck's actuator, applied from an external energy source.

input torque: torque acting on the chuck's actuator, applied from an external energy source.

master jaw: radial moving part within the chuck body to which the top jaw is mounted.

maximum rotational speed: maximum rotational speed in rpm specified by the manufacturer for a chuck with