

PD IEC/PAS 62953:2015



BSI Standards Publication

Industrial communication networks — Fieldbus specifications

bsi.

...making excellence a habit.™

National foreword

This Published Document is the UK implementation of IEC/PAS 62953:2015.

The UK participation in its preparation was entrusted to Technical Committee AMT/7, Industrial communications: process measurement and control, including fieldbus.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2015.

Published by BSI Standards Limited 2015

ISBN 978 0 580 88098 8

ICS 25.040.40; 35.100.01

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 30 April 2015.

Amendments/corrigenda issued since publication

Date	Text affected
-------------	----------------------



PUBLICLY AVAILABLE SPECIFICATION

PRE-STANDARD

Industrial communication networks – Fieldbus specifications

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 25.040.40; 35.100.01

ISBN 978-2-8322-2445-8

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

Industrial communication networks – Fieldbus specifications – Part 3-25: Data-link layer service definition – Type 25 elements.....	6
Industrial communication networks – Fieldbus specifications – Part 4-25: Data-link layer protocol specification – Type 25 elements	32
Industrial communication networks – Fieldbus specifications – Part 5-25: Application layer service definition – Type 25 elements.....	94
Industrial communication networks – Fieldbus specifications – Part 6-25: Application layer protocol specification – Type 25 elements	158
CPF20 input for IEC 61784-2: Industrial communication networks – Profiles – Part 2: Additional fieldbus profiles for real-time networks based on ISO/IEC 8802-3.....	270

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS
SPECIFICATIONS AND PROFILES – ADS-NET**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

A PAS is a technical specification not fulfilling the requirements for a standard, but made available to the public.

IEC PAS 62953 has been processed by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation.

The text of this PAS is based on the following document:

This PAS was approved for publication by the P-members of the committee concerned as indicated in the following document

Draft PAS	Report on voting
65C/787/PAS	65C/799/RVD

Following publication of this PAS, which is a pre-standard publication, the technical committee or subcommittee concerned may transform it into an International Standard.

This PAS shall remain valid for an initial maximum period of 3 years starting from the publication date. The validity may be extended for a single period up to a maximum of 3 years, at the end of which it shall be published as another type of normative document, or shall be withdrawn.

INTRODUCTION

This PAS contains the ADS-net fieldbus specifications and profiles (Communication profile CP 20/1 ADS-net/ μ SNETWORK-1000, CP 20/2 ADS-net/NX) for inclusion in the IEC 61158 series as well as IEC 61784-2.

The intention is to make this technical content available immediately, while a corresponding new work item proposal (NP) has been launched. If the NP is accepted, this contents will be included in the next editions of the IEC 61158 series and of IEC 61784-2.

This PAS contains the relevant ADS-net (Type 25) elements for the DL and AL services and protocols and information with references to:

- IEC 61158-1:2014
- IEC 61158-2:2014
- IEC 61784-2:2014

The present IEC PAS is structured in the same way as the IEC 61158 series and IEC 61784-2:

- IEC PAS 62953-3-25 is intended to become a future IEC 61158-3-25;
- IEC PAS 62953-4-25 is intended to become a future IEC 61158-4-25;
- IEC PAS 62953-5-25 is intended to become a future IEC 61158-5-25;
- IEC PAS 62953-6-25 is intended to become a future IEC 61158-6-25;
- IEC PAS 62953-2 is intended to be merged into a revised version of IEC 61784-2:2014.

INCLUDED SUBPARTS

Industrial communication networks – Fieldbus specifications – Part 3-25: Data-link layer service definition – Type 25 elements

Industrial communication networks – Fieldbus specifications – Part 4-25: Data-link layer protocol specification – Type 25 elements

Industrial communication networks – Fieldbus specifications – Part 5-25: Application layer service definition – Type 25 elements

Industrial communication networks – Fieldbus specifications – Part 6-25: Application layer protocol specification – Type 25 elements

CPF20 input for IEC 61784-2: Industrial communication networks – Profiles – Part 2: Additional fieldbus profiles for real-time networks based on ISO/IEC 8802-3

CONTENTS

1	Scope	9
1.1	General	9
1.2	Specifications	9
1.3	Conformance	9
2	Normative references	10
3	Terms, definitions, symbols and abbreviations	10
3.1	Reference model terms and definitions	11
3.1.1	DL-address [ISO/IEC 7498-3]	11
3.1.2	DL-address-mapping [ISO/IEC 7498-1]	11
3.1.3	called-DL-address [ISO/IEC 7498-3]	11
3.1.4	calling-DL-address [ISO/IEC 7498-3]	11
3.1.5	centralized multi-end-point-connection [ISO/IEC 7498-1]	11
3.1.6	DL-connection [ISO/IEC 7498-1]	11
3.1.7	DL-connection-end-point [ISO/IEC 7498-1]	11
3.1.8	DL-connection-end-point-identifier [ISO/IEC 7498-1]	11
3.1.9	DL-connection-mode transmission [ISO/IEC 7498-1]	11
3.1.10	DL-connectionless-mode transmission [ISO/IEC 7498-1]	11
3.1.11	correspondent (N)-entities [ISO/IEC 7498-1]	11
3.1.12	DL-duplex-transmission [ISO/IEC 7498-1]	11
3.1.13	(N)-entity [ISO/IEC 7498-1]	11
3.1.14	DL-facility [ISO/IEC 7498-1]	11
3.1.15	flow control [ISO/IEC 7498-1]	11
3.1.16	(N)-layer [ISO/IEC 7498-1]	11
3.1.17	layer-management [ISO/IEC 7498-1]	12
3.1.18	DL-local-view [ISO/IEC 7498-3]	12
3.1.19	DL-name [ISO/IEC 7498-3]	12
3.1.20	naming-(addressing)-domain [ISO/IEC 7498-3]	12
3.1.21	peer-entities [ISO/IEC 7498-1]	12
3.1.22	primitive name [ISO/IEC 7498-3]	12
3.1.23	DL-protocol [ISO/IEC 7498-1]	12
3.1.24	DL-protocol-connection-identifier [ISO/IEC 7498-1]	12
3.1.25	DL-protocol-data-unit [ISO/IEC 7498-1]	12
3.1.26	DL-relay [ISO/IEC 7498-1]	12
3.1.27	reset [ISO/IEC 7498-1]	12
3.1.28	responding-DL-address [ISO/IEC 7498-3]	12
3.1.29	routing [ISO/IEC 7498-1]	12
3.1.30	segmenting [ISO/IEC 7498-1]	12
3.1.31	(N)-service [ISO/IEC 7498-1]	12
3.1.32	(N)-service-access-point [ISO/IEC 7498-1]	12
3.1.33	DL-service-access-point-address [ISO/IEC 7498-3]	12
3.1.34	DL-service-connection-identifier [ISO/IEC 7498-1]	12
3.1.35	DL-service-data-unit [ISO/IEC 7498-1]	12
3.1.36	DL-simplex-transmission [ISO/IEC 7498-1]	12
3.1.37	DL-subsystem [ISO/IEC 7498-1]	12
3.1.38	systems-management [ISO/IEC 7498-1]	12
3.1.39	DLS-user-data [ISO/IEC 7498-1]	12

3.2	Service convention terms and definitions	12
3.2.1	acceptor	12
3.2.2	asymmetrical service	12
3.2.3	confirm (primitive);	12
3.2.4	deliver (primitive)	13
3.2.5	DL-confirmed-facility	13
3.2.6	DL-facility	13
3.2.7	DL-local-view	13
3.2.8	DL-mandatory-facility	13
3.2.9	DL-non-confirmed-facility	13
3.2.10	DL-provider-initiated-facility	13
3.2.11	DL-provider-optional-facility	13
3.2.12	DL-service-primitive;	13
3.2.13	DL-service-provider	13
3.2.14	DL-service-user	13
3.2.15	DLS-user-optional-facility	13
3.2.16	indication (primitive);	13
3.2.17	multi-peer	13
3.2.18	request (primitive);	13
3.2.19	requestor	13
3.2.20	response (primitive);	13
3.2.21	submit (primitive)	13
3.2.22	symmetrical service	13
3.3	Terms and definitions	13
3.4	Symbols and abbreviations	16
3.5	Common conventions	17
3.6	Additional Type 25 conventions	18
4	DL services and concepts	18
4.1	Overview	18
4.2	Types of DLS	18
4.2.1	General	18
4.2.2	Primitive of the RCL communication and RT communication	18
4.3	Detailed description of the RCL communication service	19
4.3.1	Sequence of primitives	19
4.3.2	Transmit / Receive DLSDU	19
4.4	Detailed description of the RT communication service	21
4.4.1	Sequence of primitives	21
4.4.2	Transmit / Receive DLSDU	21
5	DL management services	22
5.1	General	22
5.2	Facilities of the DLMS	22
5.3	Service of the DL-management	22
5.3.1	Overview	22
5.3.2	Reset	23
5.3.3	Set value	23
5.3.4	Get value	23
5.3.5	RCL stop	23
5.3.6	RCL start	23
5.3.7	Node status	23

5.3.8	Event.....	23
5.4	Overview of interactions.....	23
5.5	Detail specification of service and interactions.....	24
5.5.1	Reset.....	24
5.5.2	Set value.....	25
5.5.3	Get value.....	26
5.5.4	RCL stop.....	26
5.5.5	RCL start.....	27
5.5.6	Event.....	28
	Bibliography.....	30
	Figure 1 – Relationships of DLSAPs, DLSAP-addresses and group DL-addresses.....	14
	Figure 2 – Sequence diagram of RCL communication and RT communication services.....	19
	Figure 3 – Reset, Set value, and Get value services.....	24
	Figure 4 – Event service.....	24
	Table 1 – Primitives and parameters used on the RCL communication service.....	19
	Table 2 – Transmit DLSDU primitives and parameters.....	20
	Table 3 – Primitives and parameters used on the RT communication service.....	21
	Table 4 – Transmit DLSDU primitives and parameters.....	21
	Table 5 – Transmit DLSDU primitives and parameters.....	23
	Table 6 – DLM_Reset primitives and parameters.....	24
	Table 7 – DLM_Set primitives and parameters.....	25
	Table 8 – DLM_Get primitives and parameters.....	26
	Table 9 – DLM_RCL_STOP primitives and parameters.....	27
	Table 10 – DLM_RCL_START primitives and parameters.....	27
	Table 11 – DLM_RCL_START primitives and parameters.....	28
	Table 12 – DLM_Event primitives and parameters.....	29

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 3-25: Data-link layer service definition – Type 25 elements

1 Scope

1.1 General

This part of IEC PAS 62953 provides common elements for basic time-critical messaging communications between devices in an automation environment. The term “time-critical” is used to represent the presence of a time-window, within which one or more specified actions are required to be completed with some defined level of certainty. Failure to complete specified actions within the time window risks failure of the applications requesting the actions, with attendant risk to equipment, plant and possibly human life.

This standard defines in an abstract way the externally visible service provided by the Type 25 fieldbus data-link layer in terms of

- a) the primitive actions and events of the service;
- b) the parameters associated with each primitive action and event, and the form which they take; and
- c) the interrelationship between these actions and events, and their valid sequences.

The purpose of this standard is to define the services provided to

- the Type 25 fieldbus application layer at the boundary between the application and data-link layers of the fieldbus reference model;
- systems management at the boundary between the data-link layer and systems management of the fieldbus reference model.

1.2 Specifications

The principal objective of this standard is to specify the characteristics of conceptual data-link layer services suitable for time-critical communications, and thus supplement the OSI Basic Reference Model in guiding the development of data-link protocols for time-critical communications. A secondary objective is to provide migration paths from previously-existing industrial communications protocols.

This specification may be used as the basis for formal DL-Programming-Interfaces. Nevertheless, it is not a formal programming interface, and any such interface will need to address implementation issues not covered by this specification, including

- a) the sizes and octet ordering of various multi-octet service parameters, and
- b) the correlation of paired request and confirm, or indication and response, primitives.

1.3 Conformance

This standard does not specify individual implementations or products, nor does it constrain the implementations of data-link entities within industrial automation systems.

There is no conformance of equipment to this data-link layer service definition standard. Instead, conformance is achieved through implementation of the corresponding data-link protocol that fulfills the Type 25 data-link layer services defined in this standard.