

Institute of Environmental Sciences and Technology

IEST-RP-CC007.3

Contamination Control Division
Recommended Practice 007.3

Testing ULPA Filters



Arlington Place One
2340 S. Arlington Heights Road, Suite 620
Arlington Heights, IL 60005-4510
Phone: (847) 981-0100 • Fax: (847) 981-4130
E-mail: information@iest.org • Web: www.iest.org

This Recommended Practice was prepared by and is under the jurisdiction of Working Group 007 of the IEST Contamination Control Division (WG-CC007). The following WG voting members contributed to the development of this edition of this Recommended Practice.

R. Vijayakumar, WG-CC007 Chair, AERFIL

Anthony Caughron, TEC Services, Inc.

Rick Meyer, Superior Laboratory Service, Inc.

Daniel Dennison, NNE Pharmaplan, Inc.

Matt Middlebrooks, Filtration Group

Keith Flyzik, Micro-Clean, Inc.

Andrew Stillo, Camfil USA, Inc.

Donna Kasper, Hollingsworth & Vose

Todd Urton, Quality Cleanroom Consulting

Timothy McDiarmid, Air Techniques International

Copyright © 2016 by the Institute of Environmental Sciences and Technology

First printing, April 2016

ISBN 978-1-937280-20-8

PROPOSAL FOR IMPROVEMENT: The Working Groups of the Institute of Environmental Sciences and Technology are continually working on improvements to their Recommended Practices and Reference Documents. Suggestions from users of these documents are welcome. If you have a suggestion regarding this document, please use the online Proposal for Improvement form found on the IEST website at www.iest.org.

Institute of Environmental Sciences and Technology
Arlington Place One
2340 S. Arlington Heights Road, Suite 620
Arlington Heights, IL 60005-4510
Phone: (847) 981-0100 • Fax: (847) 981-4130
E-mail: information@iest.org • Web: www.iest.org

NOTICE AND DISCLAIMER: This Recommended Practice is published by the Institute of Environmental Sciences and Technology (IEST) to advance the technical and engineering sciences. Use of this document is entirely voluntary, and determination of its applicability and suitability for any particular use is solely the responsibility of the user. Use of this Recommended Practice does not imply any warranty or endorsement by IEST.

The information in this publication was considered technically sound by the consensus of persons engaged in the development and approval of the document at the time it was developed. Consensus does not necessarily mean that there is unanimous agreement among all persons participating in the development of this document.

IEST standards, recommended practices, and guideline publications, of which the document contained herein is one, are developed through a voluntary consensus standards development process. This process brings together volunteers and seeks out the views of persons who have an interest in the topic covered by this publication. While IEST administers the process to promote fairness in the development of consensus, the organization does not write the document and does not independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgments contained in IEST standards, recommended practices, and guideline publications.

IEST disclaims liability for any personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on this document. IEST disclaims and makes no guaranty or warranty, express or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any of the particular purposes or needs of users of the document. IEST does not guarantee the performance of any individual manufacturer or seller's products or services by virtue of this standard or guide.

In publishing and making this document available, IEST is not undertaking to render professional or other services for or on behalf of any person or entity, nor is IEST undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. Information and other standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

IEST has no power, nor does it undertake to police or enforce compliance with the contents of this document. IEST does not certify, test, or inspect products, designs, or installations for safety or health purposes. Any certification or other statement of compliance with any health or safety-related information in this document shall not be attributable to IEST and is solely the responsibility of the certifier or maker of the statement.

COPYING IS ILLEGAL

Testing ULPA Filters

IEST-RP-CC007.3

CONTENTS

SECTION

1	SCOPE AND LIMITATIONS	7
2	REFERENCES.....	8
3	TERMS AND DEFINITIONS	9
4	TEST SYSTEM.....	11
5	SYSTEM QUALIFICATION AND CALIBRATION.....	16
6	TEST PROCEDURE	22
7	DATA REDUCTION	23
8	REPORTING AND MARKING	24

FIGURE

1	BLOCK DIAGRAM OF AN ULPA FILTER TEST SYSTEM	12
---	---	----

TABLE

A1	UPPER AND LOWER CONFIDENCE LIMITS FOR UPSTREAM AND DOWNSTREAM COUNTS	29
B1	MINIMUM FREQUENCY OF CALIBRATION	34

APPENDIX

A	FACTORS INFLUENCING MEASURED PENETRATION.....	25
B	RECOMMENDED CALIBRATION INTERVALS.....	34
C	CONSIDERATIONS FOR SPECIFIC MEDIA TYPES.....	35
D	OTHER TEST METHODS FOR ULPA FILTERS	36
E	PARTICLE DETECTION AND PARTICLE SIZE DISTRIBUTION	37
F	BIBLIOGRAPHY	39

COPYING IS ILLEGAL

Testing ULPA Filters

IEST-RP-CC007.3

1 SCOPE AND LIMITATIONS

1.1 Scope

This Recommended Practice (RP) describes the equipment, aerosol properties, processes, and calculations for determining the efficiency of ULPA and super ULPA filters in the factory, using particle counters. The procedure may be applied to production applications. This RP provides guidelines for constructing a suitable test duct and sampling system. Also provided are test criteria for quantifying penetration in the range of 0.0010% to 0.00010%, using test aerosol particles in the size range of 0.1 to 0.2 μm .

1.2 Limitations

Filters tested per IEST-RP-CC007 are typically factory-tested with uniform airflow across the filter. Ducted filters, fan filter units (FFUs), and poorly designed inlet housings for in-line filters may result in non-uniform media air velocity that can possibly reduce the *in-situ* filter efficiency.

1.3 Application of method

Application of this RP is by mutual agreement between the customer and the supplier. To apply this RP, the agreement should also include:

- a) acceptance criteria for penetration and pressure drop;
- b) the test aerosol;
- c) the test volume flow rate.

Prior to testing filters according to this RP, the most penetrating particle size (MPPS) should be determined. The determination can be made for the filter medium in flat sheet form, provided that the test is conducted with an aerosol as defined in section 4.2.9.

The test is performed at the same velocity as the average velocity through the medium in the assembled filter at the test volume flow rate.

CAUTION: Testing in accordance with this RP may involve hazardous materials, operations, and equipment. This RP does not purport to address the safety problems associated with its use. It is the responsibility of the user to consult and establish appropriate safety and health practices and to determine the applicability of regulatory limitations prior to use of this RP.

The methodology described in this RP may be applied for particle-counter testing of filters outside the efficiency and particle size range covered in the document.