

INTERNATIONAL STANDARD



Product package labels for electronic components using bar code and two-dimensional symbologies





THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2017 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.



IEC 62090

Edition 2.0 2017-04

INTERNATIONAL STANDARD



Product package labels for electronic components using bar code and two-dimensional symbologies

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 31.190; 31.200; 35.040.50

ISBN 978-2-8322-4160-8

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	4
1 Scope.....	6
2 Normative references	6
3 Terms and definitions	7
4 Label data content and requirements	7
4.1 Data elements – general	7
4.2 Mandatory data elements	8
4.2.1 Manufacturer item identification – DI “1P” and “25P”	8
4.2.2 Customer product code – DI “P”	8
4.2.3 Manufacturer identification – DI “18V” and “21V”	8
4.2.4 Quantity – DI “Q” and “7Q”	8
4.2.5 Traceability identification – DI “S” and “25S”, “1T” and “25T”	9
4.2.6 Country of origin – DI “4L”	9
4.2.7 Production date – DI “16D”	9
4.2.8 Package identification – DI “J” and “3S”	9
4.3 Optional data elements	10
4.3.1 Expiration date – DI “14D”	10
4.3.2 Revision level – DI “2P”	10
4.3.3 EIAJ ID – DI “3N”	10
4.3.4 Manufacturer location – DI “25L”	10
4.3.5 Customer assigned supplier code – DI “V”	10
4.3.6 Moisture sensitivity level – DI “13E”	11
4.3.7 URL – DI “33L” and “34L”	11
4.4 Data semantics and formats defined by the data identifiers	11
4.5 Data representation	13
4.5.1 General formatting	13
4.5.2 General formatting for machine-readable symbols	14
4.5.3 General formatting for human-readable information	14
4.6 Data carrier selection	15
4.6.1 Linear bar code symbols	15
4.6.2 Two-dimensional (2D) symbols	16
4.7 Label size, layout, and location	17
4.7.1 Label size	17
4.7.2 Label layout	17
4.7.3 Examples of label and label layout	17
4.7.4 Label location	18
Annex A (informative) Quality aspects of labels – Adhesive characteristics and durability of marking	20
A.1 General.....	20
A.2 Recommendations	20
A.2.1 General	20
A.2.2 Adhesion characteristics	20
A.2.3 Use and protection	20
A.2.4 Storage conditions	21
A.2.5 Durability	21
A.2.6 Blank label stock contamination	21
A.3 Method of test.....	21

A.3.1	Adhesive strength.....	21
A.3.2	Blank label stock contamination.....	21
A.3.3	Recyclability	22
Annex B (informative)	ISO/IEC 15434 Data Transfer Syntax	23
Annex C (informative)	URL	24
C.1	General.....	24
C.2	Principle of using the URL DI “33L”.....	24
C.3	Principle of using the P2P URL DI “34L”	25
C.4	Implementation of product to internet communication by help of P2P data identifier “34L”	25
Annex D (informative)	Examples of data element short titles.....	27
Annex E (informative)	Package levels for component package labels.....	28
E.1	Inner and outer product packages.....	28
E.2	"Unit load packages" / "handling units" / "overpacks"	29
E.3	"Shipping units" / "transport packages"	29
Bibliography.....		30
Figure 1 – Label with a linear bar code, Data Matrix symbol and human-readable information.....		17
Figure 2 – Label with minimum content, Data Matrix and human-readable information		17
Figure 3 – Label with minimum content, QR Code and human-readable information.....		18
Figure 4 – Typical label locations.....		19
Figure A.1 – Adhesion tester.....		22
Figure B.1 – Example of encoding data elements in a 2D symbol.....		23
Figure C.1 – Smartphone with P2P App for access to P2P information.....		26
Figure E.1 – Examples for intimate/inner packages.....		28
Figure E.2 – Example for outer package with more than one inner package.....		28
Figure E.3 – Example of "unit loads" or "handling units" or "overpacks"		29
Figure E 4 – Examples of transport packages		29
Table 1 – Data identifiers.....		11
Table 2 – Mandatory data elements and their representations		13
Table 3 – Valid combinations of representation of optional data elements.....		14
Table 4 – Product package label symbol requirements – Code 39.....		15
Table 5 – Product package label symbol requirements – Code 128.....		16
Table C.1 – How to use the URL DI “33L”.		24
Table C.2 – How to use the P2P URL DI “34L”		25
Table C.3 –ASC DIs used for the P2P code example:		26
Table D.1 – Examples of data element short titles.....		27

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**PRODUCT PACKAGE LABELS FOR ELECTRONIC COMPONENTS
USING BAR CODE AND TWO-DIMENSIONAL SYMBOLOGIES**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62090 has been prepared by IEC technical committee 91: Electronics assembly technology.

This second edition cancels and replaces the first edition published in 2002. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) Applicable data elements have been added. Data identifiers of those data elements are "10D", "14D", "2P", "25L", "18V", "V", "J", "3S", "13E", "33L" and "34L".
- b) The following new informative annexes have been added:
 - Annex C, *URL*;
 - Annex D, *Examples of data element short titles*;
 - Annex E, *Package levels for component package labels*.

The text of this International Standard is based on the following documents:

CDV	Report on voting
91/1394/CDV	91/1430/RVC

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

PRODUCT PACKAGE LABELS FOR ELECTRONIC COMPONENTS USING BAR CODE AND TWO-DIMENSIONAL SYMBOLOGIES

1 Scope

This document applies to labels on the packaging of electronic components for automatic handling in B2B processes. These labels use linear bar code and two-dimensional (2D) symbols. Labels for direct product marking and shipping labels are excluded. Labels required on the packaging of electronic components that are intended for the retail channel of distribution in B2C processes are also excluded from this document.

Bar code and 2D symbol markings are used, in general, for automatic identification and automatic handling of components in electronics assembly lines. Intended applications include systems that automate the control of component packages during production, inventory and distribution.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 15417, *Information technology – Automatic identification and data capture techniques – Code 128 bar code symbology specification*

ISO/IEC 15418, *Information technology – Automatic identification and data capture techniques – GS1 Application Identifiers and ASC MH 10 Data Identifiers and maintenance*

ISO/IEC 15434, *Information technology – Automatic identification and data capture techniques – Syntax for high-capacity ADC media*

ISO/IEC 15459 (all parts), *Information technology – Automatic identification and data capture techniques – Unique identification*

ISO/IEC 16022, *Information technology – Automatic identification and data capture techniques – Data Matrix bar code symbology specification*

ISO/IEC 16388, *Information technology – Automatic identification and data capture techniques – Code 39 bar code symbology specification*

ISO/IEC 18004, *Information technology – Automatic identification and data capture techniques – QR Code bar code symbology specification*

ISO/IEC 19762, *Information technology – Automatic Identification and data capture (AIDC) techniques – Harmonized vocabulary*

ISO 8601, *Data elements and interchange formats – Information interchange – Representation of dates and times*

ANSI MH10.8.2, *Data Identifier and Application Identifier Standard*