

IPC-6013D

2017 - September

Qualification and Performance Specification for Flexible/ Rigid-Flexible Printed Boards

Supersedes IPC-6013C
December 2013

An international standard developed by IPC

Association Connecting Electronics Industries



The Principles of Standardization

In May 1995 the IPC's Technical Activities Executive Committee (TAEC) adopted Principles of Standardization as a guiding principle of IPC's standardization efforts.

Standards Should:

- Show relationship to Design for Manufacturability (DFM) and Design for the Environment (DFE)
- Minimize time to market
- Contain simple (simplified) language
- Just include spec information
- Focus on end product performance
- Include a feedback system on use and problems for future improvement

Standards Should Not:

- Inhibit innovation
- Increase time-to-market
- Keep people out
- Increase cycle time
- Tell you how to make something
- Contain anything that cannot be defended with data

Notice

IPC Standards and Publications are designed to serve the public interest through eliminating misunderstandings between manufacturers and purchasers, facilitating interchangeability and improvement of products, and assisting the purchaser in selecting and obtaining with minimum delay the proper product for his particular need. Existence of such Standards and Publications shall not in any respect preclude any member or nonmember of IPC from manufacturing or selling products not conforming to such Standards and Publication, nor shall the existence of such Standards and Publications preclude their voluntary use by those other than IPC members, whether the standard is to be used either domestically or internationally.

Recommended Standards and Publications are adopted by IPC without regard to whether their adoption may involve patents on articles, materials, or processes. By such action, IPC does not assume any liability to any patent owner, nor do they assume any obligation whatever to parties adopting the Recommended Standard or Publication. Users are also wholly responsible for protecting themselves against all claims of liabilities for patent infringement.

IPC Position Statement on Specification Revision Change

It is the position of IPC's Technical Activities Executive Committee that the use and implementation of IPC publications is voluntary and is part of a relationship entered into by customer and supplier. When an IPC publication is updated and a new revision is published, it is the opinion of the TAEC that the use of the new revision as part of an existing relationship is not automatic unless required by the contract. The TAEC recommends the use of the latest revision. Adopted October 6, 1998

Why is there a charge for this document?

Your purchase of this document contributes to the ongoing development of new and updated industry standards and publications. Standards allow manufacturers, customers, and suppliers to understand one another better. Standards allow manufacturers greater efficiencies when they can set up their processes to meet industry standards, allowing them to offer their customers lower costs.

IPC spends hundreds of thousands of dollars annually to support IPC's volunteers in the standards and publications development process. There are many rounds of drafts sent out for review and the committees spend hundreds of hours in review and development. IPC's staff attends and participates in committee activities, typesets and circulates document drafts, and follows all necessary procedures to qualify for ANSI approval.

IPC's membership dues have been kept low to allow as many companies as possible to participate. Therefore, the standards and publications revenue is necessary to complement dues revenue. The price schedule offers a 50% discount to IPC members. If your company buys IPC standards and publications, why not take advantage of this and the many other benefits of IPC membership as well? For more information on membership in IPC, please visit www.ipc.org or call 847/597-2872.

Thank you for your continued support.



IPC-6013D

Qualification and Performance Specification for Flexible/Rigid-Flexible Printed Boards

Developed by the Flexible Circuits Performance Specifications Subcommittee (D-12) of the Flexible Circuits Committee (D-10) of IPC

Supersedes:

IPC-6013C - December 2013
IPC-6013B - January 2009
IPC-6013A with Amendment 2 -
April 2006
IPC-6013A with Amendment 1 -
January 2005
IPC-6013A - November 2003
Amendment 1 - December 2005
IPC-6013 with
Amendment 1
Includes:
IPC-6013 - November 1998
Amendment 1 - April 2000
IPC-RF-245 - April 1987
IPC-FC-250A - January 1974

Users of this publication are encouraged to participate in the development of future revisions.

Contact:

IPC
3000 Lakeside Drive, Suite 105N
Bannockburn, Illinois
60015-1219
Tel 847 615.7100
Fax 847 615.7105

This Page Intentionally Left Blank

Acknowledgment

Any document involving a complex technology draws material from a vast number of sources across many continents. While the principal members of the Flexible Circuits Performance Specifications Subcommittee (D-12) of the Flexible Circuits Committee (D-10) are shown below, it is not possible to include all of those who assisted in the evolution of this standard. To each of them, the members of the IPC extend their gratitude.

Flexible Circuits Committee	Flexible Circuits Performance Specifications Subcommittee	Technical Liaison of the IPC Board of Directors
Chair Nick S. Koop TTM Technologies	Chair Nick S. Koop TTM Technologies	Bob Neves Microtek Laboratories
Vice Chair William A. Ortloff Raytheon Company	Vice-Chair Mahendra Gandhi Northrop Grumman Aerospace Systems	
Flexible Circuits Performance Specifications Subcommittee		
Allison Elizabeth, NTS - Baltimore	Collier Michael, Teledyne Printed Circuit Technologies	Henault Philip, Raytheon Company
Amar Alisha, Lockheed Martin Space Systems Company	Connitt David, L-3 Fuzing and Ordnance Systems, Cincinnati	Hill Mike, TTM Technologies
Arredondo Gustavo, Para Tech Coating Inc.	Corbett David, DLA Land and Maritime	Hook Lorraine, Streamline Circuits
Auer Lance, Raytheon Missile Systems	Cote Andrea, UL LLC	Hudson Emma, UL International UK Ltd.
Babiyak Rick, TTM Technologies, Inc.	Cox Sidney, Sidney G. Cox	Jawitz Michael, Orbital ATK
Ballou Chris, TTM Technologies	Dangler John, IBM Corporation	Kummer William, Raytheon Company
Bauer John, Rockwell Collins	Daniluk Kelly, NASA Goddard Space Flight Center	Lee Minsu, Korea Printed Circuit Association
Beauchesne Michael, BAE Systems	Dupriest Don, Lockheed Martin Missiles & Fire	Leeper Lynne, Lockheed Martin Space Systems Company
Boutte Alvin, NASA Goddard Space Flight Center	Ferrari Gary, FTG Circuits	Leschisin John, Minco Products, Inc.
Bowles Scott, L-3 Fuzing and Ordnance System	Finstad Mark, Flexible Circuit Technologies, Inc.	Lipps Daniel, L-3 Fuzing and Ordnance Systems, Cincinnati
Bowles Steven, ALL Flex LLC	Fox William, Lockheed Martin Missile & Fire Control	Loew Dan, L-3 Fuzing and Ordnance Systems, Cincinnati
Buechner Mark, BAE Systems	Fuentes Laura, Summit Interconnect - Anaheim	Ly Jennifer, TTM Technologies
Buss Jeremy, Naval Air Warfare Center Weapons Division	Gardenour Tom, Amphenol Printed Circuits, Inc.	MacFadden Todd, Bose Corporation
Cairns Rodd, Starkey Hearing Technologies	Gardeski Thomas, Gemini Sciences, LLC	Maddox Clifford, Boeing Company
Cardoza Donald, Cirexx International, Inc.	Gleason Michael, Draper	McCarthy Thomas, Taconic Advanced Dielectric Division
Case Byron, L-3 Communications	Goolsby Josh, Lockheed Martin Missiles & Fire Control	McGarry Robert, RPM Solutions
Chevalier Denise, Amphenol Printed Circuits, Inc.	Gragg Ty, Unicircuit Inc.	McQueen Matthew, NSW Crane
Clark James, Multek Flexible Circuits, Inc.	Griffith Russell, Flexible Circuits Inc.	Meath Jonas, All Flex
Cockcroft Duane, Cirexx International, Inc.	Grinvalds Rachel, Rockwell Collins	Menuet Peter, L-3 Communications - Cincinnati
	Hammill Vicka, Honeywell Inc. Air Transport S	Miedico Roger, Raytheon Company
		Miyasato Keita, Taiyo Industrial Co., Ltd.
		Monarchio James, TTM Technologies, Inc.

Murray Steven, Northrop Grumman Corporation	Romont Thomas, IFTEC	Stevens Brian, Rockwell Collins
Musante Steve, Raytheon Missile Systems	Russo Mitch, TTM Technologies	Takahara Kunio, Japan Electronics Packaging an
Nakajima Yoji, Asahi Glass Co., Ltd.	Sam Chan, Minco Products, Inc.	Takahashi Mamoru, Asahi Glass Co., Ltd.
Nargi-Toth Kathleen, NCAB Group USA, Inc.	Sanchez Enrique, Cirexx International, Inc.	Takeuchi Hiroki, JX Nippon Mining and Metals
Neves Robert, Microtek (Changzhou) Laborator	Sandor Edward, Taconic Advanced Dielectric Division	Taylor Jamin, ALL Flex LLC
Nguyen Thi, Lockheed Martin Missile & Fire	Savage Rolland, Savage Consulting	Toone Bradley, L-3 Communications
Oliver Glenn, Raytheon Missile Systems	Schmitt Jeff, Coast to Coast Circuits, Inc.	Vanderpan Crystal, UL LLC
Ortloff William, Raytheon Company	Shelby Gilbert, Raytheon Systems Company	Vargas Carlos, TTM Technologies
Pedersen Jan, Elmatica AS	Sheldon Robert, Pioneer Circuits Inc.	Wasserzug Alex, Cirexx International, Inc.
Pfingston William, Miraco, Inc.	Shepherd Russell, National Technical Systems Anaheim	Weatherford David, Teledyne Advanced Electronic Solutions
Rios Nef, Summit Interconnect - Anaheim	Shepler Terry, Electro-Materials, Inc.	Webster Clark, ALL Flex LLC
	Stark Herb, Flexible Circuits Inc.	Yoshimura Ryoichi, Nippon Mektron Ltd.
	Steinbauer Rebecca, ALL Flex LLC	

Table of Contents

1	SCOPE	1	3.2.6	Base Metallic Plating Depositions and Conductive Coatings	8
1.1	Statement of Scope	1	3.2.7	Final Finish Depositions and Coatings – Metallic and Non-Metallic	8
1.2	Purpose	1	3.2.8	Polymer Coating (Solder Mask)	12
1.3	Performance Classification, Board Type, and Installation Usage	1	3.2.9	Fusing Fluids and Fluxes	12
1.3.1	Classification	1	3.2.10	Marking Inks	12
1.3.2	Printed Board Type	1	3.2.11	Hole Fill Insulation Material	12
1.3.3	Installation Uses	1	3.2.12	Heatsink Planes, External	12
1.3.4	Selection for Procurement	1	3.2.13	Via Protection	12
1.3.5	Material, Plating Process and Final Finish	2	3.2.14	Embedded Passive Materials	12
1.4	Terms and Definitions	3	3.3	Visual Examination	12
1.4.1	As Agreed Upon Between User and Supplier (AABUS)	3	3.3.1	Profile	12
1.4.2	Button Plating	3	3.3.2	Construction Imperfections	13
1.4.3	Cover Material	3	3.3.3	Plating and Coating Voids in the Hole	17
1.4.4	Target Land (Via Bottom Land)	4	3.3.4	Lifted Lands	17
1.4.5	Capture Land (Via Top Land)	4	3.3.5	Marking	17
1.4.6	Microvia	4	3.3.6	Solderability	18
1.4.7	Core	4	3.3.7	Plating Adhesion	18
1.5	Interpretation	4	3.3.8	Edge Board Contact, Junction of Gold Plate to Solder Finish	18
1.6	Presentation	4	3.3.9	Adhesive/Strain Relief	19
1.7	Revision Level Changes	4	3.3.10	Workmanship	19
2	APPLICABLE DOCUMENTS	4	3.4	Dimensional Requirements	19
2.1	IPC	4	3.4.1	Hole Size, Hole Pattern Accuracy and Pattern Feature Accuracy	19
2.2	Joint Industry Standards	6	3.4.2	Annular Ring and Breakout (External)	20
2.3	Other Publications	6	3.4.3	Bow and Twist (Individual Rigid or Stiffener Portions Only)	22
2.3.1	American Society for Testing and Materials	6	3.4.4	Array Sub-Pallets	22
2.3.2	Underwriters Lab	6	3.5	Conductor Definition	22
2.3.3	National Electrical Manufacturers Association	6	3.5.1	Conductor Width and Thickness	23
2.3.4	American Society for Quality	6	3.5.2	Conductor Spacing	23
2.3.5	AMS	7	3.5.3	Conductor Imperfections	23
2.3.6	American Society of Mechanical Engineers	7	3.5.4	Conductive Surfaces	24
2.3.7	Federal	7	3.6	Structural Integrity	26
3	REQUIREMENTS	7	3.6.1	Thermal Stress Testing	26
3.1	General	7	3.6.2	Requirements for Microsectioned Coupons or Production Boards	28
3.2	Materials Used in this Specification	7	3.7	Solder Mask Requirements	42
3.2.1	Laminates and Bonding Materials	7	3.7.1	Solder Mask Coverage	42
3.2.2	External Bonding Materials	7	3.7.2	Solder Mask Cure and Adhesion	42
3.2.3	Other Dielectric Materials	7	3.7.3	Solder Mask Thickness	43
3.2.4	Metal Foils	7	3.8	Electrical Requirements	43
3.2.5	Metal Planes/Cores	8			

3.8.1	Dielectric Withstanding Voltage	43	APPENDIX A	55
3.8.2	Electrical Continuity and Isolation Resistance	43		
3.8.3	Circuit/PTH Shorts to Metal Substrates	43		
3.8.4	Moisture and Insulation Resistance (MIR)	43		
3.9	Cleanliness	44		
3.9.1	Cleanliness Prior to Solder Mask Application	44		
3.9.2	Cleanliness After Solder Mask, Solder, or Alternative Surface Coating Application	44		
3.9.3	Cleanliness of Inner Layers After Oxide Treatment Prior to Lamination	44		
3.10	Special Requirements	44		
3.10.1	Outgassing	44		
3.10.2	Fungus Resistance	44		
3.10.3	Vibration	44		
3.10.4	Mechanical Shock	44		
3.10.5	Impedance Testing	44		
3.10.6	Coefficient of Thermal Expansion (CTE)	44		
3.10.7	Thermal Shock	45		
3.10.8	Surface Insulation Resistance (As Received)	45		
3.10.9	Metal Core (Horizontal Microsection)	45		
3.10.10	Ionic (Resistivity of Solvent Extract)	45		
3.10.11	Rework Simulation	45		
3.10.12	Bending Test	45		
3.10.13	Flexible Endurance	46		
3.10.14	Bond Strength (Unsupported Lands)	46		
3.10.15	Bond Strength (Stiffener)	46		
3.10.16	Destructive Physical Analysis	46		
3.11	Repair	46		
3.11.1	Circuit Repair	46		
3.12	Rework	46		
4	QUALITY ASSURANCE PROVISIONS	47		
4.1	General	47		
4.1.1	Qualification	47		
4.1.2	Sample Test Coupons	47		
4.2	Acceptance Testing and Frequency	50		
4.2.1	C=0 Zero Acceptance Number Sampling Plan	50		
4.2.2	Referee Tests	50		
4.3	Quality Conformance Testing	54		
4.3.1	Coupon Selection	54		
5	NOTES	54		
5.1	Ordering Data	54		
5.2	Superseded Specifications	54		
			Figures	
	Figure 1-1	Microvia Definition		4
	Figure 3-1	Transition Zone		13
	Figure 3-2	Unacceptable Covercoat Coverage		15
	Figure 3-3	Solder Wicking and Plating Penetration		17
	Figure 3-4	Annular Ring Measurement (External)		21
	Figure 3-5	Breakout of 90° and 180°		21
	Figure 3-6	Conductor Width Reduction		21
	Figure 3-7	Major and Minor Access Holes for Flexible Printed Boards		21
	Figure 3-8	Squeeze-Out of Cover Film Adhesive and Ooze-Out of Covercoat		22
	Figure 3-9	Missing Material or Skips in the Bead of Adhesive Squeeze-Out at Coverlay Edges		22
	Figure 3-10	Unnecessary Copper Between Conductor and Nodule of Conductor		23
	Figure 3-11	Isolated Reductions of Conductor Thickness		23
	Figure 3-12	Rectangular Surface Mount Lands		24
	Figure 3-13	Round Surface Mount Lands		24
	Figure 3-14	Printed Board Edge Connector Lands		25
	Figure 3-15	Plated Hole Microsection (Grinding/Polishing) Tolerance		27
	Figure 3-16	An Example of Plating to Target Land Separation		27
	Figure 3-17	Separation at External Foil		29
	Figure 3-18	Crack Definition		29
	Figure 3-19	Examples of Thermal Zones for Microsection Evaluation Laminate Attributes		30
	Figure 3-20	Measurement for Etchback		30
	Figure 3-21	Measurement for Dielectric Removal		31
	Figure 3-22	Smear Removal Allowance		31
	Figure 3-23	Measurement Locations for Fluoropolymer Resin Smear		32
	Figure 3-24	Negative Etchback		33
	Figure 3-25	Plating Folds/Inclusions – Minimum Measurement Points		33
	Figure 3-26	Annular Ring Measurement (Internal)		33
	Figure 3-27	Microsection Rotations for Breakout Detection		34
	Figure 3-28	Comparison of Microsection Rotations		34
	Figure 3-29	Example of Non-Conforming Dielectric Spacing Reduction Due to Breakout at Microvia Target Land		34
	Figure 3-30	Surface Copper Wrap Measurement for Filled Holes		35
	Figure 3-31	Wrap Copper in Type 4 Printed Board (Acceptable)		35
	Figure 3-32	Wrap Copper Removed by Excessive Sanding/Planarization/Etching (Not Acceptable)		36

Figure 3-33	Copper Cap Thickness	37	Table 3-4	Surface and Hole Copper Plating Minimum Requirements for Buried Vias > 2 Layers, and Blind Vias	11
Figure 3-34	Copper Cap Filled Via Height (Bump)	37	Table 3-5	Surface and Hole Copper Plating Minimum Requirements for Microvias (Blind and Buried)	11
Figure 3-35	Copper Cap Depression (Dimple)	37	Table 3-6	Surface and Hole Copper Plating Minimum Requirements for Buried Via Cores (2 Layers)	11
Figure 3-36	Copper Cap Plating Voids	37	Table 3-7	Covercoat Adhesion	16
Figure 3-37	Enclosed Inclusion in Copper Cap Plating	37	Table 3-8	Solder Wicking/Plating Penetration Limits	16
Figure 3-38	Example of Acceptable Voiding in a Copper Filled Microvia	38	Table 3-9	Plating and Coating Voids Visual Examination	17
Figure 3-39	Example of Acceptable Voiding in a Copper Filled Microvia without Cap Plating	38	Table 3-10	Edge Board Contact Gap	19
Figure 3-40	Example of Nonconforming Void in Copper Filled Microvia	38	Table 3-11	Minimum Etch Annular Ring	20
Figure 3-41	Example of Nonconforming Void in a Copper Filled Microvia without Cap Plating	38	Table 3-12	Allowable Squeeze-Out of Coverlay Adhesive and Ooze-Out of Covercoat	22
Figure 3-42	Microvia Contact Dimension	38	Table 3-13	Minimum Solderable Annular Ring on Land Area	22
Figure 3-43	Exclusion of Separations in Microvia Target Land Contact Dimension	38	Table 3-14	Conductor Spacing Requirements	23
Figure 3-44	Penetration of Microvia Target Land	39	Table 3-15	PTH Integrity after Stress	28
Figure 3-45	Measurement of Total Copper Thickness When Selective Hole Plating is Specified	40	Table 3-16	Cap Plating Requirements	36
Figure 3-46	Metal Core to PTH	41	Table 3-17	Microvia Contact Dimension	39
Figure 3-47	Measurement of Minimum Dielectric Spacing	41	Table 3-18	Internal Layer Foil Thickness after Processing	39
Figure 3-48	Fill Material in Blind/Through Vias When Cap Plating Not Specified	41	Table 3-19	External Conductor Thickness after Plating	40
Figure 3-49	Bending Test	45	Table 3-20	Solder Mask Adhesion	43
Tables					
Table 1-1	Default Requirements	2	Table 3-21	Dielectric Withstanding Test Voltages	43
Table 3-1	Internal or External Metal Planes	8	Table 3-22	Insulation Resistance	43
Table 3-2	Final Finish and Coating Requirements	9	Table 4-1	Qualification Testing	47
Table 3-3	Surface and Hole Copper Plating Minimum Requirements for Through-Holes	11	Table 4-2	C=0 Sampling Plan Per Lot Size	50
			Table 4-3	Acceptance Testing and Frequency	50
			Table 4-4	Quality Conformance Testing	54

This Page Intentionally Left Blank

Qualification and Performance Specification for Flexible/Rigid-Flexible Printed Boards

1 SCOPE

1.1 Statement of Scope This specification covers qualification and performance requirements of flexible printed boards. The flexible printed board may be single-sided, double-sided, multilayer, or rigid-flex multilayer. All of these constructions may or may not include stiffeners, plated-through holes (PTHs), and blind/buried vias.

The flexible or rigid-flex printed board may contain build up High Density Interconnect (HDI) layers. The printed board may contain embedded active or passive circuitry with distributive capacitive planes, capacitive or resistive components conforming to IPC-6017.

The rigid section of the printed board may contain a metal core or external metal heat frame, which may be active or non-active.

Revision level changes are described in 1.7.

1.2 Purpose The purpose of this specification is to provide requirements for qualification and performance of flexible printed boards designed to IPC-2221 and IPC-2223.

1.3 Performance Classification, Board Type, and Installation Usage

1.3.1 Classification This specification recognizes that flexible printed boards will be subject to variations in performance requirements based on end-use. These performance classes (Class 1, Class 2, and Class 3) are defined in IPC-6011.

1.3.2 Printed Board Type Performance requirements are established for the different types of flexible printed boards, classified as follows:

Type 1 – Single-sided flexible printed boards containing one conductive layer, with or without stiffeners.

Type 2 – Double-sided flexible printed boards containing two conductive layers with PTHs, with or without stiffeners.

Type 3 – Multilayer flexible printed boards containing three or more conductive layers with PTHs, with or without stiffeners.

Type 4 – Multilayer rigid and flexible material combinations containing three or more conductive layers with PTHs.

Type 5 – Flexible or rigid-flex printed boards containing two or more conductive layers without PTHs.

1.3.3 Installation Uses

Use A – Capable of withstanding flex during installation.

Use B – Capable of withstanding continuous flexing for the number of cycles as specified on the procurement documentation.

Use C – High temperature environment (over 105 °C [221 °F]).

Use D UL – Recognition. See UL 94 and UL 796F.

1.3.4 Selection for Procurement For procurement purposes, performance class and installation usage **shall** be specified in the procurement documentation.

The documentation **shall** provide sufficient information to the supplier so that the supplier can fabricate the flexible printed boards and ensure that the user receives the desired product. **Information that should be included in the procurement documentation is to be in accordance with IPC-2611 and IPC-2614.**

Note: If the drawing specifies the requirement in words, designators are not required.

The procurement documentation **shall** specify the thermal stress test method and the number of cycles (in relation to reflow profiles in IPC-TM-650, Method 2.6.27) to be used to meet the requirement of 3.6.1. Selection **shall** be from those depicted in 3.6.1.1, 3.6.1.2, 3.6.1.3 and 3.6.1.4. If not specified (see 5.1), the default **shall** be per Table 1-1.