

STANDARD FOR
CATEGORY 3, 5, & 5e INDIVIDUALLY UNSHIELDED TWISTED PAIR
INDOOR CABLES (WITH OR WITHOUT AN OVERALL SHIELD) FOR USE IN
GENERAL PURPOSE AND LAN COMMUNICATION WIRING SYSTEMS
TECHNICAL REQUIREMENTS

Published By
INSULATED CABLE ENGINEERS ASSOCIATION, INC.
Post Office Box 1568
Carrollton, GA 30112, USA.

© 2012 by ICEA

Approved: March 16, 2012 by
Insulated Cable Engineers Association, Inc.

Approved: June 22, 2012 by
American National Standards Institute

Purchase Now

ANSI/ICEA S-90-661-2012

Copyrighted by the ICEA
Contents may not be reproduced
in any form without permission of the
INSULATED CABLE ENGINEERS ASSOCIATION, INC.

Copies of this publication may be obtained from:

IHS
15 Inverness Way East
Englewood, CO 80113-5776 USA
Telephone: (800) 854-7179
www.ihs.com

NOTICE AND DISCLAIMER

The information in this publication was considered technically sound by the consensus of persons engaged in the development and approval of the document at the time it was developed. Consensus does not necessarily mean that there is unanimous agreement among every person participating in the development of this document.

The Insulated Cable Engineers Association, Inc. (ICEA) standards and guideline publications, of which the document contained herein is one, are developed through a voluntary consensus standards development process. This process brings together persons who have an interest in the topic covered by this publication. While ICEA administers the process and establishes rules to promote fairness in the development of consensus, it does not independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgements contained in its standards and guideline publications.

ICEA disclaims liability for personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on this document. ICEA disclaims and makes no guaranty or warranty, expressed or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any of your particular purposes or needs. ICEA does not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this standard or guide.

In publishing and making this document available, ICEA is not undertaking to render professional or other services for or on behalf of any person or entity, nor is ICEA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgement or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. Information and other standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

ICEA has no power, nor does it undertake to police or enforce compliance with the contents of this document. ICEA does not certify, test, or inspect products, designs, or installations for safety or health purposes. Any certification or other statement of compliance with any health or safety-related information in this document shall not be attributable to ICEA and is solely the responsibility of the certifier or maker of the statement.

Purchase Now

ANSI/ICEA S-90-661-2012

(page intentionally left blank)

FOREWORD

ICEA Standards are published in the public interest and are intended to promote product uniformity and quality throughout the industry. Existence of an ICEA publication does not in any respect preclude the manufacture or use of products not conforming to the Standard.

The user of this Standard is cautioned to observe any applicable health or safety regulations and rules relative to the manufacture and use of cable made in conformity with this Standard. This Standard hereafter assumes that manufacture, testing, installation, and maintenance of cables defined by this Standard will be performed only by properly trained personnel using suitable equipment and employing appropriate safety precautions.

Questions of interpretation of ICEA Standards can only be accepted in writing, and the reply shall be provided in writing. Suggestions for improvements in this Standard are welcome. Questions and suggestions shall be sent to:

Secretary
Insulated Cable Engineers Association, Inc.
Post Office Box 1568
Carrollton, GA 30117, U.S.A
United States of America

This Standard was developed by the ICEA Communications Division, Copper Cable Section, whose membership consisted of technical experts from the manufacturing segment of the industry. It was approved by ICEA on March 16, 2012.

The members of the ICEA Communications Division, Copper Cable Section, who participated in this project, were:

R. Gould D. Baker P. Fraley G. Dorna

TABLE OF CONTENTS

CONTENTS:	SECTION	PAGE
	ACRONYMS, ABBREVIATIONS AND SYMBOLS	x
1.	GENERAL	
	1.1 Purpose	1
	1.2 Scope	1
	1.3 Definition Of Cable Types	2
	1.4 Options and Information	2
	1.5 Units and Tolerances	3
	1.6 References	3
	1.7 Quality Assurance	3
	1.8 Safety Considerations	3
	1.9 Installation Precautions	3
2.	CONDUCTORS	
	2.1 Solid Conductors for Horizontal Cables, Backbone Cables	4
	2.1.1 Solid Conductors	4
	2.1.2 Tin Coated Conductors	4
	2.1.3 Conductor Size	4
	2.1.4 Conductor Elongation	4
	2.1.5 Factory Joints	4
	2.2 Stranded Conductors for Patch Cordage	4
	2.2.1 Individual Strands	4
	2.2.2 Metallically Bonded Conductors	4
	2.2.3 Stranded Conductor Size	4
	2.2.3.1 UTP	4
	2.2.3.2 FTP	5
	2.2.4 Factory Joints	5
3.	CONDUCTOR INSULATION	
	3.1 Insulation Material	5
	3.1.1 Heavy Metal Free Insulation	5
	3.1.2 Low halogen Insulation	5
	3.2 Insulation Dimensions, Colors, and Splices	5
	3.2.1 Dimensions for Horizontal and Backbone Cables	5
	3.2.2 Dimensions for Patch Cordage	5
	3.2.3 Colors	6
	3.2.4 Color Systems	6
	3.2.5 Splices	6

TABLE OF CONTENTS

CONTENTS:	SECTION	PAGE
	3.3 Insulation Physical Requirements.....	6
	3.3.1 Adhesion of Solid Conductors.....	6
	3.3.2 Elongation.....	6
	3.3.3 Compression of Solid Conductors.....	7
	3.3.4 Cold Bend.....	7
	3.3.5 Shrinkback.....	7
	3.3.6 Heat Exposure (Aging).....	7
	3.3.7 Aged Flexibility.....	7
	3.3.8 Heavy Metal Content.....	7
	3.3.8 Halogen Content.....	8
	3.4 Twist Length and Color Coding.....	8
	3.4.1 Pairs.....	8
	3.4.2 Horizontal and Backbone Cables.....	8
	3.4.3 Patch Cordage.....	8
	3.4.4 Tight Twist Pairs.....	8
4.	CORE CONSTRUCTION	
	4.1 Core Layup.....	10
	4.2 Binders.....	10
	4.3 Core Wrap.....	10
	4.4 Ripcord.....	10
5.	SHIELDS	
	5.1 Shielding System.....	11
	5.2 Shielding Materials.....	11
	5.2.1 Aluminum Tape.....	11
	5.2.2 Copper Tape.....	11
	5.2.3 Laminated Tape.....	11
	5.2.4 Copper Braid.....	11
	5.2.5 Laminated Tape/Braid.....	11
	5.3 Metal Tape Shield Application.....	11
	5.4 Metal Tape Shield Splices.....	11
6.	JACKET	
	6.1 Jacket Material.....	11
	6.1.1 Heavy Metal Free Jacket.....	12
	6.1.2 Low Halogen Jacket.....	12
	6.2 Jacket Thickness.....	12
	6.3 Completed Cable Jacket Requirements.....	12
	6.3.1 Tensile Strength.....	12

TABLE OF CONTENTS

CONTENTS:	SECTION	PAGE
	6.3.2 Elongation.....	12
	6.3.3 Heat exposure (Aging)	12
6.4	Jacket Color.....	13
7.	TRANSMISSION AND ELECTRICAL REQUIREMENTS	
7.1	Transmission Classifications.....	13
7.2	Measurement Precaution.....	13
	7.2.1 General	13
	7.2.2 NEXT, ELFEXT and Delay Skew	13
7.3	DC Resistance.....	14
7.4	DC Resistance Unbalance.....	14
7.5	Mutual Capacitance	14
7.6	Pair-To-Ground Capacitance Unbalance.....	14
7.7	Attenuation (α)	14
	7.7.1 Solid Conductors.....	14
	7.7.2 Elevated Temperature Test.....	15
	7.7.3 Stranded Conductors	16
7.8	Near-End Crosstalk (NEXT).....	16
	7.8.1 Power Sum NEXT (PSNEXT)	17
7.9	Far-End Crosstalk (FEXT)	18
	7.9.1 Attenuation Crosstalk Ratio Far-End.....	18
	7.9.2 Power Sum Attenuation Crosstalk Ratio Far-End	19
7.10	Characteristic Impedance (Z_0)	19
7.11	Return Loss (RL)	20
7.12	Structural Return Loss (SRL).....	20
7.13	Phase Delay (τ).....	21
7.14	Phase Delay Skew.....	21
	7.14.1 Phase Delay Skew	21
	7.14.2 Environmental Effects	21
7.15	Insulation Resistance.....	22
7.16	Conductor-To-Conductor DC Proof Test	22
7.17	Core-To-Shield DC Proof Test.....	22
7.18	AC Leakage Test.....	22
7.19	Continuity of Metallic Cable Elements	22
7.20	Transfer Impedance.....	22
8.	MECHANICAL REQUIREMENTS	
8.1	Cable Cold Wrap Test	22
8.2	Wire and Cable Bending Test.....	23
8.3	Flex Test.....	23

TABLE OF CONTENTS

CONTENTS:	SECTION	PAGE
	8.4 Sheath Adherence	23
	8.5 Cable Pulling Tension.....	23
	8.6 Cable Flammability	24
	8.7 Limited Smoke	24
	8.8 National Electrical Code	24
9.	GENERAL REQUIREMENTS	
	9.1 Identification and Marking.....	25
	9.1.1 Method of Identification	25
	9.1.2 Length Marking	25
	9.2 Jacket Ink Marking Durability	26
	9.3 Packaging.....	26

TABLES

Table I:	Specifications Referenced in this Standard	27
----------	--	----

FIGURES

Figure 1:	Cable Flex Test Configuration and Apparatus.....	29
Figure 2:	Sheath Adherence Sample Preparation	30
Figure A-1:	Wicking Test Configuration.....	32

APPENDICES

Appendix A:	Test Procedures for Wicking and Hygroscopicity	31
Appendix B:	Test Procedure for Cable Ripcord Performance.....	33
Appendix C:	Test Procedure for Metallic Tape Splice Breaking Strength, Percent Retention.....	34
Appendix D:	Test Procedure for Durability of Ink Marking	35

ANNEXES

Annex A:	Product Guide.....	A-1
Annex B:	ICEA Standards.....	B-1

ACRONYMS, ABBREVIATIONS AND SYMBOLS

ACR	attenuation-to-crosstalk ratio
ANSI	American National Standards Institute
ASTM	American Society for Testing and Materials
ASQC	American Society for Quality Control
AWG	American Wire Gauge
CM	UL Listing designation for General Purpose Communication Cable
CMG	UL Listing designation for General Purpose Communication Cable
CMR	UL Listing designation for Riser Communication Cable
CMP	UL Listing designation for Plenum Communication Cable
CMX	UL Listing designation for Communication Cable, Limited Use
DOD	diameter over the dielectric, overall diameter of the insulated conductor
ELFEXT	equal level far-end crosstalk
FEXT	far-end crosstalk
FTP	overall shielded twisted pairs
F	constant representing a specific frequency
ICEA	Insulated Cable Engineers Association
IO FEXT	input/output far-end crosstalk
LAN	local area network
LS	limited smoke
NEC	National Electrical Code
NEXT	near-end crosstalk
NFPA	National Fire Protection Association
P-P ACR	pair-to-pair attenuation-to-crosstalk ratio
P-P ELFEXT	pair-to-pair equal level far-end crosstalk
P-P NEXT	pair-to-pair near-end crosstalk
PS ACR	power sum attenuation-to-crosstalk ratio
PS ELFEXT	power sum equal level far-end crosstalk
PS NEXT	power sum near-end crosstalk
RL	return loss
SI	International System of Units
SRL	structural return loss
UL	Underwriters Laboratories
UTP	unshielded twisted pairs
α	attenuation

CATEGORY 3, 5, & 5e INDIVIDUALLY UNSHIELDED TWISTED PAIR INDOOR CABLES (WITH OR WITHOUT AN OVERALL SHIELD) FOR USE IN GENERAL PURPOSE AND LAN COMMUNICATION WIRING SYSTEMS TECHNICAL REQUIREMENTS

SECTION 1 GENERAL

- 1.1 **PURPOSE:** This Standard establishes generic technical requirements that may be referenced by individual telecommunications cable specifications covering products intended for normal indoor premises use in the wiring systems of communications users. The parameters covered provide material, construction, and performance requirements.

Because this Standard does not cover all details of individual cable design, it cannot be used as a single document for procurement of product. This Standard is intended for use in conjunction with an individual product specification that provides complete design details for the specific cable type and designates the applicable performance requirements. Such individual cable specifications may be prepared either by the user or the manufacturer. The specification designated for procurement is at the option of the user.

- 1.2 **SCOPE:** This Standard covers mechanical, electrical and flammability requirements for thermoplastic insulated and jacketed, copper conductor, individually unshielded twisted pair indoor cables, with or without an overall shield, intended primarily for use as horizontal cables, backbone cables, or patch cordage. Depending upon the application and system requirements, this Standard provides choices for materials, transmission characteristics and flammability ratings.

This Standard covers the minimum transmission performance requirements for the following three Categories of cable based on existing system requirements and projected application needs. Multi-pair cables, conforming to the generic designation, ARxM, are not covered by this specification. See instead, ICEA S-103-701.

Category 3: Intended for voice, text, data, video and image transmission with transmission characteristics specified for frequencies up to 16 MHz.

Category 5: Intended for voice, text, data, video and image transmission:

- i: Category 5: transmission characteristics specified for frequencies up to 100 MHz.

- ii: Category 5e: enhanced transmission characteristics specified for frequencies up to 100 MHz.

1.3 DEFINITION OF CABLE TYPES:

Horizontal cables are normally used in that portion of the telecommunications cabling system between the telecommunications room and the work area telecommunications outlet.

Backbone cables are normally used in that portion of the telecommunications cabling system between telecommunications closets, equipment rooms, and entrance facilities within a building.

Patch cordage is a length of cable used in the manufacture of patch cords where it is combined with connectors on one or both ends to join telecommunication circuits/links at the cross-connect and to connect work stations to the wall outlet. The conductors are typically stranded.

1.4 OPTIONS AND INFORMATION: For those characteristics where no differentiation is made, the performance requirements are applicable to all cable categories. Selection of the applicable category shall be at the discretion of the user and shall be designated in the product specification.

This Standard is arranged in Sections covering specific areas of cable requirements and may be referenced as complete Sections or as individual paragraphs.

Paragraphs of this Standard where the user may specify a particular option are listed below:

2.1, 2.2	Conductors
3.1.1, 3.1.2	Insulation Material
3.4.3	Color Code for Patch Cordage
4.4	Ripcord
5.2	Shielding Designs
6.1.1, 6.1.2	Jacket Material
6.4	Jacket Color
7.1	Transmission Classifications
8.6	Cable Flammability
8.7	Limited Smoke
9.1.2	Length Marking
9.3	Packaging

To assist the user in selection of options and to avoid possible misunderstandings between the manufacturer and user, it is suggested that a check-off sheet similar to that shown in Informative Annex A be utilized.

1.5 UNITS AND TOLERANCES: SI units are specified throughout this Standard except for conductor size following guidelines of NIST SP-811. Approximate US (inch-pound) equivalents and Fahrenheit temperatures are provided for information only. Unless otherwise specified, the rounding-off method of ASTM E 29 shall be used for determining conformance to this Standard.

1.6 REFERENCES: All documents referenced herein are listed in Table I with issues and/or dates as indicated.

1.7 QUALITY ASSURANCE: It is the responsibility of the manufacturer to establish a quality assurance system consistent with ISO Q9001 or an alternate system acceptable to the user. When the user requires a specific quality assurance program and/or special testing procedures, agreement between the user and the manufacturer should be reached before the order is placed.

Requirements shall be met on every length of completed cable as assured by quality control methods. The term “completed cable” refers to a continuous length of finished cable resulting from the last jacketing operation.

Properties that shall be tested on every length of completed cable prior to shipment are listed below by paragraph number.

- 7.17 Conductor - To - Conductor DC Proof Test
- 7.18 Core - To - Shield DC Proof Test
- 7.20 Continuity of Metallic Cable Elements

As an exception to these requirements for products packaged in-line, the above tests may be performed at the last assembly operation prior to jacketing.

1.8 SAFETY CONSIDERATIONS: Materials in the cable shall present no dermal, environmental, or other safety hazards as defined by current industry standards or applicable federal, state, or local laws and regulations.

The user of this Standard is cautioned to observe any applicable health or safety regulations and rules relative to the manufacture and use of cable made in conformity with this Standard. This Standard hereafter assumes that manufacture, test, installation, and maintenance of cables, defined by this Standard, will be performed only by properly trained personnel using suitable equipment and employing appropriate safety precautions.

1.9 INSTALLATION PRECAUTIONS: As with all transmission media, if recommended cabling precautions and installation methods are not observed, specified transmission capabilities may not be achieved. Contact the cable manufacturer for installation guidelines.