

ANSI/ESD STM2.1-2018

ESD Association Standard Test Method

ANSI/ESD STM2.1-2018
Reaffirmation of ANSI/ESD STM2.1-2013

*For the Protection of Electrostatic
Discharge Susceptible Items*

*Garments -
Resistive Characterization*



*Electrostatic Discharge Association
7900 Turin Road, Bldg. 3
Rome, NY 13440*

*An American National Standard
Approved June 27, 2018*

*ESD Association Standard Test Method for
the Protection of Electrostatic Discharge
Susceptible Items -*

*Garments -
Resistive Characterization*

Approved April 15, 2018
EOS/ESD Association, Inc.



**CAUTION
NOTICE**

Electrostatic Discharge Association (ESDA) standards and publications are designed to serve the public interest by eliminating misunderstandings between manufacturers and purchasers, facilitating the interchangeability and improvement of products and assisting the purchaser in selecting and obtaining the proper product for his particular needs. The existence of such standards and publications shall not in any respect preclude any member or non-member of the Association from manufacturing or selling products not conforming to such standards and publications. Nor shall the fact that a standard or publication that is published by the Association preclude its voluntary use by non-members of the Association, whether the document is to be used either domestically or internationally. Recommended standards and publications are adopted by the ESDA in accordance with the ANSI Patent policy.

Interpretation of ESDA Standards: The interpretation of standards in-so-far as it may relate to a specific product or manufacturer is a proper matter for the individual company concerned and cannot be undertaken by any person acting for the ESDA. The ESDA Standards Chairman may make comments limited to an explanation or clarification of the technical language or provisions in a standard, but not related to its application to specific products and manufacturers. No other person is authorized to comment on behalf of the ESDA on any ESDA Standard.

**DISCLAIMER OF
WARRANTIES**

THE CONTENTS OF ESDA'S STANDARDS AND PUBLICATIONS ARE PROVIDED "AS-IS," AND ESDA MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESSED OR IMPLIED, OF ANY KIND WITH RESPECT TO SUCH CONTENTS. ESDA DISCLAIMS ALL REPRESENTATIONS AND WARRANTIES, INCLUDING WITHOUT LIMITATION, WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR USE, TITLE, AND NON-INFRINGEMENT.

**DISCLAIMER OF
GUARANTY**

ESDA STANDARDS AND PUBLICATIONS ARE CONSIDERED TECHNICALLY SOUND AT THE TIME THEY ARE APPROVED FOR PUBLICATION. THEY ARE NOT A SUBSTITUTE FOR A PRODUCT SELLER'S OR USER'S OWN JUDGEMENT WITH RESPECT TO ANY PARTICULAR PRODUCT DISCUSSED, AND ESDA DOES NOT UNDERTAKE TO GUARANTEE THE PERFORMANCE OF ANY INDIVIDUAL MANUFACTURERS' PRODUCTS BY VIRTUE OF SUCH STANDARDS OR PUBLICATIONS. THUS, ESDA EXPRESSLY DISCLAIMS ANY RESPONSIBILITY FOR DAMAGES ARISING FROM THE USE, APPLICATION, OR RELIANCE BY OTHERS ON THE INFORMATION CONTAINED IN THESE STANDARDS OR PUBLICATIONS.

**LIMITATION ON
ESDA's LIABILITY**

NEITHER ESDA, NOR ITS FORMER AND PRESENT MEMBERS, OFFICERS, EMPLOYEES, OR OTHER REPRESENTATIVES WILL BE LIABLE FOR DAMAGES ARISING OUT OF, OR IN CONNECTION WITH, THE USE OR MISUSE OF ESDA STANDARDS OR PUBLICATIONS, EVEN IF ADVISED OF THE POSSIBILITY THEREOF. THIS IS A COMPREHENSIVE LIMITATION OF LIABILITY THAT APPLIES TO ALL DAMAGES OF ANY KIND, INCLUDING WITHOUT LIMITATION, LOSS OF DATA, INCOME OR PROFIT, LOSS OF OR DAMAGE TO PROPERTY, AND CLAIMS OF THIRD PARTIES.

Published by:

**Electrostatic Discharge Association
7900 Turin Road, Bldg. 3
Rome, NY 13440**

Copyright © 2018 by EOS/ESD Association, Inc.
All rights reserved

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

Printed in the United States of America

ISBN: 1-58537-304-4

(This foreword is not part of ESD Association Standard Test Method ANSI/ESD STM2.1-2018)

FOREWORD

This standard test method¹ (STM) provides test methods for evaluating the electrical resistance of garments that contain surface conductive or dissipative components or materials used in the electronics industry for the control of electrostatic discharge. This document defines procedures for measuring electrical resistance, including a system resistance test for garments that provide a ground path for personnel.

Clothing made from synthetic fibers is a common source of electrostatic charge. Wearing an appropriate static control garment over personal clothing can minimize the effect of this charge. To effectively control electrostatic charges, the static control garment must be grounded.

Three categories of garments are considered in this document.

- ESD Category 1 garment; a **static control garment** may suppress or otherwise affect an electric field from clothing worn underneath the garment without being attached to ground. However, without grounding, a charge may accumulate on conductive or dissipative elements of a garment, if present, resulting in a charged source.
- ESD Category 2 garment; a **groundable static control garment**, when connected to ground, provides a higher level of suppression of the affects of an electric field from clothing worn underneath the garment.
- ESD Category 3 garment; a **groundable static control garment system** provides a ground path for a person that suppresses the electrical field from clothing worn underneath the garment and also bonds the skin of the test subject to an identified ground path. Groundable static control garment systems may also be used in conjunction with a continuous or constant monitoring system in a manner similar to those used in continuous monitoring of wrist straps in an ESD protected area (EPA).

Resistive characterization is only one aspect to consider in evaluating garments for any specific application. To fully characterize a garment, electrical field attenuation, static charge decay, peak voltage, residual voltage and triboelectric charging may need to be considered. Other attributes related to applications and environments, such as cleanroom compatibility, chemical and fire resistance, etc., should be evaluated in the garment selection process but are beyond the scope of this document.

Garments constructed from fabrics made with fibers that are not surface conductive but may have other related properties that impart some level of electrostatic charge dissipation or suppression when connected to ground, are not specifically measured by the methods provided in this STM.

Some garment fabrics and construction may allow for surface voltage accumulation and charge transfer to occur, which may be detrimental to electronic items.

This document was originally designated ANSI/ESD STM2.1-1997 and approved on September 20, 1997. On September 7, 2011, ANSI administratively withdrew ANSI/ESD STM2.1-1997 and the document was redesignated ESD STM2.1-1997. ANSI/ESD STM2.1-2013 was a revision of ESD STM2.1-1997 and was approved on February 10, 2013. ANSI/ESD STM2.1-2018 is a reaffirmation of ANSI/ESD STM2.1-2013 and was approved on April 15, 2018.

¹ **ESD Association Standard Test Method (STM):** A definitive procedure for the identification, measurement and evaluation of one or more qualities, characteristics or properties of a material, product, system or process that yields a reproducible test result.

The following individuals contributed to the development of ANSI/ESD STM2.1-2013 and/or ESD STM2.1-1997:

Kay Adams Tech Wear, Inc.	Tom Albano Exelis, Inc. Geospatial Systems	Sheila Akins-Davis Fluke Electronics Corporation
Donn Bellmore Advanced ESD Services +	Donald Boehm Dou Yee Enterprises	Julius Brodbeck USAF
Edward B. Davis Vidaro Corp.	Rejean Dion Bystat International, Inc.	Kurt Edwards Lubrizol Conductive Polymers
Gene Felder Desco Industries, Inc.	Ron Gibson Advanced Static Control Consulting	Vaughn Gross IBM Micro Electronics
Jay Hamlin Medtronic	Kelly Hogan Litton Guidance & Control Systems	Joe Jesse Key Industries
Michele McSwain	Gene Monroe NASA - LARC	Carl Newberg Microstat Labs
Elaine Olson Intel Corporation	Dale Parkin Seagate Technology	Rita L. Shartzter Motorola
Ron Small Precision Fabrics Group	David E. Swenson Affinity Static Control Consulting, LLC	Wayne Tan Advanced Micro Devices
Julius Turangan Ovation Polymers		Bob Vermillion RMV Technology Group, LLC

TABLE OF CONTENTS

1.0 PURPOSE, SCOPE, AND APPLICATION	1
1.1 PURPOSE	1
1.2 SCOPE	1
1.3 APPLICATION	1
2.0 REFERENCED PUBLICATIONS	2
3.0 DEFINITIONS	2
4.0 PERSONNEL SAFETY	2
5.0 EQUIPMENT AND MATERIALS	3
5.1 TEST EQUIPMENT REQUIREMENTS.....	3
5.1.1 <i>Resistance Measurement Apparatus</i>	3
5.1.2 <i>Resistance Measurement Electrode(s)</i>	3
5.1.3 <i>Insulative Support</i>	4
5.1.4 <i>Environment</i>	5
6.0 TEST METHODS	6
6.1 SAMPLE PREPARATION.....	6
6.1.1 <i>Sample Size</i>	6
6.1.2 <i>Sample Sketch</i>	6
6.2 HUMIDITY REQUIREMENTS.....	6
6.2.1 Product Qualification	6
6.2.2 Acceptance Testing.....	6
6.2.3 Periodic Verification	6
6.3 TEST METHOD – PRODUCT QUALIFICATION	6
6.3.1 <i>Static Control Garment</i>	7
6.3.2 <i>Groundable Static Control Garment</i>	8
6.3.3 <i>Groundable Static Control Garment System</i>	10
6.3.4 <i>Groundable Static Control Garment System in Combination with a Person</i>	15
6.4 TEST METHOD - ACCEPTANCE TESTING	18
6.5 PERIODIC VERIFICATION TESTING	18
6.5.1 <i>Resistance Point-to-Point (Rpp) Test Method</i>	18
6.5.2 <i>Hanging Clamp/Electrode Sleeve-to-Sleeve (Alternate Test Method)</i>	20
6.5.3 <i>Groundable Static Control Garment System In Combination with a Person</i>	20
6.6 COMPLIANCE VERIFICATION TESTING.....	22
7.0 TEST DATA REPORTING	22

ANNEXES

ANNEX A (INFORMATIVE) - Garment Categories and Resistance Values 23
ANNEX B (INFORMATIVE) - Data Collection Sheet (Example) 24
ANNEX C (INFORMATIVE) - Additional Considerations 26
ANNEX D (INFORMATIVE) - ANSI/ESD STM2.1-2018 Revision History 27

TABLES

Table 1: Test Locations and Test Equipment for Product Qualification 17
Table 2: Garment Categories and Resistance Values 23

FIGURES

Figure 1: Clamp/Electrodes for Hanging Sleeve-to-Sleeve (Alternate Test Method) 5
Figure 2: Cuff Test Fixture for BCP Measurement..... 5
Figure 3a: Rpp - Sleeve-to-Sleeve Test Method with Insulative Sleeve Inserts 7
Figure 3b: Rpp - Insulative Sleeve Insert Positioned into Sleeve Detail 8
Figure 3c: Rpp - Panel-to-Panel Test Method on Specimen Support Surface 8
Figure 4: Rpgp - Sleeve to Groundable Point Test Method with Insulative Sleeve Inserts 10
Figure 5a: Rpp - BCP to BCP or Cuff-to-Cuff Test Method 11
Figure 5b: Rpp - Electrode Inserted into BCP-Detail 11
Figure 5c: Rpp - Garment with conductive cuff or other wrist strap type BCP to garment panel 12
Figure 6a: Rpgp - BCP to Garment Groundable Point Test Method..... 13
Figure 6b: Rpgp - Sleeve to Garment Groundable Point Test Method with Insulative Sleeve Inserts 13
Figure 7: Rpgp - BCP to Garment Groundable Point Test Method with Cuff Test Fixture 14
Figure 8a: Test Setup - Groundable Static Control Garment System Resistance (Ohmmeter Test Method) 15
Figure 8b: Test Setup - Groundable Static Control Garment System Resistance (Integrated Tester Test Method)..... 16
Figure 9a: Rpp - Sleeve-to-Sleeve Test Method with Insulative Sleeve Inserts 19
Figure 9b: Rpp - BCP to BCP or Cuff-to-Cuff Test Method 19
Figure 10: Test Setup - Hanging Clamp/Electrode Sleeve-to-Sleeve (Alternate Test Method). 20
Figure 11a: Test Setup - Groundable Static Control Garment System Resistance (Groundable Garment in Combination with a Person – Ohmmeter Test Method)..... 21
Figure 11b: Test Setup - Groundable Static Control Garment System Resistance (Groundable Garment in Combination with a Person - Integrated Tester Test Method) 22

ESD Association Standard Test Method for the Protection of Electrostatic Discharge Susceptible Items – Garments – Resistive Characterization

1.0 PURPOSE, SCOPE, AND APPLICATION

1.1 Purpose

This document provides test methods for evaluating the electrical resistance of static control garments that contain surface conductive or dissipative components or materials.

1.2 Scope

This document applies to outer garments that utilize surface conductive or dissipative components or materials, used for static control applications.

NOTE: The test methods defined in this document are not intended to measure materials with buried conductive layers.

1.3 Application

The test methods defined in this document utilize standard instruments to measure the electrical resistance of static control garments that are constructed with surface conductive or dissipative components or materials.

1.3.1 The resistance point-to-point test method (Figures 3a, 3b, 3c, 4, 5a, 5b, and 5c) tests the electrical resistance between the two sleeves, any two panels, or any two or more electrically interconnected components of the static control garment, including the electrical resistance across the seams and body contact point (BCP) of the garment as applicable.

1.3.1.1 An alternate sleeve-to-sleeve test method is provided in Section 6.5.2. It uses clamp/electrodes to hang the garment during the measurement, as shown in Figure 10.

1.3.2 Static control garments that electrically bond to the test subject and provide a path to ground for the test subject (Category 3) shall be evaluated by all three methods:

- the resistance point-to-point test method (Fig 5a, 5b and 5c);
- the resistance point-to-groundable point test method (Figures 4, 6a, 6b and 7); and
- the system test to determine the resistance from the person, through the garment groundable point of the garment to the groundable point, including the ground cord (Figures 8a and 8b).

1.3.3 The BCP measurement test method is provided in Section 6.3.3.3 for garments so equipped. The cuff test fixture shown in Figure 2 and applied in Figure 7 is required for these measurements. This cuff test fixture is also described in ANSI/ESD S1.1 - Wrist Straps.