

IPC-4204B

2018 - August

Flexible Metal-Clad Dielectrics for Use in Fabrication of Flexible Printed Boards

Supersedes IPC-4204A with Amendment 1
October 2013

An international standard developed by IPC

Association Connecting Electronics Industries



The Principles of Standardization

In May 1995 the IPC's Technical Activities Executive Committee (TAEC) adopted Principles of Standardization as a guiding principle of IPC's standardization efforts.

Standards Should:

- Show relationship to Design for Manufacturability (DFM) and Design for the Environment (DFE)
- Minimize time to market
- Contain simple (simplified) language
- Just include spec information
- Focus on end product performance
- Include a feedback system on use and problems for future improvement

Standards Should Not:

- Inhibit innovation
- Increase time-to-market
- Keep people out
- Increase cycle time
- Tell you how to make something
- Contain anything that cannot be defended with data

Notice

IPC Standards and Publications are designed to serve the public interest through eliminating misunderstandings between manufacturers and purchasers, facilitating interchangeability and improvement of products, and assisting the purchaser in selecting and obtaining with minimum delay the proper product for his particular need. Existence of such Standards and Publications shall not in any respect preclude any member or nonmember of IPC from manufacturing or selling products not conforming to such Standards and Publication, nor shall the existence of such Standards and Publications preclude their voluntary use by those other than IPC members, whether the standard is to be used either domestically or internationally.

Recommended Standards and Publications are adopted by IPC without regard to whether their adoption may involve patents on articles, materials, or processes. By such action, IPC does not assume any liability to any patent owner, nor do they assume any obligation whatever to parties adopting the Recommended Standard or Publication. Users are also wholly responsible for protecting themselves against all claims of liabilities for patent infringement.

IPC Position Statement on Specification Revision Change

It is the position of IPC's Technical Activities Executive Committee that the use and implementation of IPC publications is voluntary and is part of a relationship entered into by customer and supplier. When an IPC publication is updated and a new revision is published, it is the opinion of the TAEC that the use of the new revision as part of an existing relationship is not automatic unless required by the contract. The TAEC recommends the use of the latest revision. Adopted October 6, 1998

Why is there a charge for this document?

Your purchase of this document contributes to the ongoing development of new and updated industry standards and publications. Standards allow manufacturers, customers, and suppliers to understand one another better. Standards allow manufacturers greater efficiencies when they can set up their processes to meet industry standards, allowing them to offer their customers lower costs.

IPC spends hundreds of thousands of dollars annually to support IPC's volunteers in the standards and publications development process. There are many rounds of drafts sent out for review and the committees spend hundreds of hours in review and development. IPC's staff attends and participates in committee activities, typesets and circulates document drafts, and follows all necessary procedures to qualify for ANSI approval.

IPC's membership dues have been kept low to allow as many companies as possible to participate. Therefore, the standards and publications revenue is necessary to complement dues revenue. The price schedule offers a 50% discount to IPC members. If your company buys IPC standards and publications, why not take advantage of this and the many other benefits of IPC membership as well? For more information on membership in IPC, please visit www.ipc.org or call 847/597-2809.

Thank you for your continued support.



IPC-4204B

Flexible Metal-Clad Dielectrics for Use in Fabrication of Flexible Printed Boards

Developed by the Flexible Circuits Base Materials Subcommittee (D-13)
of the Flexible Circuits Committee (D-10) of IPC

Supersedes:

IPC-4204A with Amendment 1 -
October 2013
IPC-4204A - October 2011
IPC-4204 - May 2002

Users of this publication are encouraged to participate in the
development of future revisions.

Contact:

IPC
3000 Lakeside Drive, Suite 105N
Bannockburn, Illinois
60015-1249
Tel 847 615.7100
Fax 847 615.7105

This Page Intentionally Left Blank

Acknowledgment

Any document involving a complex technology draws material from a vast number of sources across many continents. While the principal members of the Flexible Circuits Base Materials Subcommittee (D-13) of the Flexible Circuits Committee (D-10) are shown below, it is not possible to include all of those who assisted in the evolution of this standard. To each of them, the members of IPC extend their gratitude.

Flexible Circuits Committee	Flexible Circuits Base Materials Subcommittee	Technical Liaison of the IPC Board of Directors
Chair Nick S. Koop TTM Technologies	Chair Clark F. Webster All Flex LLC	Robert Neves Microtek (Changzhou) Laboratories
Vice Chair William A. Ortloff Raytheon Company		
Flexible Circuits Base Materials Subcommittee		
Takahisa Akatsuka, Nippon Mektron Ltd.	Greg Clements, Kaneka North America LLC	Mahendra Gandhi, Northrop Grumman Aerospace Systems
Alisha Amar, Lockheed Martin Space Systems Company	Michael Collier, Teledyne Printed Circuit Technologies	Feng (Andrew) Gao, Huawei Technologies Co., Ltd.
Masamitsu (Matt) Aoki, JETPA	David Corbett, DLA Land and Maritime	Thomas Gardeski, Gemini Sciences, LLC
Lance Auer, Raytheon Missile Systems	Andrea Cote, UL LLC	Donna Gardner, DuPont
Richard Barnett, Hewlett-Packard Company	Michelle Courier, UL LLC	Michael Gleason, Draper
John Bauer, Rockwell Collins	Dr. Sidney Cox	Ty Gragg, Unicircuit Inc.
Roger Bell, Space Systems/Loral	Michael Crutchfield, Dupont-RTP	Russell Griffith, Flexible Circuits Inc.
Mary Bellon	Jay Desai, M-FLEX	Rachel Grinvalds, Rockwell Collins
Dr. Tad Bergstresser, Bakaert Specialty Films LLC	Michael Dickson, UL LLC	Christine Harrington, Amphenol Printed Circuits, Inc.
Robert Black, Northrop Grumman Corporation	Joseph DiPalermo, M-Flex/Pica Sales & Engineering	William Hazen, Raytheon Company
Frank Boehm	Mitsuharu Douwaki, Fujikura Ltd.	Todd Henninger, TTM Technologies
Scott Bowles, L-3 Fuzing and Ordnance Systems, Cincinnati	Don Dupriest, Lockheed Martin Missiles & Fire Control	Hillary Herbert, DuPont
JianWei Cai, Shengyi Technology Co. Ltd.	Jim Edmonds, Shin-Etsu MicroSi	Donald Herr, Adhesives Research, Inc.
Tracy Cai, Shengyi Technology Co. Ltd.	Theodore Edwards	Scott Herrmann, DuPont
Rodd Cairns, Starkey Hearing Technologies	Steven Ethridge, Dell Inc.	Stephen Jaarsma, Taconic Advanced Dielectric Division
Byron Case, L-3 Communications	Alan Exley, Raytheon Company	William Jacobi, William Jacobi & Associates
Shawn Chaput, Raytheon Missile Systems	Thomas Farrell	Michael Jawitz, Orbital ATK
Dr. Wennei Chen, Northrop Grumman Aerospace Systems	Jason Ferguson, NSWC Crane	Tamotsu Kitagawa, ABC Corp.
Jeffrey Ciesla, DLA Land and Maritime	Mark Finstad, Flexible Circuit Technologies, Inc.	Nick Koop, TTM Technologies
	Terry Fischer, Hitachi Chemical Co. America, Ltd.	Toshiaki Kuroiwa, UBE
	Thomas Fisher, DuPont-RTP	Karin LaBerge, KAL Consulting
	Scott Foll, DuPont	Emi Lee, NTS - Anaheim
	Lionel Fullwood, WKK Distribution Ltd.	Grant Lee, Kaneka North America LLC

Minsu Lee, Korea Printed Circuit Association	Joel Peiffer, 3M Company	Vern Solberg, Solberg Technical Consulting
John Leschisin, Minco Products, Inc.	Tony Plemel, Minco Products, Inc.	Valerie A. St. Cyr, Teradyne Inc.
Dr. Yanmei Li, Schlumberger Well Services	John Potenza, Lockheed Martin Mission Systems & Training	Herb Stark, Flexible Circuits Inc.
Daniel Lunger, DuPont	Damon Rachell, NTS - Anaheim	Rebecca Steinbauer, ALL Flex LLC
Duane Mahnke, DBMahnke Consulting	Donna Richardson, L-3 Communications	Brian Stevens, Rockwell Collins
John Marke, UL LLC	Thomas Romont, IFTEC	James Stockhausen, ELANTAS PDG, Inc.
Eric Matuska, ALL Flex LLC	Jim Ryan, Insulectro	Darin Stotz, Northfield Automation Systems Inc.
Mark McAlees, DuPont	Dr. Jerome Sallo, Sallo Consulting Services	Brent Sweitzer, Multek Flexible Circuits, Inc.
Dr. Thomas McCarthy, Taconic Advanced Dielectric Division	Edward Sandor, Taconic Advanced Dielectric Division	Kunio Takahara, JPCA-Japan Electronics Packaging and Circuits Assoc.
Daniel McCormick, NSWC Crane	Takeshi Sasaki, Nippon Steel Chemical Company	Mamoru (Mark) Takahashi, Asahi Glass
Robert P. McGarry, RPM Solutions	Sie Sauers, GE Healthcare	Dung (Young)Tiet, Lockheed Martin Space Systems Company
Paul Meloni, Kaneka North America LLC	Rolland Savage, Savage Consulting	Randy Tolbert, NSWC Crane
Peter B. Menuiez	Charles Schamberg, Raytheon Missile Systems	Crystal Vanderpan, UL LLC
Roger J. Miedico, Raytheon Company	Joseph Schmidt, Raytheon Missile Systems	Steve Vetter, NSWC Crane
Keita Miyasato, Taiyo Industrial Co., Ltd.	Julie Scopel, UL LLC	Jennet Volden, Rockwell Collins
Steve A. Musante, Raytheon Missile Systems	Mark Seelhammer, Rogers Corporation	Nicholas Watts, Intel Corporation
Dr. Yoji Nakajima, Asahi Glass Co., Ltd.	Tony Senese, Panasonic Industrial Devices Sales Company of America	David Weatherford, Teledyne Printed Circuit Technologies
Robert Neves, Microtek (Changzhou) Laboratories	Jesse Session, Taiyo America Inc.	Vern Welk, Molex Copper Flex Products
Dr. Thi Nguyen, Lockheed Martin Missile & Fire Control	Gilbert Shelby, Raytheon Systems Company	Richard Wessel, DuPont - RTP
Dominique Numakura, DKN Research	Robert Sheldon, Pioneer Circuits Inc.	Kurt Whitcomb, Amphenol Printed Circuits, Inc.
Chiaki Okawa, Taiyo Industrial Co., Ltd.	Terry Shepler, Electro-Materials, Inc.	Jay Wu, Taiflex Scientific Co., Ltd.
Glenn Oliver, Raytheon Missile Systems	Lowell Sherman, DLA Land and Maritime	Miou Yamaoka, Meiko Electronics Co. Ltd.
William Ortloff, Raytheon Company	Caroline Simonian-Owens, UL LLC	Ryoichi Yoshimura, Nippon Mektron Ltd.
Dr. J. Lee Parker, JLP	Doug Sober, Essex Technologies Group Inc.	Haida Yvjiro, Nippon Mektron Ltd.

Table of Contents

1 SCOPE	1	3.5	Visual Requirements	7
1.1 Classification System	1	3.5.1	Marking	7
1.1.1 Nonspecific Designation	1	3.5.2	Wrinkles, Creases, Streaks and Scratches	7
1.1.2 Specific Designation	1	3.5.3	Inclusions	8
1.1.2.1 Base Material Type	2	3.5.4	Voids	8
1.1.2.2 Reinforcement Method	2	3.5.5	Holes, Tears and Delaminations	8
1.1.2.3 Reinforcement Type	2	3.5.6	Pits and Dents	8
1.1.2.4 Base Material Thickness	3	3.5.7	Discoloration	8
1.1.2.5 Adhesive Type	3	3.6	Dimensional Requirements	8
1.1.2.6 Adhesive Thickness	3	3.6.1	Sheet Width and Length	8
1.1.2.7 Metal Cladding	3	3.6.2	Roll Width	8
1.1.2.7.1 Metal Foil	4	3.6.3	Roll Length	8
1.1.2.7.2 Metal Foil Type	4	3.6.4	Dielectric Thickness	8
1.1.2.7.3 Foil Designation	4	3.6.5	Adhesive Thickness	9
1.1.2.7.4 Nominal Metal Cladding Thickness	4	3.6.6	Metal Foil Thickness	9
1.1.2.7.5 Bond Enhancement Treatment	5	3.7	Physical Requirements	9
1.2 Qualification	5	3.7.1	Dimensional Stability	9
1.3 Quality Conformance	5	3.7.2	Peel Strength	9
1.4 Material Characteristics	5	3.7.2.1	Peel Strength As Received	9
1.5 New Materials	5	3.7.2.2	Peel Strength After Solder Float	9
2 APPLICABLE DOCUMENTS	5	3.7.2.3	Peel Strength After Temperature Cycling	9
2.1 IPC	5	3.7.3	Initiation Tear Strength	9
2.2 American Society For Testing and Materials (ASTM)	6	3.7.4	Propagation Tear Strength	9
2.3 Underwriters Laboratories Standards	6	3.7.5	Flexural Endurance	9
2.4 ISO	6	3.7.6	Low Temperature Flexibility	9
3 REQUIREMENTS	6	3.8	Chemical Requirements	9
3.1 Terms and Definitions	6	3.8.1	Chemical Resistance	9
3.1.1 Qualification Testing	6	3.8.2	Solder Float	9
3.1.2 Quality Conformance Testing	6	3.8.3	Solderability	9
3.1.3 User Inspection Lot	6	3.9	Electrical Requirements	10
3.1.4 Supplier Inspection Lot	6	3.9.1	Permittivity (Dielectric Constant)	10
3.1.5 Structurally Similar Construction	6	3.9.2	Loss Tangent (Dissipation Factor)	10
3.2 Specification Sheets	7	3.9.3	Volume Resistivity (Damp Heat)	10
3.3 Conflict	7	3.9.4	Surface Resistance (Damp Heat)	10
3.4 Materials	7	3.9.5	Dielectric Strength	10
3.4.1 Base Material	7	3.10	Environmental Requirements	10
3.4.2 Adhesive	7	3.10.1	Fungus Resistance	10
3.4.3 Metal-Cladding	7	3.10.2	Moisture Absorption	10
3.4.4 Sheet Material	7	3.10.3	Flammability	10
3.4.5 Roll Material	7	3.10.4	Service Temperature	11
		3.10.5	Moisture and Insulation Resistance	11
		3.11	Workmanship	11

Flexible Metal-Clad Dielectrics for Use in Fabrication of Flexible Printed Boards

1 SCOPE

This standard establishes the classification system, the qualification and quality conformance requirements for flexible metal-clad dielectric materials to be used for the fabrication of flexible printed boards.

1.1 Classification System The system described in 1.1.1 through 1.1.2.7 identifies flexible metal-clad dielectrics.

1.1.1 Nonspecific Designation A nonspecific designation is intended for use by *designers* on master drawings to designate their material choice. At the end of this standard is a series of material specification sheets identified by specification sheet numbers. Each sheet outlines engineering and performance data for a flexible metal-clad dielectrics, indicating base material type, adhesive type and method of reinforcement.

Example of nonspecific designation:

IPC-4204/I, where “I” refers to the specification sheet detailing copper-clad polyimide dielectric with acrylic adhesive. If further material specification details (such as dielectric, adhesive or copper thicknesses) are required, they should be highlighted in cross sectional views or notes on the master drawing.

1.1.2 Specific Designation The specific designation should be in the form shown in the following example, and is intended for use on material purchase orders by *fabricators* (see 6.1). The specific designation should not be used by designers on master drawings to indicate their material selection, as the designation is lengthy and requires fabricator level knowledge in making the detailed selections.

NOTE: The alpha character “Z” replaces and is entirely equivalent to the alpha character “O” (ref: Table 1-5) in the original release (prior revision) of this IPC standard. This interchange of characters within the designation will help alleviate confusion from using both the alpha character “O” and the digit “0” from the original release of this IPC standard. Legacy designs that utilize a designation and material description from the original release of this IPC standard [alpha character “O” (from Table 1-5)] may continue to be used. Supplier material certifications will reflect the current IPC standard’s revision, and accordingly, the alpha character “Z” in the designation.

Example of specific designation:

IPC-4204/I – E1E2M2/2 CU-W7-1P/IP

Where:

IPC-4204/I – Nonspecific Designation (see 1.1.1) specifying copper-clad dielectric with acrylic adhesive

E – Base Dielectric Type Designation (see 1.1.2.1) specifying polyimide

I – Reinforcement Method Designation (see 1.1.2.2) specifying non-reinforced

E – Reinforcement Type Designation (see 1.1.2.3) specifying non-reinforced film

2 – Base Dielectric Thickness Designation (see 1.1.2.4) specifying 50microns [0.002 in]

M – Adhesive Type Designation (see 1.1.2.5) specifying acrylic adhesive

2/2 – Adhesive Thickness Designation (see 1.1.2.6) specifying 50 micron both sides (Not used for adhesiveless product)

CU-W7-1P/IP – Metal Cladding Designation (see 1.1.2.7) specifying wrought rolled annealed copper, 35 microns both sides with no treatment