

Australian/New Zealand Standard™

Specification for preservative treatment

Part 4: Laminated veneer lumber (LVL)



AS/NZS 1604.4:2010

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee TM-006, Timber Preservation and Durability. It was approved on behalf of the Council of Standards Australia on 15 September 2010 and on behalf of the Council of Standards New Zealand on 24 September 2010. This Standard was published on 25 October 2010.

The following are represented on Committee TM-006:

A3P

Australian Pesticides and Veterinary Medicines Authority
CSIRO, Materials Science and Engineering
Department of Building and Housing (New Zealand)
Department of Primary Industries and Fisheries Queensland
Engineered Wood Products Association of Australasia
Engineers Australia
Forests New South Wales
Glued Laminated Timber Association of Australia
New Zealand Chemical Industry Council
New Zealand Pine Manufacturers Association
New Zealand Timber Industry Federation
New Zealand Timber Preservation Council
Timber Preservers Association of Australia
Timber Queensland
Wood Processors Association

Additional Interests:

Dr Harry Greaves

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about joint Australian/New Zealand Standards can be found by visiting the Standards Web Shop at www.saiglobal.com.au or Standards New Zealand web site at www.standards.co.nz and looking up the relevant Standard in the on-line catalogue.

For more frequent listings or notification of revisions, amendments and withdrawals, Standards Australia and Standards New Zealand offer a number of update options. For information about these services, users should contact their respective national Standards organization.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Please address your comments to the Chief Executive of either Standards Australia or Standards New Zealand at the address shown on the back cover.

This Standard was issued in draft form for comment as DR AS/NZS 1604.4.

Australian/New Zealand Standard™

Specification for preservative treatment

Part 4: Laminated veneer lumber (LVL)

Originated as AS/NZS 1604.4:2002.
Previous edition 2004.
Third edition 2010.

COPYRIGHT

© Standards Australia Limited/Standards New Zealand

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Australia) or the Copyright Act 1994 (New Zealand).

Jointly published by SAI Global Limited under licence from Standards Australia Limited, GPO Box 476, Sydney, NSW 2001 and by Standards New Zealand, Private Bag 2439, Wellington 6140

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee TM-006, Timber Preservation and Durability, to supersede AS/NZS 1604.4:2004.

The objective of this Standard is to specify requirements for preservative treatment of laminated veneer lumber (LVL) for protection against decay or insect attack.

The objectives of this revision are to—

- (a) include requirements for additional glueline treatments for both hazard class 1 and hazard class 2 exposure conditions;
- (b) amend the composition of copper quat preservatives to include both alkaline copper and micronized copper systems; and
- (c) add copper azole to Table H5.

This Standard does not specify the methods of preservative treatment to be adopted to achieve the specified penetrations and retentions. Where the user is uncertain of the appropriate preservative treatment, additional information may be obtained from state, territory or federation forestry authorities or traders' associations.

This Standard is part of a series that covers specifications for preservative treatment of timber products, as follows:

AS 1604	Specification for preservative treatment
AS 1604.1	Part 1: Sawn and round timber
AS/NZS 1604	Specification for preservative treatment
AS/NZS 1604.2	Part 2: Reconstituted wood-based products
AS/NZS 1604.3	Part 3: Plywood
AS/NZS 1604.4	Part 4: Laminated veneer lumber (LVL) (this Standard)
AS/NZS 1604.5	Part 5: Glued laminated timber products

Preservatives not covered in this edition, and which may have general application, should be brought to the attention of Standards Australia for consideration for inclusion in future editions.

WARNING: Important Safety Notice

Improper use of the preservative chemicals and treated products may be hazardous. All individuals involved in the production or testing of treated products should be familiar with the relevant material safety data sheets.

Consumer information sheets dealing with the appropriate use and handling of treated products should be provided as point-of-sale literature.

Treated timber should not be used for food preparation surfaces nor in storage units or containers where the foodstuffs will be in direct contact with the treated timber surface.

Statements expressed in mandatory terms in notes to tables are deemed to be requirements of this Standard.

The terms 'normative' and 'informative' have been used in this Standard to define the application of the appendix to which they apply. A 'normative' appendix is an integral part of a Standard, whereas an 'informative' appendix is only for information and guidance.

CONTENTS

	<i>Page</i>
FOREWORD.....	5
SECTION 1 SCOPE AND GENERAL	
1.1 SCOPE	6
1.2 APPLICATION	6
1.3 NORMATIVE REFERENCES	7
1.4 DEFINITIONS	7
1.5 TIMBER PRESERVATIVES	8
1.6 PRODUCT REQUIREMENTS	8
1.7 SELECTION OF HAZARD CLASS	9
1.8 PRESERVATIVE TREATMENT	9
1.9 USE IN NEW ZEALAND	10
SECTION 2 HAZARD CLASS H1	
2.1 GENERAL	11
2.2 PRESERVATIVE PENETRATION REQUIREMENT	11
2.3 PRESERVATIVE RETENTION REQUIREMENT	11
SECTION 3 HAZARD CLASS H2	
3.1 GENERAL	12
3.2 PRESERVATIVE PENETRATION REQUIREMENT	12
3.3 PRESERVATIVE RETENTION REQUIREMENT	13
SECTION 4 HAZARD CLASS H3	
4.1 GENERAL	14
4.2 PRESERVATIVE PENETRATION REQUIREMENT	14
4.3 PRESERVATIVE RETENTION REQUIREMENT	14
4.4 USE OF TBTN AND TBTO.....	14
SECTION 5 HAZARD CLASS H4	
5.1 GENERAL	16
5.2 PRESERVATIVE PENETRATION REQUIREMENT	16
5.3 PRESERVATIVE RETENTION REQUIREMENT	17
SECTION 6 HAZARD CLASS H5	
6.1 GENERAL	18
6.2 PRESERVATIVE PENETRATION REQUIREMENT	18
6.3 PRESERVATIVE RETENTION REQUIREMENT	18
SECTION 7 MARKING	
7.1 LEGIBLE MARKING.....	19
7.2 MARKING INFORMATION	19
7.3 LAYOUT OF BRANDS.....	19
7.4 ADVISORY LABEL—ENVELOPE PENETRATION	20
7.5 USE RESTRICTION.....	20
7.6 COMPLIANCE TESTING	20

APPENDICES

A GUIDE TO HAZARD CLASSIFICATIONS FOR VARIOUS END-USE APPLICATIONS 21

B METHOD OF SELECTION AND PREPARATION OF TEST SPECIMEN 22

BIBLIOGRAPHY 24

FOREWORD

The purpose of preservation is to extend the life of the laminated veneer lumber (LVL) by protecting it from decay or insect attack. This increases the range for the end application of the laminated veneer lumber (LVL) and renders it a more useful and reliable material for construction, building and engineering purposes.

The service life of the laminated veneer lumber (LVL) depends on a variety of factors. These include the natural durability of the timber species, the degree of preservative treatment, the range of hazards, the quality and type of glueline, and type of environment anticipated during the service life of the laminated veneer lumber (LVL). In addition, the severity of exposure can be reduced by alternative design. Regular inspection and maintenance procedures will assist in minimizing the effects of exposure.

In all conditions of use, the non-durable timber component of the laminated veneer lumber (LVL) can be made durable by correct preservative treatment. Service life may depend upon the laminated veneer lumber (LVL) having been ripped, cross-cut, shaped, bored, machined or having had any such operations or processes carried out after preservative treatment. Where subsequent machining is unavoidable and the treatment type is an envelope, supplementary protection should be applied to the cut surface; however, this protection cannot be expected to be as effective as the original recommended treatment.

STANDARDS AUSTRALIA/STANDARDS NEW ZEALAND

Australian/New Zealand Standard
Specification for preservative treatment

Part 4: Laminated veneer lumber (LVL)

SECTION 1 SCOPE AND GENERAL

1.1 SCOPE

This Standard sets out a specification for preservative treatment of laminated veneer lumber (LVL). It specifies the bond type, preservative penetration pattern, and the preservative retention requirements suitable for each hazard class (see Table 1).

This Standard does not cover grade or seasoning condition.

1.2 APPLICATION

This Standard, in conjunction with AS 1604.1 and the AS/NZS 1605 series, is intended for application throughout Australia and New Zealand.

NOTES:

- 1 This Standard does not apply to finger-jointed material. For finger-jointed material, the specifications in AS 1604.1 apply.
- 2 In Queensland the *Timber Utilisation and Marketing Act 1987* and in New South Wales the *Timber Marketing Act 1977* require approval of a preservative treatment and registration of a brand before timber, offered for sale in either of these states, can be described as preservative-treated. Detailed information about requirements of such legislation may be obtained from the state, territory or federation forestry authorities, or traders' associations.
- 3 Where products are to be treated to comply with the requirements of this Standard, timber treaters should select suitable timber material to ensure that the finished product can be penetrated to the depth required for each hazard class.
- 4 Where a timber species' treatment properties are not known, trial samples placed into a normal charge/process should give indications of the timber's treatability. These indications should serve as a guide for the treater.
- 5 The following references set down the treatment properties of some well known commercial timbers of the world:
 - (a) EN 350-2 (see Bibliography).
 - (b) Keating WG, Bolza E, *Characteristics and uses of timber*, Vol.1, S.E. Asia, Northern Australia and the Pacific, INKATA PRESS Melbourne 1982.
- 6 Additional guidance on the use/application of preservative-treated laminated veneer lumber is provided in the following FWPA publication:

Bolden S and Greaves H, *Guide to the specification, installation and use of preservative treated engineered wood products*, Project No. PR08.1062.