

Australian/New Zealand Standard™

**Specification for preservative treatment**

**Part 5: Glued laminated timber products**



Standards Australia



STANDARDS  
NEW ZEALAND  
Pūrongo Aotearoa

## **AS/NZS 1604.5:2002**

---

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee TM-006, Timber Preservation and Durability. It was approved on behalf of the Council of Standards Australia on 26 October 2001 and on behalf of the Council of Standards New Zealand on 28 November 2001. It was published on 4 January 2002.

---

The following interests are represented on Committee TM-006:

Australian Building Codes Board  
CSIRO Forestry and Forest Products  
Consumers Federation of Australia  
Housing Industry Association  
Institution of Engineers, Australia  
National Registration Authority for Agricultural and Veterinary Chemicals  
New Zealand Forest Research Institute  
New Zealand Timber Industry Federation  
New Zealand Preservation Council  
Plywood Association of Australia  
Queensland Forestry Research Institute  
State Forests of New South Wales  
Timber Preservers Association of Australia  
Timber Promotion Council  
Timber Research and Development Advisory Council of Queensland

---

### **Keeping Standards up-to-date**

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about joint Australian/New Zealand Standards can be found by visiting the Standards Australia web site at [www.standards.com.au](http://www.standards.com.au) or Standards New Zealand web site at [www.standards.co.nz](http://www.standards.co.nz) and looking up the relevant Standard in the on-line catalogue.

Alternatively, both organizations publish an annual printed Catalogue with full details of all current Standards. For more frequent listings or notification of revisions, amendments and withdrawals, Standards Australia and Standards New Zealand offer a number of update options. For information about these services, users should contact their respective national Standards organization.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Please address your comments to the Chief Executive of either Standards Australia International or Standards New Zealand at the address shown on the back cover.

Australian/New Zealand Standard™

**Specification for preservative treatment**

**Part 5: Glued laminated timber products**

First published as AS/NZS 1604.5:2002.

**COPYRIGHT**

© Standards Australia/Standards New Zealand

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Jointly published by Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001 and Standards New Zealand, Private Bag 2439, Wellington 6020

ISBN 0 7337 4184 5

## PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee TM/6, Timber Preservation and Durability.

The objective of this Standard is to specify requirements for preservative treatment of glued laminated timber products for protection against decay or insect attack.

This Standard does not specify the methods of preservative treatment that may be adopted to achieve the specified penetrations and retentions. Where the user is uncertain of the appropriate preservative treatment, additional information may be obtained from state, territory or federal forestry authorities or traders' associations.

This Standard is the third part in AS 1604, a series of Standards, which covers specification for preservative treatment of timber products, as follows:

AS 1604	Specification for preservative treatment
AS 1604.1	Part 1: Sawn and round timber
AS/NZS 1604.2	Part 2: Reconstituted wood-based products
AS/NZS 1604.3	Part 3: Plywood
AS/NZS 1604.4	Part 4: Laminated veneer lumber (LVL)
AS/NZS 1604.5	Part 5: Glued laminated timber products (this Standard)

Preservatives not covered in this edition, and which may have general application, should be brought to the attention of Standards Australia for consideration for inclusion in future editions.

### **Important Safety Notice**

**Improper use of the preservative chemicals and treated products may be hazardous. All individuals involved in the production or testing of treated products should be familiar with the relevant material safety data sheets.**

**Consumer information sheets dealing with the appropriate use and handling of treated products should be provided as the point of sale literature.**

For the purpose of user friendliness, the following colour page coding is used to differentiate between the four hazard classes:

- (i) *Orange*—Hazard class selection guide.
- (ii) *Yellow*—Hazard class 1.
- (iii) *Blue*—Hazard class 2.
- (iv) *Pink*—Hazard class 3.
- (v) *Green*—Hazard class 4.

Statements expressed in mandatory terms in notes to tables are deemed to be an integral part of this Standard.

The terms 'normative' and 'informative' have been used in this Standard to define the application of the appendix to which they apply. A 'normative' appendix is an integral part of a Standard, whereas an 'informative' appendix is only for information and guidance.

## CONTENTS

	<i>Page</i>
FOREWORD.....	4
SECTION 1 SCOPE AND GENERAL	
1.1 SCOPE.....	5
1.2 APPLICATION .....	5
1.3 REFERENCED DOCUMENTS.....	5
1.4 DEFINITIONS.....	6
1.5 TIMBER PRESERVATIVES .....	7
1.6 PRODUCT REQUIREMENTS.....	7
1.7 SELECTIONS OF HAZARD CLASS NUMBER.....	8
1.8 PRESERVATIVE TREATMENT.....	10
SECTION 2 HAZARD CLASS 1	
2.1 GENERAL.....	11
2.2 PRESERVATIVE PENETRATION REQUIREMENT.....	11
2.3 PRESERVATIVE RETENTION REQUIREMENT.....	11
SECTION 3 HAZARD CLASS 2	
3.1 GENERAL.....	13
3.2 PRESERVATIVE PENETRATION REQUIREMENT.....	13
3.3 PRESERVATIVE RETENTION REQUIREMENT.....	14
SECTION 4 HAZARD CLASS 3	
4.1 GENERAL.....	15
4.2 PRESERVATIVE PENETRATION REQUIREMENT.....	15
4.3 PRESERVATIVE RETENTION REQUIREMENT.....	16
SECTION 5 HAZARD CLASS 4	
5.1 GENERAL.....	17
5.2 PRESERVATIVE PENETRATION REQUIREMENT.....	17
5.3 PRESERVATIVE RETENTION REQUIREMENT.....	18
SECTION 6 MARKING	
6.1 LEGIBLE MARKING .....	19
6.2 MARKING INFORMATION .....	19
6.3 NUMERICAL LAYOUT OF BRANDS .....	19
6.4 COMPLIANCE TESTING .....	19
APPENDICES	
A GUIDE TO HAZARD CLASSIFICATIONS FOR VARIOUS END-USE APPLICATIONS .....	20
B METHOD OF SELECTION AND PREPARATION OF TEST SPECIMEN.....	21

## FOREWORD

The purpose of preservation is to extend the life of the glued laminated timber product by protecting it from decay or insect attack. This increases the range for the end application of the glued laminated timber products and renders it a more useful and reliable material for construction, building and engineering purposes.

The service life of the glued laminated timber product depends on a variety of factors. These include the natural durability of the timber species, the degree of preservative treatment, and the range of hazards and type of environment anticipated during the service life of the product. In addition, the severity of exposure can be reduced by alternative design. Regular inspection and maintenance procedures will assist in minimizing the effects of exposure.

In all conditions of use, the non-durable timber component of the glued laminated timber products can be made durable by correct preservative treatment. Service life may depend upon the glued laminated timber products having been ripped, cross-cut, shaped, bored, machined or having had any such operations or processes carried out prior to preservative treatment. Where subsequent machining is unavoidable, supplementary protection should be applied to the cut surface; however, this protection cannot be expected to be as effective as the original recommended treatment.

STANDARDS AUSTRALIA/STANDARDS NEW ZEALAND

**Australian/New Zealand Standard**  
**Specification for preservative treatment**

**Part 5: Glued laminated timber products**

S E C T I O N 1 S C O P E A N D G E N E R A L

**1.1 SCOPE**

This Standard sets out a specification for preservative treatment of glued laminated timber products.

This Standard specifies the preservative penetration pattern and the preservative retention requirements suitable for each hazard class (see Table 1). This Standard does not cover grade or seasoning condition.

**1.2 APPLICATION**

This Standard, in conjunction with AS 1604.1 and AS/NZS 1605, is intended for application throughout Australia and New Zealand.

NOTES:

- 1 This Standard does not apply to finger-jointed material, except where finger-jointed laminates are used to fabricate glued laminated timber products. In any other case, the specifications in AS 1604.1 apply.
- 2 In Queensland the Timber Utilisation and Marketing Act 1987 and in New South Wales the Timber Marketing Act 1977 require approval of a preservative treatment and registration of a brand before timber, offered for sale in either of these states, can be described as preservative-treated. Detailed information about requirements of such legislation may be obtained from the state, territory or federation forestry authorities or traders' associations.
- 3 Where products are to be treated to comply with the requirements of this Standard, timber treaters should select suitable timber material to ensure that the finished product can be penetrated to the depth required for each hazard class.
- 4 Where a timber species' treatment properties are not known, trial samples placed into a normal charge/process should give indications of the timber's treatability. These indications should serve as a guide for the treater.

In addition, the following references set down the treatment properties of some well known commercial timbers of the world:

- (a) BS EN 350-2 (see Clause 1.3).
- (b) Keating W.G., Bolza., *Characteristics and uses of timber*, Vol.1, S.E. Asia, Northern Australia and the Pacific, INKATA PRESS Melbourne 1982.

**1.3 REFERENCED DOCUMENTS**

AS

- 1604 Specification for preservative treatment  
 1604.1 Sawn and round timber

AS/NZS

- 1328 Glued laminated structural timber  
 1328.1 Part 1: Performance requirements and minimum production requirements