

Australian Standard™

**Digital television—Requirements for
receivers**

**Part 1: VHF/UHF DVB-T television
broadcasts**

This Australian Standard was prepared by Committee CT-002, Broadcasting and Related Services. It was approved on behalf of the Council of Standards Australia on 8 March 2005. This Standard was published on 3 May 2005.

The following are represented on Committee CT-002:

Australian Broadcasting Authority
Australian Broadcasting Corporation
Australian Caption Centre
Australian Chamber of Commerce and Industry
Australian Communications Authority
Australian Electrical and Electronic Manufacturers Association
Australian Greenhouse Office
Australian Information Industry Association
Australian Subscription Television and Radio Association
Broadcast Australia
Community Broadcasting Association of Australia
Consumer Electronics Suppliers Association, Australia
Consumers Telecommunications Network Inc, Australia
Department of Communications, Information Technology and the Arts, Australia
Department of Industry Science and Resources (Commonwealth), Australia
Electronic Services Industry Association Inc, Australia
Free Television Australia
Optus Communications, Australia
Special Broadcasting Service, Australia
Telstra Corporation, Australia

Additional Interests:

ADB
Austar Entertainment
BTC Australia P/L - Consultants
Foxtel
Intermedia
JJB Associates
Modern Antenna Systems
Motorola Semiconductor Products
NDS Asia Pacific
Network Ten Pty Limited
Nine Network Australia
Panasonic AV Networks Australia
Philips Consumer Electronics
Samsung Electronics Australia
Sanyo Australia Ltd
Seven Network (Operations)
Sharp Corporation of Australia
Sony (Australia)
UEC Technologies

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Web Shop at www.standards.com.au and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Global Standard*, has a full listing of revisions and amendments published each month.

Australian Standards™ and other products and services developed by Standards Australia are published and distributed under contract by SAI Global, which operates the Standards Web Shop.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.org.au, or write to the Chief Executive, Standards Australia, GPO Box 5420, Sydney, NSW 2001.

This Standard was issued in draft form for comment as DR 03657.

Australian Standard™

Digital television—Requirements for receivers

Part 1: VHF/UHF DVB-T television broadcasts

First published as AS 4933.1—2000.
Second edition 2005.

COPYRIGHT

© Standards Australia

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia GPO Box 5420, Sydney, NSW 2001, Australia
ISBN 0 7337 6676 5

PREFACE

This Standard was prepared by the Australian members of the Joint Standards Australia/Standards New Zealand Committee CT 002, Broadcasting and Related Services. After consultation with stakeholders in both countries, Standards Australia and Standards New Zealand decided to develop this Standard as an Australian, rather than Australian/New Zealand Standard.

The objective of this Standard is to provide television receiver manufacturers with the technical specifications and requirements of digital television receivers in order to achieve successful reception from free-to-air DTTB transmissions that comply with the Australian DTTB transmission Standard AS 4599.1-2005, *Digital television—Terrestrial broadcasting—Characteristics of digital terrestrial television transmissions*.

Interoperability issues for DVB-S, DVB-C and Datacasting are not addressed in this part of the Standard.

The terms ‘normative’ and ‘informative’ have been used in this Standard to define the application of the Appendix to which they apply.

A ‘normative’ Appendix is an integral part of a Standard, whereas an ‘informative’ Appendix is only for information and guidance. Informative sections are included also in the main body of this standard.

CONTENTS

	<i>Page</i>
SECTION 1 SCOPE AND APPLICATION	11
1.1 Scope	11
1.2 Application	11
SECTION 2 REFERENCES.....	13
SECTION 3 ESSENTIAL AND OPTIONAL REQUIREMENTS.....	17
3.1 RECEIVER REQUIREMENTS.....	17
1 Basic features	18
1.1 Minimum requirements for Terrestrial Reception—Conformance.....	18
1.2 Receive capability for analog PAL transmissions.....	18
1.3 Australian regulatory and safety requirements.....	19
1.3.1 Electrical safety	19
1.3.2 EMC	19
1.4 Receiver display resolution specification.....	19
2 Power on operations	19
2.1 First time operation initialisation	19
2.2 Subsequent switch-on.....	19
2.3 Identifying new services in current or new location	19
2.4 Standby Power	20
3 User operation	20
3.1 Operating system.....	20
3.2 Hardware reset	20
3.3 Initial set-up	20
3.3.1 Set-up menu and non-volatile information storage	20
3.3.2 Initial tuning scan	20
3.4 Assigning numbering to services and navigation.....	20
3.4.1 Menu list of services.....	20
3.4.2 Logical Channel Numbering (LCN)	21
3.4.3 Services without LCNs	21
3.4.4 Duplicated LCNs and Service (Channel) list editing.....	22
3.4.5 Linkage descriptor	22
3.4.6 Dynamic response to PAT, PMT, NIT and SDT updates	22
3.5 Display Electronic Services Guide (OSD) and navigation	23
3.6 Signal quality monitor	23
3.7 Selection of radio services	23
3.8 Service unavailable— On-screen advice:	23
3.9 Remote control.....	24
4 RF characteristics, COFDM demodulation and channel decoding	24
4.1 RF characteristics.....	24
4.1.1 Transmission channel bandwidth.....	24
4.1.2 Notional receiver noise figure	24
4.1.3 RF connector	24
4.1.4 Digital terrestrial receiver tuner’s frequency range.....	24
4.1.5 Channel offsets	24

4.1.6	COFDM Intermediate Frequency (IF) and spectrum polarity	24
4.2	Operation in Single Frequency Network (SFN) environments	25
4.3	COFDM modes	25
4.3.1	COFDM mode change acquisition time	25
4.3.2	Reception of Hierarchical Modulation (HM) transmissions	26
4.4	Interference immunity	26
4.4.1	Impulse noise rejection	26
5	Multiplex and transport stream	27
5.1	PID filters	27
6	Service information (SI) processing	27
6.1	Interpretation of SI variations for Australia	27
6.2	Interpretation of MPEG-2, DVB mandatory and DVB optional tables	27
6.3	Interpretation of other descriptors	27
6.4	Interpretation of time and date and time offset tables	28
6.5	Content descriptors	29
6.6	EITs and present/following (Now/Next)	29
6.7	EIT (optional schedules)	29
6.8	Radio services	29
7	Video decode and display	29
7.1	MPEG video decoding	29
7.1.1	Decode 'SD' MP@ML video formats	29
7.1.2	Decode 'HD' MP@HL video formats	30
7.2	Reproduction of progressive scan video formats	30
7.3	Video scaling for display and output, up and down	30
7.4	Display of transmitted video stills	30
7.5	Multiview display	30
7.6	Mosaic display	31
7.7	SD decoder response to a HD Service	31
7.8	Aspect ratio	31
7.8.1	Picture 'shape' setup for a receiver and/or display	31
7.8.2	Identification of 4:3 and 16:9 pictures	31
7.8.3	Changing between 16:9 and 4:3 pictures on displays	32
7.8.4	Display of broadcast 14:9 pictures	32
7.8.5	On 4:3 displays, show full height 4:3 pictures cut from a 16:9 video program stream by use of MPEG-2 pan and scan vectors	32
7.8.6	Frame accuracy of use of scan offset when cutting 4:3 picture from transmitted 16:9 picture	32
7.9	Picture colorimetry	32
7.9.1	Chroma_format	32
7.9.2	Colorimetry	33
8	Audio—Decode and reproduction	33
8.1	Audio outputs	33
8.2	MPEG audio	33
8.2.1	Decode audio stream using MPEG-1 Layer II	33
8.2.2	Decode all MPEG-1 Layer II sampling rates	33
8.2.3	Decode all MPEG-1 Layer II formats	33
8.2.4	Ability to decode MPEG-2 audio formats	33
8.3	AC-3—Decoding and output	33

8.3.1	Ability to decode other services in AC-3	33
8.3.2	AC-3 karaoke mode	34
8.3.3	Dual AC-3 decoders	34
8.3.4	Decodable AC-3 sampling frequency range.....	34
8.3.5	Decodable AC-3 bitrate range	34
8.3.6	Recognition of AC-3 in a DVB MPEG transport stream.....	34
8.4	Audio identification and control	34
8.4.1	Identifying which audio stream present	34
8.4.2	User access to other audio streams (including other language).....	34
8.4.3	Receiver auto-switch when program audio changes from MPEG-1 Layer II to AC-3 or vice versa	34
8.4.4	Ability to present stereo audio encoded with surround information suitable for external Dolby Pro Logic™ decoding.....	35
8.4.5	System reference level.....	35
8.4.6	Receiver average output level.....	35
8.4.7	Modulated RF output deviation	36
8.4.8	Operating mode and audio dynamic range control.....	36
8.4.9	Maximum picture-sound timing misalignment (Lip Sync).....	36
9	Operating software and middleware API	37
9.1	API	37
9.2	Middleware API.....	37
9.2.1	DVB MHP.....	37
10	Interactivity and on-screen display	37
10.1	Remote control.....	37
10.1.1	Conformance of remote control design - (where supplied)	37
10.1.2	Capability to operate interactively	37
10.2	On-Screen-Displays (OSD).....	37
10.2.1	Video planes.....	37
10.3	Teletext closed captions	38
10.3.1	Access to closed captions in a teletext format for hearing impaired.....	38
10.3.2	Decoding of teletext information	38
10.3.3	Teletext re-insertion on VBI of analog SD or ED 625 line output- (applies to set-top-boxes).....	39
10.3.4	Use assigned colour and position where displayed on 4:3 and 16:9 pictures.....	39
10.3.5	Time accuracy of closed captions (CC)	39
10.4	Bit-mapped subtitles.....	39
10.4.1	Decoding of bit-mapped information.....	39
10.4.2	Features of display minimum number of colours.....	39
10.4.3	Closed caption display.....	39
10.4.4	Time accuracy of display of closed captions.....	39
10.5	Electronic program guide (EPG).....	39
10.5.1	EPG general.....	39
10.5.2	Use of EPG flush.....	39
10.5.3	Display of broadcaster supplied EPGs.....	39
10.5.4	Use of now/next (present/following)	39
10.5.5	Use of extended program information	39
10.5.6	Running status table	40

17.3	Via DTTB transmission	45
17.4	Other methods	45
18	Memory and processor requirements	45
18.1	Ability to expand.....	45
18.2	Minimum memory requirement	45
18.2.1	Video memory	45
18.2.2	Non-volatile and volatile for operation and applications.....	45
18.2.3	Other storage	45
18.3	Processor	45

APPENDICES

A	DTTB RECEIVER RF SPECIFICATION	46
B	RANGE OF RECEIVERS AND RECEIVER BLOCK DIAGRAM	51
C	RECEPTION QUALITY OSD METER	53
D	BROADCAST AND NON-BROADCAST BAND 7 MHz CHANNEL PLAN	54
E	AUSTRALIAN PARENTAL GUIDANCE CODES.....	57
F	TELETEXT FORMAT FOR CLOSED CAPTION TRANSMISSIONS	59
G	50 Hz HD AND SD PICTURE TIMINGS PARTICULARLY RELATED TO SCAN RATES FOR CRT BASED DISPLAYS	61
H	RECEIVER FUNCTIONAL DESIGN ISSUES OF SPECIAL NOTE FOR AUSTRALIAN DTTB.....	75
I	ABBREVIATIONS AND GLOSSARY	82
	INDEX.....	94

FOREWORD

Digital terrestrial television broadcasting (DTTB) in Australia officially commenced on 1 January 2001. The transmissions are based on the DVB-T¹ system, however, it should be noted that the international DVB Standards and related ETSI, IEC/ISO and ITU-R documents provide a range of operational choices.

Many other implementations of digital television systems around the world operate on pay satellite and cable systems where compatibility between transmission and reception equipment of each system is generally under the control of a single system operator. These are known as ‘vertical’ markets.

In contrast, no single operator is in control of the Australian implementation of the digital terrestrial television broadcasting system. There are multiple free-to-air services and multiple receiver/decoder manufacturers, as well as subscription television services and datacasting services delivered in the digital television broadcasting environment. Domestic digital television receivers are expected to be available from a wide range of manufacturers through many retail suppliers; this is known as a ‘retail’ or ‘horizontal’ market.

Consumers expect a choice of receiving equipment from many manufacturers, ranging from fully integrated receivers with inbuilt displays to modular set-top-box receivers intended for connection to a separate display and sound reproduction system, (see Appendix B). This equipment will be expected to satisfactorily receive digital terrestrial television broadcasts from a choice of multiple broadcasters (each probably using a different brand of encoding and transmission equipment).

A separate Australian Standard, AS 4599.1, details information specific to the transmission aspects of the Australian adaptation of the relevant ETSI DVB-T Standards. For an overview on DVB documents the reader is referred to the technical report from DVB: TR 101 200; ‘Digital Video Broadcasting (DVB); A guideline for the use of DVB specifications and Standards’.

This Standard aims to provide the necessary information so that any digital terrestrial television receiving equipment made for the Australian system will operate satisfactorily on Australian digital terrestrial television broadcast transmissions.

While some receiver requirements are nominated to be essential, in general, it will be a marketing choice by the manufacturer as to how the various receiver models operate with a variety of conditions.

Conformance testing related to this standard is the responsibility of the manufacturer.

See below for a summary of important DTTB receiver requirements to operate in the Australian environment.

Manufacturers should note that DTTB is a rapidly evolving technological environment and, consequently, this Standard may require revisions and additions. Readers are urged to contact any Standards Australia office or broadcasters regarding such changes.

¹ DVB-T: Digital Video Broadcasting (project) – Terrestrial. The DVB Project Office is co-located at the headquarters of the European Broadcasting Union in Geneva, Switzerland. Their web site is <http://www.dvb.org/>

Summary of minimum DTTB receiver requirements and recommendations for Australia

The minimum DTTB receiver requirements and recommendations for Australia are as follows:

- (a) The receiver shall operate in a 7 MHz VHF/UHF channel allocation with possibly higher powered analog PAL signals present in adjacent channels—digital channel allocations range from 174 MHz to 820 MHz, some with 125 kHz offsets.
- (b) All COFDM modes, except hierarchical modulation which is optional shall be receivable by both SD-only receivers and receivers that also have HD capabilities. (See Items 4.1 and 4.3 of Section 3, Table 1).
- (c) Receivers shall be able to demodulate and decode the Transmission Parameter Signalling (TPS) data to determine or confirm transmission parameters when an RF transmission is first accessed or when a service on a different RF transmission is selected. As COFDM transmission parameters may change from time-to-time, TPS data should also be accessed if a signal is lost.
- (d) Single Frequency Network (SFNs) are in use and all receivers are expected to operate in environments, that include pre and post echoes.
- (e) Receivers should use the broadcast Logical Channel Numbering of services to simplify channel selection. (This is an Australian adaptation from the UK DTG and EACEM definition of Logical Channel Numbering and is found in the NIT 2nd loop with tag of 0x83 – See Appendix H, Paragraph H1).
- (f) Broadcasters may change COFDM modes and available services in the transport stream from time-to-time, requiring receivers to refresh the ‘PAT’, ‘PMT’, ‘NIT’ and ‘SDT’ data on a regular (typically 10 sec), basis. Receivers shall check in the PMT, the PID values for video, audio and other components of a service when selected, as these may change from time-to-time. Receivers shall not assume any sequenced or ordered numbering of the PID values of various components of a service.
- (g) All receivers shall be capable of decoding 50 Hz based Standard Definition (SD) MPEG-2 picture formats with displayable closed captions and MPEG-1 Layer II sound, and optionally, Dolby Digital[®] (AC-3) sound. Receivers may also decode a number of 50 Hz based High Definition (HD) picture formats (see preferred interface and scanning details in Appendix G), with additional decoding for up to 5.1 channel Dolby Digital[®] (AC-3) sound (See Items 7 and 8 of Section 3, Table 1).
- (h) Standard Definition receivers (SD-only), if switched to a HD (MP@HL) service, should not attempt to decode the service and either present a message to the user or a blank screen (See Appendix H Paragraph H6).
- (i) Receivers should use Australian specific look-up tables for on-screen display for time-zone region setting using the transmitted Time Offset Table (TOT) and Parental-Guidance codes and Program Content (Genre) codes using the transmitted Event Information Table (EIT).
- (j) If a receiver includes an optional Dolby Digital[®] (AC-3) sound decoder, then the receiver shall operate to a viewer’s preset preference or indicate and give a choice to the viewer if a service has other audio channels (sound tracks), which the receiver is able to decode.
- (k) Some transmissions will include radio (audio-only) services in MPEG-1 Layer II format, which receivers shall be able to decode.

- (l) Receivers shall be able to provide decoding of Closed Captions broadcast in Teletext. Bit-mapped format decoding may also be provided. In the case of set-top-boxes, the teletext should be added to the VBI on the analog video outputs on the same VBI lines as indicated in the transmission (see ETSI EN 300 472 Standard).
- (m) Optionally provide DSM-CC support to enable capability for data broadcasting and system software upgrade (SSU) by over-the-air download, conforming to DVB/ETSI standards.
- (n) Optionally provide interactivity conforming to the DVB MHP standards.

Manufacturers of DTTB receivers incorporating interactive capabilities will need to confirm aspects of the Australian Interactive Digital Television 'Feature Set' which is currently under development.

STANDARDS AUSTRALIA

Australian Standard

Digital television—Requirements for receivers

Part 1: VHF/UHF DVB-T television broadcasts

SECTION 1 SCOPE AND APPLICATION

1.1 SCOPE

This Standard defines both essential and optional requirements for DVB-T compliant digital broadcast television receivers for Australia with the capability of receiving Standard Definition television and optionally High Definition television via terrestrial broadcasting services. Other optional features include interactivity, datacasting services, surround sound, multi-lingual and appropriate interfaces for ancillary equipment. Specifications for subscription/pay services should be obtained from the operators of those services although specifications for the possible addition to a receiver of a Conditional Access system or other features are included.

NOTES:

- 1 See Appendix G for details on 50 Hz HD and SD scanning and interface parameters.
- 2 See Appendix H for receiver functional design issues that have attracted attention since the commencement of transmissions.
- 3 See Appendix I for abbreviations and a glossary of terms used in this Standard.

1.2 APPLICATION

Australian digital terrestrial transmissions will include SD pictures at 576i and HDTV pictures at 576p, 720p and 1080i. The terrestrial transmissions' sound format for SD services will be MPEG-1 Layer II, or both MPEG-1 Layer II and AC-3, whereas for HD, the sound format will be MPEG-1 Layer II or AC-3, or both.

A range of receiving equipment may be available either in modular or fully integrated forms that extend from low-cost limited-facility with a standard definition video and monophonic sound output to premium full-facility features providing high definition display with full surround sound. Modular equipment may be set-top box style integrated-receiver-decoders or plug-in PC card tuner-decoders.

NOTE: Appendix B gives an example of the components of the architecture of a typical digital terrestrial television receiver and set-top-box.

While this Standard seeks to identify minimum essential requirements for reception, demodulation and decoding of television broadcasts complying with the Australian implementation of DVB-T, additional information and recommendations are provided to clarify preferred implementation if a feature is included in the receiver's design.

As a minimum requirement, equipment must be capable of simultaneously decoding from the transport stream, a video stream, an associated audio stream and associated teletext closed captions. Also optionally, bit-mapped subtitle decoding may be provided. The decoded information shall be presented in a time-synchronized manner suitable for a display device and sound reproduction system.