

Australian/New Zealand Standard™

Specification for preservative treatment

Part 3: Plywood



AS/NZS 1604.3:2004

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee TM-006, Timber Preservation and Durability. It was approved on behalf of the Council of Standards Australia on 13 September 2004 and on behalf of the Council of Standards New Zealand on 24 September 2004. This Standard was published on 15 October 2004.

The following are represented on Committee TM-006:

Australian Pesticides and Veterinary Medicines Authority
CSIRO Forestry and Forest Products
Department of Primary Industries and Fisheries, Queensland
Engineers Australia
Forests of New South Wales
Housing Industry Association, Australia
LOSP Treated Timber Association
New Zealand Forest Research Institute
New Zealand Timber Industry Federation
New Zealand Timber Preservation Council
Plywood Association of Australasia
Timber Preservers Association of Australasia
Timber Promotion Council
Timber Queensland

Additional Interests:

Dr Harry Greaves

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about joint Australian/New Zealand Standards can be found by visiting the Standards Web Shop at www.standards.com.au or Standards New Zealand web site at www.standards.co.nz and looking up the relevant Standard in the on-line catalogue.

Alternatively, both organizations publish an annual printed Catalogue with full details of all current Standards. For more frequent listings or notification of revisions, amendments and withdrawals, Standards Australia and Standards New Zealand offer a number of update options. For information about these services, users should contact their respective national Standards organization.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Please address your comments to the Chief Executive of either Standards Australia or Standards New Zealand at the address shown on the back cover.

This Standard was issued in draft form for comment as DR 03438.

Australian/New Zealand Standard™

Specification for preservative treatment

Part 3: Plywood

Originated as AS/NZS 1604.3:2002.
Second edition 2004.
Reissued incorporating Amendment No. 1 (July 2006).
Reissued incorporating Amendment No. 2 (March 2008).

COPYRIGHT

© Standards Australia/Standards New Zealand

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Jointly published by Standards Australia, GPO Box 476, Sydney, NSW 2001 and Standards New Zealand, Private Bag 2439, Wellington 6020

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee TM-006, Timber Preservation and Durability, to supersede AS/NZS 1604.3:2002.

This Standard incorporates Amendments No. 1 (July 2006) and No. 2 (March 2008). The changes required by the Amendment are indicated in the text by a marginal bar and amendment number against the clause, note, table, figure, or part thereof affected.

The objective of this Standard is to specify requirements for preservative treatment of plywood products for protection against decay or insect attack.

The objectives of this revision are to—

- (a) include requirements for seasoned softwood framing to be used south of the Tropic of Capricorn in hazard class H2 exposure conditions (in Section 3); and
- (b) amend the requirements for tributyltin-naphthenate-based preservatives used in structural products in hazard class H3 exposure conditions.

This Standard does not specify the methods of preservative treatment to be adopted to achieve the specified penetrations and retentions. Where the user is uncertain of the appropriate preservative treatment, additional information may be obtained from state, territory or federation forestry authorities or traders' associations.

This Standard is the third part in the AS/NZS 1604 series of Standards, which covers specification for preservative treatment of timber products, as follows:

AS 1604	Specification for preservative treatment
AS 1604.1	Part 1: Sawn and round timber
AS/NZS 1604.2	Part 2: Reconstituted wood-based products
AS/NZS 1604.3	Part 3: Plywood (this Standard)
AS/NZS 1604.4	Part 4: Laminated veneer lumber (LVL)
AS/NZS 1604.5	Part 5: Glued laminated timber products

Preservatives not covered in this edition, and which may have general application, should be brought to the attention of Standards Australia for consideration for inclusion in future editions.

WARNING: Important Safety Notice

Improper use of the preservative chemicals and treated products may be hazardous. All individuals involved in the production or testing of treated products should be familiar with the relevant material safety data sheets.

Consumer information sheets dealing with the appropriate use and handling of treated products should be provided as the point of sale literature.

CCA-treated timber should not be used for food preparation surfaces nor in storage units or containers where the foodstuffs will be in direct contact with the treated timber surface.

For the purpose of user friendliness, the following colour page coding is used to differentiate between the five hazard classes:

- (i) *Orange*—Hazard class selection guide.
- (ii) *Yellow*—Hazard class H1.
- (iii) *Blue*—Hazard class H2.
- (iv) *Pink*—Hazard class H3.
- (v) *Green*—Hazard class H4.

(vi) *Cream*—Hazard class H5.

(vii) *Grey*—Hazard class H6.

Statements expressed in mandatory terms in notes to tables are deemed to be requirements of this Standard.

The terms ‘normative’ and ‘informative’ have been used in this Standard to define the application of the appendix to which they apply. A ‘normative’ appendix is an integral part of a Standard, whereas an ‘informative’ appendix is only for information and guidance.

CONTENTS

	<i>Page</i>
FOREWORD.....	6
SECTION 1 SCOPE AND GENERAL	
1.1 SCOPE	7
1.2 APPLICATION	7
1.3 REFERENCED DOCUMENTS	7
1.4 DEFINITIONS	8
1.5 TIMBER PRESERVATIVES	9
1.6 PRODUCT REQUIREMENTS	9
1.7 SELECTION OF HAZARD CLASS	10
1.8 PRESERVATIVE TREATMENT	11
1.9 USE IN NEW ZEALAND	12
SECTION 2 HAZARD CLASS H1	
2.1 GENERAL	13
2.2 PRESERVATIVE PENETRATION REQUIREMENT	13
2.3 PRESERVATIVE RETENTION REQUIREMENT	13
SECTION 3 HAZARD CLASS H2	
3.1 GENERAL	15
3.2 PRESERVATIVE PENETRATION REQUIREMENT	15
3.3 PRESERVATIVE RETENTION REQUIREMENT	16
SECTION 4 HAZARD CLASS H3	
4.1 GENERAL	17
4.2 PRESERVATIVE PENETRATION REQUIREMENT	17
4.3 PRESERVATIVE RETENTION REQUIREMENT	17
4.4 USE OF TBTN AND TBTO.....	17
SECTION 5 HAZARD CLASS H4	
5.1 GENERAL	19
5.2 PRESERVATIVE PENETRATION REQUIREMENT	19
5.3 PRESERVATIVE RETENTION REQUIREMENT	20
SECTION 6 HAZARD CLASS H5	
6.1 GENERAL	21
6.2 PRESERVATIVE PENETRATION REQUIREMENT	21
6.3 PRESERVATIVE RETENTION REQUIREMENT	22
SECTION 7 HAZARD CLASS H6	
7.1 GENERAL	23
7.2 PRESERVATIVE PENETRATION REQUIREMENT	23
7.3 PRESERVATIVE RETENTION REQUIREMENT	23
SECTION 8 MARKING	
8.1 LEGIBLE MARKING.....	25
8.2 MARKING INFORMATION	25
8.3 LAYOUT OF BRANDS.....	26
8.4 ADVISORY LABEL—ENVELOPE PENETRATION	26
8.5 USE RESTRICTION.....	27
8.6 COMPLIANCE TESTING	27

Page

APPENDICES

A	GUIDE TO HAZARD CLASSIFICATIONS FOR VARIOUS END-USE APPLICATIONS	28
B	METHOD OF SELECTION AND PREPARATION OF TEST SPECIMEN	29

FOREWORD

The purpose of preservation is to extend the life of the plywood product by protecting it from decay, insect or marine borer attack. This increases the range for the end application of the plywood product and renders it a more useful and reliable material for construction, building and engineering purposes.

The service life of the plywood product depends on a variety of factors. These include the natural durability of the timber species, the degree of preservative treatment, the range of hazards, the quality and type of glueline, and the type of environment anticipated during the service life of the product. In addition, the severity of exposure can be reduced by alternative design. Regular inspection and maintenance procedures will assist in minimizing the effects of exposure.

In all conditions of use, the non-durable timber component of the plywood products can be made durable by correct preservative treatment. Service life may depend upon the plywood products having been ripped, cross-cut, shaped, bored, machined or having had any such operations or processes carried out prior to preservative treatment. Where subsequent machining is unavoidable and the treatment type is an envelope, supplementary protection should be applied to the cut surface; however, this protection cannot be expected to be as effective as the original recommended treatment.

STANDARDS AUSTRALIA/STANDARDS NEW ZEALAND

Australian/New Zealand Standard
Specification for preservative treatment

Part 3: Plywood

SECTION 1 SCOPE AND GENERAL

1.1 SCOPE

This Standard sets out a specification for preservative treatment of plywood products where the maximum thickness of any veneer does not exceed 5.0 mm. It specifies the bond type, preservative penetration pattern, and the preservative retention requirements suitable for each hazard class (see Table 1).

This Standard does not cover grade or seasoning condition.

1.2 APPLICATION

This Standard, in conjunction with AS 1604.1 and the AS/NZS 1605 series, is intended for application throughout Australia and New Zealand.

NOTES:

- 1 This Standard does not apply to finger-jointed material. For finger-jointed material, the specifications in AS 1604.1 apply.
- 2 In Queensland the Timber Utilisation and Marketing Act 1987 and in New South Wales the Timber Marketing Act 1977 require approval of a preservative treatment and registration of a brand before timber, offered for sale in either of these states, can be described as preservative-treated. Detailed information about requirements of such legislation may be obtained from the state, territory or federal forestry authorities, or trades' associations.
- 3 Where products are to be treated to comply with the requirements of this Standard, timber treaters should select suitable timber material to ensure that the finished product can be penetrated to the depth required for each hazard class.
- 4 Where a timber species' treatment properties are not known, trial samples placed into a normal charge/process should give indications of the timber's treatability. These indications should serve as a guide for the treater.
- 5 The following references set down the treatment properties of some well known commercial timbers of the world:
 - (a) BS EN 350-2 (see Clause 1.3).
 - (b) Keating W.G., Bolza., *Characteristics and uses of timber*, Vol.1, S.E. Asia, Northern Australia and the Pacific, INKATA PRESS Melbourne 1982.

1.3 REFERENCED DOCUMENTS

AS

1604	Specification for preservative treatment
1604.1	Part 1: Sawn and round timber
2754	Adhesives for timber and timber products
2754.1	Part 1: Adhesives for plywood manufacture
5604	Timber—Natural durability ratings