

**CGA G-4.8—2020**

**SAFE USE OF  
ALUMINUM-STRUCTURED  
PACKING FOR  
OXYGEN DISTILLATION**

**FIFTH EDITION**

**CGA**

**Compressed Gas Association**

*The Standard For Safety Since 1913*

## PREFACE:

As part of a program of harmonization of industry standards, the Compressed Gas Association (CGA) has published CGA G-4.8, *Safe Use of Aluminum-Structured Packing for Oxygen Distillation*, jointly produced by members of the International Harmonization Council.

This publication is intended as an international harmonized standard for the worldwide use and application of all members of the Asia Industrial Gases Association (AIGA), Compressed Gas Association (CGA), European Industrial Gases Association (EIGA), and Japan Industrial and Medical Gases Association (JIMGA). Each association's technical content is identical, except for regional regulatory requirements and minor changes in formatting and spelling.

## PLEASE NOTE:

The information contained in this document was obtained from sources believed to be reliable and is based on technical information and experience currently available from members of the Compressed Gas Association, Inc. and others. However, the Association or its members, jointly or severally, make no guarantee of the results and assume no liability or responsibility in connection with the information or suggestions herein contained. Moreover, it should not be assumed that every acceptable commodity grade, test or safety procedure or method, precaution, equipment or device is contained within, or that abnormal or unusual circumstances may not warrant or suggest further requirements or additional procedure.

This document is subject to periodic review, and users are cautioned to obtain the latest edition. The Association invites comments and suggestions for consideration. In connection with such review, any such comments or suggestions will be fully reviewed by the Association after giving the party, upon request, a reasonable opportunity to be heard. Proposed changes may be submitted via the Internet at our web site, [www.cganet.com](http://www.cganet.com).

This document should not be confused with federal, state, provincial, or municipal specifications or regulations; insurance requirements; or national safety codes. While the Association recommends reference to or use of this document by government agencies and others, this document is purely voluntary and not binding unless adopted by reference in regulations.

A listing of all publications, audiovisual programs, safety and technical bulletins, and safety posters is available via the Internet at our website at [www.cganet.com](http://www.cganet.com). For more information contact CGA at Phone: 703-788-2700, ext. 799. E-mail: [customerservice@cganet.com](mailto:customerservice@cganet.com).

Work Item 17-053  
Atmospheric Gases and Equipment Committee

NOTE—Technical changes from the previous edition are underlined.

FIFTH EDITION: 2020  
FOURTH EDITION: 2012  
THIRD EDITION: 2005  
SECOND EDITION: 2000

© 2020 The Compressed Gas Association, Inc. All rights reserved.

All materials contained in this work are protected by United States and international copyright laws. No part of this work may be reproduced or transmitted in any form or by any means, electronic or mechanical including photocopying, recording, or any information storage and retrieval system without permission in writing from The Compressed Gas Association, Inc. All requests for permission to reproduce material from this work should be directed to The Compressed Gas Association, Inc., 14501 George Carter Way, Suite 103, Chantilly VA 20151. You may not alter or remove any trademark, copyright or other notice from this work.

<b>Contents</b>	<b>Page</b>
1 Introduction.....	1
2 Scope .....	1
3 Definitions.....	1
4 Summary .....	1
5 Literature survey.....	2
6 Industry survey on incidents of aluminum/oxygen combustion .....	3
6.1 General.....	3
6.2 Survey scope.....	3
6.3 Survey results.....	4
6.4 Interpretation of survey results .....	4
6.5 Conclusions from survey .....	5
7 Ignition mechanisms.....	6
7.1 General.....	6
7.2 Conditions for ignition of aluminum .....	7
7.3 Sources of ignition energy .....	7
7.4 Direct ignition.....	7
7.5 Indirect ignition (promoted ignition) .....	7
7.6 Ignition by adjacent equipment.....	8
8 Ignition experiments .....	9
8.1 Ignition promoters for use in experimentation .....	9
8.2 Lubricating oil .....	9
8.3 Accumulated hydrocarbons .....	9
8.4 Mechanical impact.....	9
9 Experimental work on aluminum/oxygen combustion .....	9
9.1 Reports of experimentation .....	9
9.2 Propagation investigations on small samples.....	9
9.3 Propagation investigations on large samples.....	10
9.4 Molten aluminum in liquid oxygen .....	10
9.5 Conclusions from experimental work.....	10
10 Cleanliness .....	11
10.1 General.....	11
10.2 Required cleanliness level for residual lubricating oil .....	11
10.3 Protection of cleaned packing .....	11
10.4 Quality control.....	11
11 Design and operational considerations .....	11
12 References .....	12
 <b>Table</b>	
Table 1—Results of industry survey of aluminum/oxygen combustion incidents.....	4

This page is intentionally blank.

## 1 Introduction

Many air separation plants use aluminum sieve trays in their distillation columns. Most plants built after 1990 have used structured packing in place of trays. The low pressure drop and good mass transfer effectiveness of packing make it attractive for some air separation applications, particularly for columns operating at near-atmospheric pressure.

## 2 Scope

This publication addresses the use of aluminum-structured packing in oxygen distillation. Other materials that can be used in this service such as brass, copper, or stainless steel are not addressed.

A summary of current knowledge and industrial practices used in the safe application of aluminum-structured packing in columns for the distillation of oxygen is included.

This publication is not intended to be a mandatory standard. It is based upon the combined experimental work, operating experience, and design practices of major producers and operators of air separation plants.

## 3 Definitions

For the purpose of this publication, the following definitions apply.

### 3.1 Publication terminology

#### 3.1.1 Shall

Indicates that the procedure is mandatory. It is used wherever the criterion for conformance to specific recommendations allows no deviation.

#### 3.1.2 Should

Indicates that a procedure is recommended.

#### 3.1.3 May

Indicates that the procedure is optional.

#### 3.1.4 Will

Is used only to indicate the future, not a degree of requirement.

#### 3.1.5 Can

Indicates a possibility or ability.

### 3.2 Technical definitions

#### 3.2.1 Structured packing

Engineered structure consisting of numerous layers of thin, vertically oriented, corrugated metal sheets to facilitate intimate contact between liquid and vapor for mass transfer [1].<sup>1</sup>

#### 3.2.2 Violent energy release (VER)

Experimental result in which the following indications were observed during the combustion of aluminum in oxygen: a loud noise, white light, and physical destruction or substantial deformation of the specimen and/or the test vessel.

## 4 Summary

Aluminum components have been used extensively in oxygen service since the late 1950s. This has included piping, heat exchangers, vaporizers, pressure vessels, distillation trays, and packing. Overall, the safety record of aluminum in oxygen service has been very good.

---

<sup>1</sup> References are shown by bracketed numbers and are listed in order of appearance in the reference section.