



Illuminating
ENGINEERING SOCIETY

APPROVED METHOD:
**PHOTOMETRIC TESTING OF SKYLIGHTS AND
TUBULAR DAYLIGHTING DEVICES UNDER
HEMISPHERICAL SKY CONDITIONS**
AN AMERICAN NATIONAL STANDARD



ANSI/IES LM-81-20

**APPROVED METHOD:
PHOTOMETRIC TESTING OF SKYLIGHTS
AND TUBULAR DAYLIGHTING DEVICES
UNDER HEMISPHERICAL SKY CONDITIONS
AN AMERICAN NATIONAL STANDARD**

Publication of this Committee
report has been approved by IES.
Suggestions for revisions
should be directed to IES.

**Prepared by:
IES Testing Procedures Committee**



Copyright 2020 by the Illuminating Engineering Society.

Approved by the IES Standards Committee November 22, 2019 as a Transaction of the Illuminating Engineering Society.

Approved February 7, 2020 as an American National Standard

All rights reserved. No part of this publication may be reproduced in any form, in any electronic retrieval system or otherwise, without prior written permission of the IES.

Published by the Illuminating Engineering Society, 120 Wall Street, New York, New York 10005.

IES Standards are developed through committee consensus and produced by the IES Office in New York. Careful attention is given to style and accuracy. If any errors are noted in this document, they should be forwarded to Brian Liebel, Director Standards, at standards@ies.org or the above address for verification and correction. The IES welcomes and urges feedback and comments.

Printed in the United States of America.

ISBN# 978-0-87995-239-6

DISCLAIMER

IES publications are developed through the consensus standards development process approved by the American National Standards Institute. This process brings together volunteers representing varied viewpoints and interests to achieve consensus on lighting recommendations. While the IES administers the process and establishes policies and procedures to promote fairness in the development of consensus, it makes no guaranty or warranty as to the accuracy or completeness of any information published herein.

The IES disclaims liability for any injury to persons or property or other damages of any nature whatsoever, whether special, indirect, consequential or compensatory, directly or indirectly resulting from the publication, use of, or reliance on this document.

In issuing and making this document available, the IES is not undertaking to render professional or other services for or on behalf of any person or entity. Nor is the IES undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances.

The IES has no power, nor does it undertake, to police or enforce compliance with the contents of this document. Nor does the IES list, certify, test or inspect products, designs, or installations for compliance with this document. Any certification or statement of compliance with the requirements of this document shall not be attributable to the IES and is solely the responsibility of the certifier or maker of the statement.

AMERICAN NATIONAL STANDARD

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria have been met by the standards developer.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether that person has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation to any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

CAUTION NOTICE: This American National Standard may be revised at any time. The procedures of the American National Standards Institute require that action be taken to reaffirm, revise, or withdraw this standard no later than five years from the date of approval. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Prepared by the IES Testing Procedures Committee.

Becky Kuebler, *Chair*

Andrew Jackson, *Vice Chair*

David N. Randolph, *Secretary*

Jianzhong Jiao, *Treasurer*

Members

C. K. Andersen

R. P. Bergin

R. S. Bergman

E. Bretschneider

P. Elizondo

K. C. Fletcher

M. L. Grather

Y. Hiebert

J. Hospodarsky

J. N. Hulett

P.-C. Hung

M. Kotrebai

J. E. Leland

S. Longo

J. P. Marella

P. McCarthy

G. McKee

C. C. Miller

E. Radkov

M. B. Sapcoe

Advisory Members

L. M. Ayers

J. Baker

C. A. Bloomfield

P.-T. Chou

P. Cruz

M. Damle

L. Davis

J. J. Demirjian

M. E. Duffy

V. Eberhard

A. A. Feldman

J. Frazer

K. J. Hemmi

S. Hua

G. John

J. Juhasz

H. Kashaninejad

T. Kawabata

J. D. Kramer

K. C. Lerbs

K. M. Liepmann

J. Lockner

Y. Ohno

E. Page

D. Park

E. S. Perkins

M. Piscitelli

T. W. Rasinski

D. Rogers

M. P. Royer

T. Schneider

A. W. Serres

G. A. Steinberg

L. Swainston

J. S. Swiernik

A. Thorseth

R. C. Tuttle

J. C. Vollers

J. E. Walker

Y. Zong

CONTENTS

1.0	Introduction and Scope	1
1.1	Introduction	1
1.2	Scope	1
2.0	Test Distance	1
3.0	Goniophotometer Basic Construction	2
3.1	Small Aperture (Tubular) Goniophotometer	2
3.2	Skylight Goniophotometer	2
3.3	Electrical/Electronic System	3
3.4	Amplifier Box	4
3.5	Electronic Interface Box	4
3.6	Computer Interface Board	4
3.7	Vertical Angular Planes (Step Motor)	4
3.8	Data Collection Speed	5
3.9	Automated Goniophotometer	5
4.0	Photometer Structure	5
5.0	Calibration	6
5.1	Periodic Calibration and Accuracy	6
5.2	Data Reduction	7
5.3	Stray Light	7
6.0	Sky Conditions	8
7.0	Testing Procedures	8
7.1	General Test Conditions	8
7.2	Daylight Device Positioning	9
7.3	Sun Angles	9
7.4	Selection of Angles for Photometric Measurements	10
7.4.1	Angles of Measurement	10
7.4.2	Planes for Measurement	10
7.5	Testing Start Time in Relation to Sun Angle Times	10
7.6	Reporting	11

8.0	Testing Procedure	12
9.0	Limitations of Skylight Photometry.....	12
	Annex A – Accuracy of the Quadrant Testing Method	13
	Annex B – The Testing of Transparent Skylights	14
	Annex C – Accuracy Analysis of Reflections from Black Card	14
	Annex D – Calculation of Standard Time for Different Solar Elevations	15
	Additional Reading	17
	References	17

1.0 Introduction and Scope

1.1 Introduction

Unlike electric luminaires, which require only one photometric test, skylights require a separate test to characterize their performance at different sun angles as well as a separate measurement to determine the sky conditions. Skylights are very often large; some exceed the size capabilities of typical intensity distribution goniophotometers. Therefore, a method was developed to quickly and accurately measure daylight data and place the results in a standardized photometric file format such as ANSI/IES LM-63-19.¹ The collection of results can then be used by lighting design software programs to simulate how skylights under the desired test conditions will fill a space with daylight. This equipment tested also proved to be accurate with regard to the effects of test distance.⁶

This is only one method of achieving luminous intensity distribution curves and efficiency data for skylights and tubular daylighting devices with diffusing properties. In addition, this method mirrors the proven method used to measure electric lights but includes many adjustments because of the very intense, movable light source, the sun. Since 2002, this method has proved to produce consistent repeatable results for measuring skylights and tubular daylighting devices under actual sky conditions.

The procedures contained in this document are a benefit to the lighting industry in characterizing the performance of daylighting products and are backed by significant experience using this measurement method. However, daylight photometry is in infancy stages of research, and further development of these methods will continue. In addition, further research is being conducted to compare measurements to simulation methods. Simulations of daylight system performance use predicted sky models from either the International Commission on Illumination (CIE) or IES and allow for the rapid comparisons of multiple design options or sky conditions. Further research will also be conducted to methods of achieving accurate luminous intensity distribution curves and efficiency data.

1.2 Scope

This Lighting Measurement (LM) document provides the IES recommended uniform method for determining and reporting the photometric characteristics of skylights and tubular daylighting devices that incorporate a means to diffuse the natural hemispherical daylight as the daylight passes through the daylighting system. It describes the procedures followed and the precautions observed in obtaining uniform and reproducible measurements of tubular daylighting devices and skylights with glass or plastic glazing. This document identifies the components and the structure type needed to adequately measure daylighting devices. The procedures, calibration of the equipment, and determination of sun angles and sky conditions are also discussed. This method is not recommended for daylight devices with clear glazing (see **Annex B**).

Additional information on subjects covered in this document may be found in:

- Illuminating Engineering Society. ANSI/IES LS-4-20²
- Illuminating Engineering Society. ANSI/IES LM-63-19¹

2.0 Test Distance

The goniophotometer and the building enclosure should be set up to measure the largest desirable device. The distance between the daylight luminaire and the photodetector should be sufficiently large that the inverse-square law (ISL) can be applied at the distance needed for the largest daylight luminaire to be tested by the goniophotometer. Smaller daylight luminaires can also be tested. It is required that the distance from the daylight luminaire to the photo detector be at least five times the largest luminous dimension of the daylighting luminaire.

For example, when measuring the luminous intensity of a 610 mm x 610 mm (24 in. x 24 in.) skylight, the longest distance would be the 864-mm (35-in.) diagonal. Therefore, the minimum test distance needs to be 5 times 864 mm (5 x 35 in.), which is 4.45 m (14.6 ft). For a tubular daylighting device with a circular daylight opening of 533 mm (21 in.) the minimum test distance would be 2.67 m (8.75 ft). (See **Figure 2-1**.)