

**Please be aware that this PDF has been created from the original hardcopy document, which might not be in good condition and so the PDF might reflect this.**

w/D S/S by April 1975 issue

+ 1 Amd

**BRITISH STANDARD 1377 : 1967**

UDC 624.131

**METHODS OF TESTING**

**SOILS**

**FOR CIVIL ENGINEERING**

**PURPOSES**



**BRITISH STANDARDS INSTITUTION**

**PD 6412**

**Amendment No. 1, published 1 May, 1968**

to BS 1377 : 1967

Methods of testing soils for civil engineering purposes

**Revision**

**2.7.4.5.2.(2)a.** Delete the 2nd paragraph (i.e. the last line on page 78 and the first two lines on page 79).



METHODS OF TESTING

# SOILS

FOR CIVIL ENGINEERING

PURPOSES

**BS 1377 : 1967**

Price 60/- net

**BRITISH STANDARDS INSTITUTION**

INCORPORATED BY ROYAL CHARTER

BRITISH STANDARDS HOUSE, 2 PARK ST., LONDON, W.1

TELEGRAMS: STANDARDS LONDON W1

TELEPHONE: 01-629 9000

THIS BRITISH STANDARD, having been approved by the Road Engineering Industry Standards Committee and endorsed by the Chairman of the Engineering Divisional Council, was published under the authority of the General Council on 20th December, 1967.

First published, July, 1948.

First revision, July, 1961.

Second revision, December, 1967.

The Institution desires to call attention to the fact that this British Standard does not purport to include all the necessary provisions of a contract.

In order to keep abreast of progress in the industries concerned, British Standards are subject to periodical review. Suggestions for improvements will be recorded and in due course brought to the notice of the committees charged with the revision of the standards to which they refer.

A complete list of British Standards, numbering over 4000, fully indexed and with a note of the contents of each, will be found in the British Standards Yearbook, price 15s. The BS Yearbook may be consulted in many public libraries and similar institutions.

This standard makes reference to the following British Standards:

- BS 410. Test sieves.
- BS 593. Laboratory thermometers.
- BS 604. Graduated measuring cylinders.
- BS 718. Density hydrometers and specific gravity hydrometers.
- BS 733. Density bottles.
- BS 812. Methods for sampling and testing of mineral aggregates, sands and fillers.
- BS 846. Burettes and bulb burettes.
- BS 892. Glossary of highway engineering terms.
- BS 903. Methods of testing vulcanized rubber.
- BS 1154. Vulcanized natural rubber compounds.
- BS 1583. One-mark pipettes.
- BS 1610. Methods for the load verification of testing machines.

- BS 1739. Filter flasks.
- BS 1752. Laboratory sintered or fritted filters.
- BS 1780. Bourdon tube pressure and vacuum gauges.
- BS 1792. One-mark volumetric flasks.
- BS 1796. Methods for the use of British Standard fine-mesh test sieves.
- BS 1923. Glass filter funnels.
- BS 1924. Methods of test for stabilized soils.
- BS 1991. Letter symbols, signs and abbreviations.
- BS 2648. Performance requirements for electrically-heated laboratory drying ovens.
- BS 3423. Recommendations for the design of glass vacuum desiccators.
- BS 4019. Rotary core drilling equipment.
- CP 2001. Site investigations.

*British Standards are revised, when necessary, by the issue either of amendment slips or of revised editions. It is important that users of British Standards should ascertain that they are in possession of the latest amendments or editions.*

The following BSI references relate to the work on this standard:  
Committee references RDE/9, RDE/9/7 and RDE/9/8  
Drafts for comment D 65/7607 and D 65/10540

## CONTENTS

	Page
Co-operating organizations	7
Foreword	8

## METHODS

## 1. GENERAL

1.1 Definitions and symbols	10
1.2 Apparatus	14
1.3 Grouping of soils	14
1.4 Preparation of disturbed samples for testing	15

## 2. SOIL CLASSIFICATION TESTS

2.1 Test 1. Determination of the moisture content	25
1(A). Standard method (oven-drying method)	25
1(B). Subsidiary method (sand-bath method)	28
1(C). Subsidiary method (alcohol method)	31
2.2 Test 2. Determination of the liquid limit	33
2(A). Standard method	33
2(B). Subsidiary method (one point method)	39
2.3 Test 3. Determination of the plastic limit	42
2.4 Test 4. Calculation of the plasticity index	44
2.5 Test 5. Determination of the linear shrinkage	45
2.6 Test 6. Determination of the specific gravity of soil particles	48
6(A). Method for fine-grained soils	48
6(B). Method for medium- and coarse-grained soils	52
2.7 Test 7. Determination of the particle size distribution	55
7(A). Standard method by wet sieving	55
7(B). Subsidiary method by dry sieving	58
7(C). Standard method for fine-grained soils (pipette method)	61
7(D). Subsidiary method for fine-grained soils (hydrometer method)	73

## 3. SOIL CHEMICAL TESTS

3.1 Test 8. Determination of the organic matter content	86
---	----

	Page
3.2 Test 9. Determination of the sulphate content of soil and the sulphate content of the ground-water	90
9(A). Standard method (gravimetric method)	90
9(B). Subsidiary method (ion-exchange method)	95
3.3 Test 10. Determination of the pH value	101
10(A). Standard method (electrometric)	101
10(B). Subsidiary method (colorimetric)	103

## 4. SOIL COMPACTION TESTS

4.1 Test 11. Determination of the dry density/moisture content relation—5.5 lb (2.5 kg) rammer method	105
4.2 Test 12. Determination of the dry density/moisture content relation—10 lb (4.5 kg) rammer method	111
4.3 Test 13. Determination of the dry density/moisture content relation of granular soil-vibrating hammer method	117
4.4 Test 14. Determination of the dry density of soil on the site	122
14(A). Sand replacement method suitable for fine- and medium-grained soils: small pouring cylinder method	122
14(B). Sand replacement method suitable for fine-, medium- and coarse-grained soils: large pouring cylinder method	131
14(C). Sand replacement method suitable for fine-, medium- and coarse-grained soils: hand scoop method	138
14(D). Core-cutter method for fine-grained and chalk soils free from stones	142
14(E). Weight in water method	145
14(F). Water displacement method	150

## 5. SOIL STRENGTH TESTS

5.1 Test 15. Determination of the California Bearing Ratio	154
--	-----

		Page
5.2	Test 16. Determination of the one-dimensional consolidation properties	169
5.3	Test 17. Determination of shear strength in the field by the vane test	184
5.4	Test 18. Determination of the penetration resistance using the split-barrel sampler	189
5.5	Test 19. Determination of the unconfined compressive strength using portable apparatus	195
5.6	Test 20. Determination of the compressive strength of a specimen tested in undrained triaxial compression without the measurement of pore water pressure	199

#### APPENDICES

A.	Maximum weight of material to be retained on each test sieve at the completion of sieving (from BS 812)	206
B.	Typical data and calculation forms	207

#### CO-OPERATING ORGANIZATIONS

The Road Engineering Industry Standards Committee, under whose supervision this British Standard was prepared, consists of representatives from the following Government departments and scientific and industrial organizations:

- \*Asphalt and Coated Macadam Association
- \*Association of Consulting Engineers
- British Granite and Whinstone Federation
- \*British Road Tar Association
- British Slag Federation
- British Tarpaviors' Federation
- \*Cement and Concrete Association
- Concrete Society Ltd.
- Contractors' Plant Association
- \*County Surveyors' Society
- \*Federation of Civil Engineering Contractors
- Federation of Manufacturers of Construction Equipment
- \*Institute of Petroleum
- \*Institution of Civil Engineers
- \*Institution of Highway Engineers
- \*Institution of Municipal Engineers
- \*Institution of Structural Engineers
- Limestone Federation
- \*Ministry of Defence, Army Department
- \*Ministry of Public Building and Works
- \*Ministry of Transport
- \*Ministry of Transport, Road Research Laboratory
- Sand and Gravel Association of Great Britain
- Society of Chemical Industry

The Government departments and scientific and industrial organizations marked with an asterisk in the above list, together with the following, were directly represented on the committee entrusted with the preparation of this British Standard:

- Building Research Station—Ministry of Public Building and Works
- Greater London Council
- Imperial College of Science and Technology
- Road Emulsion Association Ltd.
- Rothamsted Experimental Station
- Individual manufacturers and user

# BRITISH STANDARD METHODS OF TESTING SOILS FOR CIVIL ENGINEERING PURPOSES

## FOREWORD

This British Standard was first published under the authority of the Road Engineering Industry Standards Committee in 1948 and revised in 1961. It has now been revised for the second time and is being published simultaneously with the related British Standard 1924, 'Methods of test for stabilized soils', which has also been revised. This has been done to ensure that where similar tests exist for natural and stabilized soils the same test procedures are specified in the respective standards, thus making it possible to compare results obtained with natural and stabilized soils.

No changes of principle have been made to the test procedures given in the second edition of the standard but the detail has been revised to take account of the increased knowledge that has been gained in the testing of soils. The opportunity has also been taken to include a number of new test procedures and to standardize test procedures which, although widely used, had not hitherto been standardized. The additional tests that have been included comprise:

- (1) The linear shrinkage test which provides indirect methods of assessing the plasticity index of soils having low clay contents.
- (2) An additional compaction test which utilizes a vibratory method of compaction and which has been found to give results that are closer to field conditions with granular materials.
- (3) An additional test for determining the dry density of soil on the site.
- (4) A subsidiary method for determining the sulphate content of soils by an ion-exchange procedure.
- (5) A new section containing a number of soil strength tests such as the California Bearing Ratio, shear strength and the one-dimensional consolidation of soil.

In several instances methods are termed 'standard method' and 'subsidiary method' respectively. The former are more accurate but may be unsatisfactory for use in the laboratory or the field owing to the time taken or the need for equipment which is not easily obtainable.

Typical forms are included for nearly all the test methods to illustrate how the results may conveniently be calculated and recorded. The layout of such forms is a matter of individual preference, but most of the typical layouts have been printed so that photographic reproduction and enlargement to about foolscap size will provide a usable standard form.

In each of the methods the measurement is required of only one value of the quantity concerned. It is recognized that it is necessary in many practical applications to make a number of tests in order to obtain a mean value and an indication of its reliability. Guidance on the number of measurements required and the treatment of the results obtained is regarded as being beyond the scope of the present standard.

NOTE. The values stated in British units are to be regarded as the standard. Any metric equivalents are approximate. More accurate conversions should be based on the data in BS 350, 'Conversion factors and tables'.

## METHODS

### 1. GENERAL

#### 1.1 DEFINITIONS AND SYMBOLS

**1.1.1 Definitions\*.** For the purposes of this British Standard the following definitions apply:

(1) *Liquid limit (LL)*. The moisture content at which a soil passes from the plastic to the liquid state as determined by the liquid limit test.

(2) *Plastic limit (PL)*. The moisture content at which a soil becomes too dry to be in a plastic condition as determined by the plastic limit test.

(3) *Plasticity index (PI)*. The numerical difference between the liquid limit and the plastic limit of a soil.

(4) *Non-plastic*. A soil with a plasticity index of zero or one on which the plastic limit cannot be determined.

(5) *Particle size distribution*. The percentages of the various grain sizes present in a soil as determined by sieving, sedimentation, elutriation or other means.

(6) *Cobbles*. Rounded or sub-angular stones of sizes between 200 mm (8 in) and 60 mm (2½ in).

(7) *Gravel fraction*. The fraction of a soil composed of particles between the sizes of 60 mm (2½ in) and 2 mm (0.08 in). The gravel fraction may be sub-divided as follows:

Coarse gravel	60 mm–20 mm
Medium gravel	20 mm– 6 mm
Fine gravel	6 mm– 2 mm

(8) *Sand fraction*. The fraction of a soil composed of particles between the sizes 2.0 mm and 0.06 mm. The sand fraction may be sub-divided as follows:

Coarse sand	2.0 mm–0.6 mm
Medium sand	0.6 mm–0.2 mm
Fine sand	0.2 mm–0.06 mm

(9) *Silt fraction*. The fraction of a soil composed of particles between the sizes 0.06 mm and 0.002 mm. The silt fraction may be sub-divided as follows:

Coarse silt	0.06 mm–0.02 mm
Medium silt	0.02 mm–0.006 mm
Fine silt	0.006 mm–0.002 mm

\* See also BS 892, 'Glossary of highway engineering terms', and BS 1991, 'Letter symbols and abbreviations'.

(10) *Clay fraction*. The fraction of a soil composed of particles smaller in size than 0.002 mm.

(11) *Cohesive soil*. A soil which, by virtue of its clay content, will form a coherent mass.

(12) *Non-cohesive soil*. *Granular soil*. A soil which will not form a coherent mass.

(13) *Sampling*. The selection of a representative portion of a material.

(14) *Quartering*. The reduction in quantity of a large sample of material by dividing a circular heap into four approximately equal parts by diameters at right angles, removing two diagonally opposite quarters, and mixing the two remaining quarters intimately together so as to obtain a truly representative half of the original mass. The process is repeated until a sample of the required size is obtained.

(15) *Riffing*. The reduction in quantity of a large sample of material by dividing the mass into two approximately equal halves by passing the sample through an appropriately sized riffle (or riffle box). The process is repeated until a sample of the required size is obtained.

(16) *Compaction*. The process of packing soil particles more closely together by rolling or other mechanical means, thus increasing the dry density of the soil.

(17) *Consolidation*. The process whereby soil particles are packed more closely together over a *period* of time by application of continued pressure.

(18) *Bulk density*. The weight of a material (including solid particles and any contained water) per unit volume including voids.

(19) *Dry density*. The weight of the dry material after drying to constant weight at 105°C (221°F) contained in unit volume of undried material.

(20) *Moisture content*. The quantity of water which can be removed from the soil, usually by heating at 105°C (221°F), expressed as a percentage of the dry weight.

(21) *Optimum moisture content*. The moisture content at which a specified amount of compaction will produce the maximum dry density (see Fig. 1).

(22) *Maximum dry density*. The dry density obtained using a specified amount of compaction at the optimum moisture content (see Fig. 1).

(23) *Relative compaction*. The percentage ratio of the dry density of the soil to the maximum dry density of that soil as determined by a specified laboratory compaction test.