

AGA
Gas Measurement Manual
(Revised)

PART TWO
DISPLACEMENT METERING

Prepared by the Customer Field Services and Measurement
And Transmission Measurement Committees
Of the Operating Section



Copyright 2021 © American Gas Association
All Rights Reserved

Catalog # XQ2103
September 2021

Acknowledgements

Gas Measurement Manual – Part 2: Displacement Metering was revised by a Distribution Measurement Committee (DMC) task group under the chairmanship of Pat Donnelly of NiSource Energy and the co-chairmanship of Jon Fickinger of Itron, Inc.

Members of the Part 2 Task Group

Tod Bradley, Elster American Meter
Lee Gelnett, Sensus Metering Systems
Ralph Richter, NIST
Phil Whittemore, Dresser Meters and Instruments
Tushar Shah, Eagle Research
Craig Lam, Sick
Shane Dollar, Dominion Energy
Rick Spann, Dominion Energy
Bill Haddad, Honeywell
Robert Bennett, Honeywell
Ardis Bartle, Apex Measurement
Koby Avery, TECO Energy
Christian Overgaard, Consultant
Ron Strong, Dresser
John Hand, TC Energy

Staff Executive

Kenneth Buys, American Gas Association

Table of Contents

1	Introduction	1
1.1	Scope.....	1
1.2	History.....	1
1.3	Definitions	4
2	Diaphragm Meters	7
2.1	Basic Operating Principle	7
2.2	Operation of a Four-Chamber Diaphragm Meter.....	7
2.3	Operation of a Three-Chamber Diaphragm Meter.....	9
2.4	Compensation Mechanisms.....	10
2.4.1	Temperature Compensation	10
2.4.2	Pressure Compensation	12
2.5	Standards.....	13
2.5.1	Capacity	13
2.5.2	Accuracy.....	14
2.5.3	Sizing	15
2.5.4	Testing.....	16
2.5.5	Installation.....	16
2.5.6	Maintenance	17
3	Rotary Displacement Meters.....	19
3.1	Operation	19
3.2	Capacity	20
3.3	Performance, Accuracy, Rangeability	20
3.3.1	Performance	20
3.3.2	Accuracy.....	21
3.3.3	Rangeability.....	21
3.4	Sizing	22
3.5	Verification	23
3.6	Periodic Inspection	25
3.7	Installation & Maintenance Considerations.....	26
3.8	Attachments and Accessory Units	28
4	References.....	29
5	Appendix A.....	30

5.1	FORM FOR PROPOSALS ON AGA REPORT NO. 4A, March 2021	30
	Figure 1-1 Coin Operated Diaphragm Meter.....	2
	Figure 1-2 Current Diaphragm Meter	3
	Figure 1-3 Vintage Rotary Meter (Circa 1940).....	3
	Figure 1-4 Current Rotary Meter	4
	Figure 2-1 Four Chamber Diaphragm Meter Movement.....	8
	Figure 2-2 Four Chamber Diaphragm Cutaway	8
	Figure 2-3 Linkage on Top of Diaphragm Meter.....	9
	Figure 2-4 Non-Temperature Compensated Diaphragm Meter.....	11
	Figure 2-5 Temperature Compensated (TC) Diaphragm Meter.....	11
	Figure 2-6 Temperature Compensation for Diaphragm	12
	Figure 2-7 Red-Faced Pressure Compensating Index.....	13
	Figure 2-8 Diaphragm meter with proper installation practices including: meter off the ground and properly installed, filter, strainer, pressure protection, painted, guards, and the entire assembly is readily accessible for easy maintenance	17
	Figure 2-9 Wear Points: Factors affecting meter accuracy include wear, friction, leakage and Diaphragm stability	18
	Figure 3-1 Cutaway of Two-Impeller Rotary Meter	19
	Figure 3-2 Two Impeller Rotary Meter: Principle of Operation.....	20
	Figure 3-3 Accuracy Curve Showing Rangeability of Meter.....	21
	Figure 3-4 Meter Badge Rating	22
	Figure 3-5 Typical Rotary Meter Differential Testing Setup.....	25
	Figure 3-6 Strainer Gaskets.....	26
	Figure 3-7 Rotary Meter Oil Sight Glasses.....	27
	Figure 3-8 Horizontal (Side Inlet) Installation of Rotary Meter	27
	Figure 3-9 Vertical (Top Inlet) Installation of Rotary Meter	28

Appendix A

FORM FOR PROPOSALS ON AGA GMM 2 July 2021

DISCLAIMER AND COPYRIGHT

The American Gas Association's (AGA) Operations and Engineering Section provides a forum for industry experts to bring their collective knowledge together to improve the state of the art in the areas of operating, engineering and technological aspects of producing, gathering, transporting, storing, distributing, measuring and utilizing natural gas.

Through its publications, of which this is one, AGA provides for the exchange of information within the natural gas industry and scientific, trade and governmental organizations. Many AGA publications are prepared or sponsored by an AGA Operations and Engineering Section technical committee. While AGA may administer the process, neither AGA nor the technical committee independently tests, evaluates or verifies the accuracy of any information or the soundness of any judgments contained therein.

AGA disclaims liability for any personal injury, property or other damages of any nature whatsoever, whether special, indirect, consequential or compensatory, directly or indirectly resulting from the publication, use of or reliance on AGA publications. AGA makes no guaranty or warranty as to the accuracy and completeness of any information published therein. The information contained therein is provided on an "as is" basis and AGA makes no representations or warranties including any expressed or implied warranty of merchantability or fitness for a particular purpose.

In issuing and making this document available, AGA is not undertaking to render professional or other services for or on behalf of any person or entity. Nor is AGA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances.

AGA has no power, nor does it undertake, to police or enforce compliance with the contents of this document. Nor does AGA list, certify, test or inspect products, designs or installations for compliance with this document. Any certification or other statement of compliance is solely the responsibility of the certifier or maker of the statement.

AGA does not take any position with respect to the validity of any patent rights asserted in connection with any items that are mentioned in or are the subject of AGA publications, and AGA disclaims liability for the infringement of any patent resulting from the use of or reliance on its publications. Users of these publications are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Users of this publication should consult applicable federal, state and local laws and regulations. AGA does not, through its publications intend to urge action that is not in compliance with applicable laws, and its publications may not be construed as doing so.

Changes to this document may become necessary from time to time. If changes are believed appropriate by any person or entity, such suggested changes should be communicated to AGA in writing and sent to: **Operations & Engineering Section, American Gas Association, 400 North Capitol Street, NW, 4th Floor, Washington, DC 20001, U.S.A.** *Suggested changes must include: contact information, including name, address and any corporate affiliation; full name of the document; suggested revisions to the text of the document; the rationale for the suggested revisions; and permission to use the suggested revisions in an amended publication of the document.*

Copyright © 2021, American Gas Association, All Rights Reserved.

1 Introduction

1.1 Scope

This document is intended to describe the theory of operation, typical operating characteristics, and applications of diaphragm and rotary positive displacement meters. This document covers sizing meters, accuracy, rangeability (turndown), installation specifications, proof testing, maintenance procedures, and computations used in the calculation of displacement meter flow for the measurement of natural gas.

Applications include measuring single-phase gas flow found in production, processing, distribution, and end-use gas measurement systems. Typical use is the measurement of fuel-grade natural gas and associated hydrocarbon gases, either as pure hydrocarbons or as a mixture of pure hydrocarbons and diluents.

Refer to manufacturers' accessory equipment used to measure pressure, temperature, and density of the flowing gas, or for other mechanical or electronic instruments that convert meter outputs from line conditions to base conditions. This document does not cover characteristics of electronic pulse signal generating devices within or attached to the meter, although it does address the use of their outputs.

In addition to providing guidance on the use of gas displacement meters, this section provides practical formulas for reference and training of new entrants to the industry as well as back office and non-technical individuals unfamiliar with natural gas displacement meter measurement.

This section is intended for use in conjunction with ANSI B109.1, B109.2, and B109.3 (B109.1: Diaphragm-Type Gas Displacement Meters (Under 500-Cubic-Foot-per-hour Capacity), B109.2: Diaphragm-Type Gas Displacement Meters (500-Cubic-Foot-per-hour Capacity and over), & B109.3: Rotary Type Gas Displacement Meters) and manuals produced by positive displacement meter manufacturers. Consult with the specific meter's manufacturer for guidance in cases where manufacturer-supplied information is not consistent with information presented in this section or other AGA documents. This section is not intended for use as a standard and is not intended for reference in a tariff or other regulatory documents.

1.2 History

Initially, gas companies typically did not measure the amount of gas consumers used: most consumers were charged a flat rate. Wet type positive displacement meters were developed in 1815 (Clegg) to measure actual gas volume used by each customer. The dry type diaphragm positive displacement meter was developed in 1844 (Richards and Croll). Thomas Glover improved this design, and the meter became known as the Glover two diaphragm slide valve type meter. Meter connections sizes (5 light, 10 light, etc.) were used to indicate the number of gas lights that the meter could accurately measure. This basic meter design is still in use today and is available in four-chamber and three-chamber configurations.

Over the ensuing years, new materials and manufacturing techniques have been developed to make diaphragm meters lighter, longer lasting, more accurate, and more reliable. For example, meter bodies formerly made of ductile iron are now made from lightweight aluminum. Diaphragm materials have advanced from leather, which required periodic lubrication to stay flexible, to synthetic rubber which has a maintenance free service life. Slide valve materials have also