

ASME HST-4-2021
(Revision of ASME HST-4-2016)

Performance Standard for Overhead Electric Wire Rope Hoists

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

ASME HST-4-2021
(Revision of ASME HST-4-2016)

Performance Standard for Overhead Electric Wire Rope Hoists

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

Two Park Avenue • New York, NY • 10016 USA

Date of Issuance: November 30, 2021

The next edition of this Standard is scheduled for publication in 2026.

ASME issues written replies to inquiries concerning interpretations of technical aspects of this Standard. Interpretations are published on the Committee web page and under go.asme.org/InterpsDatabase. Periodically certain actions of the ASME HST Committee may be published as Cases. Cases are published on the ASME website under the HST Committee Page at <http://go.asme.org/HSTcommittee> as they are issued.

Errata to codes and standards may be posted on the ASME website under the Committee Pages to provide corrections to incorrectly published items, or to correct typographical or grammatical errors in codes and standards. Such errata shall be used on the date posted.

The HST Committee Page can be found at <http://go.asme.org/HSTcommittee>. There is an option available to automatically receive an e-mail notification when errata are posted to a particular code or standard. This option can be found on the appropriate Committee Page after selecting "Errata" in the "Publication Information" section.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The Standards Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment that provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not "approve," "rate," or "endorse" any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor assume any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.

The American Society of Mechanical Engineers
Two Park Avenue, New York, NY 10016-5990

Copyright © 2021 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All rights reserved
Printed in U.S.A.

CONTENTS

Foreword	v
Committee Roster	vi
Correspondence With the HST Committee	vii
Chapter 4-0	
Scope, Definitions, References, and Appendices	1
Section 4-0.1 Scope	1
Section 4-0.2 Definitions	1
Section 4-0.3 References	5
Section 4-0.4 Appendices	5
Chapter 4-1	
Performance	7
Section 4-1.1 General	7
Section 4-1.2 Hoist Duty Service Classification	7
Section 4-1.3 Application Analysis	8
Section 4-1.4 Specification of Lift, Headroom, and Reach	10
Section 4-1.5 Speeds: Hoist and Trolley	10
Section 4-1.6 Types of Trolleys	10
Chapter 4-2	
Mechanical	12
Section 4-2.1 Reeving	12
Section 4-2.2 Bearings	12
Section 4-2.3 Overload Limiting Device	12
Chapter 4-3	
Electrical	13
Section 4-3.1 General	13
Section 4-3.2 Motors	13
Section 4-3.3 Controllers	14
Section 4-3.4 Control Enclosures	14
Section 4-3.5 Resistors	15
Section 4-3.6 Current Conductor Systems	15
Chapter 4-4	
Inquiry Data Form	16
Section 4-4.1 Typical Electric Wire Rope Hoist and Trolley Inquiry Data Form	16
 Nonmandatory Appendices	
A	Performance Requirements for Electric Wire Rope Hoists Used in Marine and Other Applications As Required by the U.S. Department of Defense (DOD) 18
B	Examples of Detailed Application Analysis 25
C	Mechanical Spark Resistance Guidance for Applications in Hazardous (Potentially Explosive) Locations 28
 Figures	
4-0.2-1	Hoist Mounting Headroom, Lift, and Reach 4
4-0.2-2	Single and Double Reeving 5

Tables

4-1.2.3-1	Hoist Duty Service Classification	9
4-1.5-1	Typical Hoist and Motorized Trolley Speeds	11
4-3.2-1	Typical Rated Motor Voltages	13
A-3.2-1	Hook Throat Openings	20
A-4.2.5-1	Electromagnetic Environment	23
B-2-1	Example of Detailed Analysis Worksheet	26

Form

4-4.1-1	Typical Electric Wire Rope Hoist and Trolley Inquiry Data Form	17
---------	--	----

FOREWORD

This Standard is one in a series that provides performance requirements for hoists and was originally issued in 1986. It was developed by The American Society of Mechanical Engineers (ASME) HST Standards Committee, Hoists — Overhead. It is intended to serve as a guide to manufacturers of the equipment, and to the purchasers and users of the equipment. Standards in this series are

Designator	Title
HST-1	Performance Standard for Electric Chain Hoists
HST-2	Performance Standard for Hand Chain Manually Operated Chain Hoists
HST-3	Performance Standard for Manually Lever Operated Chain Hoists
HST-4	Performance Standard for Overhead Electric Wire Rope Hoists
HST-5	Performance Standard for Air Chain Hoists
HST-6	Performance Standard for Air Wire Rope Hoists

This edition contains a [Nonmandatory Appendix A](#) that, in conjunction with this Standard, is intended to replace MIL-H-15317.

This Standard has been formatted in accordance with the 2019 ASME Codes and Standards Writing Guide and Style Guide.

This Standard is available for public review on a continuing basis. This provides an opportunity for additional public review input from industry, academia, regulatory agencies, and the public-at-large.

This Standard was approved by ANSI as an American National Standard on July 6, 2021.

ASME HST COMMITTEE

Hoists — Overhead

(The following is the roster of the Committee at the time of approval of this Standard.)

STANDARDS COMMITTEE OFFICERS

J. Burkey, *Chair*
M. Martinez Correa, *Vice Chair*
J. Cassamassino, *Secretary*

STANDARDS COMMITTEE PERSONNEL

J. R. Burkey , Columbus McKinnon Corp.	E. K. Marburg , Columbus McKinnon Corp.
B. M. Casey , Electric Boat	M. Martinez Correa , Chevron Upstream and Gas
J. Cassamassino , The American Society of Mechanical Engineers	K. Sprague , Ineos O&P, USA
J. E. Eaglin , John Group International	D. C. Staber , NWP, LLC
F. G. Heath , Heath and Associates	W. E. Osborn , <i>Honorary Member</i> , Ingersoll Rand
J. D. Hoke , Harrington Hoists and Cranes	

CORRESPONDENCE WITH THE HST COMMITTEE

General. ASME Standards are developed and maintained with the intent to represent the consensus of concerned interests. As such, users of this Standard may interact with the Committee by requesting interpretations, proposing revisions or a case, and attending Committee meetings. Correspondence should be addressed to:

Secretary, HST Standards Committee
The American Society of Mechanical Engineers
Two Park Avenue
New York, NY 10016-5990
<http://go.asme.org/Inquiry>

Proposing Revisions. Revisions are made periodically to the Standard to incorporate changes that appear necessary or desirable, as demonstrated by the experience gained from the application of the Standard. Approved revisions will be published periodically.

This Standard is always open for comment, and the Committee welcomes proposals for revisions. Such proposals should be as specific as possible, citing the paragraph number(s), the proposed wording, and a detailed description of the reasons for the proposal, including any pertinent documentation.

Proposing a Case. Cases may be issued to provide alternative rules when justified, to permit early implementation of an approved revision when the need is urgent, or to provide rules not covered by existing provisions. Cases are effective immediately upon ASME approval and shall be posted on the ASME Committee web page.

Requests for Cases shall provide a Statement of Need and Background Information. The request should identify the Standard and the paragraph, figure, or table number(s), and be written as a Question and Reply in the same format as existing Cases. Requests for Cases should also indicate the applicable edition(s) of the Standard to which the proposed Case applies.

Interpretations. Upon request, the HST Standards Committee will render an interpretation of any requirement of the Standard. Interpretations can only be rendered in response to a written request sent to the Secretary of the HST Standards Committee.

Requests for interpretation should preferably be submitted through the online Interpretation Submittal Form. The form is accessible at <http://go.asme.org/InterpretationRequest>. Upon submittal of the form, the Inquirer will receive an automatic e-mail confirming receipt.

If the Inquirer is unable to use the online form, he/she may mail the request to the Secretary of the HST Standards Committee at the above address. The request for an interpretation should be clear and unambiguous. It is further recommended that the Inquirer submit his/her request in the following format:

- Subject: Cite the applicable paragraph number(s) and the topic of the inquiry in one or two words.
- Edition: Cite the applicable edition of the Standard for which the interpretation is being requested.
- Question: Phrase the question as a request for an interpretation of a specific requirement suitable for general understanding and use, not as a request for an approval of a proprietary design or situation. Please provide a condensed and precise question, composed in such a way that a “yes” or “no” reply is acceptable.
- Proposed Reply(ies): Provide a proposed reply(ies) in the form of “Yes” or “No,” with explanation as needed. If entering replies to more than one question, please number the questions and replies.
- Background Information: Provide the Committee with any background information that will assist the Committee in understanding the inquiry. The Inquirer may also include any plans or drawings that are necessary to explain the question; however, they should not contain proprietary names or information.

Requests that are not in the format described above may be rewritten in the appropriate format by the Committee prior to being answered, which may inadvertently change the intent of the original request.

Moreover, ASME does not act as a consultant for specific engineering problems or for the general application or understanding of the Standard requirements. If, based on the inquiry information submitted, it is the opinion of the Committee that the Inquirer should seek assistance, the inquiry will be returned with the recommendation that such assistance be obtained.

ASME procedures provide for reconsideration of any interpretation when or if additional information that might affect an interpretation is available. Further, persons aggrieved by an interpretation may appeal to the cognizant ASME Committee or Subcommittee. ASME does not “approve,” “certify,” “rate,” or “endorse” any item, construction, proprietary device, or activity.

Attending Committee Meetings. The HST Standards Committee regularly holds meetings and/or telephone conferences that are open to the public. Persons wishing to attend any meeting and/or telephone conference should contact the Secretary of the HST Standards Committee. Future Committee meeting dates and locations can be found on the Committee Page at <http://go.asme.org/HSTcommittee>.

Chapter 4-0

Scope, Definitions, References, and Appendices

SECTION 4-0.1: SCOPE

(a) This Standard establishes performance requirements for electric wire rope hoists for vertical lifting service involving material handling of freely suspended (unguided) loads using wire rope with one of the following types of suspension:

- (1) lug
- (2) hook
- (3) trolley
- (4) base or deck mounted (does not include base-mounted winches of the type covered by ASME B30.7)
- (5) wall or ceiling mounted (does not include base-mounted winches of the type covered by ASME B30.7)

(b) This Standard is applicable to hoists manufactured after the date on which this Standard is issued. This Standard is not applicable to

- (1) damaged or malfunctioning hoists
- (2) hoists that have been misused or abused
- (3) hoists that have been altered without authorization of the manufacturer or a qualified person
- (4) hoists used for the purpose of lifting or lowering people
- (5) hoists used for the purpose of drawing both the load and the hoist up or down the hoist's own wire rope
- (6) hoists used for marine and other applications as required by the U.S. Department of Defense (DOD) unless

[Nonmandatory Appendix A](#) is invoked

(c) The requirements of this Standard shall be applied together with the requirements of ASME B30.16. Please also refer to ASME B30.16 for requirements pertaining to marking, construction, and installation; inspection, testing, and maintenance; and operation.

SECTION 4-0.2: DEFINITIONS

abnormal operating conditions: environmental conditions that are unfavorable, harmful, or detrimental to the operation of a hoist, such as excessively high or low ambient temperatures; exposure to weather, corrosive fumes, dust-laden or moisture-laden atmospheres; and hazardous locations.

ambient temperature: the temperature of the atmosphere surrounding the hoist.

base or deck mounted: a type of mounting where the hoist is mounted to the top side of a horizontal supporting surface.

beam: an overhead standard structural or specially fabricated shape on which the trolley operates.

block, load: the assembly of hook or shackle, swivel, bearing, pins, sheaves, and frame suspended by the rope. This shall include all appurtenances reeved into the hoisting rope.

brake: a device, other than a motor, used for retarding or stopping motion by friction or power means.

brake, holding: a friction brake for a hoist that is automatically applied and prevents motion when power is off.

brake, mechanical load: an automatic type of friction brake used for controlling loads in a lowering direction. This unidirectional device requires torque from the motor to lower a load but does not impose additional load on the motor when lifting a load. A mechanical load brake may also be used as a holding brake if designed as such by the manufacturer.

braking, control: a method of controlling speed by removing energy from the moving body or by imparting energy in the opposite direction.

braking, countertorque (plugging): a method of controlling speed by applying a variable motor torque in the direction opposite to the direction that the motor is rotating as it is being overhauled by the load.