

ANSI/IES/IUVA LM-92-22



Illuminating
ENGINEERING SOCIETY

APPROVED METHOD:
OPTICAL AND ELECTRICAL
MEASUREMENT OF ULTRAVIOLET LEDS
AN AMERICAN NATIONAL STANDARD



www.ies.org

ANSI/IES/IUVA LM-92-22

**APPROVED METHOD:
OPTICAL AND ELECTRICAL MEASUREMENT OF
ULTRAVIOLET LEDS
AN AMERICAN NATIONAL STANDARD**

Publication of this document
has been approved by IES.
Suggestions for revisions
should be directed to IES.

**Prepared for IES
IES Testing Procedures Committee**



Copyright 2022 by the Illuminating Engineering Society.

Approved by the IES Standards Committee, February 28, 2022, as a Transaction of the Illuminating Engineering Society.

Approved March 10, 2022, as an American National Standard.

All rights reserved. No part of this publication may be reproduced in any form, in any electronic retrieval system or otherwise, without prior written permission of the IES.

Published by the Illuminating Engineering Society, 120 Wall Street, New York, New York 10005.

IES Standards are developed through committee consensus and produced by the IES Office in New York. Careful attention is given to style and accuracy. If any errors are noted in this document, please forward them to Brian Liebel, Director of Standards, at standards@ies.org or the above address for verification and correction. The IES welcomes and urges feedback and comments.

Printed in the United States of America.

ISBN# 978-0-87995-419-2

DISCLAIMER

IES publications are developed through the consensus standards development process approved by the American National Standards Institute. This process brings together volunteers representing varied viewpoints and interests to achieve consensus on lighting recommendations. While the IES administers the process and establishes policies and procedures to promote fairness in the development of consensus, it makes no guaranty or warranty as to the accuracy or completeness of any information published herein.

The IES disclaims liability for any injury to persons or property or other damages of any nature whatsoever, whether special, indirect, consequential or compensatory, directly or indirectly resulting from the publication, use of, or reliance on this document.

In issuing and making this document available, the IES is not undertaking to render professional or other services for or on behalf of any person or entity. Nor is the IES undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances.

The IES has no power, nor does it undertake, to police or enforce compliance with the contents of this document. Nor does the IES list, certify, test or inspect products, designs, or installations for compliance with this document. Any certification or statement of compliance with the requirements of this document shall not be attributable to the IES and is solely the responsibility of the certifier or maker of the statement.

IUVA

The International Ultraviolet Association (IUVA) makes no guaranty or warranty as to the accuracy or completeness of any information published herein.

The IUVA disclaims liability for any injury to persons or property or other damages of any nature whatsoever, whether special, indirect, consequential or compensatory, directly or indirectly resulting from the publication, use of, or reliance on this document.

In issuing and making this document available, the IUVA is not undertaking to render professional or other services for or on behalf of any person or entity. Nor is the IUVA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances.

The IUVA has no power, nor does it undertake, to police or enforce compliance with the contents of this document. Nor does the IUVA list, certify, test or inspect products, designs, or installations for compliance with this document. Any certification or statement of compliance with the requirements of this document shall not be attributable to the IUVA and is solely the responsibility of the certifier or maker of the statement.

AMERICAN NATIONAL STANDARD

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria have been met by the standards developer.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether that person has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation to any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

CAUTION NOTICE: This American National Standard may be revised at any time. The procedures of the American National Standards Institute require that action be taken to reaffirm, revise, or withdraw this standard no later than five years from the date of approval. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Prepared by the IES Testing Procedures Committee.

KC Fletcher, *Chair*

Andy Jackson, *Vice Chair*

David N. Randolph, *Secretary*

Members

C. K. Andersen

R. S. Bergman

B. Boudreaux

E. Bretschneider

F. Carpenter

M. L. Grather

Y. H. Hiebert

J. N. Hulett

P.-C. Hung

J. Jiao

M. Kotrebai

J. E. Leland

K. M. Liepmann

S. Longo

L. Loudin

J. P. Marella

P. McCarthy

C. C. Miller

S. Mitsuhashi

E. Radkov

D. Rogers

M. B. Sapcoe

J. S. Swiernik

J. C. Vollers

Advisory Members

R. P. Bergin

C. A. Bloomfield

J. J. Demirjian

D. J. Ellis

B. Feagin Jr.

A. A. Feldman

J. Frazer

G. John

H. Kashaninejad

J. D. Kramer

J. Lockner

G. McKee

E. Page

D. Park

E. S. Perkins

D. P. Ramer

A. W. Serres

D. Spicer

G. S. Steinberg

A. Thorseth

CONTENTS

1.0	Introduction and Scope	1
1.1	Introduction	1
1.2	Scope	1
2.0	Normative References	2
2.1	ANSI/IES LM-58-20	2
2.2	ANSI/IES LM-75-19	2
2.3	ANSI/IES LM-78-20	2
2.4	ANSI/IES LS-1-21	2
3.0	Definitions	2
3.1	data acquisition (DAQ)	2
3.2	device under test (DUT)	2
3.3	digital multimeter (DMM)	2
3.4	junction temperature (T_J)	2
3.5	out-of-band light	2
3.6	pulse period jitter	2
3.7	pulse width error	2
3.8	pulse width jitter	2
3.9	pulsed current source (PCS)	2
3.10	settling time	3
3.11	source measure unit (SMU)	3
3.12	temperature-controlled mount (TCM)	3
3.13	UV LED	3
4.0	Physical and Environmental Test Conditions	3
4.1	Thermal Conditions	3
4.1.1	Junction Temperature, T_J	3
4.1.2	Temperature Control of the DUT	3
4.1.3	Ambient Temperature (T_A)	3
4.2	Airflow	3
4.3	Thermal Conditions for Mounting DUTs	3
4.4	Vibration	3
4.5	Humidity	4
5.0	Electrical Test Equipment	4
5.1	Pulsed Current Source (PCS) or Source Measure Unit (SMU)	4
5.2	Pulse Amplitude Measuring Device	5
5.3	Current Shunt or Current Probe	5
5.4	DMM with Multi-slope Integrator or High-Speed DAQ	5

5.5	Oscilloscope or SMU Display	6
5.6	Temperature-Controlled Mount	6
6.0	Optical Measurement and Equipment.....	6
6.1	Integrating Sphere	6
6.1.1	Detector	6
6.1.2	Radiometer	6
6.1.3	Spectroradiometer	7
6.1.4	Auxiliary Source.....	7
6.1.5	Fluorescence and Phosphorescence	8
6.1.6	Stray Light	8
6.2	Goniometer	8
6.2.1	Detector	8
6.2.2	Radiometer	8
6.2.3	Spectroradiometer	8
6.2.4	Stray Light	9
6.2.5	Angular Resolution and Sampling	9
6.2.6	Angular Range	9
6.2.7	Goniometer Alignment.....	9
7.0	Test Preparation	10
7.1	DUT Identification	10
7.2	DUT Handling	10
7.3	Seasoning.....	10
7.4	Temperature Stabilization	10
7.5	Operating Position and Orientation	10
8.0	Measurement Methods.....	10
8.1	Continuous Pulse Measurement Technique – Foundation for the Differential Methods	10
8.1.1	Overview	10
8.1.2	Notes on Instrumentation	11
8.2	Differential Continuous Pulse Method	11
8.3	Mean Differential Continuous Pulse (M-DCP) Method.....	16
8.4	DC Method.....	17
8.5	Continuous Pulse Time Resolved (CPT) Method	17
9.0	Measurement Uncertainty.....	18
10.0	Test Report	18
	Annex A – Determination of Temperature Stability	19
	Annex B – Determination of Transient Voltage Effect.....	19
	Informative References	21

1.0 Introduction and Scope

1.1 Introduction

This document is a guide developed for the measurement of ultraviolet (UV) light emitting diodes (LEDs), normally in the form of an LED package, array, or module. This document provides uniform methods for operation of UV LEDs and test methods for optical and electrical measurements of UV LED output at a given junction temperature in a continuous-pulse mode, and provides the grounds for specification of UV LEDs at high temperature conditions. The continuous-pulse mode of measurement provides a radiant efficiency (optical power [watts] divided by electrical power [watts]) at a given peak current for a given junction temperature, which allows the calculation of optical power output for a given electrical power input at a specific junction temperature.

The UV optical output of an LED depends on its thermal conditions, in particular, the junction temperature, T_j . Manufacturers of visible-range emitting LEDs normally use single-pulse operation for quality control and binning, whereby LEDs are measured with no heat sink and with the underlying assumption that the junction temperature under these conditions is equal to the room temperature, typically 25 °C. Therefore, published LED specifications are normally for a junction temperature of 25 °C. Furthermore, under a single-pulse mode of operation (often lasting tens of milliseconds) the junction temperature may increase significantly; therefore, the resulting efficiency may correspond to a much hotter junction temperature than the reported 25 °C.

UV LEDs in actual products, however, are typically operating in direct current (DC) and at much higher temperatures (the junction temperature typically ranges from 60 °C to over 100 °C). At these temperatures their emitted flux tends to deviate significantly from what it is under the room temperature condition of 25 °C. Thus, UV product manufacturers often need to know the performance of UV LEDs operating at full rated DC current, and at a thermal equilibrium temperature much higher than 25 °C. To set or measure thermal conditions of the UV LED, case temperature,

pin temperature, board temperature, solder-point temperature, or heat sink temperature is commonly used, depending on the type of UV LED. While these methods are useful to reproduce the same condition for the particular LED, the results using these different methods cannot easily be compared with each other and cannot be reconciled into a universal standard method. Due to the optical characteristics of UV LEDs and their dependence on junction temperature, the only way to obtain reproducible results universally for all types of UV LEDs is by setting them to a specified junction temperature. The test method described in this document sets the UV LED under test to a pre-determined junction temperature for measurement under a continuous-pulse mode of operation. Such a method can establish equivalence of results between the pulse mode operation (normally performed by UV LED manufacturers) and the DC mode operation in products.

The radiometric information typically required for UV LEDs to be used in products includes total radiant flux (watts, or joules per second), centroid wavelength, peak wavelength, and bandwidth. For the purpose of this document, the determination of these values is referred to as *optical measurement*.

The electrical characteristics typically required for UV LEDs to be used in products are peak input current, forward voltage, and input power. For the purpose of this document, the determination of these values is referred to as *electrical measurement*.

1.2 Scope

This document describes the procedures to be followed and precautions to be observed in performing measurements of total radiant flux (total radiant power), electrical power, and wavelength characteristics of ultraviolet (UV) light emitting diodes (LEDs). This document covers measurement of UV LEDs in the wavelength range of 200 nm to 400 nm* under continuous-pulse operation. Where the term “thermal condition” is used with respect to a UV LED, this refers to the junction temperature.

* LEDs with wavelengths longer than 360 nm are covered in ANSI/IES-LM-85-20.¹