



American Gas Association

AGA Report No. 3

ORIFICE METERING OF NATURAL GAS AND OTHER RELATED HYDROCARBON FLUIDS

PART 4

Background, Development, Implementation Procedure, and Subroutine Documentation for Empirical Flange- Tapped Discharge Coefficient Equation

Copyright ©

American Gas Association and American Petroleum Institute 1992, 1995, 2003
All Rights Reserved

**American Gas Association
400 North Capitol Street, N.W., 4th Floor
Washington, DC 20001
U.S.A.**

**Third Edition, October 1992
2nd Printing, August 1995
3rd Printing, June 2003**

Catalog No. XQ9211

DISCLAIMERS AND COPYRIGHT

Nothing contained in this publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use in connection with any method, apparatus, or product covered by letters patent, or as insuring anyone against liability for infringement of letters patent.

This publication was developed as a service to the natural gas industry and to the public. Use of this publication is voluntary and should be taken after an independent review of the applicable facts and circumstances.

Efforts have been made to ensure the accuracy and reliability of the data contained in this publication; however, the American Gas Association (AGA) makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or from the use of any product or methodology described herein; for any violation of any federal, state, or municipal regulation with which this publication may conflict; or for the infringement of any patent from the use of this publication. Nothing contained in this publication should be viewed as an endorsement by AGA of any particular manufacturer's products.

Permission is granted to republish material herein in laws or ordinances, and in regulations, administrative orders, or similar documents issued by public authorities. Those desiring permission for other publications should consult the Operations and Engineering Section, American Gas Association, 400 North Capitol Street, NW, 4th Floor, Washington, DC 20001, USA.

Copyright © 1992, 1995, 2003 American Gas Association and American Petroleum Institute, All Rights Reserved.

FOREWORD

AGA Report No. 3, *Orifice Metering of Natural Gas and other Related Hydrocarbon Fluids*, consists of four parts. **This one is Part 4 – Background, Development, Implementation Procedure, and Subroutine Documentation for Empirical Flange-Tapped Discharge Coefficient Equation.** Other parts are:

Part 1 – *General Equations and Uncertainty Guidelines*

Part 2 – *Specification and Installation Requirements*

Part 3 – *Natural Gas Applications*

Each of the four parts is published separately to facilitate future changes, allow immediate use, and reduce the size of the applicable part needed by most users. Although for many applications each part can be used independently, users with natural gas applications are advised to obtain Parts 1, 2 and 3.

This report applies to fluids that, for all practical purposes, are considered to be clean, single phase, homogeneous, and Newtonian, and the Part 4 of the report describes the background and development of the equation for the coefficient of discharge of flange-tapped square-edged concentric orifice meters, and recommends a flow rate calculation procedure. The recommended procedures provide consistent computational results for the quantification of fluid flow under defined conditions, regardless of the point of origin or destination, or the units of measure required by governmental customs or statute. The procedures allow different users with different computer languages on different computing hardware to arrive at almost identical results using the same standardized input data.

This report has been developed through the cooperative efforts of many individuals from industry under the sponsorship of the American Gas Association, the American Petroleum Institute, and the Gas Processors Association, with contributions from the Chemical Manufacturers Association, the Canadian Gas Association, the European Community, Norway, Japan and others.

It may become necessary to make revisions to this document in the future. Whenever any revisions are advisable, recommendations should be forwarded to the Operations and Engineering Section, **American Gas Association**, 400 N. Capitol Street, NW, 4th Floor, Washington, DC 20001, U.S.A. A form has been included at the end of this report for that purpose.

ACKNOWLEDGMENTS

From the initial data-collection phase through the final publication of this revision of the AGA Report No. 3, *Orifice Metering of Natural Gas and Other Related Hydrocarbon Fluids*, many individuals have devoted time and technical expertise. However, a small group of individuals has been very active for much of the project life. This group includes the following people:

H. Bean, EL Paso Natural Gas Company (Retired)
R. Beaty, Amoco Production Company, *Committee Chairman*
D. Bell, NOVA Corporation
T. Coker, Phillips Petroleum Company
W. Fling, OXY USA Inc. (Retired), *Project Manager*
J. Gallagher, Shell Pipe Line Corporation
L. Hillburn, Phillips Petroleum Company (Retired)
P. Hoglund, Washington Natural Gas Company (Retired)
P. LaNasa, CPL & Associates
G. Less, Natural Gas Pipeline Company of America (Retired)
J. Messmer, Chevron U.S.A. Inc. (Retired)
R. Teyssandier, Texaco Inc.
E. Upp
K. West, Mobil Research and Development Corporation

During much of the corresponding time period, a similar effort occurred in Europe. The following individuals provided valuable liaison between the two efforts:

D. Gould, Commission of the European Communities
F. Kinghorn, National Engineering Laboratory
M. Reader-Harris, National Engineering Laboratory
J. Sattary, National Engineering Laboratory
E. Spencer, Consultant
J. Stolz, Consultant
P. van der Kam, Gasunie

The American Petroleum Institute provided most of the funding for the research project. Additional support was provided by the American Gas Association and the Gas Processors Association. Special thanks is given to the Gas Research Institute and K. Kothari for providing funding and manpower for the natural gas calculations used in this project and to the National Institute of Standards and Technology in Boulder, Colorado, for additional flow work.

J. Whetstone and J. Brennan were responsible for the collection of water data at the National Institute of Standards and Technology in Gaithersburg, Maryland. C. Britton, S. Caldwell, and W. Seidl of the Colorado Engineering Experiment Station Inc., were responsible for the oil data. G. Less, J. Brennan, J. Ely, C. Sindt, K. Starling, and R. Ellington were responsible for the Natural Gas Pipeline of America test data on natural gas.

Over the years many individuals have been a part of the Chapter 14.3 Working Group and its many task forces. The list below is the roster of the working group and its task forces at the time of publication but is by no means a complete list of the individuals who participated in the development of this document.

R. Adamski, Exxon Chemical Americas - BOP
R. Bass
M. Bayliss, Occidental Petroleum (Caledonia) Ltd.
R. Beaty, Amoco Production Company
D. Bell, NOVA Company
B. Berry
J. Bosio, Statoil

J. Bosio, Statoil
J. Brennan, National Institute of Standards and Technology
E. Buxton
S. Caldwell
R. Chittum, American Petroleum Institute
T. Coker, Phillips Petroleum Company
H. Colvard, Exxon Company, U.S.A.
L. Datta-Barua, United Gas Pipeline Company
D. Embry, Phillips Petroleum Company
W. Fling
J. Gallagher, Shell Pipe Line Corporation
V. Gebben, Kerr-McGee Corporation
B. George, Amoco Production Company
G. Givens, CNG Transmission Corporation
T. Glazebrook, Tenneco Gas Transportation Company
D. Goedde, Texas Gas Transmission Corporation
D. Gould, Commission of the European Communities
K. Gray, Phillips Petroleum Company
R. Hankinson, Phillips 66 Natural Gas Company
R. Haworth
E. Hickl, Union Carbide Corporation
L. Hillburn
P. Hogle, Washington Natural Gas Company
J. Hord, National Institute of Standards and Technology
E. Jones, Jr., Chevron Oil Field Research Company
M. Keady
K. Kothari, Gas Research Institute
P. LaNasa
G. Less
G. Lynn, Oklahoma Natural Gas Company
R. Maddox
G. Mattingly, National Institute of Standards and Technology
B. McConaghy, NOVA Corporation
C. Mentz
L. Norris, Exxon Production Research Company
K. Olson, Chemical Manufacturers Association
A. Raether, Gas Company of New Mexico
E. Raper, OXY USA, Inc.
W. Ryan, El Paso Natural Gas Company
R. Segers
J. Sheffield
S. Stark, Williams Natural Gas Company
K. Starling
J. Stolz
J. Stuart, Pacific Gas and Electric Company
W. Studzinski, NOVA/Husky Research Company
M. Sutton, Gas Processors Association
R. Teyssandier, Texaco Inc.
V. Ting, Chevron Oil Field Research Company
L. Traweck, American Gas Association
E. Upp
F. Van Orsdol, Chevron U.S.A. Inc.
N. Watanabe, National Research Laboratory of Metrology, Japan

K. West, Mobil Research and Development Corporation
P. Wilcox, Total of France
J. Williams, Oryx Energy Company
M. Williams, Amoco Production Company
E. Woome, United Gas Pipeline Company
C. Worrell, OXY USA, Inc.

CONTENTS

	Page
4.1 Introduction and Nomenclature	
4.1.1 Introduction	1
4.1.2 Nomenclature	1
4.2 History and Development	
4.2.1 Background	3
4.2.2 Historical Data Base.....	5
4.2.3 Recent Data Collection Efforts	6
4.2.4 Basis for Equation.....	10
4.2.5 Reader-Harris/Gallagher Equation.....	13
4.3 Implementation Procedures	
4.3.1 Introduction.....	20
4.3.2 Solution for Mass or Volume Flow Rate.....	20
4.3.3 Special Procedures and Example Calculations for Natural Gas Applications	31
4.3.4 Example Calculations.....	48
APPENDIX 4-A—DEVELOPMENT OF FLOW EQUATION SOLUTION ALGORITHM	63
APPENDIX 4-B—RECOMMENDED ROUNDING PROCEDURES	71
APPENDIX 4-C—ROUND ROBIN TESTING	75
Figures	
4-1—Flange Tap Data Comparison—Mean Deviation (%) versus Nominal Beta Ratio	16
4-2—Flange Tap Data Comparison—Mean Deviation (%) versus Nominal Pipe Diameter	16
4-3—Flange Tap Data Comparison—Mean Deviation (%) versus Reynolds Number Ranges	16
4-4—Corner Tap Data Comparison—Mean Deviation (%) versus Nominal Beta Ratio	17
4-5—Corner Tap Data Comparison—Mean Deviation (%) versus Reynolds Number Ranges	17
4-6— $D-D/2$ (Radius) Tap Data Comparison—Mean Deviation (%) versus Nominal Beta Ratios	18
4-7— $D-D/2$ (Radius) Tap Data Comparison—Mean Deviation (%) versus Reynolds Number Ranges	18
4-8—Scatter Diagram Based on Buckingham Equation	19
4-9—Scatter Diagram Based on Reader-Harris/Gallagher Equation	19
4-A-1—Number of Iterations Required to Solve for Orifice Plate Coefficient of Discharge—Direct Substitution Method.....	68
4-A-2—Number of Iterations Required to Solve for Orifice Plate Coefficient of Discharge—Newton-Raphson Method	70
Tables	
4-1—Regression Database Point Distribution for Flange Taps.....	9
4-2—Regression Database Point Distribution for Corner Taps.....	10
4-3—Regression Database Point Distribution for $D-D/2$ (Radius) Taps.....	11

4-4—Typical Values of Linear Coefficients of Thermal Expansion	22
4-5—Units, Conversion Constants, and Universal Constants	23

Page

Tables (continued)

4-6—Input Parameters for Six Example Test Cases (US, IP, Metric, and SI Units)	49
4-7—Intermediate Output for Example Test Case Number 1	51
4-8—Intermediate Output for Example Test Case Number 2	53
4-9—Intermediate Output for Example Test Case Number 3	55
4-10—Intermediate Output for Example Test Case Number 4	57
4-11—Intermediate Output for Example Test Case Number 5	59
4-12—Intermediate Output for Example Test Case Number 6	61
4-B-1—Recommended Rounding Tolerances	74
4-C-1—Round Robin Test Parameters (US Units)	76
4-C-2—Round Robin Test Parameters (IP Units)	77
4-C-3—Round Robin Test Parameters (Metric Units)	78
4-C-4—Round Robin Test Parameters (SI Units)	79
4-C-5—Selected Round Robin Test Results Matrix (US Units)	81
4-C-6—Selected Round Robin Test Results Matrix (SI Units)	111

PART 4—BACKGROUND, DEVELOPMENT, IMPLEMENTATION PROCEDURES AND SUBROUTINE DOCUMENTATION

4.1 Introduction and Nomenclature

4.1.1 INTRODUCTION

This part of the standard for Concentric Square-Edged Orifice Meters provides the background and history of the development of the standard and recommends a method to solve the flow equations for mass and volumetric flow.

4.1.2 NOMENCLATURE

The symbols used have, in some cases, been given a more general definition than that used in other parts of API 2530. Some symbols have a different meaning than that defined elsewhere in the standard. Care should therefore be given to the meaning of variables used in this document.

Symbol	Represented Quantity
α_1	Linear coefficient of thermal expansion of the orifice plate material.
α_2	Linear coefficient of thermal expansion of the meter tube material.
β	Ratio of orifice plate bore diameter to meter tube internal diameter (d/D) calculated at flowing temperature, T_f .
β_m	Ratio of orifice plate bore diameter to meter tube internal diameter (d/D) calculated at measured temperature, T_m .
β_r	Ratio of orifice plate bore diameter to meter tube internal diameter (d/D) calculated at reference temperature, T_r .
C_d	Orifice plate coefficient of discharge.
$C_d(\text{FT})$	Coefficient of discharge at a specified pipe Reynolds number for flange-tapped orifice meter.
C_{d_0}	First flange-tapped orifice plate coefficient of discharge constant within iteration scheme.
C_{d_1}	Second flange-tapped orifice plate coefficient of discharge constant within iteration scheme.
C_{d_2}	Third flange-tapped orifice plate coefficient of discharge constant within iteration scheme.
C_{d_3}	Fourth flange-tapped orifice plate coefficient of discharge constant within iteration scheme.
C_{d_4}	Fifth flange-tapped orifice plate coefficient of discharge constant within iteration scheme.
C_{d-f}	Orifice plate coefficient of discharge bounds flag within iteration scheme.
d	Orifice plate bore diameter calculated at flowing temperature T_f .
D	Meter tube internal diameter calculated at flowing temperature T_f .
d_r	Orifice plate bore diameter calculated at reference temperature T_r .
D_r	Meter tube internal diameter calculated at reference temperature T_r .
d_m	Orifice plate bore diameter calculated at measured temperature T_m .
D_m	Meter tube internal diameter calculated at measured temperature T_m .
D_c	Orifice plate coefficient of discharge convergence function derivative.

ΔP	Orifice differential pressure.
e	Napierian constant, 2.71828.
E_v	Velocity of approach factor.
F_c	Orifice plate coefficient of discharge convergence function.
F_l	Iteration flow factor.
F_{I_c}	Iteration flow factor pressure—independent factor.
F_{I_p}	Iteration flow factor pressure—dependent factor.
F_{mass}	Mass flow factor.
G_i	Ideal gas relative density (specific gravity).
G_r	Real gas relative density (specific gravity).
GCN	Real relative density (specific gravity), % carbon dioxide, and % nitrogen.
k	Isentropic exponent.
m	Mass.
μ	Absolute viscosity of flowing fluid.
Mr_{air}	Molar mass (molecular weight) of dry air.
M	Dimensionless downstream dam height.
n	Number of moles.
N_c	Unit conversion factor (orifice flow).
N_{I_c}	Unit conversion factor (Reynolds number).
N_3	Unit conversion factor (expansion factor).
N_4	Unit conversion factor (discharge coefficient).
N_5	Unit conversion factor (absolute temperature).
P_b	Base pressure.
P_f	Static pressure of fluid at the pressure tap.
P_{f_1}	Absolute static pressure at the orifice upstream differential pressure tap.
P_{f_2}	Absolute static pressure at the orifice downstream differential pressure tap.
$P_{m_{air}}$	Measured air pressure.
$P_{m_{gas}}$	Measured gas pressure.
π	Pi, 3.14159...
q_m	Mass flow rate.
Q_b	Volume flow rate per hour at base conditions.
q_v	Volume flow rate flowing (actual) conditions.
R	Universal gas constant.
Re_D	Pipe Reynolds number.
ρ_b	Density of the fluid at base conditions, (P_b, T_b) .
$\rho_{b_{air}}$	Air density at base conditions, (P_b, T_b) .
$\rho_{b_{gas}}$	Gas density at base conditions, (P_b, T_b) .
ρ_s	Density at standard conditions, (P_s, T_s) .
$\rho_{t,p}$	Density at flowing conditions, (P_f, T_f) .
T_b	Base temperature.
T_d	Measured orifice plate bore diameter temperature.
T_{D_m}	Measured meter tube internal diameter temperature.
$T_{m_{air}}$	Measured temperature of air.
$T_{m_{gas}}$	Measured temperature of gas.
T_f	Flowing temperature.
T_r	Reference temperature of the orifice plate bore diameter and/or meter tube internal diameter.
T_d	Downstream tap correction factor.
T_s	Small meter tube correction factor.