



ANSI S1.16-2000
Reaffirmed by ANSI May 28, 2020

AMERICAN NATIONAL STANDARD

Method for Measuring the Performance of Noise Discriminating and Noise Canceling Microphones

Secretariat:

Acoustical Society of America

Approved on 19 May 2000:

American National Standards Institute, Inc.

Abstract

This American National Standard describes procedures for measuring the performance of noise discriminating and noise canceling microphones. The signal-to-noise ratio is measured at 1/3 octave band intervals with the desired test source in a diffuse noise field. The noise canceling performance of the microphone is defined as the noise canceling index (NCI), a weighted summation of the signal-to-noise ratios. The NCI of the microphone under test can be compared to the required baseline NCI of a laboratory standard pressure microphone..

ANSI S1.16-2000
Reaffirmed by ANSI
May 28, 2020

Reaffirmed by ANSI
April 27, 2005

Reaffirmed by ANSI
February 20, 2015

AMERICAN NATIONAL STANDARD
**METHOD FOR MEASURING
THE PERFORMANCE OF NOISE
DISCRIMINATING
AND NOISE CANCELING
MICROPHONES**


ANSI S1.16-2000

Accredited Standards Committee S1, Acoustics

Standards Secretariat
Acoustical Society of America
120 Wall Street, 32nd Floor
New York, New York 10005-3993

The American National Standards Institute, Inc. (ANSI) is the national coordinator of voluntary standards development and the clearing house in the U.S. for information on national and international standards.

The Acoustical Society of America (ASA) is an organization of scientists and engineers formed in 1929 to increase and diffuse the knowledge of acoustics and to promote its practical applications.



American National Standard

**Method for Measuring the Performance of
Noise Discriminating and Noise Canceling
Microphones**

Secretariat

Acoustical Society of America

Approved 19 May 2000

American National Standards Institute, Inc.

Abstract

This American National Standard describes procedures for measuring the performance of noise discriminating and noise canceling microphones. The signal-to-noise ratio is measured at 1/3 octave band intervals with the desired test source in a diffuse noise field. The noise canceling performance of the microphone is defined as the noise canceling index (NCI), a weighted summation of the signal-to-noise ratios. The NCI of the microphone under test can be compared to the required baseline NCI of a laboratory standard pressure microphone.

AMERICAN NATIONAL STANDARDS ON ACOUSTICS

The Acoustical Society of America (ASA) provides the Secretariat for Accredited Standards Committees S1 on Acoustics, S2 on Mechanical Vibration and Shock, S3 on Bioacoustics, and S12 on Noise. These committees have wide representation from the technical community (manufacturers, consumers, and general-interest representatives). The Standards are published by the Acoustical Society of America through the American Institute of Physics as American National Standards after approval by their respective standards committees and the American National Standards Institute.


These standards are developed and published as a public service to provide standards useful to the public, industry, and consumers, and to Federal, State, and local governments.

Each of the Accredited Standards Committees (operating in accordance with procedures approved by ANSI) is responsible for developing, voting upon, and maintaining or revising its own Standards. The ASA Standards Secretariat administers committee organization and activity, and provides liaison between the Accredited Standards Committees and ANSI. After the Standards have been produced and adopted by the Accredited Standards Committees, and approved as American National Standards by ANSI, the ASA Standards Secretariat arranges for their publication and distribution.

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary. Their existence does not in any respect preclude anyone, whether he or she has approved the Standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this Standard.



Standards Secretariat Acoustical Society
of America 120 Wall Street, 32nd Floor
New York, New York 10005-3993 USA

Telephone: +1 212 248-0373

Telefax: +1 212 248-0146

E-mail:

standards@acousticalsociety.org

Internet: <http://asa.aip.org>

Contents

	Page
Foreword	ii
1 Scope, Purpose, and Applications	1
1.1 Scope	1
1.2 Purpose	1
1.3 Applications	1
2 Normative References	1
3 Definitions	1
3.1 Noise Canceling Microphone	1
3.2 Noise Discriminating Microphone	1
3.3 Microphone System	1
3.4 Test Volume	1
3.5 Bandwidth	2
3.6 Diffuse Random Pink Noise Field	2
3.7 Signal-To-Noise Ratio (SNR)	3
3.8 Weighted Signal-To-Noise Ratio	3
3.9 Noise Canceling Index (NCI)	3
4 Diffuse Field Method	3
4.1 Physical Requirements	3
4.2 Test Procedure	3
4.3 Reporting Data	4
Tables	
1 Allowable random incidence field response variation for corresponding microphone free-field rejection	4
2 Method for calculation of the Weighted SNR (WSNR)	4
Figure	
1 Test geometry	2

Foreword

[This Foreword is for information only and is not an integral part of *American National Standard Method for Measuring the Performance of Noise Discriminating and Noise Canceling Microphones*, ANSI S1.16-2000.]

Noise canceling microphones are used in numerous applications where improved signal-to-noise ratios are important for speech communication and/or other audio applications. Arrays of microphones connected together by hardware and/or software can also improve the signal-to-noise ratio. This Standard addresses the need to have a standard methodology to measure the performance of these types of devices.

This Standard was developed under the jurisdiction of Accredited Standards Committee S1, Acoustics, which has the following scope:

Standards, specifications, methods of measurement and test, and terminology in the fields of physical acoustics including architectural acoustics, electroacoustics, sonics and ultrasonics, and underwater sound, but excluding those aspects which pertain to biological safety, tolerance, and comfort.

At the time this Standard was submitted to Accredited Standards Committee S1, Acoustics, for approval, the membership was as follows:

G. S. K. Wong, *Chair*
T. J. Kuemmel, *Vice Chair*
A. Brenig, *Secretary*

Acoustical Society of America	G. S. K. Wong
	T. J. Kuemmel (<i>Alt.</i>)
Air-Conditioning and Refrigeration Institute (ARI)	R. Comparin
	S. R. Sanders (<i>Alt.</i>)
American Industrial Hygiene Association (AIHA)	L. H. Royster
	J. F. Meagher (<i>Alt.</i>)
Audio Engineering Society	L. W. Sepmeyer
	M. R. Chial (<i>Alt.</i>)
Bruel & Kjaer Instruments, Inc.	M. Alexander
	J. Chou (<i>Alt.</i>)
Information Technology Industry Council (ITIC)	R. Lotz
	W. H. Johnson (<i>Alt.</i>)
Larson-Davis Laboratories	L. Davis
	J. M. Carey (<i>Alt.</i>)
Lucent Technologies	L. Marcus
	J. Baumauer (<i>Alt.</i>)
National Council of Acoustical Consultants	G. Winzer
National Institute of Standards and Technology (NIST)	V. Nedzelnitsky
	D. J. Evans (<i>Alt.</i>)
Sonetronics, Inc.	R. T. Linderoth
U.S. Department of the Air Force	R. L. McKinley
U.S. Army Construction Engineering Research Laboratories (USA-CERL)	P. D. Schomer

U.S. Army Human Research and Engineering Directorate J. Kalb
 L. Letowski (*Alt.*)
U.S. Army Primary Standards Laboratory (APSL) of the TMDE
Support Group J. R. Arrington

Individual experts of Accredited Standards Committee S1, Acoustics, were:

J. R. Bareham	T. J. Kuemmel	L. W. Sepmeyer
S. L. Ehrlich	D. L. Johnson	P. D. Schomer
K. M. Eldred	W. W. Lang	H. E. von Gierke
W. J. Galloway	A. H. Marsh	G. S. K. Wong
		R. W. Young

Working Group S1/WG15, Noise Canceling Microphones, which assisted Accredited Standards Committee S1, Acoustics, in the development of this Standard, had the following membership:

R. L. McKinley, *Chair*

J. Bareham	J. J. Earshen	R. J. Peppin
A. Campanella	T. A. Heline	G. S. K. Wong
R. Campbell	A. H. Marsh	R. W. Young

Suggestions for improvement of this Standard will be welcomed. Send suggestions for improvement to Accredited Standards Committee S1, Acoustics, in care of the ASA Standards Secretariat, 120 Wall Street, 32nd Floor, New York, NY 10005-3993, USA.

Telephone: +1 212 248 0373
 Fax: +1 212 248 0146
 E-mail: asastds@aip.org

American National Standard

Method for Measuring the Performance of Noise Discriminating and Noise Canceling Microphones

1 Scope, purpose, and applications

1.1 Scope

This Standard specifies the laboratory physical measurement procedure, calculation, and results reporting for quantifying the performance of noise canceling and noise discriminating microphones in a diffuse noise field.

1.2 Purpose

The purpose of this Standard is to describe procedures designed to measure the noise canceling performance of noise canceling and noise discrimination microphones in a diffuse sound field. This method provides a measure of merit, the Noise Canceling Index, which can be used to quantify the overall performance of a microphone in canceling or discriminating noise when compared to a laboratory quality pressure microphone meeting ANSI S1.12-1967 (R 1997).

1.3 Applications

The test method used in this Standard applies to measuring the noise canceling performance of noise canceling microphones, such as first and second order pressure gradient microphones, noise discriminating microphones, such as cardioid or shotgun microphones, and microphone systems, such as array microphones.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this American National Standard. At the time of approval by the American National Standards Institute, Inc. (ANSI), the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this American National Standard are encouraged to investigate the possibility of applying the most recent editions of

the standards listed below. Information on the recent editions is available from the ASA Standards Secretariat.

ANSI S1.1-1995 (R 1999), *American National Standard, Acoustical Terminology*

ANSI S1.15-1997/Part 1, *American National Standard Measurement Microphones, Part 1: Specifications for Laboratory Standard Microphones*

3 Definitions

3.1 A Noise canceling microphone uses a pressure gradient transducer to differentiate a signal having a high pressure gradient from noise having a low pressure gradient.

3.2 A Noise discriminating microphone uses only its directional polar response to differentiate a signal arriving on the axis of greatest sensitivity from a noise arriving from all directions.

3.3 Microphone system. A system consisting of one or more microphones, elements interconnected to perform a specific response function as an integrated physical transducer.

3.4 Test volume. A volume, as in figure 1, where a microphone device under test (DUT or LS1P) can be placed to determine its noise discriminating characteristics. This volume must be free of reflections and must furnish a uniform and diffuse acoustical noise field over the range of audio frequencies at which the DUT will be evaluated. This volume should be large enough to allow positioning and securing of the microphone device under test as well as an LS1P microphone, to determine the test sound level. Test sound field gradient and noise field should be present.

3.4.1 rho (radius vector). The radius vector from the source center, usually assumed to be at the center of the lip ring, to the measurement position in the test volume.

3.4.2 theta (azimuthal angle). The horizontal angle from the normal to the lip ring plane to the plane containing the measurement position and the source position.

3.4.3 phi (elevation angle). The vertical angle from the normal to the lip ring plane to the plane containing the measurement position and a horizontal line through the source.

3.4.4 test fixture. An apparatus or jig which maintains the relative positions of the source, the